



# BT Prime Mover Selector Guide

| TRUCK MODEL | VOLT | BATTERY TYPE | CAPACITY 6 HOUR RATE                     |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|------|--------------|--|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|             |      |              | A.H.                                     | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
|             |      |              | CENTER CONTROL PALLET TRUCK, TOW TRACTOR |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| CMX60/80    | 24   | 125F13       | 750                                      | 17.5 | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24   | 125C13       | 750                                      | 17.5 | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24   | 100G11       | 500                                      | 11.8 | 30.70              | 12.75         | 28.42          | 1035             | M8901210011NPP059    | Y     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|             | 24   | 140T13       | 840                                      | 19.6 | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24   | 125L13       | 750                                      | 17.5 | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
| TMX         | 24   | 125F13       | 750                                      | 17.5 | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24   | 125C13       | 750                                      | 17.5 | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24   | 140T13       | 840                                      | 19.6 | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24   | 125L13       | 750                                      | 17.5 | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
| PMX         | 12   | 085C11       | 425                                      | 4.9  | 26.06              | 7.69          | 23.25          | 438              | M1600608511A1        | N     | (CALL)             | SCR20006475S1H             | SCR20006475T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 085C11       | 425                                      | 4.9  | 26.06              | 7.69          | 23.25          | 438              | M1600608511A1        | N     | (CALL)             | SCR20006475S1L             | SCR20006475T1H            | (CALL)                 | (CALL)                 |
| PMX         | 12   | 085F13       | 510                                      | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 085F13       | 510                                      | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 085C13       | 510                                      | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 085C13       | 510                                      | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 100T13       | 600                                      | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 100T13       | 600                                      | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 085L13       | 510                                      | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 085L13       | 510                                      | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
| PMX         | 24   | 085C07       | 255                                      | 5.9  | 25.38              | 8.69          | 23.25          | 565              | M1601208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24   | 100T07       | 300                                      | 7.0  | 25.38              | 8.69          | 23.25          | 601              | M1801210007D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24   | 085L07       | 255                                      | 5.9  | 25.38              | 8.69          | 23.25          | 585              | M1901208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
| PMX         | 24   | 085C07       | 255                                      | 5.9  | 25.38              | 8.69          | 23.25          | 565              | M1601208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24   | 100T07       | 300                                      | 7.0  | 25.38              | 8.69          | 23.25          | 601              | M1801210007D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24   | 085L07       | 255                                      | 5.9  | 25.38              | 8.69          | 23.25          | 585              | M1901208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
| PMX1        | 12   | 085C11       | 425                                      | 4.9  | 26.06              | 7.69          | 23.25          | 438              | M1600608511A1        | N     | (CALL)             | SCR20006475S1H             | SCR20006475T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 085C11       | 425                                      | 4.9  | 26.06              | 7.69          | 23.25          | 438              | M1600608511A1        | N     | (CALL)             | SCR20006475S1L             | SCR20006475T1H            | (CALL)                 | (CALL)                 |
|             | 12   | 085C07       | 255                                      | 3.0  | 26.75              | 6.63          | 23.25          | 325              | M1600608507A6        | N     | (CALL)             | SCR20006260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 12   | 085C07       | 255                                      | 3.0  | 26.75              | 6.63          | 23.25          | 325              | M1600608507A6        | N     | (CALL)             | SCR20006260S1L             |                           | (CALL)                 | (CALL)                 |
| PMX1        | 24   | 085C07       | 255                                      | 5.9  | 25.38              | 8.69          | 23.25          | 565              | M1601208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24   | 100T07       | 300                                      | 7.0  | 25.38              | 8.69          | 23.25          | 601              | M1801210007D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24   | 085L07       | 255                                      | 5.9  | 25.38              | 8.69          | 23.25          | 585              | M1901208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# BT Prime Mover Selector Guide

| TRUCK MODEL  | VOLT                             | BATTERY TYPE | CAPACITY 6 HOUR RATE                     |      | BATTERY DIMENSIONS     |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER                         | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|--------------|----------------------------------|--------------|--|------|------------------------|---------------|----------------|------------------|--|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|              |                                  |              | A.H.                                     | KwH  | X in. (Length)         | Y in. (Width) | Z in. (Height) |                  |  |       |                    |                            |                           |                        |                        |
| <b>PMX2</b>  | <b>PALLET TRUCK</b>              |              | <b>12 VOLTS , 29.00 X 8.75 X 28.00</b>   |      |                        |               |                |                  |  |       |                    |                            |                           |                        |                        |
|              |                                  |              | <b>Weight Minimum 0</b>                  |      | <b>Connector SB175</b> |               | <b>GRAY</b>    |                  | <b>, Position B , Lead Length 015 Inches</b> |       |                    |                            |                           |                        |                        |
|              | 12                               | 085C11       | 425                                      | 4.9  | 26.06                  | 7.69          | 23.25          | 438              | M1600608511A1                                | N     | (CALL)             | SCR20006475S1H             | SCR20006475T1H            | (CALL)                 | (CALL)                 |
|              | 12                               | 085C11       | 425                                      | 4.9  | 26.06                  | 7.69          | 23.25          | 438              | M1600608511A1                                | N     | (CALL)             | SCR20006475S1L             | SCR20006475T1H            | (CALL)                 | (CALL)                 |
| <b>PMX2</b>  | <b>PALLET TRUCK</b>              |              | <b>24 VOLTS , 29.00 X 8.75 X 28.00</b>   |      |                        |               |                |                  |  |       |                    |                            |                           |                        |                        |
|              |                                  |              | <b>Weight Minimum 400</b>                |      | <b>Connector SB175</b> |               | <b>GRAY</b>    |                  | <b>, Position B , Lead Length 015 Inches</b> |       |                    |                            |                           |                        |                        |
|              | 24                               | 085C07       | 255                                      | 5.9  | 25.38                  | 8.69          | 23.25          | 565              | M1601208507D                                 | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|              | 24                               | 100T07       | 300                                      | 7.0  | 25.38                  | 8.69          | 23.25          | 601              | M1801210007D                                 | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|              | 24                               | 085L07       | 255                                      | 5.9  | 25.38                  | 8.69          | 23.25          | 585              | M1901208507D                                 | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
| <b>PMX45</b> | <b>PALLET TRUCK</b>              |              | <b>24 VOLTS , 28.25 X 9.00 X 24.00</b>   |      |                        |               |                |                  |  |       |                    |                            |                           |                        |                        |
|              |                                  |              | <b>Weight Minimum 200</b>                |      | <b>Connector SB175</b> |               | <b>RED</b>     |                  | <b>, Position B , Lead Length 012 Inches</b> |       |                    |                            |                           |                        |                        |
|              | 24                               | 085C07       | 255                                      | 5.9  | 25.38                  | 8.69          | 23.25          | 565              | M1601208507D                                 | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|              | 24                               | 100T07       | 300                                      | 7.0  | 25.38                  | 8.69          | 23.25          | 601              | M1801210007D                                 | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|              | 24                               | 085L07       | 255                                      | 5.9  | 25.38                  | 8.69          | 23.25          | 585              | M1901208507D                                 | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
| <b>HT45</b>  | <b>PALLET TRUCK, TOW TRACTOR</b> |              | <b>24 VOLTS , 32.00 X 13.50 X 999.00</b> |      |                        |               |                |                  |  |       |                    |                            |                           |                        |                        |
|              |                                  |              | <b>Weight Minimum 800</b>                |      | <b>Connector SB175</b> |               | <b>RED</b>     |                  | <b>, Position B , Lead Length 015 Inches</b> |       |                    |                            |                           |                        |                        |
|              | 24                               | 100C13       | 600                                      | 14.0 | 30.63                  | 12.69         | 26.13          | 1107             | M1601210013A                                 | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 100F13       | 600                                      | 14.0 | 30.63                  | 12.69         | 26.13          | 1149             | M1501210013A                                 | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 125F11       | 625                                      | 14.6 | 30.69                  | 12.94         | 31.00          | 1283             | M1501212511A6                                | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 125C11       | 625                                      | 14.6 | 30.69                  | 12.94         | 31.00          | 1226             | M1601212511A6                                | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 125F13       | 750                                      | 17.5 | 30.63                  | 12.81         | 31.00          | 1383             | M1501212513A                                 | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 125C13       | 750                                      | 17.5 | 30.63                  | 12.81         | 31.00          | 1341             | M1601212513A                                 | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 085F13       | 510                                      | 11.9 | 30.63                  | 12.69         | 23.25          | 1001             | M1501208513A                                 | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 085C11       | 425                                      | 9.9  | 26.06                  | 12.81         | 23.25          | 821              | M1601208511A                                 | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 100C11       | 500                                      | 11.6 | 26.13                  | 12.94         | 26.13          | 1029             | M1601210011A                                 | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 100G09       | 400                                      | 9.4  | 31.00                  | 12.75         | 24.20          | 860              | M8901210009NPP                               | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|              | 24                               | 100G09       | 400                                      | 9.4  | 31.00                  | 12.88         | 21.92          | 825              | M8901210009N059                              | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 140T11       | 700                                      | 16.3 | 30.69                  | 12.94         | 31.00          | 1302             | M1801214011A6                                | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 140T13       | 840                                      | 19.6 | 30.63                  | 12.81         | 31.00          | 1435             | M1801214013A                                 | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 100T13       | 600                                      | 14.0 | 30.63                  | 12.69         | 23.25          | 1020             | M1801210013A                                 | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 085L13       | 510                                      | 11.9 | 30.63                  | 12.69         | 23.25          | 983              | M1901208513A                                 | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 125L11       | 625                                      | 14.6 | 30.69                  | 12.94         | 31.00          | 1260             | M1901212511A6                                | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 125L13       | 750                                      | 17.5 | 30.63                  | 12.81         | 31.00          | 1358             | M1901212513A                                 | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                               | 085C13       | 510                                      | 11.9 | 30.63                  | 12.69         | 23.25          | 966              | M1601208513A                                 | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL  | VOLT | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|--|------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|  |      |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| HT60 PALLET TRUCK, TOW TRACTOR 24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 015 Inches  |      |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 24   | 100C13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 100F13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125F11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125C11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 085F13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 085C13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 085C11       | 425                  | 9.9  | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 100C11       | 500                  | 11.6 | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 100G09       | 400                  | 9.4  | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|  | 24   | 100G09       | 400                  | 9.4  | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 140T11       | 700                  | 16.3 | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 100T13       | 600                  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 085L13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125L11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
| HT60W PALLET TRUCK, TOW TRACTOR 24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 015 Inches |      |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 24   | 100C13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 100F13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125F11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125C11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 085F13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 085C13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 085C11       | 425                  | 9.9  | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 100C11       | 500                  | 11.6 | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 100G09       | 400                  | 9.4  | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|  | 24   | 100G09       | 400                  | 9.4  | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 140T11       | 700                  | 16.3 | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 100T13       | 600                  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 085L13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125L11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|  | 24   | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL                           | VOLT   | BATTERY TYPE | CAPACITY 6 HOUR RATE                     |       | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER      | Q-SHP                  | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)                   | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |  |
|---------------------------------------|--------|--------------|--|-------|--------------------|---------------|----------------|------------------|---------------------------|------------------------|--------------------|--|---------------------------|------------------------|------------------------|--|
|                                       |        |              | A.H.                                     | KwH   | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                           |                        |                    |  |                           |                        |                        |  |
| <b>HX65 PALLET TRUCK, TOW TRACTOR</b> |        |              | <b>24 VOLTS , 32.00 X 13.50 X 999.00</b> |       |                    |               |                |                  | <b>Weight Minimum 800</b> | <b>Connector SB175</b> | <b>RED</b>         | <b>, Position B , Lead Length 015 Inches</b> |                           |                        |                        |  |
| 24                                    | 100C13 | 600          | 14.0                                     | 30.63 | 12.69              | 26.13         | 1107           | M1601210013A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100F13 | 600          | 14.0                                     | 30.63 | 12.69              | 26.13         | 1149           | M1501210013A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125F11 | 625          | 14.6                                     | 30.69 | 12.94              | 31.00         | 1283           | M1501212511A6    | N                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125C11 | 625          | 14.6                                     | 30.69 | 12.94              | 31.00         | 1226           | M1601212511A6    | N                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125F13 | 750          | 17.5                                     | 30.63 | 12.81              | 31.00         | 1383           | M1501212513A     | Y                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125C13 | 750          | 17.5                                     | 30.63 | 12.81              | 31.00         | 1341           | M1601212513A     | Y                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 085F13 | 510          | 11.9                                     | 30.63 | 12.69              | 23.25         | 1001           | M1501208513A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 085C13 | 510          | 11.9                                     | 30.63 | 12.69              | 23.25         | 966            | M1601208513A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 085C11 | 425          | 9.9                                      | 26.06 | 12.81              | 23.25         | 821            | M1601208511A     | N                         | (CALL)                 | SCR20012475S1H     | SCR20012475T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100C11 | 500          | 11.6                                     | 26.13 | 12.94              | 26.13         | 1029           | M1601210011A     | N                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100G09 | 400          | 9.4                                      | 31.00 | 12.75              | 24.20         | 860            | M8901210009NPP   | N                         | (CALL)                 |                    |  | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100G09 | 400          | 9.4                                      | 31.00 | 12.88              | 21.92         | 825            | M8901210009N059  | N                         | (CALL)                 | SCR20012475S1H     | SCR20012475T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 140T11 | 700          | 16.3                                     | 30.69 | 12.94              | 31.00         | 1302           | M1801214011A6    | N                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 140T13 | 840          | 19.6                                     | 30.63 | 12.81              | 31.00         | 1435           | M1801214013A     | Y                         | (CALL)                 | SCR20012965S1H     | SCR20012865T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100T13 | 600          | 14.0                                     | 30.63 | 12.69              | 23.25         | 1020           | M1801210013A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 085L13 | 510          | 11.9                                     | 30.63 | 12.69              | 23.25         | 983            | M1901208513A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125L11 | 625          | 14.6                                     | 30.69 | 12.94              | 31.00         | 1260           | M1901212511A6    | N                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125L13 | 750          | 17.5                                     | 30.63 | 12.81              | 31.00         | 1358           | M1901212513A     | Y                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| <b>HX80 PALLET TRUCK, TOW TRACTOR</b> |        |              | <b>24 VOLTS , 32.00 X 13.50 X 999.00</b> |       |                    |               |                |                  | <b>Weight Minimum 800</b> | <b>Connector SB175</b> | <b>RED</b>         | <b>, Position B , Lead Length 015 Inches</b> |                           |                        |                        |  |
| 24                                    | 100C13 | 600          | 14.0                                     | 30.63 | 12.69              | 26.13         | 1107           | M1601210013A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100F13 | 600          | 14.0                                     | 30.63 | 12.69              | 26.13         | 1149           | M1501210013A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125F11 | 625          | 14.6                                     | 30.69 | 12.94              | 31.00         | 1283           | M1501212511A6    | N                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125C11 | 625          | 14.6                                     | 30.69 | 12.94              | 31.00         | 1226           | M1601212511A6    | N                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125F13 | 750          | 17.5                                     | 30.63 | 12.81              | 31.00         | 1383           | M1501212513A     | Y                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125C13 | 750          | 17.5                                     | 30.63 | 12.81              | 31.00         | 1341           | M1601212513A     | Y                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 085F13 | 510          | 11.9                                     | 30.63 | 12.69              | 23.25         | 1001           | M1501208513A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 085C13 | 510          | 11.9                                     | 30.63 | 12.69              | 23.25         | 966            | M1601208513A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 085C11 | 425          | 9.9                                      | 26.06 | 12.81              | 23.25         | 821            | M1601208511A     | N                         | (CALL)                 | SCR20012475S1H     | SCR20012475T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100C11 | 500          | 11.6                                     | 26.13 | 12.94              | 26.13         | 1029           | M1601210011A     | N                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100G09 | 400          | 9.4                                      | 31.00 | 12.75              | 24.20         | 860            | M8901210009NPP   | N                         | (CALL)                 |                    |  | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100G09 | 400          | 9.4                                      | 31.00 | 12.88              | 21.92         | 825            | M8901210009N059  | N                         | (CALL)                 | SCR20012475S1H     | SCR20012475T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 140T11 | 700          | 16.3                                     | 30.69 | 12.94              | 31.00         | 1302           | M1801214011A6    | N                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 140T13 | 840          | 19.6                                     | 30.63 | 12.81              | 31.00         | 1435           | M1801214013A     | Y                         | (CALL)                 | SCR20012965S1H     | SCR20012865T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 100T13 | 600          | 14.0                                     | 30.63 | 12.69              | 23.25         | 1020           | M1801210013A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 085L13 | 510          | 11.9                                     | 30.63 | 12.69              | 23.25         | 983            | M1901208513A     | Y                         | (CALL)                 | SCR20012600S1H     | SCR20012600T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125L11 | 625          | 14.6                                     | 30.69 | 12.94              | 31.00         | 1260           | M1901212511A6    | N                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |
| 24                                    | 125L13 | 750          | 17.5                                     | 30.63 | 12.81              | 31.00         | 1358           | M1901212513A     | Y                         | (CALL)                 | SCR20012750S1H     | SCR20012750T1H                               | (CALL)                    | (CALL)                 |                        |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# BT Prime Mover Selector Guide

| TRUCK MODEL | VOLT                             | BATTERY TYPE | CAPACITY 6 HOUR RATE |   | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|----------------------------------|--------------|----------------------|---|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|             |                                  |              | A.H.                 | KwH   | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| <b>MX50</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              |                      | <b>12 VOLTS , 32.00 X 8.00 X 999.00 Weight Minimum 500 Connector SB175 YELLOW , Position B , Lead Length 015 Inches</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 12                               | 085F13       | 510                  | 5.9   | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085F13       | 510                  | 5.9   | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085C13       | 510                  | 5.9   | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085C13       | 510                  | 5.9   | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 100C13       | 600                  | 7.0   | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 100C13       | 600                  | 7.0   | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 125F13       | 750                  | 8.7   | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 125C13       | 750                  | 8.7   | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 100T13       | 600                  | 7.0   | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 100T13       | 600                  | 7.0   | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 140T13       | 840                  | 9.8   | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085L13       | 510                  | 5.9   | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085L13       | 510                  | 5.9   | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 125L13       | 750                  | 8.7   | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
| <b>MX50</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              |                      | <b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 015 Inches</b>   |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                               | 100C13       | 600                  | 14.0  | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100F13       | 600                  | 14.0  | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125F11       | 625                  | 14.6  | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125C11       | 625                  | 14.6  | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125F13       | 750                  | 17.5  | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125C13       | 750                  | 17.5  | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 085F13       | 510                  | 11.9  | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 085C13       | 510                  | 11.9  | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 085C11       | 425                  | 9.9   | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100C11       | 500                  | 11.6  | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100G09       | 400                  | 9.4   | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|             | 24                               | 100G09       | 400                  | 9.4   | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 140T11       | 700                  | 16.3  | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 140T13       | 840                  | 19.6  | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100T13       | 600                  | 14.0  | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 085L13       | 510                  | 11.9  | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125L11       | 625                  | 14.6  | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125L13       | 750                  | 17.5  | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                             | BATTERY TYPE | CAPACITY 6 HOUR RATE |  | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE    |                        |               |  |
|-------------|----------------------------------|--------------|----------------------|--|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|---------------------------|------------------------|---------------|--|
|             |                                  |              | A.H.                 | KwH                                      | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                           |                        |               |  |
| <b>MX65</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              |                      | <b>12 VOLTS , 32.00 X 8.00 X 999.00</b>  |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 500</b> | <b>Connector SB175</b> | <b>YELLOW</b> | <b>, Position B , Lead Length 015 Inches</b> |
|             | 12                               | 085F13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 085F13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 085C13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 085C13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 100C13       | 600                  | 7.0                                      | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 100C13       | 600                  | 7.0                                      | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 125F13       | 750                  | 8.7                                      | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 125C13       | 750                  | 8.7                                      | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 100T13       | 600                  | 7.0                                      | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 100T13       | 600                  | 7.0                                      | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 140T13       | 840                  | 9.8                                      | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 085L13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 085L13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 12                               | 125L13       | 750                  | 8.7                                      | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                    |                        |               |  |
| <b>MX65</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              |                      | <b>24 VOLTS , 32.00 X 13.50 X 999.00</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 800</b> | <b>Connector SB175</b> | <b>RED</b>    | <b>, Position B , Lead Length 015 Inches</b> |
|             | 24                               | 100C13       | 600                  | 14.0                                     | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 100F13       | 600                  | 14.0                                     | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 125F11       | 625                  | 14.6                                     | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 125C11       | 625                  | 14.6                                     | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 125F13       | 750                  | 17.5                                     | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 125C13       | 750                  | 17.5                                     | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 085F13       | 510                  | 11.9                                     | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 085C13       | 510                  | 11.9                                     | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 085C11       | 425                  | 9.9                                      | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 100C11       | 500                  | 11.6                                     | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 100G09       | 400                  | 9.4                                      | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 100G09       | 400                  | 9.4                                      | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 140T11       | 700                  | 16.3                                     | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 140T13       | 840                  | 19.6                                     | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 100T13       | 600                  | 14.0                                     | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 085L13       | 510                  | 11.9                                     | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 125L11       | 625                  | 14.6                                     | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |               |  |
|             | 24                               | 125L13       | 750                  | 17.5                                     | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |               |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# BT Prime Mover Selector Guide

| TRUCK MODEL | VOLT                      | BATTERY TYPE | CAPACITY 6 HOUR RATE |                                   | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                 |  |  |
|-------------|---------------------------|--------------|----------------------|-----------------------------------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|-----------------|--|--|
|             |                           |              | A.H.                 | KwH                               | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |                 |  |  |
| PE45        | PALLET TRUCK, TOW TRACTOR |              |                      | 12 VOLTS , 32.00 X 8.00 X 999.00  |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 500     | Connector SB175 | YELLOW , Position B , Lead Length 015 Inches |  |
|             | 12                        | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100C13       | 600                  | 7.0                               | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100C13       | 600                  | 7.0                               | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 125F13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 125C13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 140T13       | 840                  | 9.8                               | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 125L13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
| PE45        | PALLET TRUCK, TOW TRACTOR |              |                      | 24 VOLTS , 32.00 X 13.50 X 999.00 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 800     | Connector SB175 | RED , Position B , Lead Length 015 Inches    |  |
|             | 24                        | 100C13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100F13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125F11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125C11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125F13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125C13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085F13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085C13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085C11       | 425                  | 9.9                               | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100C11       | 500                  | 11.6                              | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100G09       | 400                  | 9.4                               | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100G09       | 400                  | 9.4                               | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 140T11       | 700                  | 16.3                              | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 140T13       | 840                  | 19.6                              | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100T13       | 600                  | 14.0                              | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085L13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125L11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125L13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                      | BATTERY TYPE | CAPACITY 6 HOUR RATE |                                   | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                 |  |  |
|-------------|---------------------------|--------------|----------------------|-----------------------------------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|-----------------|--|--|
|             |                           |              | A.H.                 | KwH                               | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |                 |  |  |
| PE45R       | PALLET TRUCK, TOW TRACTOR |              |                      | 12 VOLTS , 32.00 X 8.00 X 999.00  |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 500     | Connector SB175 | YELLOW , Position B , Lead Length 015 Inches |  |
|             | 12                        | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100C13       | 600                  | 7.0                               | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100C13       | 600                  | 7.0                               | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 125F13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 125C13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 140T13       | 840                  | 9.8                               | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 125L13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
| PE45R       | PALLET TRUCK, TOW TRACTOR |              |                      | 24 VOLTS , 32.00 X 13.50 X 999.00 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 800     | Connector SB175 | RED , Position B , Lead Length 015 Inches    |  |
|             | 24                        | 100C13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100F13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125F11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125C11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125F13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125C13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085F13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085C13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085C11       | 425                  | 9.9                               | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100C11       | 500                  | 11.6                              | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100G09       | 400                  | 9.4                               | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100G09       | 400                  | 9.4                               | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 140T11       | 700                  | 16.3                              | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 140T13       | 840                  | 19.6                              | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100T13       | 600                  | 14.0                              | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085L13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125L11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125L13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



| TRUCK MODEL | VOLT                      | BATTERY TYPE | CAPACITY 6 HOUR RATE |                                   | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                 |  |  |
|-------------|---------------------------|--------------|----------------------|-----------------------------------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|-----------------|--|--|
|             |                           |              | A.H.                 | KwH                               | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |                 |  |  |
| PE60        | PALLET TRUCK, TOW TRACTOR |              |                      | 12 VOLTS , 32.00 X 8.00 X 999.00  |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 500     | Connector SB175 | YELLOW , Position B , Lead Length 015 Inches |  |
|             | 12                        | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100C13       | 600                  | 7.0                               | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100C13       | 600                  | 7.0                               | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 125F13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 125C13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 140T13       | 840                  | 9.8                               | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 12                        | 125L13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
| PE60        | PALLET TRUCK, TOW TRACTOR |              |                      | 24 VOLTS , 32.00 X 13.50 X 999.00 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 800     | Connector SB175 | RED , Position B , Lead Length 015 Inches    |  |
|             | 24                        | 100C13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100F13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125F11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125C11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125F13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125C13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085F13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085C13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085C11       | 425                  | 9.9                               | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100C11       | 500                  | 11.6                              | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100G09       | 400                  | 9.4                               | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100G09       | 400                  | 9.4                               | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 140T11       | 700                  | 16.3                              | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 140T13       | 840                  | 19.6                              | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 100T13       | 600                  | 14.0                              | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 085L13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125L11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |
|             | 24                        | 125L13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |  |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                      | BATTERY TYPE | CAPACITY 6 HOUR RATE |                                   | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                 |        |              |                          |
|-------------|---------------------------|--------------|----------------------|-----------------------------------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|-----------------|--------|--------------|--------------------------|
|             |                           |              | A.H.                 | KwH                               | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |                 |        |              |                          |
| PE60R       | PALLET TRUCK, TOW TRACTOR |              |                      | 12 VOLTS , 32.00 X 8.00 X 999.00  |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 500     | Connector SB175 | YELLOW | , Position B | , Lead Length 015 Inches |
|             | 12                        | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 100C13       | 600                  | 7.0                               | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 100C13       | 600                  | 7.0                               | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 125F13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 125C13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 140T13       | 840                  | 9.8                               | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 12                        | 125L13       | 750                  | 8.7                               | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
| PE60R       | PALLET TRUCK, TOW TRACTOR |              |                      | 24 VOLTS , 32.00 X 13.50 X 999.00 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 800     | Connector SB175 | RED    | , Position B | , Lead Length 015 Inches |
|             | 24                        | 100C13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 100F13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 125F11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 125C11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 125F13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 125C13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 085F13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 085C13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 085C11       | 425                  | 9.9                               | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 100C11       | 500                  | 11.6                              | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 100G09       | 400                  | 9.4                               | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 100G09       | 400                  | 9.4                               | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 140T11       | 700                  | 16.3                              | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 140T13       | 840                  | 19.6                              | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 100T13       | 600                  | 14.0                              | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 085L13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 125L11       | 625                  | 14.6                              | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |
|             | 24                        | 125L13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |                 |        |              |                          |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                             | BATTERY TYPE | CAPACITY 6 HOUR RATE |   | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE    |                        |   |  |
|-------------|----------------------------------|--------------|----------------------|---|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|---------------------------|------------------------|---|--|
|             |                                  |              | A.H.                 | KwH                                     | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                           |                        |   |  |
| <b>RX50</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              |                      | <b>12 VOLTS , 32.00 X 8.00 X 999.00</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 500</b> | <b>Connector SB175</b> | <b>YELLOW , Position B , Lead Length 015 Inches</b> |  |
|             | 12                               | 085F13       | 510                  | 5.9                                     | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085F13       | 510                  | 5.9                                     | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085C13       | 510                  | 5.9                                     | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085C13       | 510                  | 5.9                                     | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 100C13       | 600                  | 7.0                                     | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 100C13       | 600                  | 7.0                                     | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 125F13       | 750                  | 8.7                                     | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 125C13       | 750                  | 8.7                                     | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 100T13       | 600                  | 7.0                                     | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 100T13       | 600                  | 7.0                                     | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 140T13       | 840                  | 9.8                                     | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085L13       | 510                  | 5.9                                     | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085L13       | 510                  | 5.9                                     | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 125L13       | 750                  | 8.7                                     | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                    |                        |   |  |

|             |                                  |        |     |  |       |       |       |      |                 |   |        |                |                |        |                           |                        |  |  |
|-------------|----------------------------------|--------|-----|--|-------|-------|-------|------|-----------------|---|--------|----------------|----------------|--------|---------------------------|------------------------|--|--|
| <b>RX50</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |        |     | <b>24 VOLTS , 32.00 X 13.50 X 999.00</b> |       |       |       |      |                 |   |        |                |                |        | <b>Weight Minimum 800</b> | <b>Connector SB175</b> | <b>RED , Position B , Lead Length 015 Inches</b> |  |
|             | 24                               | 100C13 | 600 | 14.0                                     | 30.63 | 12.69 | 26.13 | 1107 | M1601210013A    | Y | (CALL) | SCR20012600S1H | SCR20012600T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 100F13 | 600 | 14.0                                     | 30.63 | 12.69 | 26.13 | 1149 | M1501210013A    | Y | (CALL) | SCR20012600S1H | SCR20012600T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 125F11 | 625 | 14.6                                     | 30.69 | 12.94 | 31.00 | 1283 | M1501212511A6   | N | (CALL) | SCR20012750S1H | SCR20012750T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 125C11 | 625 | 14.6                                     | 30.69 | 12.94 | 31.00 | 1226 | M1601212511A6   | N | (CALL) | SCR20012750S1H | SCR20012750T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 125F13 | 750 | 17.5                                     | 30.63 | 12.81 | 31.00 | 1383 | M1501212513A    | Y | (CALL) | SCR20012750S1H | SCR20012750T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 125C13 | 750 | 17.5                                     | 30.63 | 12.81 | 31.00 | 1341 | M1601212513A    | Y | (CALL) | SCR20012750S1H | SCR20012750T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 085F13 | 510 | 11.9                                     | 30.63 | 12.69 | 23.25 | 1001 | M1501208513A    | Y | (CALL) | SCR20012600S1H | SCR20012600T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 085C11 | 425 | 9.9                                      | 26.06 | 12.81 | 23.25 | 821  | M1601208511A    | N | (CALL) | SCR20012475S1H | SCR20012475T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 100C11 | 500 | 11.6                                     | 26.13 | 12.94 | 26.13 | 1029 | M1601210011A    | N | (CALL) | SCR20012600S1H | SCR20012600T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 100G09 | 400 | 9.4                                      | 31.00 | 12.75 | 24.20 | 860  | M8901210009NPP  | N | (CALL) |                |                | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 100G09 | 400 | 9.4                                      | 31.00 | 12.88 | 21.92 | 825  | M8901210009N059 | N | (CALL) | SCR20012475S1H | SCR20012475T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 140T11 | 700 | 16.3                                     | 30.69 | 12.94 | 31.00 | 1302 | M1801214011A6   | N | (CALL) | SCR20012750S1H | SCR20012750T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 140T13 | 840 | 19.6                                     | 30.63 | 12.81 | 31.00 | 1435 | M1801214013A    | Y | (CALL) | SCR20012965S1H | SCR20012865T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 100T13 | 600 | 14.0                                     | 30.63 | 12.69 | 23.25 | 1020 | M1801210013A    | Y | (CALL) | SCR20012600S1H | SCR20012600T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 085L13 | 510 | 11.9                                     | 30.63 | 12.69 | 23.25 | 983  | M1901208513A    | Y | (CALL) | SCR20012600S1H | SCR20012600T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 125L11 | 625 | 14.6                                     | 30.69 | 12.94 | 31.00 | 1260 | M1901212511A6   | N | (CALL) | SCR20012750S1H | SCR20012750T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 125L13 | 750 | 17.5                                     | 30.63 | 12.81 | 31.00 | 1358 | M1901212513A    | Y | (CALL) | SCR20012750S1H | SCR20012750T1H | (CALL) | (CALL)                    |                        |  |  |
|             | 24                               | 085C13 | 510 | 11.9                                     | 30.63 | 12.69 | 23.25 | 966  | M1601208513A    | Y | (CALL) | SCR20012600S1H | SCR20012600T1H | (CALL) | (CALL)                    |                        |  |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                             | BATTERY TYPE | CAPACITY 6 HOUR RATE  |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|----------------------------------|--------------|---|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|             |                                  |              | A.H.  | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| <b>RX65</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              | <b>12 VOLTS , 32.00 X 8.00 X 999.00 Weight Minimum 500 Connector SB175 YELLOW , Position B , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 12                               | 085F13       | 510   | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085F13       | 510   | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085C13       | 510   | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085C13       | 510   | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 100C13       | 600   | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 100C13       | 600   | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 125F13       | 750   | 8.7  | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 125C13       | 750   | 8.7  | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 100T13       | 600   | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 100T13       | 600   | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 140T13       | 840   | 9.8  | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085L13       | 510   | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 085L13       | 510   | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                               | 125L13       | 750   | 8.7  | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
| <b>RX65</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              | <b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 015 Inches</b>   |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                               | 100C13       | 600   | 14.0 | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100F13       | 600   | 14.0 | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125F11       | 625   | 14.6 | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125C11       | 625   | 14.6 | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125F13       | 750   | 17.5 | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125C13       | 750   | 17.5 | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 085F13       | 510   | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 085C11       | 425   | 9.9  | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100C11       | 500   | 11.6 | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100G09       | 400   | 9.4  | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|             | 24                               | 100G09       | 400   | 9.4  | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 140T11       | 700   | 16.3 | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 140T13       | 840   | 19.6 | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100T13       | 600   | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 085L13       | 510   | 11.9 | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125L11       | 625   | 14.6 | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 125L13       | 750   | 17.5 | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 085C13       | 510   | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| <b>SR30</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              | <b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 1000 Connector SB175 RED , Position B , Lead Length 015 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                               | 100C13       | 600   | 14.0 | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100F13       | 600   | 14.0 | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                               | 100T13       | 600   | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                             | BATTERY TYPE | CAPACITY 6 HOUR RATE |  | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE    |                        |   |  |
|-------------|----------------------------------|--------------|----------------------|--|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|---------------------------|------------------------|---|--|
|             |                                  |              | A.H.                 | KwH                                      | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                           |                        |   |  |
| <b>TE50</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              |                      | <b>12 VOLTS , 32.00 X 8.00 X 999.00</b>  |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 500</b> | <b>Connector SB175</b> | <b>YELLOW , Position B , Lead Length 015 Inches</b> |  |
|             | 12                               | 085F13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085F13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085C13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085C13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 100C13       | 600                  | 7.0                                      | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 100C13       | 600                  | 7.0                                      | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 125F13       | 750                  | 8.7                                      | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 125C13       | 750                  | 8.7                                      | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 100T13       | 600                  | 7.0                                      | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 100T13       | 600                  | 7.0                                      | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 140T13       | 840                  | 9.8                                      | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085L13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 085L13       | 510                  | 5.9                                      | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 12                               | 125L13       | 750                  | 8.7                                      | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
| <b>TE70</b> | <b>PALLET TRUCK, TOW TRACTOR</b> |              |                      | <b>24 VOLTS , 32.00 X 13.50 X 999.00</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 800</b> | <b>Connector SB175</b> | <b>RED , Position B , Lead Length 015 Inches</b>    |  |
|             | 24                               | 100C13       | 600                  | 14.0                                     | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 100F13       | 600                  | 14.0                                     | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 125F11       | 625                  | 14.6                                     | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 125C11       | 625                  | 14.6                                     | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 125F13       | 750                  | 17.5                                     | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 125C13       | 750                  | 17.5                                     | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 085F13       | 510                  | 11.9                                     | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 085C11       | 425                  | 9.9                                      | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 100C11       | 500                  | 11.6                                     | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 100G09       | 400                  | 9.4                                      | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 100G09       | 400                  | 9.4                                      | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 140T11       | 700                  | 16.3                                     | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 140T13       | 840                  | 19.6                                     | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 100T13       | 600                  | 14.0                                     | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 085L13       | 510                  | 11.9                                     | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 125L11       | 625                  | 14.6                                     | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 125L13       | 750                  | 17.5                                     | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |   |  |
|             | 24                               | 085C13       | 510                  | 11.9                                     | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |   |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL     | VOLT                               | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)               | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                           |                        |   |  |
|-----------------|------------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|--|---------------------------|------------------------|------------------------|---------------------------|------------------------|---|--|
|                 |                                    |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |  |                           |                        |                        |                           |                        |   |  |
| <b>TT50</b>     | <b>PALLET TRUCK, TOW TRACTOR</b>   |              |                      |      |                    |               |                |                  |                      |       |                    | <b>12 VOLTS , 32.00 X 8.00 X 999.00</b>  |                           |                        |                        | <b>Weight Minimum 500</b> | <b>Connector SB175</b> | <b>YELLOW , Position B , Lead Length 015 Inches</b> |  |
|                 | 12                                 | 085F13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 085F13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 085C13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 085C13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 100C13       | 600                  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 100C13       | 600                  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 125F13       | 750                  | 8.7  | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |  | SCR20006750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 125C13       | 750                  | 8.7  | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |  | SCR20006750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 100T13       | 600                  | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 100T13       | 600                  | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 140T13       | 840                  | 9.8  | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H                           | SCR20006865T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 085L13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 085L13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L                           | SCR20006600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 12                                 | 125L13       | 750                  | 8.7  | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |  | SCR20006750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
| <b>TT70</b>     | <b>PALLET TRUCK, TOW TRACTOR</b>   |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 32.00 X 13.50 X 999.00</b> |                           |                        |                        | <b>Weight Minimum 800</b> | <b>Connector SB175</b> | <b>RED , Position B , Lead Length 015 Inches</b>    |  |
|                 | 24                                 | 100C13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 100F13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 125F11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N     | (CALL)             | SCR20012750S1H                           | SCR20012750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 125C11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N     | (CALL)             | SCR20012750S1H                           | SCR20012750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H                           | SCR20012750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H                           | SCR20012750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 085F13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 085C11       | 425                  | 9.9  | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H                           | SCR20012475T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 100C11       | 500                  | 11.6 | 26.13              | 12.94         | 26.13          | 1029             | M1601210011A         | N     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 100G09       | 400                  | 9.4  | 31.00              | 12.75         | 24.20          | 860              | M8901210009NPP       | N     | (CALL)             |  |                           | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 100G09       | 400                  | 9.4  | 31.00              | 12.88         | 21.92          | 825              | M8901210009N059      | N     | (CALL)             | SCR20012475S1H                           | SCR20012475T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 140T11       | 700                  | 16.3 | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N     | (CALL)             | SCR20012750S1H                           | SCR20012750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H                           | SCR20012865T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 100T13       | 600                  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 085L13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 125L11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N     | (CALL)             | SCR20012750S1H                           | SCR20012750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H                           | SCR20012750T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 085C13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 085C13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
| <b>HMX65/80</b> | <b>WALKIE / RIDER PALLET TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 31.75 X 13.30 X 999.00</b> |                           |                        |                        | <b>Weight Minimum 900</b> | <b>Connector SB175</b> | <b>RED , Position B , Lead Length 015 Inches</b>    |  |
|                 | 24                                 | 100C13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 100F13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H                           | SCR20012600T1H            | (CALL)                 | (CALL)                 |                           |                        |   |  |
| <b>RMX65/80</b> | <b>WALKIE / RIDER PALLET TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 31.75 X 8.13 X 32.00</b>   |                           |                        |                        | <b>Weight Minimum 400</b> | <b>Connector SB175</b> | <b>RED , Position B , Lead Length 015 Inches</b>    |  |
|                 | 24                                 | MSB          | 195                  | .0   | 29.00              | 7.50          | 26.45          | 400              | M90004S24CHPB        | N     | (CALL)             |  |                           | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 085L05       | 170                  | 4.0  | 25.25              | 6.63          | 27.25          | 415              | M1901208505GFPCZ     | Y     | (CALL)             |  |                           | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 085F05       | 170                  | 4.0  | 25.25              | 6.63          | 23.25          | 421              | M1501208505G         | N     | (CALL)             | SCR20012260S1H                           |                           | (CALL)                 | (CALL)                 |                           |                        |   |  |
|                 | 24                                 | 085C05       | 170                  | 4.0  | 25.25              | 6.63          | 23.25          | 406              | M1601208505G         | Y     | (CALL)             | SCR20012260S1H                           |                           | (CALL)                 | (CALL)                 |                           |                        |   |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL     | VOLT                               | BATTERY TYPE | CAPACITY 6 HOUR RATE   |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-----------------|------------------------------------|--------------|--|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|                 |                                    |              | A.H.   | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| <b>RMX65/80</b> | <b>WALKIE / RIDER PALLET TRUCK</b> |              | <b>24 VOLTS , 31.75 X 13.30 X 999.00 Weight Minimum 900 Connector SB175 RED , Position B , Lead Length 015 Inches</b>    |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                 | 24                                 | 100C13       | 600  | 14.0 | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 100F13       | 600  | 14.0 | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085F13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085C11       | 425  | 9.9  | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085L13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085C13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| <b>RMX80</b>    | <b>WALKIE / RIDER PALLET TRUCK</b> |              | <b>24 VOLTS , 31.75 X 13.30 X 999.00 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 015 Inches</b>    |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                 | 24                                 | 100C13       | 600  | 14.0 | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 100F13       | 600  | 14.0 | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085F13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085C11       | 425  | 9.9  | 26.06              | 12.81         | 23.25          | 821              | M1601208511A         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085L13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085C13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| <b>WSX22</b>    | <b>WALKIE PALLET</b>               |              | <b>24 VOLTS , 32.30 X 9.00 X 999.00 Weight Minimum 290 Connector SB175 RED , Position B , Lead Length 020 Inches</b>     |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                 | 24                                 | 085F07       | 255  | 5.9  | 30.00              | 8.63          | 23.25          | 567              | M1501208507D2        | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085C07       | 255  | 5.9  | 30.00              | 8.63          | 23.25          | 567              | M1601208507D2        | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                 | 24                                 | MSB          | 195  | .0   | 29.00              | 7.50          | 26.45          | 400              | M90004S24CHPB        | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|                 | 24                                 | 100T07       | 300  | 7.0  | 30.00              | 8.63          | 23.25          | 604              | M1801210007D2        | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085L07       | 255  | 5.9  | 30.00              | 8.63          | 23.25          | 581              | M1901208507D2        | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
| <b>RMX50</b>    | <b>WALKIE PALLET TRUCK</b>         |              | <b>12 VOLTS , 31.75 X 8.10 X 999.00 Weight Minimum 400 Connector SB175 RED , Position B , Lead Length 015 Inches</b>     |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                 | 12                                 | 100C13       | 600  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|                 | 12                                 | 100C13       | 600  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|                 | 12                                 | 125F13       | 750  | 8.7  | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|                 | 12                                 | 125C13       | 750  | 8.7  | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|                 | 12                                 | 140T13       | 840  | 9.8  | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |
|                 | 12                                 | 125L13       | 750  | 8.7  | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
| <b>RMX53</b>    | <b>WALKIE PALLET TRUCK</b>         |              | <b>12 VOLTS , 31.75 X 13.30 X 999.00 Weight Minimum 400 Connector SB175 YELLOW , Position B , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                 | 12                                 | 085C19       | 765  | 8.9  | 22.31              | 12.94         | 23.25          | 708              | M1600608519C         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |
| <b>WSX20/25</b> | <b>WALKIE PALLET TRUCK</b>         |              | <b>24 VOLTS , 27.30 X 8.75 X 999.00 Weight Minimum 290 Connector SB175 RED , Position A , Lead Length 020 Inches</b>     |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                 | 24                                 | 085C07       | 255  | 5.9  | 25.38              | 8.69          | 23.25          | 565              | M1601208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                 | 24                                 | 100T07       | 300  | 7.0  | 25.38              | 8.69          | 23.25          | 601              | M1801210007D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085L07       | 255  | 5.9  | 25.38              | 8.69          | 23.25          | 585              | M1901208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
| <b>SMX45</b>    | <b>WALKIE/RIDER PALLET TRUCKS</b>  |              | <b>24 VOLTS , 27.00 X 7.80 X 999.00 Weight Minimum 200 Connector SB175 RED , Position B , Lead Length 020 Inches</b>     |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                 | 24                                 | 085F05       | 170  | 4.0  | 25.25              | 6.63          | 23.25          | 421              | M1501208505G         | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085C05       | 170  | 4.0  | 25.25              | 6.63          | 23.25          | 406              | M1601208505G         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                 | 24                                 | 100C05       | 200  | 4.7  | 25.25              | 6.50          | 25.63          | 455              | M1601210005G         | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                 | 24                                 | 100T05       | 200  | 4.7  | 25.25              | 6.63          | 23.25          | 429              | M1801210005G         | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                 | 24                                 | 085L05       | 170  | 4.0  | 25.25              | 6.63          | 23.25          | 423              | M1901208505G         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL        | VOLT                              | BATTERY TYPE | CAPACITY 6 HOUR RATE   |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|--------------------|-----------------------------------|--------------|--|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|                    |                                   |              | A.H.   | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| <b>SMX45</b>       | <b>WALKIE/RIDER PALLET TRUCKS</b> |              | <b>24 VOLTS , 27.00 X 9.00 X 999.00 Weight Minimum 200 Connector SB175 RED , Position B , Lead Length 020 Inches</b>   |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                    | 24                                | 085C07       | 255  | 5.9  | 25.38              | 8.69          | 23.25          | 565              | M1601208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                    | 24                                | 100T07       | 300  | 7.0  | 25.38              | 8.69          | 23.25          | 601              | M1801210007D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|                    | 24                                | CHP          | 195  | .0   | 25.50              | 8.69          | 26.16          | 400              | M90004S24CHPC        | N     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|                    | 24                                | 085L07       | 255  | 5.9  | 25.38              | 8.69          | 23.25          | 585              | M1901208507D         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
| <b>CSX20/30/40</b> | <b>WALKIE, STACKER</b>            |              | <b>24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 020 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                    | 24                                | 125F13       | 750  | 17.5 | 30.81              | 12.94         | 30.50          | 1422             | M2501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 125C13       | 750  | 17.5 | 30.81              | 12.94         | 30.50          | 1370             | M2601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 140T13       | 840  | 19.6 | 30.81              | 12.94         | 30.50          | 1471             | M2801214013A         | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 22.63          | 1014             | M2801210013A         | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| <b>WRX30</b>       | <b>WALKIE, STACKER</b>            |              | <b>24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 020 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                    | 24                                | 125F13       | 750  | 17.5 | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 125C13       | 750  | 17.5 | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 140T13       | 840  | 19.6 | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 125L13       | 750  | 17.5 | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
| <b>WSX30/40</b>    | <b>WALKIE, STACKER</b>            |              | <b>24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 020 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                    | 24                                | 125F13       | 750  | 17.5 | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 125C13       | 750  | 17.5 | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 140T13       | 840  | 19.6 | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| <b>OPX30</b>       | <b>ORDER PICKER</b>               |              | <b>24 VOLTS , 36.25 X 13.88 X 31.50 Weight Minimum 1500 Connector SB350 RED , Position C , Lead Length 015 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                    | 24                                | 125F15       | 875  | 20.4 | 35.25              | 13.06         | 30.50          | 1662             | M2501212515A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 125C15       | 875  | 20.4 | 35.25              | 13.06         | 30.50          | 1606             | M2601212515A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|                    | 24                                | 140T15       | 980  | 22.8 | 35.25              | 13.06         | 30.50          | 1702             | M2801214015A         | Y     | (CALL)             | SCR200121050T1H            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
| <b>OPX30</b>       | <b>ORDER PICKER</b>               |              | <b>36 VOLTS , 38.25 X 13.88 X 31.50 Weight Minimum 1650 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                    | 36                                | 125C11       | 625  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|                    | 36                                | 125F11       | 625  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|                    | 36                                | 140T11       | 700  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| <b>RDX-30</b>      | <b>DEEP REACH TRUCK</b>           |              | <b>36 VOLTS , 38.75 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                    | 36                                | 125C13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|                    | 36                                | 125F13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|                    | 36                                | 140T13       | 840  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |
|                    | 36                                | 125L13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| <b>OE15C</b>       | <b>ORDER SELECTOR</b>             |              | <b>24 VOLTS , 32.00 X 13.50 X 26.50 Weight Minimum 1000 Connector SB175 RED , Position B , Lead Length 015 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|                    | 24                                | 100G11       | 500  | 11.8 | 30.69              | 12.88         | 26.40          | 1075             | M8901210011N059      | Y     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)





# BT Prime Mover Selector Guide

| TRUCK MODEL | VOLT           | BATTERY TYPE | CAPACITY 6 HOUR RATE             |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP            | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)            | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|----------------|--------------|----------------------------------|------|--------------------|---------------|----------------|------------------|----------------------|------------------|--------------------|---------------------------------------|---------------------------|------------------------|------------------------|
|             |                |              | A.H.                             | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |                  |                    |                                       |                           |                        |                        |
| OE30        | ORDER SELECTOR |              | 24 VOLTS , 36.25 X 13.80 X 31.50 |      |                    |               |                |                  | Weight Minimum 1100  | Connector SB175  | RED                | , Position B , Lead Length 018 Inches |                           |                        |                        |
|             | 24             | 125F15       | 875                              | 20.4 | 35.25              | 13.06         | 30.50          | 1662             | M2501212515A         | Y                | (CALL)             | SCR20012965S1H                        | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125C15       | 875                              | 20.4 | 35.25              | 13.06         | 30.50          | 1606             | M2601212515A         | Y                | (CALL)             | SCR20012965S1H                        | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125F13       | 750                              | 17.5 | 35.91              | 11.69         | 30.50          | 1429             | M2501212513K         | N                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125C13       | 750                              | 17.5 | 35.91              | 11.69         | 30.50          | 1381             | M2601212513K         | Y                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 100C15       | 700                              | 16.3 | 35.31              | 13.13         | 25.63          | 1270             | M2601210015A         | N                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 140T15       | 980                              | 22.8 | 35.25              | 13.06         | 30.50          | 1702             | M2801214015A         | Y                | (CALL)             |                                       | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24             | 140T13       | 840                              | 19.6 | 35.91              | 11.69         | 30.50          | 1460             | M2801214013K         | N                | (CALL)             | SCR20012965S1H                        | SCR20012865T1H            | (CALL)                 | (CALL)                 |
| OE30B       | ORDER SELECTOR |              | 24 VOLTS , 36.25 X 13.80 X 31.50 |      |                    |               |                |                  | Weight Minimum 1100  | Connector SB175  | RED                | , Position B , Lead Length 018 Inches |                           |                        |                        |
|             | 24             | 125F15       | 875                              | 20.4 | 35.25              | 13.06         | 30.50          | 1662             | M2501212515A         | Y                | (CALL)             | SCR20012965S1H                        | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125C15       | 875                              | 20.4 | 35.25              | 13.06         | 30.50          | 1606             | M2601212515A         | Y                | (CALL)             | SCR20012965S1H                        | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125F13       | 750                              | 17.5 | 35.91              | 11.69         | 30.50          | 1429             | M2501212513K         | N                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125C13       | 750                              | 17.5 | 35.91              | 11.69         | 30.50          | 1381             | M2601212513K         | Y                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 100C15       | 700                              | 16.3 | 35.31              | 13.13         | 25.63          | 1270             | M2601210015A         | N                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 140T15       | 980                              | 22.8 | 35.25              | 13.06         | 30.50          | 1702             | M2801214015A         | Y                | (CALL)             |                                       | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24             | 140T13       | 840                              | 19.6 | 35.91              | 11.69         | 30.50          | 1460             | M2801214013K         | N                | (CALL)             | SCR20012965S1H                        | SCR20012865T1H            | (CALL)                 | (CALL)                 |
| OE30C       | ORDER SELECTOR |              | 24 VOLTS , 36.25 X 13.80 X 31.50 |      |                    |               |                |                  | Weight Minimum 1100  | Connector SB175  | RED                | , Position B , Lead Length 018 Inches |                           |                        |                        |
|             | 24             | 125F15       | 875                              | 20.4 | 35.25              | 13.06         | 30.50          | 1662             | M2501212515A         | Y                | (CALL)             | SCR20012965S1H                        | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125C15       | 875                              | 20.4 | 35.25              | 13.06         | 30.50          | 1606             | M2601212515A         | Y                | (CALL)             | SCR20012965S1H                        | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125F13       | 750                              | 17.5 | 35.91              | 11.69         | 30.50          | 1429             | M2501212513K         | N                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125C13       | 750                              | 17.5 | 35.91              | 11.69         | 30.50          | 1381             | M2601212513K         | Y                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 100C15       | 700                              | 16.3 | 35.31              | 13.13         | 25.63          | 1270             | M2601210015A         | N                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 140T15       | 980                              | 22.8 | 35.25              | 13.06         | 30.50          | 1702             | M2801214015A         | Y                | (CALL)             |                                       | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24             | 140T13       | 840                              | 19.6 | 35.91              | 11.69         | 30.50          | 1460             | M2801214013K         | N                | (CALL)             | SCR20012965S1H                        | SCR20012865T1H            | (CALL)                 | (CALL)                 |
| OE30C       | ORDER SELECTOR |              | 36 VOLTS , 38.25 X 13.80 X 31.50 |      |                    |               |                |                  | Weight Minimum 1100  | Connector SB175  | GRAY               | , Position B , Lead Length 018 Inches |                           |                        |                        |
|             | 36             | 125C11       | 625                              | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y                | (CALL)             | SCR20018750S1H                        | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36             | 125F11       | 625                              | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y                | (CALL)             | SCR20018750S1H                        | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36             | 140T11       | 700                              | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y                | (CALL)             | SCR20018750S1H                        | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| OE35        | ORDER SELECTOR |              | 24 VOLTS , 36.25 X 13.80 X 31.50 |      |                    |               |                |                  | Weight Minimum 1100  | Connector SB175  | RED                | , Position B , Lead Length 018 Inches |                           |                        |                        |
|             | 24             | 125F15       | 875                              | 20.4 | 35.25              | 13.06         | 30.50          | 1662             | M2501212515A         | Y                | (CALL)             | SCR20012965S1H                        | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125C15       | 875                              | 20.4 | 35.25              | 13.06         | 30.50          | 1606             | M2601212515A         | Y                | (CALL)             | SCR20012965S1H                        | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125F13       | 750                              | 17.5 | 35.91              | 11.69         | 30.50          | 1429             | M2501212513K         | N                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 125C13       | 750                              | 17.5 | 35.91              | 11.69         | 30.50          | 1381             | M2601212513K         | Y                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 100C15       | 700                              | 16.3 | 35.31              | 13.13         | 25.63          | 1270             | M2601210015A         | N                | (CALL)             | SCR20012750S1H                        | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 140T15       | 980                              | 22.8 | 35.25              | 13.06         | 30.50          | 1702             | M2801214015A         | Y                | (CALL)             |                                       | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24             | 140T13       | 840                              | 19.6 | 35.91              | 11.69         | 30.50          | 1460             | M2801214013K         | N                | (CALL)             | SCR20012965S1H                        | SCR20012865T1H            | (CALL)                 | (CALL)                 |
| OE35        | ORDER SELECTOR |              | 36 VOLTS , 38.25 X 13.80 X 31.50 |      |                    |               |                |                  | Weight Minimum 1100  | Connector SB175  | GRAY               | , Position B , Lead Length 018 Inches |                           |                        |                        |
|             | 36             | 125C11       | 625                              | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y                | (CALL)             | SCR20018750S1H                        | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36             | 125F11       | 625                              | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y                | (CALL)             | SCR20018750S1H                        | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36             | 140T11       | 700                              | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y                | (CALL)             | SCR20018750S1H                        | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| RRB2        | REACH TRUCK    |              | 48 VOLTS , 47.50 X 13.53 X 35.44 |      |                    |               |                |                  | Weight Minimum 1800  | Connector SBX350 | GRAY               | , Position B , Lead Length 030 Inches |                           |                        |                        |
|             | 48             | 125C09       | 500                              | 23.3 | 47.50              | 13.53         | 35.44          | 2037             | M2602412509Y36N      | N                | (CALL)             | SCR20024600S1H                        | SCR20024600T1H            | (CALL)                 | (CALL)                 |
|             | 48             | 140T09       | 560                              | 26.1 | 47.50              | 13.53         | 35.44          | 2177             | M2802414009Y36N      | N                | (CALL)             | SCR20024600S1H                        | SCR20024600T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL  | VOLT                     | BATTERY TYPE | CAPACITY 6 HOUR RATE   |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|--------------|--------------------------|--------------|--|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|              |                          |              | A.H.   | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| <b>RDX30</b> | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.80 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 36                       | 125C13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 125F13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 045B31       | 675  | 23.8 | 39.25              | 15.99         | 30.69          | 2070             | M2101804531B37       | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 140T13       | 840  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 125L13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| <b>RDX30</b> | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.80 X 20.90 X 32.00 Weight Minimum 2400 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 36                       | 125C17       | 1000   | 34.9 | 38.31              | 20.13         | 30.50          | 2673             | M2601812517B         | Y     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |
|              | 36                       | 125F17       | 1000   | 34.9 | 38.31              | 20.13         | 30.50          | 2762             | M2501812517B         | Y     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |
|              | 36                       | 140T17       | 1120   | 39.1 | 38.31              | 20.13         | 30.50          | 2843             | M2801814017B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |
|              | 36                       | 060B31       | 900  | 31.8 | 39.50              | 20.25         | 30.69          | 2625             | M2101806031B0        | N     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |
| <b>RRX35</b> | <b>REACH, DEEP REACH</b> |              | <b>24 VOLTS , 38.75 X 14.40 X 32.00 Weight Minimum 1600 Connector SB350 RED , Position C , Lead Length 015 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 24                       | 125F17       | 1000   | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|              | 24                       | 125C17       | 1000   | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|              | 24                       | 170C11       | 850  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|              | 24                       | 140T17       | 1120   | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |                            | SCR200121200T1H           | (CALL)                 | (CALL)                 |
|              | 24                       | 125L17       | 1000   | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
| <b>RRX35</b> | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.75 X 14.40 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 36                       | 125C11       | 625  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 125F11       | 625  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 140T11       | 700  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| <b>RRX35</b> | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.75 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 36                       | 125C13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 125F13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 140T13       | 840  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 125L13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| <b>RRX45</b> | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.80 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 36                       | 125C13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 125F13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 045B31       | 675  | 23.8 | 39.25              | 15.99         | 30.69          | 2070             | M2101804531B37       | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 140T13       | 840  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |
|              | 36                       | 125L13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| <b>RRX45</b> | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.80 X 20.90 X 32.00 Weight Minimum 2400 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 36                       | 125C17       | 1000   | 34.9 | 38.31              | 20.13         | 30.50          | 2673             | M2601812517B         | Y     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |
|              | 36                       | 125F17       | 1000   | 34.9 | 38.31              | 20.13         | 30.50          | 2762             | M2501812517B         | Y     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |
|              | 36                       | 140T17       | 1120   | 39.1 | 38.31              | 20.13         | 30.50          | 2843             | M2801814017B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |
|              | 36                       | 060B31       | 900  | 31.8 | 39.50              | 20.25         | 30.69          | 2625             | M2101806031B0        | N     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# BT Prime Mover Selector Guide

| TRUCK MODEL    | VOLT                     | BATTERY TYPE | CAPACITY 6 HOUR RATE                    |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE  | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE                | T-1 CHARGER LIST PRICE |
|----------------|--------------------------|--------------|---|------|--------------------|---------------|----------------|------------------|----------------------|-------|---------------------|----------------------------|---------------------------|---------------------------------------|------------------------|
|                |                          |              | A.H.                                    | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                     |                            |                           |                                       |                        |
| <b>RSX40</b>   | <b>REACH, DEEP REACH</b> |              | <b>24 VOLTS , 38.75 X 14.40 X 32.00</b> |      |                    |               |                |                  |                      |       |                     |                            |                           |                                       |                        |
|                |                          |              |   |      |                    |               |                |                  |                      |       | Weight Minimum 1600 | Connector SB350            | RED                       | , Position C , Lead Length 015 Inches |                        |
|                | 24                       | 125F17       | 1000                                    | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)              |                            | SCR200121050T1H           | (CALL)                                | (CALL)                 |
|                | 24                       | 125C17       | 1000                                    | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)              |                            | SCR200121050T1H           | (CALL)                                | (CALL)                 |
|                | 24                       | 170C11       | 850                                     | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)              | SCR20012965S1H             | SCR20012865T1H            | (CALL)                                | (CALL)                 |
|                | 24                       | 140T17       | 1120                                    | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)              |                            | SCR200121200T1H           | (CALL)                                | (CALL)                 |
|                | 24                       | 125L17       | 1000                                    | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)              |                            | SCR200121050T1H           | (CALL)                                | (CALL)                 |
| <b>RSX40</b>   | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.75 X 14.40 X 32.00</b> |      |                    |               |                |                  |                      |       |                     |                            |                           |                                       |                        |
|                |                          |              |   |      |                    |               |                |                  |                      |       | Weight Minimum 1600 | Connector SB350            | GRAY                      | , Position C , Lead Length 015 Inches |                        |
|                | 36                       | 125C11       | 625                                     | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 125F11       | 625                                     | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 140T11       | 700                                     | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
| <b>RSX40</b>   | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.75 X 16.40 X 32.00</b> |      |                    |               |                |                  |                      |       |                     |                            |                           |                                       |                        |
|                |                          |              |   |      |                    |               |                |                  |                      |       | Weight Minimum 2000 | Connector SB350            | GRAY                      | , Position C , Lead Length 015 Inches |                        |
|                | 36                       | 125C13       | 750                                     | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 125F13       | 750                                     | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 140T13       | 840                                     | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)              | SCR20018865S1H             | SCR20018865T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 125L13       | 750                                     | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
| <b>RSX50</b>   | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.80 X 16.40 X 32.00</b> |      |                    |               |                |                  |                      |       |                     |                            |                           |                                       |                        |
|                |                          |              |   |      |                    |               |                |                  |                      |       | Weight Minimum 2000 | Connector SB350            | GRAY                      | , Position C , Lead Length 015 Inches |                        |
|                | 36                       | 125C13       | 750                                     | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 125F13       | 750                                     | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 045B31       | 675                                     | 23.8 | 39.25              | 15.99         | 30.69          | 2070             | M2101804531B37       | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 140T13       | 840                                     | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)              | SCR20018865S1H             | SCR20018865T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 125L13       | 750                                     | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
| <b>RSX50</b>   | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.80 X 20.90 X 32.00</b> |      |                    |               |                |                  |                      |       |                     |                            |                           |                                       |                        |
|                |                          |              |   |      |                    |               |                |                  |                      |       | Weight Minimum 2400 | Connector SB350            | GRAY                      | , Position C , Lead Length 015 Inches |                        |
|                | 36                       | 125C17       | 1000                                    | 34.9 | 38.31              | 20.13         | 30.50          | 2673             | M2601812517B         | Y     | (CALL)              |                            | SCR200181050T1H           | (CALL)                                | (CALL)                 |
|                | 36                       | 125F17       | 1000                                    | 34.9 | 38.31              | 20.13         | 30.50          | 2762             | M2501812517B         | Y     | (CALL)              |                            | SCR200181050T1H           | (CALL)                                | (CALL)                 |
|                | 36                       | 140T17       | 1120                                    | 39.1 | 38.31              | 20.13         | 30.50          | 2843             | M2801814017B         | Y     | (CALL)              |                            | SCR200181200T1H           | (CALL)                                | (CALL)                 |
|                | 36                       | 060B31       | 900                                     | 31.8 | 39.50              | 20.25         | 30.69          | 2625             | M2101806031B0        | N     | (CALL)              |                            | SCR20018965T1H            | (CALL)                                | (CALL)                 |
| <b>RTX30DR</b> | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.80 X 16.40 X 32.00</b> |      |                    |               |                |                  |                      |       |                     |                            |                           |                                       |                        |
|                |                          |              |   |      |                    |               |                |                  |                      |       | Weight Minimum 2000 | Connector SB350            | GRAY                      | , Position C , Lead Length 015 Inches |                        |
|                | 36                       | 125C13       | 750                                     | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 125F13       | 750                                     | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 045B31       | 675                                     | 23.8 | 39.25              | 15.99         | 30.69          | 2070             | M2101804531B37       | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 140T13       | 840                                     | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)              | SCR20018865S1H             | SCR20018865T1H            | (CALL)                                | (CALL)                 |
|                | 36                       | 125L13       | 750                                     | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)              | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                | (CALL)                 |
| <b>RTX30DR</b> | <b>REACH, DEEP REACH</b> |              | <b>36 VOLTS , 38.80 X 20.90 X 32.00</b> |      |                    |               |                |                  |                      |       |                     |                            |                           |                                       |                        |
|                |                          |              |   |      |                    |               |                |                  |                      |       | Weight Minimum 2400 | Connector SB350            | GRAY                      | , Position C , Lead Length 015 Inches |                        |
|                | 36                       | 125C17       | 1000                                    | 34.9 | 38.31              | 20.13         | 30.50          | 2673             | M2601812517B         | Y     | (CALL)              |                            | SCR200181050T1H           | (CALL)                                | (CALL)                 |
|                | 36                       | 125F17       | 1000                                    | 34.9 | 38.31              | 20.13         | 30.50          | 2762             | M2501812517B         | Y     | (CALL)              |                            | SCR200181050T1H           | (CALL)                                | (CALL)                 |
|                | 36                       | 140T17       | 1120                                    | 39.1 | 38.31              | 20.13         | 30.50          | 2843             | M2801814017B         | Y     | (CALL)              |                            | SCR200181200T1H           | (CALL)                                | (CALL)                 |
|                | 36                       | 060B31       | 900                                     | 31.8 | 39.50              | 20.25         | 30.69          | 2625             | M2101806031B0        | N     | (CALL)              |                            | SCR20018965T1H            | (CALL)                                | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                        | BATTERY TYPE | CAPACITY 6 HOUR RATE   |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|-----------------------------|--------------|--|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|             |                             |              | A.H.   | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| RTX35       | REACH, DEEP REACH           |              | 24 VOLTS , 38.75 X 14.40 X 32.00      Weight Minimum 1600      Connector SB350      RED , Position C , Lead Length 015 Inches  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                          | 125F17       | 1000   | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 125C17       | 1000   | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 170C11       | 850  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 140T17       | 1120   | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |                            | SCR200121200T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 125L17       | 1000   | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
| RTX35       | REACH, DEEP REACH           |              | 36 VOLTS , 38.75 X 14.40 X 32.00      Weight Minimum 1600      Connector SB350      GRAY , Position C , Lead Length 015 Inches |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 36                          | 125C11       | 625  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 125F11       | 625  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 140T11       | 700  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| RTX35       | REACH, DEEP REACH           |              | 36 VOLTS , 38.75 X 16.40 X 32.00      Weight Minimum 2000      Connector SB350      GRAY , Position C , Lead Length 015 Inches |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 36                          | 125C13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 125F13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 140T13       | 840  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 125L13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| RTX45       | REACH, DEEP REACH           |              | 36 VOLTS , 38.80 X 16.40 X 32.00      Weight Minimum 2000      Connector SB350      GRAY , Position C , Lead Length 015 Inches |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 36                          | 125C13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 125F13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 045B31       | 675  | 23.8 | 39.25              | 15.99         | 30.69          | 2070             | M2101804531B37       | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 140T13       | 840  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 125L13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| RTX45       | REACH, DEEP REACH           |              | 36 VOLTS , 38.80 X 20.90 X 32.00      Weight Minimum 2400      Connector SB350      GRAY , Position C , Lead Length 015 Inches |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 36                          | 125C17       | 1000   | 34.9 | 38.31              | 20.13         | 30.50          | 2673             | M2601812517B         | Y     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |
|             | 36                          | 125F17       | 1000   | 34.9 | 38.31              | 20.13         | 30.50          | 2762             | M2501812517B         | Y     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |
|             | 36                          | 140T17       | 1120   | 39.1 | 38.31              | 20.13         | 30.50          | 2843             | M2801814017B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |
|             | 36                          | 060B31       | 900  | 31.8 | 39.50              | 20.25         | 30.69          | 2625             | M2101806031B0        | N     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |
| RR30        | RIDER REACH, STRADDLE TRUCK |              | 24 VOLTS , 38.75 X 14.50 X 32.00      Weight Minimum 0      Connector SB350      GRAY , Position C , Lead Length 020 Inches    |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                          | 125F17       | 1000   | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 125C17       | 1000   | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 125F15       | 875  | 20.4 | 38.18              | 11.98         | 30.50          | 1619             | M2501212515B         | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125C15       | 875  | 20.4 | 38.18              | 11.98         | 30.50          | 1562             | M2601212515B         | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 170C11       | 850  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 100C15       | 700  | 16.3 | 35.31              | 13.13         | 25.63          | 1270             | M2601210015A         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 140T17       | 1120   | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |                            | SCR200121200T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 140T15       | 980  | 22.8 | 38.18              | 11.98         | 30.50          | 1638             | M2801214015B         | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 125L15       | 875  | 20.4 | 38.18              | 11.98         | 30.50          | 1588             | M2901212515B         | N     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125L17       | 1000   | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
| RR30        | RIDER REACH, STRADDLE TRUCK |              | 36 VOLTS , 38.75 X 14.50 X 32.00      Weight Minimum 0      Connector SB350      GRAY , Position C , Lead Length 020 Inches    |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 36                          | 125C11       | 625  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 125F11       | 625  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 140T11       | 700  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL  | VOLT                               | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)              | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                            |                        |             |  |
|--------------|------------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|---|---------------------------|------------------------|------------------------|----------------------------|------------------------|-------------|--|
|              |                                    |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |   |                           |                        |                        |                            |                        |             |  |
| <b>RR30</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                          | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR30B</b> | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 24                                 | 125F17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125F15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1619             | M2501212515B         | Y     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1562             | M2601212515B         | Y     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 170C11       | 850                  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H                          | SCR20012865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 100C15       | 700                  | 16.3 | 35.31              | 13.13         | 25.63          | 1270             | M2601210015A         | N     | (CALL)             | SCR20012750S1H                          | SCR20012750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T17       | 1120                 | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |   | SCR200121200T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T15       | 980                  | 22.8 | 38.18              | 11.98         | 30.50          | 1638             | M2801214015B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1588             | M2901212515B         | N     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR30B</b> | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR30B</b> | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                          | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR30C</b> | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 1600</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 24                                 | 125F17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 170C11       | 850                  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H                          | SCR20012865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T17       | 1120                 | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |   | SCR200121200T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR30C</b> | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                          | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL  | VOLT                               | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)              | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                            |                        |             |  |
|--------------|------------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|---|---------------------------|------------------------|------------------------|----------------------------|------------------------|-------------|--|
|              |                                    |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |   |                           |                        |                        |                            |                        |             |  |
| <b>RR34</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 24                                 | 125F17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125F15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1619             | M2501212515B         | Y     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1562             | M2601212515B         | Y     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 170C11       | 850                  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H                          | SCR20012865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 100C15       | 700                  | 16.3 | 35.31              | 13.13         | 25.63          | 1270             | M2601210015A         | N     | (CALL)             | SCR20012750S1H                          | SCR20012750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T17       | 1120                 | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |   | SCR200121200T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T15       | 980                  | 22.8 | 38.18              | 11.98         | 30.50          | 1638             | M2801214015B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1588             | M2901212515B         | N     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR34</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR34</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                          | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR34B</b> | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 1600</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 24                                 | 125F17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 170C11       | 850                  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H                          | SCR20012865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T17       | 1120                 | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |   | SCR200121200T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR40</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 24                                 | 125F17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125F15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1619             | M2501212515B         | Y     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1562             | M2601212515B         | Y     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 170C11       | 850                  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H                          | SCR20012865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 100C15       | 700                  | 16.3 | 35.31              | 13.13         | 25.63          | 1270             | M2601210015A         | N     | (CALL)             | SCR20012750S1H                          | SCR20012750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T17       | 1120                 | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |   | SCR200121200T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T15       | 980                  | 22.8 | 38.18              | 11.98         | 30.50          | 1638             | M2801214015B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1588             | M2901212515B         | N     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR40</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL  | VOLT                               | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)              | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                            |                        |             |  |
|--------------|------------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|---|---------------------------|------------------------|------------------------|----------------------------|------------------------|-------------|--|
|              |                                    |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |   |                           |                        |                        |                            |                        |             |  |
| <b>RR40</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                          | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR40B</b> | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 24                                 | 125F17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125F15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1619             | M2501212515B         | Y     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1562             | M2601212515B         | Y     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 170C11       | 850                  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H                          | SCR20012865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 100C15       | 700                  | 16.3 | 35.31              | 13.13         | 25.63          | 1270             | M2601210015A         | N     | (CALL)             | SCR20012750S1H                          | SCR20012750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T17       | 1120                 | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |   | SCR200121200T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T15       | 980                  | 22.8 | 38.18              | 11.98         | 30.50          | 1638             | M2801214015B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L15       | 875                  | 20.4 | 38.18              | 11.98         | 30.50          | 1588             | M2901212515B         | N     | (CALL)             | SCR20012965S1H                          | SCR20012965T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR40B</b> | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR40B</b> | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                          | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RR45</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 1600</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 24                                 | 125F17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125C17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 170C11       | 850                  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H                          | SCR20012865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 140T17       | 1120                 | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |   | SCR200121200T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 24                                 | 125L17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RS40</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 14.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
| <b>RS40</b>  | <b>RIDER REACH, STRADDLE TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b> |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b> |
|              | 36                                 | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                          | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |
|              | 36                                 | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                          | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL                  | VOLT                                  | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)                | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                            |                        |             |   |
|------------------------------|---------------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|---|---------------------------|------------------------|------------------------|----------------------------|------------------------|-------------|---|
|                              |                                       |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |   |                           |                        |                        |                            |                        |             |   |
| <b>RS40C</b>                 | <b>RIDER REACH, STRADDLE TRUCK</b>    |              |                      |      |                    |               |                |                  |                      |       |                    | <b>24 VOLTS , 38.75 X 14.50 X 32.00</b>   |                           |                        |                        | <b>Weight Minimum 1600</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b>  |
|                              | 24                                    | 125F17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1839             | M2501212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 24                                    | 125C17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1775             | M2601212517B         | Y     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 24                                    | 170C11       | 850                  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H                            | SCR20012865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 24                                    | 140T17       | 1120                 | 26.1 | 38.13              | 13.44         | 30.50          | 1885             | M2801214017B         | Y     | (CALL)             |   | SCR200121200T1H           | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 24                                    | 125L17       | 1000                 | 23.3 | 38.13              | 13.44         | 30.50          | 1809             | M2901212517B         | N     | (CALL)             |   | SCR200121050T1H           | (CALL)                 | (CALL)                 |                            |                        |             |   |
| <b>RS40C</b>                 | <b>RIDER REACH, STRADDLE TRUCK</b>    |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 14.50 X 32.00</b>   |                           |                        |                        | <b>Weight Minimum 1600</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b>  |
|                              | 36                                    | 125C11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 125F11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
| <b>RS40C</b>                 | <b>RIDER REACH, STRADDLE TRUCK</b>    |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b>   |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b>  |
|                              | 36                                    | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                            | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
| <b>RS50</b>                  | <b>RIDER REACH, STRADDLE TRUCK</b>    |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 14.50 X 32.00</b>   |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b>  |
|                              | 36                                    | 125C11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 125F11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
| <b>RS50</b>                  | <b>RIDER REACH, STRADDLE TRUCK</b>    |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b>   |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b>  |
|                              | 36                                    | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                            | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
| <b>RS50B</b>                 | <b>RIDER REACH, STRADDLE TRUCK</b>    |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 14.50 X 32.00</b>   |                           |                        |                        | <b>Weight Minimum 0</b>    | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b>  |
|                              | 36                                    | 125C11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 125F11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
| <b>RS50B</b>                 | <b>RIDER REACH, STRADDLE TRUCK</b>    |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 16.50 X 32.00</b>   |                           |                        |                        | <b>Weight Minimum 2000</b> | <b>Connector SB350</b> | <b>GRAY</b> | <b>, Position C , Lead Length 020 Inches</b>  |
|                              | 36                                    | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H                            | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 36                                    | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H                            | SCR20018750T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
| <b>RT30</b>                  | <b>SIDE SITTING RIDER REACH TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 13.50 X 999.00 X 999.00</b> |                           |                        |                        | <b>Weight Minimum 1910</b> | <b>Connector SB350</b> | <b>BLUE</b> | <b>, Position N/A, Lead Length 000 Inches</b> |
|                              | 48                                    | 125C09       | 500                  | 23.3 | 47.50              | 13.53         | 32.88          | 2004             | M2602412509Y36       | N     | (CALL)             | SCR20024600S1H                            | SCR20024600T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 48                                    | 125C09       | 500                  | 23.3 | 47.50              | 13.88         | 33.06          | 1930             | M2602412509Y36A      | N     | (CALL)             | SCR20024600S1H                            | SCR20024600T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 48                                    | 140T09       | 560                  | 26.1 | 47.50              | 13.53         | 32.88          | 2100             | M2802414009Y36       | N     | (CALL)             | SCR20024600S1H                            | SCR20024600T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
|                              | 48                                    | 140T09       | 560                  | 26.1 | 47.50              | 13.88         | 33.06          | 1930             | M2802414009Y36A      | N     | (CALL)             | SCR20024600S1H                            | SCR20024600T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |
| <b>RT30C,'94&amp;Earlier</b> | <b>SIDE SITTING RIDER REACH TRUCK</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 13.50 X 999.00 X 999.00</b> |                           |                        |                        | <b>Weight Minimum 1345</b> | <b>Connector SB350</b> | <b>BLUE</b> | <b>, Position N/A, Lead Length 000 Inches</b> |
|                              | 48                                    | 125C07       | 375                  | 17.5 | 40.94              | 13.69         | 33.63          | 1550             | M2602412507B36A      | N     | (CALL)             | SCR20024475S1H                            | SCR20024475T1H            | (CALL)                 | (CALL)                 |                            |                        |             |   |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



| TRUCK MODEL  | VOLT                           | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|--|--------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|  |                                |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| RT30C,'94&Earlier  | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C09       | 500                  | 23.3 | 40.94              | 16.88         | 33.44          | 1930             | M2602412509B36       | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 17.00 X 999.00 X 999.00 Weight Minimum 1720 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT30C,'95  | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C07       | 375                  | 17.5 | 40.94              | 13.38         | 35.44          | 1684             | M2602412507B36N      | N     | ( CALL )           | SCR20024475S1H             | SCR20024475T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 13.50 X 999.00 X 999.00 Weight Minimum 1345 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT30C,'96&Later  | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C07       | 375                  | 17.5 | 40.94              | 13.38         | 33.44          | 1641             | M2602412507B36       | N     | ( CALL )           | SCR20024475S1H             | SCR20024475T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 13.50 X 999.00 X 999.00 Weight Minimum 1345 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT30C,'96&Later  | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C09       | 500                  | 23.3 | 40.94              | 17.19         | 33.63          | 1930             | M2602412509B36A      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 17.00 X 999.00 X 999.00 Weight Minimum 1720 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT35,'94&Earlier   | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C09       | 500                  | 23.3 | 47.50              | 13.53         | 32.88          | 2004             | M2602412509Y36       | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 140T09       | 560                  | 26.1 | 47.50              | 13.53         | 32.88          | 2100             | M2802414009Y36       | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 13.50 X 999.00 X 999.00 Weight Minimum 1910 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT35,'95   | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C09       | 500                  | 23.3 | 47.50              | 13.88         | 33.06          | 1930             | M2602412509Y36A      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 125C09       | 500                  | 23.3 | 47.50              | 13.53         | 35.44          | 2037             | M2602412509Y36N      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 140T09       | 560                  | 26.1 | 47.50              | 13.53         | 35.44          | 2177             | M2802414009Y36N      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 140T09       | 560                  | 26.1 | 47.50              | 13.88         | 33.06          | 1930             | M2802414009Y36A      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 13.50 X 999.00 X 999.00 Weight Minimum 1910 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT35C,'94&Earlier  | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C07       | 375                  | 17.5 | 40.94              | 13.38         | 33.44          | 1641             | M2602412507B36       | N     | ( CALL )           | SCR20024475S1H             | SCR20024475T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 125C07       | 375                  | 17.5 | 40.94              | 13.69         | 33.63          | 1550             | M2602412507B36A      | N     | ( CALL )           | SCR20024475S1H             | SCR20024475T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 13.50 X 999.00 X 999.00 Weight Minimum 1345 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT35C,'94&Earlier  | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C09       | 500                  | 23.3 | 40.94              | 16.88         | 33.44          | 1930             | M2602412509B36       | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 125C09       | 500                  | 23.3 | 40.94              | 17.19         | 33.63          | 1930             | M2602412509B36A      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 17.00 X 999.00 X 999.00 Weight Minimum 1720 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT35C,'95  | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C07       | 375                  | 17.5 | 40.94              | 13.38         | 35.44          | 1684             | M2602412507B36N      | N     | ( CALL )           | SCR20024475S1H             | SCR20024475T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 13.50 X 999.00 X 999.00 Weight Minimum 1345 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT40,'94&Earlier   | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C09       | 500                  | 23.3 | 47.50              | 13.53         | 32.88          | 2004             | M2602412509Y36       | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 125C09       | 500                  | 23.3 | 47.50              | 13.88         | 33.06          | 1930             | M2602412509Y36A      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 140T09       | 560                  | 26.1 | 47.50              | 13.53         | 32.88          | 2100             | M2802414009Y36       | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 140T09       | 560                  | 26.1 | 47.50              | 13.88         | 33.06          | 1930             | M2802414009Y36A      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 13.50 X 999.00 X 999.00 Weight Minimum 1910 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT44,'94&Earlier   | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C09       | 500                  | 23.3 | 47.50              | 13.53         | 32.88          | 2004             | M2602412509Y36       | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 125C09       | 500                  | 23.3 | 47.50              | 13.88         | 33.06          | 1930             | M2602412509Y36A      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 140T09       | 560                  | 26.1 | 47.50              | 13.53         | 32.88          | 2100             | M2802414009Y36       | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 140T09       | 560                  | 26.1 | 47.50              | 13.88         | 33.06          | 1930             | M2802414009Y36A      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 13.50 X 999.00 X 999.00 Weight Minimum 1910 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
| RT44,'95   | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|  | 48                             | 125C09       | 500                  | 23.3 | 47.50              | 13.53         | 35.44          | 2037             | M2602412509Y36N      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
|  | 48                             | 140T09       | 560                  | 26.1 | 47.50              | 13.53         | 35.44          | 2177             | M2802414009Y36N      | N     | ( CALL )           | SCR20024600S1H             | SCR20024600T1H            | ( CALL )               | ( CALL )               |
| 48 VOLTS , 13.50 X 999.00 X 999.00 Weight Minimum 1910 Connector SB350 BLUE , Position N/A, Lead Length 000 Inches |                                |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL       | VOLT                           | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                                    |  |  |                     |                 |  |
|-------------------|--------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|------------------------------------|--|--|---------------------|-----------------|--|
|                   |                                |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |                                    |  |  |                     |                 |  |
| RT44C,'94&Earlier | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | 48 VOLTS , 13.50 X 999.00 X 999.00 |  |  | Weight Minimum 1345 | Connector SB350 | BLUE , Position N/A, Lead Length 000 Inches  |
|                   | 48                             | 125C07       | 375                  | 17.5 | 40.94              | 13.38         | 33.44          | 1641             | M2602412507B36       | N     | (CALL)             | SCR20024475S1H             | SCR20024475T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 48                             | 125C07       | 375                  | 17.5 | 40.94              | 13.69         | 33.63          | 1550             | M2602412507B36A      | N     | (CALL)             | SCR20024475S1H             | SCR20024475T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
| RT44C,'94&Earlier | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | 48 VOLTS , 17.00 X 999.00 X 999.00 |  |  | Weight Minimum 1720 | Connector SB350 | BLUE , Position N/A, Lead Length 000 Inches  |
|                   | 48                             | 125C09       | 500                  | 23.3 | 40.94              | 16.88         | 33.44          | 1930             | M2602412509B36       | N     | (CALL)             | SCR20024600S1H             | SCR20024600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 48                             | 125C09       | 500                  | 23.3 | 40.94              | 17.19         | 33.63          | 1930             | M2602412509B36A      | N     | (CALL)             | SCR20024600S1H             | SCR20024600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
| RT50,'94&Earlier  | SIDE SITTING RIDER REACH TRUCK |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | 48 VOLTS , 19.30 X 999.00 X 999.00 |  |  | Weight Minimum 2860 | Connector SB350 | BLUE , Position N/A, Lead Length 000 Inches  |
|                   | 48                             | 125C15       | 875                  | 40.7 | 47.50              | 19.31         | 32.88          | 3100             | M2602412515M36       | N     | (CALL)             |                            | SCR20024965T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
| CRX40/50          | STAND UP COUNTERBALANCE        |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | 36 VOLTS , 38.50 X 21.00 X 32.30   |  |  | Weight Minimum 2700 | Connector SB350 | GRAY , Position C , Lead Length 013 Inches   |
|                   | 36                             | 060B31       | 900                  | 31.8 | 39.62              | 20.47         | 30.81          | 3015             | M2101806031B15       | N     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
| CRX30/35          | STAND UP, COUNTERBALANCE       |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | 36 VOLTS , 38.50 X 16.25 X 32.30   |  |  | Weight Minimum 2000 | Connector SB350 | GRAY , Position C , Lead Length 013 Inches   |
|                   | 36                             | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 125F13       | 750                  | 26.2 | 38.13              | 15.88         | 30.56          | 2132             | M2501812513B28       | N     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 125C13       | 750                  | 26.2 | 38.13              | 15.88         | 30.56          | 2060             | M2601812513B28       | N     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 045B31       | 675                  | 23.8 | 39.25              | 15.99         | 30.69          | 2070             | M2101804531B37       | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 140T13       | 840                  | 29.3 | 38.13              | 15.88         | 30.56          | 2225             | M2801814013B28       | N     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 125L13       | 750                  | 26.2 | 38.13              | 15.88         | 30.50          | 2120             | M2901812513B28       | N     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
| CRX30/35          | STAND UP, COUNTERBALANCE       |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | 36 VOLTS , 38.50 X 18.50 X 32.30   |  |  | Weight Minimum 2300 | Connector SB350 | GRAY , Position C , Lead Length 013 Inches   |
|                   | 36                             | 055B31       | 825                  | 29.1 | 39.50              | 18.04         | 30.69          | 2380             | M2101805531B         | N     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 125C15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 125F15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 140T15       | 980                  | 34.2 | 38.25              | 17.81         | 30.50          | 2492             | M2801814015B         | Y     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 36                             | 125L15       | 875                  | 30.6 | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
| SC20              | WALKIE STACKER                 |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | 12 VOLTS , 32.50 X 14.00 X 999.00  |  |  | Weight Minimum 500  | Connector SB175 | YELLOW , Position B , Lead Length 015 Inches |
|                   | 12                             | 085F13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 085F13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 085C13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 085C13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 100C13       | 600                  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 100C13       | 600                  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 125F13       | 750                  | 8.7  | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 125C13       | 750                  | 8.7  | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 085C21       | 850                  | 9.9  | 24.63              | 12.88         | 23.25          | 801              | M1600608521C         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 100T13       | 600                  | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 100T13       | 600                  | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 140T13       | 840                  | 9.8  | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 085L13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 085L13       | 510                  | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |
|                   | 12                             | 125L13       | 750                  | 8.7  | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |                                    |  |  |                     |                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# BT Prime Mover Selector Guide

| TRUCK MODEL | VOLT           | BATTERY TYPE | CAPACITY 6 HOUR RATE   |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|----------------|--------------|--|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|             |                |              | A.H.   | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| SC20        | WALKIE STACKER |              | 24 VOLTS , 32.50 X 14.00 X 999.00 Weight Minimum 500 Connector SB175 RED , Position B , Lead Length 015 Inches   |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24             | 085F13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 085C13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| SC30        | WALKIE STACKER |              | 24 VOLTS , 32.50 X 14.00 X 999.00 Weight Minimum 1000 Connector SB175 RED , Position B , Lead Length 015 Inches  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24             | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| SC40        | WALKIE STACKER |              | 24 VOLTS , 32.50 X 14.00 X 999.00 Weight Minimum 1000 Connector SB175 RED , Position B , Lead Length 015 Inches  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24             | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| SN20        | WALKIE STACKER |              | 12 VOLTS , 32.00 X 8.00 X 999.00 Weight Minimum 300 Connector SB175 YELLOW , Position B , Lead Length 015 Inches |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 12             | 085F13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 085F13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 085C13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 085C13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 100C13       | 600  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 100C13       | 600  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 100G09       | 400  | 4.7  | 30.88              | 7.75          | 23.98          | 500              | M8900610009APP       | Y     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|             | 12             | 125F13       | 750  | 8.7  | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 125C13       | 750  | 8.7  | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 100C11       | 500  | 5.8  | 29.00              | 8.50          | 26.13          | 515              | M1600610011A6        | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 100C11       | 500  | 5.8  | 29.00              | 8.50          | 26.13          | 515              | M1600610011A6        | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 100T13       | 600  | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 100T13       | 600  | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 140T13       | 840  | 9.8  | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 085L13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 085L13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12             | 125L13       | 750  | 8.7  | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
| SN20        | WALKIE STACKER |              | 24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 300 Connector SB175 RED , Position B , Lead Length 015 Inches   |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24             | 085F13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24             | 085C13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                           | BATTERY TYPE | CAPACITY 6 HOUR RATE   |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|--------------------------------|--------------|--|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|             |                                |              | A.H.   | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| SN30        | WALKIE STACKER                 |              | 12 VOLTS , 32.00 X 8.00 X 999.00 Weight Minimum 300 Connector SB175 YELLOW , Position B , Lead Length 015 Inches |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 12                             | 085F13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 085F13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 534              | M1500608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 085C13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 085C13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 513              | M1600608513A         | Y     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 100C13       | 600  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 100C13       | 600  | 7.0  | 30.56              | 7.75          | 26.13          | 632              | M1600610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 100G09       | 400  | 4.7  | 30.88              | 7.75          | 23.98          | 500              | M8900610009APP       | Y     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|             | 12                             | 125F13       | 750  | 8.7  | 30.56              | 7.69          | 31.00          | 709              | M1500612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 125C13       | 750  | 8.7  | 30.56              | 7.69          | 31.00          | 708              | M1600612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 100C11       | 500  | 5.8  | 29.00              | 8.50          | 26.13          | 515              | M1600610011A6        | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 100C11       | 500  | 5.8  | 29.00              | 8.50          | 26.13          | 515              | M1600610011A6        | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 100T13       | 600  | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 100T13       | 600  | 7.0  | 30.44              | 7.63          | 23.25          | 543              | M1800610013A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 140T13       | 840  | 9.8  | 30.56              | 7.69          | 31.00          | 755              | M1800614013A         | N     | (CALL)             | SCR20006865S1H             | SCR20006865T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 085L13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 085L13       | 510  | 5.9  | 30.44              | 7.63          | 23.25          | 523              | M1900608513A         | N     | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12                             | 125L13       | 750  | 8.7  | 30.56              | 7.69          | 31.00          | 740              | M1900612513A         | N     | (CALL)             |                            | SCR20006750T1H            | (CALL)                 | (CALL)                 |
| SN30        | WALKIE STACKER                 |              | 24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 300 Connector SB175 RED , Position B , Lead Length 015 Inches   |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                             | 085F13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 085C13       | 510  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| SN40        | WALKIE STACKER                 |              | 24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 1000 Connector SB175 RED , Position B , Lead Length 015 Inches  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                             | 100T13       | 600  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
| RC20        | RIDER COUNTER BALANCED STACKER |              | 24 VOLTS , 36.25 X 12.00 X 33.50 Weight Minimum 1200 Connector SB175 N/A , Position B , Lead Length 018 Inches   |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                             | 125C13       | 750  | 17.5 | 35.75              | 11.63         | 31.00          | 1390             | M1601212513K         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 125C11       | 625  | 14.6 | 32.13              | 10.94         | 31.00          | 1205             | M1601212511J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 140T11       | 700  | 16.3 | 32.13              | 10.94         | 31.00          | 1260             | M1801214011J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 125L11       | 625  | 14.6 | 32.13              | 10.94         | 31.00          | 1290             | M1901212511J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
| RC25        | RIDER COUNTER BALANCED STACKER |              | 24 VOLTS , 36.25 X 12.00 X 33.50 Weight Minimum 1200 Connector SB175 N/A , Position B , Lead Length 018 Inches   |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                             | 125C13       | 750  | 17.5 | 35.75              | 11.63         | 31.00          | 1390             | M1601212513K         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 125C11       | 625  | 14.6 | 32.13              | 10.94         | 31.00          | 1205             | M1601212511J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 140T11       | 700  | 16.3 | 32.13              | 10.94         | 31.00          | 1260             | M1801214011J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 125L11       | 625  | 14.6 | 32.13              | 10.94         | 31.00          | 1290             | M1901212511J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
| RC30        | RIDER COUNTER BALANCED STACKER |              | 24 VOLTS , 36.25 X 12.00 X 33.50 Weight Minimum 1200 Connector SB175 N/A , Position B , Lead Length 018 Inches   |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                             | 125C13       | 750  | 17.5 | 35.75              | 11.63         | 31.00          | 1390             | M1601212513K         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 125C11       | 625  | 14.6 | 32.13              | 10.94         | 31.00          | 1205             | M1601212511J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 140T11       | 700  | 16.3 | 32.13              | 10.94         | 31.00          | 1260             | M1801214011J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24                             | 125L11       | 625  | 14.6 | 32.13              | 10.94         | 31.00          | 1290             | M1901212511J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL  | VOLT                                  | BATTERY TYPE | CAPACITY 6 HOUR RATE   |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|--------------|---------------------------------------|--------------|--|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|              |                                       |              | A.H.   | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| <b>RC30</b>  | <b>RIDER COUNTER BALANCED STACKER</b> |              | <b>24 VOLTS , 36.25 X 16.50 X 33.50 Weight Minimum 1200 Connector SB175 N/A , Position B , Lead Length 018 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 24                                    | 125F15       | 875  | 20.4 | 35.13              | 12.94         | 31.00          | 1638             | M1501212515A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|              | 24                                    | 125C15       | 875  | 20.4 | 35.13              | 12.94         | 31.00          | 1582             | M1601212515A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|              | 24                                    | 125C13       | 750  | 17.5 | 35.75              | 11.63         | 31.00          | 1390             | M1601212513K         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                                    | 140T15       | 980  | 22.8 | 35.13              | 12.94         | 31.00          | 1676             | M1801214015A         | N     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|              | 24                                    | 125L15       | 875  | 20.4 | 35.13              | 12.94         | 31.00          | 1636             | M1901212515A         | N     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
| <b>RC30B</b> | <b>RIDER COUNTER BALANCED STACKER</b> |              | <b>36 VOLTS , 38.68 X 16.00 X 32.00 Weight Minimum 1925 Connector SB350 GRAY , Position A , Lead Length 020 Inches</b> |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 36                                    | 125C13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                                    | 125F13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|              | 36                                    | 140T13       | 840  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |
|              | 36                                    | 125L13       | 750  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| <b>RC40</b>  | <b>RIDER COUNTER BALANCED STACKER</b> |              | <b>24 VOLTS , 36.25 X 12.00 X 33.50 Weight Minimum 1200 Connector SB175 N/A , Position B , Lead Length 018 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 24                                    | 125C13       | 750  | 17.5 | 35.75              | 11.63         | 31.00          | 1390             | M1601212513K         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                                    | 125C11       | 625  | 14.6 | 32.13              | 10.94         | 31.00          | 1205             | M1601212511J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                                    | 140T11       | 700  | 16.3 | 32.13              | 10.94         | 31.00          | 1260             | M1801214011J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                                    | 125L11       | 625  | 14.6 | 32.13              | 10.94         | 31.00          | 1290             | M1901212511J         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
| <b>RC40</b>  | <b>RIDER COUNTER BALANCED STACKER</b> |              | <b>24 VOLTS , 36.25 X 16.50 X 33.50 Weight Minimum 1200 Connector SB175 N/A , Position B , Lead Length 018 Inches</b>  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|              | 24                                    | 125F15       | 875  | 20.4 | 35.13              | 12.94         | 31.00          | 1638             | M1501212515A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|              | 24                                    | 125C15       | 875  | 20.4 | 35.13              | 12.94         | 31.00          | 1582             | M1601212515A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|              | 24                                    | 125C13       | 750  | 17.5 | 35.75              | 11.63         | 31.00          | 1390             | M1601212513K         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|              | 24                                    | 140T15       | 980  | 22.8 | 35.13              | 12.94         | 31.00          | 1676             | M1801214015A         | N     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|              | 24                                    | 125L15       | 875  | 20.4 | 35.13              | 12.94         | 31.00          | 1636             | M1901212515A         | N     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)