



# Cat Lift Trucks 2012 Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
<b>2ET2500</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>			<b>48 VOLTS , 32.68 X 20.55 X 24.69</b>											<b>Weight Minimum 1497</b>	<b>Connector EBC320</b>	<b>BLACK</b>	<b>, Position A , Lead Length 016 Inches</b>
	48	100T09	400	18.6	32.56	20.38	23.38	1615	M2802410009Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
	48	085L09	340	15.8	32.50	20.00	23.37	1525	M2902408509Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
	48	085F09	340	15.8	32.56	20.38	23.38	1599	M2502408509Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
	48	085C09	340	15.8	32.63	20.50	23.38	1520	M2602408509Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
<b>2ET3000/3500/4000</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>			<b>48 VOLTS , 32.68 X 29.06 X 24.69</b>											<b>Weight Minimum 2147</b>	<b>Connector EBC320</b>	<b>BLACK</b>	<b>, Position A , Lead Length 016 Inches</b>
	48	100T13	600	27.9	32.56	28.88	22.63	2354	M2802410013Z6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085L13	510	23.7	32.56	28.88	22.63	2293	M2902408513Z6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F13	510	23.7	32.56	28.88	22.63	2351	M2502408513Z6	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C13	510	23.7	32.56	28.88	22.63	2229	M2602408513Z6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100G11	500	23.5	31.89	28.75	23.18	2300	M8902410011Z782	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
<b>2ETC3000/3500</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>			<b>48 VOLTS , 32.68 X 24.80 X 24.69</b>											<b>Weight Minimum 1791</b>	<b>Connector EBC320</b>	<b>BLACK</b>	<b>, Position A , Lead Length 016 Inches</b>
	48	100T11	500	23.3	32.00	24.38	22.62	1942	M2802410011Z6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085L11	425	19.8	32.00	24.38	22.62	1878	M2902408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
	48	085F11	425	19.8	32.00	24.38	22.62	1949	M2502408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
	48	085C11	425	19.8	32.00	24.50	22.62	1835	M2602408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
	48	075B13	450	21.2	31.89	23.79	23.33	1880	M2102407513Z782	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
<b>E3000 / 3500 / EC4000</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>36 VOLTS , 35.80 X 27.80 X 23.30</b>											<b>Weight Minimum 1650</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 024 Inches</b>
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085L19	765	26.7	35.18	25.81	22.62	2285	M2901808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
<b>E3000 / 3500 / EC4000</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>48 VOLTS , 35.80 X 27.80 X 23.30</b>											<b>Weight Minimum 1650</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 024 Inches</b>
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
<b>EC22N2</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>36 VOLTS , 39.50 X 30.50 X 23.30</b>											<b>Weight Minimum 2200</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 024 Inches</b>
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
<b>EC22N2</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>48 VOLTS , 39.50 X 30.50 X 23.30</b>											<b>Weight Minimum 2200</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 024 Inches</b>
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
EC25N2	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.50 X 30.50 X 23.30		Weight Minimum 2600	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
EC25N2	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.50 X 30.50 X 23.30		Weight Minimum 2600	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
EC25EN2/25LN2/30N2/30LN2	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.50 X 34.40 X 23.30		Weight Minimum 3100	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
EC25EN2/25LN2/30N2/30LN2	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.50 X 34.40 X 23.30		Weight Minimum 3100	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	48	100T21	1000	46.6	38.75	33.00	22.63	3441	M2802410021B1	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.75	33.00	22.63	3298	M2902408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F21	850	39.6	38.75	33.00	22.63	3332	M2502408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.75	33.00	22.63	3222	M2602408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
EPC3000/3500	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 32.68 X 24.80 X 24.69		Weight Minimum 1791	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches	
	48	100T11	500	23.3	32.00	24.38	22.62	1942	M2802410011Z6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085L11	425	19.8	32.00	24.38	22.62	1878	M2902408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
	48	085F11	425	19.8	32.00	24.38	22.62	1949	M2502408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
	48	085C11	425	19.8	32.00	24.50	22.62	1835	M2602408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
EP3000/3500/4000	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 32.68 X 29.06 X 24.69		Weight Minimum 2147	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches	
	48	100T13	600	27.9	32.56	28.88	22.63	2386	M2802410013Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085L13	510	23.7	32.75	29.00	22.62	2303	M2902408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C13	510	23.7	32.63	29.00	22.63	2253	M2602408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
EP7000	CLASS I 4 WHEEL COUNTERBALANCED											80 VOLTS , 40.47 X 33.66 X 30.87		Weight Minimum 3900	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches	
	80	140T11	700	54.3	40.25	33.00	30.50	4310	M2804014011X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125L11	625	48.5	40.25	33.10	30.50	4375	M2904012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125F11	625	48.5	40.25	33.00	30.50	4312	M2504012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125C11	625	48.5	40.25	33.00	30.50	4031	M2604012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
2EPC5000 / 2EPC6000	CLASS I 4 WHEEL COUNTERBALANCED											80 VOLTS , 40.47 X 27.99 X 30.87		Weight Minimum 3263	Connector EBC320	BLACK	, Position B , Lead Length 016 Inches	
	80	125L11	625	48.5	40.35	27.88	30.28	3850	M2904012511XM	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125F11	625	48.5	40.35	27.88	30.28	3890	M2504012511XM	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125C11	625	48.5	40.35	27.88	30.28	3766	M2604012511XM	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
2EP5000/6000/6500/EP7000	CLASS I 4 WHEEL COUNTERBALANCED			80 VOLTS , 40.47 X 33.66 X 30.87 Weight Minimum 3902 Connector EBC320 BLACK , Position B , Lead Length 016 Inches											
	80	140T11	700	54.3	40.25	33.00	30.50	4310	M2804014011X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125L11	625	48.5	40.25	33.10	30.50	4375	M2904012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125F11	625	48.5	40.25	33.00	30.50	4312	M2504012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125C11	625	48.5	40.25	33.00	30.50	4031	M2604012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
EP8000/9000/10000	CLASS I 4 WHEEL COUNTERBALANCED			80 VOLTS , 40.47 X 39.33 X 30.87 Weight Minimum 4562 Connector EBC320 BLACK , Position A , Lead Length 016 Inches											
	80	140T13	840	65.2	40.35	39.21	30.28	5073	M2804014013X	N	(CALL)		SCR20040865T1H	(CALL)	(CALL)
	80	125L13	750	58.2	40.35	39.21	30.28	4777	M2904012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125F13	750	58.2	40.35	39.21	30.28	5025	M2504012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125C13	750	58.2	40.35	39.21	30.28	4751	M2604012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
EP16PNT	CLASS I 3 WHEEL COUNTERBALANCED-SOUTH/CENTRAL AMERICA ONLY			36 VOLTS , 39.60 X 20.80 X 24.80 Weight Minimum 1910 Connector SB350 GRAY , Position B , Lead Length 020 Inches											
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
EP16PNT	CLASS I 3 WHEEL COUNTERBALANCED-SOUTH/CENTRAL AMERICA ONLY			48 VOLTS , 39.60 X 20.80 X 24.80 Weight Minimum 1910 Connector SB350 GRAY , Position B , Lead Length 020 Inches											
	48	100T13	600	27.9	38.62	20.50	23.00	2501	M2802410013B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	38.62	20.50	23.00	2400	M2902408513B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	38.62	20.50	23.00	2419	M2502408513B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	38.62	20.50	22.62	1940	M2602408513B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
EP18PNT / EP20PNT	CLASS I 3 WHEEL COUNTERBALANCED-SOUTH/CENTRAL AMERICA ONLY			36 VOLTS , 39.60 X 25.10 X 24.80 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 020 Inches											
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
EP18PNT / EP20PNT	CLASS I 3 WHEEL COUNTERBALANCED-SOUTH/CENTRAL AMERICA ONLY			48 VOLTS , 39.60 X 25.10 X 24.80 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 020 Inches											
	48	100T15	700	32.6	38.56	23.88	22.88	2501	M2802410015B7	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L15	595	27.7	38.56	23.88	22.88	2400	M2902408515B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	38.56	23.88	22.88	2419	M2502408515B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.31	23.63	22.63	2308	M2602408515B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)