

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NDC100	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 31.50 X 13.40 X 24.00			Weight Minimum 825		Connector SB175		GRAY , Position B , Lead Length 018 Inches				
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
NPP40	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 29.38 X 8.80 X 25.25			Weight Minimum 200		Connector SB175		GRAY , Position B , Lead Length 012 Inches				
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
NPP60	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 31.50 X 9.20 X 24.00			Weight Minimum 575		Connector SB175		GRAY , Position B , Lead Length 018 Inches				
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
NPP60	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 31.50 X 13.44 X 24.00			Weight Minimum 826		Connector SB175		GRAY , Position B , Lead Length 018 Inches				
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
NPS60	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 31.50 X 9.25 X 24.02			Weight Minimum 575		Connector SB175		GRAY , Position B , Lead Length 018 Inches				
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
NPS60	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 31.50 X 13.40 X 24.00			Weight Minimum 966		Connector SB175		GRAY , Position B , Lead Length 018 Inches				
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
NPS80	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 31.50 X 13.40 X 24.00			Weight Minimum 966		Connector SB175		GRAY , Position B , Lead Length 018 Inches				
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
WP4500	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 25.28 X 8.70 X 23.23			Weight Minimum 220		Connector SB175		GRAY , Position A , Lead Length 018 Inches				
	24	085C07	255	5.9	25.38	8.63	22.63	532	M2601208507D	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	MSB	195	.0	25.25	8.50	25.26	400	M90004S24CHPTM	N	(CALL)			(CALL)	(CALL)
WP4500L	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 31.26 X 8.70 X 26.02			Weight Minimum 220		Connector SB175		GRAY , Position A , Lead Length 018 Inches				
	24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	(CALL)			(CALL)	(CALL)
	24	100T05	200	4.7	27.75	7.57	23.25	496	M1801210005D6	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
WP6000	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)			24 VOLTS , 25.35 X 8.54 X 24.41			Weight Minimum 485		Connector SB175		GRAY , Position B , Lead Length 018 Inches				
	24	085C07	255	5.9	25.38	8.63	22.63	532	M2601208507D	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	MSB	195	.0	25.25	8.50	25.26	400	M90004S24CHPTM	N	(CALL)			(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
WP6000L	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)							24 VOLTS , 31.97 X 13.58 X 30.98		Weight Minimum 485	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	105B13	630	14.8	30.88	12.88	26.73	1250	M2101210513N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
2WPL4500	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)							24 VOLTS , 31.26 X 9.37 X 26.57		Weight Minimum 374	Connector SB175	GRAY	, Position A , Lead Length 018 Inches			
	24	085C07	255	5.9	30.68	8.90	23.25	580	M1601208507D25628	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
2WPL6000	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)							24 VOLTS , 32.01 X 13.58 X 27.56		Weight Minimum 485	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	085C13	510	11.9	31.50	13.00	23.25	965	M1601208513A0628	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
2WP4500	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)							24 VOLTS , 26.77 X 9.37 X 26.57		Weight Minimum 154	Connector SB175	GRAY	, Position A , Lead Length 018 Inches			
	24	085C07	255	5.9	26.25	8.90	23.25	580	M1601208507D628	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
2WP6000	CLASS III LOW LIFT WALKIE PALLET (PLATFORM)							24 VOLTS , 26.77 X 9.37 X 26.57		Weight Minimum 154	Connector SB175	GRAY	, Position A , Lead Length 018 Inches			
	24	085C07	255	5.9	26.25	8.90	23.25	580	M1601208507D628	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
NPC80	CLASS III LOW LIFT WALKIE RIDER/CENTRAL CONTROL							24 VOLTS , 31.50 X 13.40 X 24.00		Weight Minimum 825	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
NPV60	CLASS III LOW-LIFT WALKIE RIDER/PALLET							24 VOLTS , 31.50 X 13.40 X 24.00		Weight Minimum 825	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
NPV80	CLASS III LOW-LIFT WALKIE RIDER/PALLET							24 VOLTS , 31.50 X 13.40 X 24.00		Weight Minimum 825	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
WR6000	CLASS III LOW-LIFT WALKIE RIDER/PALLET							24 VOLTS , 31.97 X 13.46 X 30.98		Weight Minimum 933	Connector SB175	GRAY	, Position A , Lead Length 018 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	105B13	630	14.8	30.88	12.88	26.73	1250	M2101210513N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
WR8000	CLASS III LOW-LIFT WALKIE RIDER/PALLET							24 VOLTS , 31.97 X 13.46 X 30.98		Weight Minimum 933	Connector SBX350	RED	, Position A , Lead Length 018 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	105B13	630	14.8	30.88	12.88	26.73	1250	M2101210513N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
NPC60	CLASS III STAND-UP END CONTROL COUNTERBALANCED							24 VOLTS , 31.50 X 13.40 X 24.00		Weight Minimum 825	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
NRP30	CLASS III WALKIE HIGH LIFT STRADDLE											24 VOLTS , 31.90 X 13.40 X 24.00		Weight Minimum 970	Connector SB175	GRAY	, Position B , Lead Length 018 Inches	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	100G09	400	9.4	31.00	12.88	23.00	1000	M8901210009NPP7	N	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)			
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
NSP30	CLASS III WALKIE HIGH LIFT STRADDLE											24 VOLTS , 31.90 X 13.40 X 24.00		Weight Minimum 970	Connector SB175	GRAY	, Position B , Lead Length 018 Inches	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	100G09	400	9.4	31.00	12.88	23.00	1000	M8901210009NPP7	N	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)			
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
NSP40	CLASS III WALKIE HIGH LIFT STRADDLE											24 VOLTS , 31.90 X 13.40 X 24.00		Weight Minimum 970	Connector SB175	GRAY	, Position B , Lead Length 018 Inches	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	100G09	400	9.4	31.00	12.88	23.00	1000	M8901210009NPP7	N	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)			
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
SS3000	CLASS III WALKIE HIGH LIFT STRADDLE											24 VOLTS , 25.28 X 11.02 X 24.80		Weight Minimum 509	Connector SB175	GRAY	, Position A , Lead Length 012 Inches	
	24	085C09	340	7.9	25.27	10.88	22.63	686	M2601208509D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
	24	100T09	400	9.3	25.27	10.88	22.63	728	M2801210009D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
SS3000	CLASS III WALKIE HIGH LIFT STRADDLE											24 VOLTS , 28.23 X 11.02 X 23.62		Weight Minimum 509	Connector SB175	GRAY	, Position A , Lead Length 012 Inches	
	24	085C09	340	7.9	25.27	10.88	22.63	686	M2601208509D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
	24	100T09	400	9.3	25.27	10.88	22.63	728	M2801210009D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
SS3500	CLASS III WALKIE HIGH LIFT STRADDLE											24 VOLTS , 25.28 X 11.02 X 24.80		Weight Minimum 509	Connector SB175	GRAY	, Position A , Lead Length 012 Inches	
	24	085C09	340	7.9	25.27	10.88	22.63	686	M2601208509D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
	24	100T09	400	9.3	25.27	10.88	22.63	728	M2801210009D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
SS3500	CLASS III WALKIE HIGH LIFT STRADDLE											24 VOLTS , 28.23 X 11.02 X 23.62		Weight Minimum 509	Connector SB175	GRAY	, Position A , Lead Length 012 Inches	
	24	085C09	340	7.9	25.27	10.88	22.63	686	M2601208509D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
	24	100T09	400	9.3	25.27	10.88	22.63	728	M2801210009D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
ND2500	CLASS II DOUBLE REACH											24 VOLTS , 38.58 X 14.25 X 31.65		Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)			
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)			
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)	(CALL)	SCR200121200T1H	(CALL)	(CALL)			
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)			
ND2500	CLASS II DOUBLE REACH											36 VOLTS , 38.58 X 14.25 X 31.65		Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	125C11	625	21.8	38.00	13.25	30.50	1836	M2601812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F11	625	21.8	38.06	13.50	30.50	1899	M2501812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	140T11	700	24.4	38.06	13.50	30.50	1972	M2801814011B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ND3000	CLASS II DOUBLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ND3000	CLASS II DOUBLE REACH		36 VOLTS , 38.58 X 18.25 X 31.65 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)
ND3000	CLASS II DOUBLE REACH		36 VOLTS , 38.58 X 21.25 X 31.65 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	(CALL)	(CALL)	(CALL)
ND3000P	CLASS II DOUBLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ND3000P	CLASS II DOUBLE REACH		36 VOLTS , 38.58 X 18.25 X 31.65 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)
ND3000P	CLASS II DOUBLE REACH		36 VOLTS , 38.58 X 21.25 X 31.65 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	(CALL)	(CALL)	(CALL)
NRDR25	CLASS II DOUBLE REACH		24 VOLTS , 38.60 X 14.30 X 31.50 Weight Minimum 1600 Connector SB350 RED , Position B , Lead Length 011 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)	SCR200121050T1H	(CALL)	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)	SCR200121050T1H	(CALL)	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)	SCR200121200T1H	(CALL)	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)	(CALL)
NRDR25	CLASS II DOUBLE REACH		24 VOLTS , 38.60 X 16.30 X 31.60 Weight Minimum 2000 Connector SB350 RED , Position B , Lead Length 011 Inches												
	24	125C19	1125	26.2	38.31	15.25	30.50	2105	M2601212519B7	N	(CALL)	SCR200121200T1H	(CALL)	(CALL)	(CALL)
	24	125F19	1125	26.2	38.31	15.25	30.50	2177	M2501212519B7	N	(CALL)	SCR200121200T1H	(CALL)	(CALL)	(CALL)
	24	140T19	1260	29.3	38.31	15.25	30.50	2235	M2801214019B7	N	(CALL)	SCR200121450T1H	(CALL)	(CALL)	(CALL)
	24	125L19	1125	26.2	38.13	15.25	30.50	2230	M2901212519B7	N	(CALL)	SCR200121200T1H	(CALL)	(CALL)	(CALL)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NRDR25P	CLASS II DOUBLE REACH		36 VOLTS , 38.60 X 16.30 X 31.60 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NRDR25P	CLASS II DOUBLE REACH		36 VOLTS , 38.60 X 21.30 X 31.60 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
NRDR30	CLASS II DOUBLE REACH		24 VOLTS , 38.60 X 14.30 X 31.50 Weight Minimum 1600 Connector SB350 RED , Position B , Lead Length 011 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
NRDR30	CLASS II DOUBLE REACH		24 VOLTS , 38.60 X 16.30 X 31.60 Weight Minimum 2000 Connector SB350 RED , Position B , Lead Length 011 Inches												
	24	125C19	1125	26.2	38.31	15.25	30.50	2105	M2601212519B7	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.31	15.25	30.50	2177	M2501212519B7	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.31	15.25	30.50	2235	M2801214019B7	N	(CALL)	SCR200121450T1H	SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.13	15.25	30.50	2230	M2901212519B7	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
NRDR30P	CLASS II DOUBLE REACH		36 VOLTS , 38.60 X 16.30 X 31.60 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NRDR30P	CLASS II DOUBLE REACH		36 VOLTS , 38.60 X 21.30 X 31.60 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
NRR30	CLASS II NARROW AISLE REACH		24 VOLTS , 38.67 X 14.30 X 31.50 Weight Minimum 1600 Connector SB350 RED , Position B , Lead Length 011 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
NRR30	CLASS II NARROW AISLE REACH		24 VOLTS , 38.67 X 16.30 X 31.60 Weight Minimum 2000 Connector SB350 RED , Position B , Lead Length 011 Inches												
	24	125C19	1125	26.2	38.31	15.25	30.50	2105	M2601212519B7	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.31	15.25	30.50	2177	M2501212519B7	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.31	15.25	30.50	2235	M2801214019B7	N	(CALL)	SCR200121450T1H	SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.13	15.25	30.50	2230	M2901212519B7	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NRR30P	CLASS II NARROW AISLE REACH			36 VOLTS , 38.60 X 21.30 X 31.60			Weight Minimum 2600		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
NRR30P	CLASS II NARROW AISLE REACH			36 VOLTS , 38.70 X 16.30 X 31.60			Weight Minimum 2000		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NRR35	CLASS II NARROW AISLE REACH			24 VOLTS , 38.67 X 14.30 X 31.50			Weight Minimum 1600		Connector SB350	RED	, Position B , Lead Length 011 Inches				
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NRR35	CLASS II NARROW AISLE REACH			24 VOLTS , 38.67 X 16.30 X 31.60			Weight Minimum 2000		Connector SB350	RED	, Position B , Lead Length 011 Inches				
	24	125C19	1125	26.2	38.31	15.25	30.50	2105	M2601212519B7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.31	15.25	30.50	2177	M2501212519B7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.31	15.25	30.50	2235	M2801214019B7	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.13	15.25	30.50	2230	M2901212519B7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
NRR35P	CLASS II NARROW AISLE REACH			36 VOLTS , 38.60 X 21.30 X 31.60			Weight Minimum 2600		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
NRR35P	CLASS II NARROW AISLE REACH			36 VOLTS , 38.70 X 16.30 X 31.60			Weight Minimum 2000		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NRR40	CLASS II NARROW AISLE REACH			24 VOLTS , 38.67 X 14.30 X 31.50			Weight Minimum 1600		Connector SB350	RED	, Position B , Lead Length 011 Inches				
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NRR40	CLASS II NARROW AISLE REACH		36 VOLTS , 38.67 X 16.30 X 31.60 Weight Minimum 2000 Connector SB350 RED , Position B , Lead Length 011 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NRR40P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.60 X 21.30 X 31.60 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
NRR40P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.70 X 16.30 X 31.60 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NRR45P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.60 X 21.30 X 31.60 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
NRR45P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.70 X 16.30 X 31.60 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NR3000	CLASS II NARROW AISLE REACH		24 VOLTS , 38.58 X 14.25 X 31.65 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NR3000	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 14.25 X 31.65 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C11	625	21.8	38.00	13.25	30.50	1836	M2601812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.06	13.50	30.50	1899	M2501812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.06	13.50	30.50	1972	M2801814011B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.25	13.50	30.50	1825	M2901812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
NR3500	CLASS II NARROW AISLE REACH		24 VOLTS , 38.58 X 14.25 X 31.65													Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
NR3500	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65													Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NR3500	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 18.25 X 31.65													Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
NR4000	CLASS II NARROW AISLE REACH		24 VOLTS , 38.58 X 14.25 X 31.65													Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
NR4000	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65													Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NR4000	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 18.25 X 31.65													Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
NR4000	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 21.25 X 31.65													Weight Minimum 2600	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
NR4000P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65													Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
NR4000P	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 18.25 X 31.65				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
NR4000P	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 21.25 X 31.65				Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
NR4500	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
NR4500	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 18.25 X 31.65				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
NR4500	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 21.25 X 31.65				Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
NR4500P	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
NR4500P	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 18.25 X 31.65				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
NR4500P	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 21.25 X 31.65				Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NSR30P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NSR40P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.67 X 16.25 X 31.65 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NS3000	CLASS II NARROW AISLE REACH		24 VOLTS , 38.58 X 14.25 X 31.65 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NS3000	CLASS II NARROW AISLE REACH		24 VOLTS , 38.58 X 16.25 X 31.65 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
NS3000	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 14.25 X 31.65 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C11	625	21.8	38.00	13.25	30.50	1836	M2601812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.06	13.50	30.50	1899	M2501812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.06	13.50	30.50	1972	M2801814011B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NS3000	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
NS4000	CLASS II NARROW AISLE REACH		24 VOLTS , 38.58 X 14.25 X 31.65 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NS4000	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NS4000	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 18.25 X 31.65 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
NOR22	CLASS II ORDER PICKER		24 VOLTS , 32.80 X 13.50 X 32.00 Weight Minimum 950 Connector SB175 GRAY , Position A , Lead Length 018 Inches												
	24	125F11	625	14.6	30.69	12.94	31.00	1283	M1501212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C11	625	14.6	30.69	12.94	31.00	1226	M1601212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L11	625	14.6	30.69	12.94	31.00	1260	M1901212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
NOR30	CLASS II ORDER PICKER		24 VOLTS , 31.50 X 13.20 X 30.90 Weight Minimum 920 Connector SB350 RED , Position C , Lead Length 020 Inches												
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
NOR30	CLASS II ORDER PICKER		24 VOLTS , 36.70 X 14.50 X 30.90 Weight Minimum 1600 Connector SB350 RED , Position C , Lead Length 020 Inches												
	24	055B29	770	18.1	37.08	13.00	29.87	1430	M2101205529FB	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	055B31	825	19.4	36.75	14.00	30.69	1600	M2101205531FB25	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NOR30P	CLASS II ORDER PICKER		24 VOLTS , 36.70 X 14.50 X 30.90 Weight Minimum 1600 Connector SB350 RED , Position C , Lead Length 012 Inches												
	24	055B31	825	19.4	36.75	14.00	30.69	1600	M2101205531FB25	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	13.06	30.50	1662	M2501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	13.06	30.50	1606	M2601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.25	13.06	30.50	1702	M2801214015A	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NOR30P	CLASS II ORDER PICKER		36 VOLTS , 38.40 X 14.00 X 30.90 Weight Minimum 1600 Connector SB350 GRAY , Position C , Lead Length 012 Inches												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NSR30	CLASS II STRADDLE		24 VOLTS , 38.60 X 14.20 X 31.60 Weight Minimum 1600 Connector SB350 RED , Position B , Lead Length 011 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NSR30	CLASS II STRADDLE							24 VOLTS , 38.67 X 16.25 X 31.62		Weight Minimum 2000	Connector SB350	RED	, Position B , Lead Length 011 Inches		
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
NSR40	CLASS II STRADDLE							24 VOLTS , 38.60 X 14.20 X 31.60		Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches		
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NSR40	CLASS II STRADDLE							24 VOLTS , 38.67 X 16.25 X 31.62		Weight Minimum 2000	Connector SB350	RED	, Position B , Lead Length 011 Inches		
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
EC15KS	CLASS I STAND-UP END CONTROL COUNTERBALANCED							36 VOLTS , 38.50 X 16.25 X 32.30		Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 013 Inches		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
EC15KS	CLASS I STAND-UP END CONTROL COUNTERBALANCED							36 VOLTS , 38.50 X 18.50 X 32.30		Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 013 Inches		
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EC18KS	CLASS I STAND-UP END CONTROL COUNTERBALANCED							36 VOLTS , 38.50 X 16.25 X 32.30		Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 013 Inches		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
EC18KS	CLASS I STAND-UP END CONTROL COUNTERBALANCED							36 VOLTS , 38.50 X 18.50 X 32.30		Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 013 Inches		
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
EC20KS	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 18.50 X 32.30			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 013 Inches				
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EC20KS	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 21.25 X 32.30			Weight Minimum 2600		Connector SB350	GRAY	, Position B , Lead Length 013 Inches				
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
EC25KS	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 23.75 X 32.30			Weight Minimum 2700		Connector SB350	GRAY	, Position B , Lead Length 013 Inches				
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
ES3000	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 14.25 X 31.60			Weight Minimum 1700		Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	125C11	625	21.8	38.00	13.25	30.50	1836	M2601812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.06	13.50	30.50	1899	M2501812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.06	13.50	30.50	1972	M2801814011B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ES3000	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 16.25 X 31.60			Weight Minimum 2000		Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ES3000	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 18.25 X 31.60			Weight Minimum 2300		Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ES3500	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 14.25 X 31.60			Weight Minimum 1700		Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	125C11	625	21.8	38.00	13.25	30.50	1836	M2601812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.06	13.50	30.50	1899	M2501812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.06	13.50	30.50	1972	M2801814011B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
ES3500	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 16.25 X 31.60					Weight Minimum 2000	Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
ES3500	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 18.25 X 31.60					Weight Minimum 2300	Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
ES4000	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 18.25 X 31.60					Weight Minimum 2300	Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
ES4000	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 21.25 X 31.60					Weight Minimum 2600	Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
ES5000	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 21.25 X 32.30					Weight Minimum 2600	Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
ES5000	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 23.75 X 32.30					Weight Minimum 2900	Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)	
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)	
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)	SCR200181450T1H	SCR200181450T1H	(CALL)	(CALL)	
ES5500	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 21.25 X 32.30					Weight Minimum 2600	Connector SB350	GRAY	, Position C , Lead Length 020 Inches				
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
ES5500	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 23.75 X 32.30		Weight Minimum 2900	Connector SB350	GRAY , Position C , Lead Length 020 Inches
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
EP15T	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 39.60 X 20.60 X 24.40		Weight Minimum 1900	Connector SB350	GRAY , Position D , Lead Length 030 Inches
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EP15T	CLASS I 3 WHEEL COUNTERBALANCED											48 VOLTS , 39.60 X 20.60 X 24.40		Weight Minimum 1900	Connector SB350	GRAY , Position D , Lead Length 030 Inches
	48	085C13	510	23.7	38.00	20.50	23.25	1897	M1602408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
EP16KT	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 40.00 X 20.90 X 24.80		Weight Minimum 1910	Connector SB350	GRAY , Position B , Lead Length 020 Inches
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EP18KT	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 40.00 X 24.90 X 24.80		Weight Minimum 2200	Connector SB350	GRAY , Position B , Lead Length 020 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
EP18T	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 39.60 X 24.90 X 24.40		Weight Minimum 2200	Connector SB350	GRAY , Position D , Lead Length 030 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	075B23	825	29.1	38.50	22.68	23.82	2356	M2101807523B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	075B23	825	29.1	38.50	24.00	23.82	2360	M2101807523B0	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
EP20KT	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 40.00 X 24.90 X 24.80		Weight Minimum 2200	Connector SB350	GRAY , Position B , Lead Length 020 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
EP20T	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 39.60 X 24.90 X 24.40		Weight Minimum 2200	Connector SB350	GRAY , Position D , Lead Length 030 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	075B23	825	29.1	38.50	22.68	23.82	2356	M2101807523B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	075B23	825	29.1	38.50	24.00	23.82	2360	M2101807523B0	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ET3000	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 40.0 X 20.9 X 24.80			Weight Minimum 1910		Connector SB350	GRAY	, Position B , Lead Length 020 Inches				
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ET3500	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 40.0 X 24.90 X 24.80			Weight Minimum 2200		Connector SB350	GRAY	, Position B , Lead Length 020 Inches				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ET4000	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 40.0 X 24.90 X 24.80			Weight Minimum 2200		Connector SB350	GRAY	, Position B , Lead Length 020 Inches				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
FC40	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.60 X 25.00 X 24.60			Weight Minimum 2200		Connector SB350	GRAY	, Position D , Lead Length 030 Inches				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
F25	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.60 X 20.80 X 24.60			Weight Minimum 1900		Connector SB350	GRAY	, Position D , Lead Length 030 Inches				
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
F30	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.60 X 20.80 X 24.60			Weight Minimum 1900		Connector SB350	GRAY	, Position D , Lead Length 030 Inches				
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
F35	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.60 X 25.00 X 24.60			Weight Minimum 2200		Connector SB350	GRAY	, Position D , Lead Length 030 Inches				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
F25	CLASS I 3 WHEEL COUNTERBALANCED ATIC TIRE]			36 VOLTS , 39.60 X 20.80 X 24.60			Weight Minimum 1900		Connector SB350	GRAY	, Position D , Lead Length 030 Inches				
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
F35	CLASS I 3 WHEEL COUNTERBALANCED ATIC TIRE]			36 VOLTS , 39.60 X 25.00 X 24.60			Weight Minimum 2200		Connector SB350	GRAY	, Position D , Lead Length 030 Inches				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
ET3000	CLASS I 3 WHEEL COUNTERBALANCED-SOUTH/CENTRAL AMERICA ONLY											36 VOLTS , 40.0 X 20.9 X 24.80		Weight Minimum 1910	Connector SB350	GRAY , Position B , Lead Length 020 Inches
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EC15	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 35.80 X 27.80 X 23.30		Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EC15	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 35.80 X 27.80 X 23.30		Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)	
EC15K	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 35.80 X 27.80 X 23.30		Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EC15K	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 35.80 X 27.80 X 23.30		Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)	
EC18	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 35.80 X 27.80 X 23.30		Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
EC18	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 35.80 X 27.80 X 23.30		Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)	
EC18K	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 35.80 X 27.80 X 23.30		Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
EC18K	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 35.80 X 27.80 X 23.30		Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
EC18KL	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 35.80 X 27.80 X 23.30				Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	33.31	25.75	23.25	2050	M1601808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
EC18KL	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 35.80 X 27.80 X 23.30				Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
EC20	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.90 X 30.50 X 23.30				Weight Minimum 2200	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
EC20	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.90 X 30.50 X 23.30				Weight Minimum 2200	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
EC20K	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.90 X 30.50 X 23.30				Weight Minimum 2200	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
EC20K	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.90 X 30.50 X 23.30				Weight Minimum 2200	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
EC25	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.90 X 30.50 X 23.30				Weight Minimum 2900	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.69	29.69	22.88	3064	M2501808525B7	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.69	29.69	22.88	2999	M2601808525B7	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T25	1200	41.9	38.69	29.69	22.88	3362	M2801810025B7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
EC25E	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.90 X 34.40 X 23.30				Weight Minimum 3100	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
EC25K	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.90 X 30.50 X 23.30			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.69	29.69	22.88	3064	M2501808525B7	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.69	29.69	22.88	2999	M2601808525B7	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.69	29.69	22.88	3362	M2801810025B7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
EC25KE	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.90 X 34.40 X 23.30			Weight Minimum 3100		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
EC25KL	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.90 X 34.40 X 23.30			Weight Minimum 3100		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
EC25K4S	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.90 X 30.50 X 23.30			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.69	29.69	22.88	3064	M2501808525B7	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.69	29.69	22.88	2999	M2601808525B7	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.69	29.69	22.88	3362	M2801810025B7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
EC30	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.90 X 34.40 X 23.30			Weight Minimum 3100		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
EC30K	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.90 X 34.40 X 23.30			Weight Minimum 3100		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
EC30KL	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.90 X 34.40 X 23.30			Weight Minimum 3100		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
EC4000	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 35.80 X 27.80 X 23.30			Weight Minimum 1650		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
EC4000	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 35.80 X 27.80 X 23.30											
											Weight Minimum 1650	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
EX5000	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.50 X 34.40 X 23.30											
											Weight Minimum 3100	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
E3000	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 35.80 X 27.80 X 23.30											
											Weight Minimum 1650	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
E3000	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 35.80 X 27.80 X 23.30											
											Weight Minimum 1650	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
E3500	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 35.80 X 27.80 X 23.30											
											Weight Minimum 1650	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
E3500	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 35.80 X 27.80 X 23.30											
											Weight Minimum 1650	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
E4000	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.50 X 30.50 X 23.30											
											Weight Minimum 2200	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
E4000	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 39.50 X 30.50 X 23.30											
											Weight Minimum 3090	Connector SB350	GRAY	, Position B , Lead Length 024 Inches	
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
E5000	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.50 X 30.50 X 23.30		Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085F25	1020	35.6	38.69	29.69	22.88	3064	M2501808525B7	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	085C25	1020	35.6	38.69	29.69	22.88	2999	M2601808525B7	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	100T25	1200	41.9	38.69	29.69	22.88	3362	M2801810025B7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
E5000	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.50 X 30.50 X 23.30		Weight Minimum 3090	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
E5500	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.50 X 34.40 X 23.30		Weight Minimum 3100	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
E6000	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.50 X 34.40 X 23.30		Weight Minimum 3100	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
E6500	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.50 X 34.40 X 23.30		Weight Minimum 3100	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
F60D	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 49.20 X 45.50 X 18.90		Weight Minimum 3350	Connector SB350	GRAY , Position D , Lead Length 030 Inches
	48	060C29	840	39.1	44.75	38.56	18.50	3353	M2602406029C	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
F60DSA	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 49.20 X 45.50 X 18.90		Weight Minimum 3350	Connector SB350	GRAY , Position D , Lead Length 030 Inches
	48	060C29	840	39.1	44.75	38.56	18.50	3353	M2602406029C	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
MC60DSA	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 40.20 X 34.40 X 23.60		Weight Minimum 3060	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
MC60DSA	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 40.20 X 34.40 X 23.60		Weight Minimum 3060	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
M100D	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 43.30 X 40.60 X 24.00		Weight Minimum 3750	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085C33	1360	47.5	38.81	38.75	23.13	4140	M2601808533B7	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
M100D	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 43.30 X 40.60 X 24.00			
											Weight Minimum 3750	Connector SB350	GRAY , Position B , Lead Length 024 Inches		
	48	085C27	1105	51.4	38.44	41.89	22.63	4010	M2602408527B	Y	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027B	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
M120D	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 43.30 X 40.60 X 24.00			
											Weight Minimum 4000	Connector SB350	GRAY , Position B , Lead Length 024 Inches		
	36	085C33	1360	47.5	38.81	38.75	23.13	4140	M2601808533B7	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
M120D	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 43.30 X 40.60 X 24.00			
											Weight Minimum 4000	Connector SB350	GRAY , Position B , Lead Length 024 Inches		
	48	085C27	1105	51.4	38.44	41.89	22.63	4010	M2602408527B	Y	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027B	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
M40	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 40.20 X 30.50 X 23.60			
											Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 024 Inches		
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
M40	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 40.20 X 30.50 X 23.60			
											Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 024 Inches		
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
M40DSA	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 40.20 X 30.50 X 23.60			
											Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 024 Inches		
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
M40DSA	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 40.20 X 30.50 X 23.60			
											Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 024 Inches		
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
M50	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 40.20 X 33.30 X 23.60			
											Weight Minimum 2950	Connector SB350	GRAY , Position B , Lead Length 024 Inches		
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
M50	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 40.20 X 33.30 X 23.60			
											Weight Minimum 2950	Connector SB350	GRAY , Position B , Lead Length 024 Inches		
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
			CLASS I 4 WHEEL COUNTERBALANCED												
M50DSA	36	060C29	840	29.3	38.31	33.75	18.50	2651	M1601806029B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
M50DSA	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	
M50DSA	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)	SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)	SCR20024865T1H	(CALL)	(CALL)	
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)	SCR20024750T1H	(CALL)	(CALL)	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)	SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)	SCR20024865T1H	(CALL)	(CALL)	
M70D	36	085C33	1360	47.5	38.81	38.75	23.13	4140	M2601808533B7	N	(CALL)	SCR200181450T1H	(CALL)	(CALL)	
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)	SCR200181700T1H	(CALL)	(CALL)	
M70D	48	085C27	1105	51.4	38.44	41.89	22.63	4010	M2602408527B	Y	(CALL)	SCR200241200T1H	(CALL)	(CALL)	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)	SCR20024965T1H	(CALL)	(CALL)	
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027B	N	(CALL)	SCR200241450T1H	(CALL)	(CALL)	
M80D	36	085C33	1360	47.5	38.81	38.75	23.13	4140	M2601808533B7	N	(CALL)	SCR200181450T1H	(CALL)	(CALL)	
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)	SCR200181700T1H	(CALL)	(CALL)	
M80D	48	085C27	1105	51.4	38.44	41.89	22.63	4010	M2602408527B	Y	(CALL)	SCR200241200T1H	(CALL)	(CALL)	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)	SCR20024965T1H	(CALL)	(CALL)	
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027B	N	(CALL)	SCR200241450T1H	(CALL)	(CALL)	
2EC15	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
2EC15	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)	SCR20024750T1H	(CALL)	(CALL)	
2EC18	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
2EC18	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 35.80 X 27.80 X 23.30				Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
2EC20	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.90 X 30.50 X 23.30				Weight Minimum 2200	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
2EC20	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.90 X 30.50 X 23.30				Weight Minimum 2200	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
2EC25	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.90 X 30.50 X 23.30				Weight Minimum 2900	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.69	29.69	22.88	3064	M2501808525B7	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.69	29.69	22.88	2999	M2601808525B7	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T25	1200	41.9	38.69	29.69	22.88	3362	M2801810025B7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
2EC25E	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.90 X 34.40 X 23.30				Weight Minimum 3100	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
2EC30	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.90 X 34.40 X 23.30				Weight Minimum 3100	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
2EC18	FOUR WHEEL SIT DOWN RIDER											48 VOLTS , 35.80 X 27.80 X 23.30				Weight Minimum 1650	Connector SB350	GRAY , Position B , Lead Length 024 Inches
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)