

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>EWP45</b>	<b>CLASS III LOW LIFT WALKIE PALLET</b>											<b>24 VOLTS , 29.40 X 8.81 X 999.00</b>				<b>Weight Minimum 200</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 015 Inches</b>
	24	100T05	200	4.7	27.75	7.57	23.25	496	M1801210005D6	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085L05	170	4.0	27.75	7.57	23.25	497	M1901208505D6	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)				
	24	085F05		.0	27.75	7.57	23.25	493	M1501208505D6	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085C05	170	4.0	27.75	7.57	23.25	481	M1601208505D6	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
<b>PWX-30,40</b>	<b>CLASS III LOW LIFT WALKIE PALLET</b>											<b>24 VOLTS , 31.40 X 13.60 X 999.00</b>				<b>Weight Minimum 821</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 015 Inches</b>
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)				
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	105B13	630	14.8	30.88	12.88	26.73	1250	M2101210513N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)				
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)				
<b>PWX-30,40</b>	<b>CLASS III LOW LIFT WALKIE PALLET</b>											<b>24 VOLTS , 35.50 X 7.00 X 999.00</b>				<b>Weight Minimum 456</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 015 Inches</b>
	24	100T07	300	7.0	33.81	6.56	23.25	590	M1801210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	085L07	255	5.9	33.81	6.56	23.25	600	M1901208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085L07	255	5.9	33.81	6.56	27.25	598	M1901208507GFPCZ	N	(CALL)			(CALL)	(CALL)				
	24	085F07	255	5.9	33.81	6.56	23.25	578	M1501208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085C07	255	5.9	33.81	6.56	23.25	554	M1601208507G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
<b>HWX-30,40</b>	<b>CLASS III LOW LIFT WALKIE RIDER</b>											<b>24 VOLTS , 31.40 X 13.60 X 999.00</b>				<b>Weight Minimum 821</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 015 Inches</b>
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)				
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	105B13	630	14.8	30.88	12.88	26.73	1250	M2101210513N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)				
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)				
<b>HWX-30,40</b>	<b>CLASS III LOW LIFT WALKIE RIDER</b>											<b>24 VOLTS , 35.50 X 7.00 X 999.00</b>				<b>Weight Minimum 456</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 015 Inches</b>
	24	100T07	300	7.0	33.81	6.56	23.25	590	M1801210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	085L07	255	5.9	33.81	6.56	23.25	600	M1901208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085L07	255	5.9	33.81	6.56	27.25	598	M1901208507GFPCZ	N	(CALL)			(CALL)	(CALL)				
	24	085F07	255	5.9	33.81	6.56	23.25	578	M1501208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085C07	255	5.9	33.81	6.56	23.25	554	M1601208507G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
<b>CTX40</b>	<b>CLASS III WALKIE STACKER</b>											<b>48 VOLTS , 32.80 X 16.50 X 23.20</b>				<b>Weight Minimum 882</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 020 Inches</b>
	48	100T07	300	14.0	32.00	15.50	23.00	1352	M2802410007Z50	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085L07	255	11.9	32.00	15.50	23.00	1291	M2902408507Z50	N	(CALL)	SCR20024260S1H		(CALL)	(CALL)				
	48	085F07	255	11.9	32.00	15.50	23.00	1302	M2502408507Z50	N	(CALL)	SCR20024260S1H		(CALL)	(CALL)				
	48	085C07	255	11.9	32.00	15.50	23.00	1258	M2602408507Z50	N	(CALL)	SCR20024260S1H		(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
<b>CTX70</b>	<b>CLASS III WALKIE STACKER</b>			<b>48 VOLTS , 32.80 X 16.55 X 23.20</b>											<b>Weight Minimum 1191</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 020 Inches</b>
	48	100T07	300	14.0	32.00	15.50	23.00	1352	M2802410007Z50	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)			
	48	085L07	255	11.9	32.00	15.50	23.00	1291	M2902408507Z50	N	(CALL)	SCR20024260S1H		(CALL)	(CALL)			
	48	085F07	255	11.9	32.00	15.50	23.00	1302	M2502408507Z50	N	(CALL)	SCR20024260S1H		(CALL)	(CALL)			
	48	085C07	255	11.9	32.00	15.50	23.00	1258	M2602408507Z50	N	(CALL)	SCR20024260S1H		(CALL)	(CALL)			
<b>CSM7,10,15</b>	<b>CLASS III WALKIE STRADDLE STACKER</b>			<b>24 VOLTS , 28.60 X 9.00 X 24.60</b>											<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 028 Inches</b>
	24	100T05	200	4.7	27.76	8.75	23.25		M1801210005G6	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085L05	170	4.0	26.50	7.50	23.25	477	M1901208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)			
	24	085F05	170	4.0	26.50	7.50	23.25	480	M1501208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C05	170	4.0	27.76	8.75	23.25	467	M1601208505G6	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C05	170	4.0	26.50	7.50	23.25	465	M1601208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
<b>CST10</b>	<b>CLASS III WALKIE COUNTERBALANCED STACKER</b>			<b>24 VOLTS , 32.00 X 13.25 X 999.00</b>											<b>Weight Minimum 900</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 028 Inches</b>
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)			
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
<b>CST15,20</b>	<b>CLASS III WALKIE COUNTERBALANCED STACKER</b>			<b>24 VOLTS , 32.00 X 13.25 X 999.00</b>											<b>Weight Minimum 900</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 028 Inches</b>
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
<b>CS15,20</b>	<b>CLASS III WALKIE STRADDLE STACKER REACH</b>			<b>24 VOLTS , 32.00 X 13.25 X 999.00</b>											<b>Weight Minimum 900</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 028 Inches</b>
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)			
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
<b>CSP15</b>	<b>CLASS III WALKIE STRADDLE STACKER REACH</b>			<b>24 VOLTS , 32.00 X 13.25 X 999.00</b>											<b>Weight Minimum 900</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 028 Inches</b>
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)			
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
OSX15	CLASS II ORDERPICKER		24 VOLTS , 38.30 X 14.20 X 32.70 Weight Minimum 1520 Connector SB350 RED , Position C , Lead Length 015 Inches												
	24	140T15	980	22.8	35.25	13.06	30.50	1702	M2801214015A	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.25	13.06	30.50	1648	M2901212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	13.06	30.50	1662	M2501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	13.06	30.50	1606	M2601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
OSX15	CLASS II ORDERPICKER		36 VOLTS , 38.30 X 14.20 X 32.70 Weight Minimum 1600 Connector SB350 GRAY , Position C , Lead Length 015 Inches												
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.01	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NPR17,20	CLASS II NARROW AISLE REACH		24 VOLTS , 38.75 X 13.88 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	055B29	770	18.1	37.08	13.50	29.87	1630	M2101205529FB7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
NPR17,20	CLASS II NARROW AISLE REACH		24 VOLTS , 38.75 X 16.13 X 32.00 Weight Minimum 1900 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125C19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
NPR17,20	CLASS II NARROW AISLE REACH		36 VOLTS , 38.75 X 13.88 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.01	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NPR17,20	CLASS II NARROW AISLE REACH		36 VOLTS , 38.75 X 16.13 X 32.00 Weight Minimum 1900 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	38.50	15.90	31.38	2070	M2101804531B0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
NPR22,15D	CLASS II NARROW AISLE REACH		36 VOLTS , 38.75 X 18.50 X 32.00 Weight Minimum 2175 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>NPR22,15D</b>	<b>CLASS II NARROW AISLE REACH</b>			<b>36 VOLTS , 38.75 X 21.00 X 32.00</b>											
											<b>Weight Minimum 2460</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 014 Inches</b>		
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	38.50	19.41	31.38	2600	M2101806031B25	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
<b>TMX12,15S</b>	<b>CLASS I 3-WHEEL SIT DOWN COUNTERBALANCED</b>			<b>36 VOLTS , 38.80 X 13.75 X 31.00</b>											
											<b>Weight Minimum 1650</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>		
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>TMX15/17/20/25</b>	<b>CLASS I 3-WHEEL SIT DOWN COUNTERBALANCED</b>			<b>36 VOLTS , 38.80 X 20.50 X 31.00</b>											
											<b>Weight Minimum 2590</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>		
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
<b>TMX15/17/20/25</b>	<b>CLASS I 3-WHEEL SIT DOWN COUNTERBALANCED</b>			<b>48 VOLTS , 38.80 X 25.00 X 31.00</b>											
											<b>Weight Minimum 2590</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>		
	48	140T15	980	45.6	38.31	23.62	30.50	3283	M2802414015B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	125L15	825	38.4	38.31	23.62	30.50	3167	M2902412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	125F15	875	40.7	38.31	23.62	30.50	3170	M2502412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	125C15	875	40.7	38.31	23.62	30.50	3084	M2602412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
<b>ECX20/25/30</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED CUSHION</b>			<b>36 VOLTS , 39.25 X 30.50 X 23.50</b>											
											<b>Weight Minimum 2600</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>		
	36	100T25	1200	41.9	38.69	29.69	22.88	3362	M2801810025B7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.69	29.69	22.88	3362	M2901808525B7	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.69	29.69	22.88	3064	M2501808525B7	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.69	29.69	22.88	2999	M2601808525B7	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>ECX20/25/30</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED CUSHION</b>			<b>36 VOLTS , 39.25 X 34.50 X 23.50</b>											
											<b>Weight Minimum 3000</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>		
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>ECX20/25/30</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED CUSHION</b>			<b>48 VOLTS , 39.25 X 30.50 X 23.50</b>											
											<b>Weight Minimum 2600</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>		
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>ECX20/25/30</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED CUSHION</b>											<b>48 VOLTS , 39.25 X 34.50 X 23.50</b>				<b>Weight Minimum 3000</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>ECX32</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED CUSHION</b>											<b>36 VOLTS , 39.25 X 34.50 X 23.50</b>				<b>Weight Minimum 3100</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>ECX32</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED CUSHION</b>											<b>48 VOLTS , 39.25 X 34.50 X 23.50</b>				<b>Weight Minimum 3100</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>GTX16</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED PNEUMATIC</b>											<b>48 VOLTS , 32.90 X 20.80 X 24.69</b>				<b>Weight Minimum 1483</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 004 Inches</b>
	48	100T09	400	18.6	32.56	20.38	23.38	1615	M2802410009Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085L09	340	15.8	32.50	20.00	23.37	1525	M2902408509Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085F09	340	15.8	32.56	20.38	23.38	1599	M2502408509Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085C09	340	15.8	32.63	20.50	23.38	1520	M2602408509Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
<b>GTX18,20S</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED PNEUMATIC</b>											<b>48 VOLTS , 32.90 X 25.00 X 25.20</b>				<b>Weight Minimum 1793</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 004 Inches</b>
	48	100T11	500	23.3	32.00	24.38	22.62	1942	M2802410011Z6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085L11	425	19.8	32.00	24.38	22.62	1878	M2902408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085F11	425	19.8	32.00	24.38	22.62	1949	M2502408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085C11	425	19.8	32.00	24.50	22.62	1835	M2602408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
<b>GEX20,25,30S</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED PNEUMATIC</b>											<b>80 VOLTS , 40.50 X 28.00 X 30.75</b>				<b>Weight Minimum 3717</b>	<b>Connector SBE160</b>	<b>BLACK</b>	<b>, Position A , Lead Length 014 Inches</b>
	80	140T09	560	43.5	40.40	27.75	30.50	3550	M2804014009X50	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125L09	500	38.8	40.40	27.75	30.50	3760	M2904012509X50	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125F09	500	38.8	40.00	27.50	30.50	3579	M2504012509X50	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125C09	500	38.8	40.40	27.75	30.50	3458	M2604012509X50	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
<b>GEX30,32</b>	<b>CLASS I 4-WHEEL SIT DOWN COUNTERBALANCED PNEUMATIC</b>											<b>80 VOLTS , 40.50 X 33.62 X 30.75</b>				<b>Weight Minimum 4108</b>	<b>Connector SBE160</b>	<b>BLACK</b>	<b>, Position A , Lead Length 014 Inches</b>
	80	140T11	700	54.3	40.40	33.10	30.50	4165	M2804014011X50	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125L11	625	48.5	40.40	33.10	30.50	4400	M2904012511X50	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125F11	625	48.5	40.40	33.10	30.50	4314	M2504012511X50	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125C11	625	48.5	40.40	33.10	30.50	4172	M2604012511X50	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
<b>ESX12</b>	<b>CLASS I STAND UP END CONTROL COUNTERBALANCED</b>											<b>36 VOLTS , 38.80 X 13.88 X 31.00</b>				<b>Weight Minimum 1280</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position D , Lead Length 012 Inches</b>
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)		SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)		SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)		SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)		SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>ESX15S</b>	<b>CLASS I STAND UP END CONTROL COUNTERBALANCED</b>										<b>36 VOLTS , 38.80 X 13.88 X 31.00</b>		<b>Weight Minimum 1590</b>	<b>Connector SB350</b>	<b>GRAY , Position D , Lead Length 012 Inches</b>	
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>ESX15</b>	<b>CLASS I STAND UP END CONTROL COUNTERBALANCED</b>										<b>36 VOLTS , 38.80 X 16.13 X 31.00</b>		<b>Weight Minimum 1885</b>	<b>Connector SB350</b>	<b>GRAY , Position D , Lead Length 012 Inches</b>	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	38.50	15.90	31.38	2070	M2101804531B0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
<b>ESX17</b>	<b>CLASS I STAND UP END CONTROL COUNTERBALANCED</b>										<b>36 VOLTS , 38.80 X 18.38 X 31.00</b>		<b>Weight Minimum 2175</b>	<b>Connector SB350</b>	<b>GRAY , Position D , Lead Length 012 Inches</b>	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
<b>ESX20</b>	<b>CLASS I STAND UP END CONTROL COUNTERBALANCED</b>										<b>36 VOLTS , 38.80 X 20.88 X 31.00</b>		<b>Weight Minimum 2460</b>	<b>Connector SB350</b>	<b>GRAY , Position D , Lead Length 012 Inches</b>	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
<b>ESX22</b>	<b>CLASS I STAND UP END CONTROL COUNTERBALANCED</b>										<b>36 VOLTS , 38.80 X 20.88 X 31.00</b>		<b>Weight Minimum 1845</b>	<b>Connector SB350</b>	<b>GRAY , Position D , Lead Length 012 Inches</b>	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
<b>ESX25</b>	<b>CLASS I STAND UP END CONTROL COUNTERBALANCED</b>										<b>36 VOLTS , 38.80 X 20.88 X 31.00</b>		<b>Weight Minimum 2460</b>	<b>Connector SB350</b>	<b>GRAY , Position D , Lead Length 012 Inches</b>	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)