



Combilift Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
C6000GTElectric72V	72V	Stand-up GT Series	72 VOLTS , 56.76 X 20.53 X 29.72 Weight Minimum 0 Connector EBC320 N/A , Position D , Lead Length 036 Inches												
	72	100C11	500	34.9	56.75	20.54	29.72	3048	M2603610011H25	N	(CALL)		SCR20036600T1H	(CALL)	(CALL)
	72	140T11	700	48.9	56.75	20.54	30.75	3877	M2803614011H25	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)