

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
WP2340-45	CLASS III LOW LIFT WALKIE PALLET PLATFORM			24 VOLTS , 25.75 X 9.10 X 26.00			Weight Minimum 330		Connector SB175	GRAY , Position A , Lead Length 020 Inches					
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	090G07	270	6.4	24.00	8.64	25.36	582	M8901209007E059	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
WP2345-45	CLASS III LOW LIFT WALKIE PALLET PLATFORM			24 VOLTS , 25.75 X 9.10 X 26.00			Weight Minimum 330		Connector SB175	GRAY , Position A , Lead Length 020 Inches					
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	090G07	270	6.4	24.00	8.64	25.36	582	M8901209007E059	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
PW3510-60	CLASS III LOW LIFT WALKIE PALLET PLATFORM			12 VOLTS , 31.12 X 7.94 X 999.00			Weight Minimum 400		Connector SB350	GRAY , Position A , Lead Length 020 Inches					
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.69	6.56	23.25	533	M1800610013A1	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.69	6.56	23.25	533	M1800610013A1	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.69	6.56	23.25	535	M1900608513A1	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.69	6.56	23.25	535	M1900608513A1	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.69	6.56	23.25	508	M1600608513A1	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.69	6.56	23.25	508	M1600608513A1	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
PW3520-60	CLASS III LOW LIFT WALKIE PALLET PLATFORM			24 VOLTS , 31.12 X 13.19 X 999.00			Weight Minimum 815		Connector SB175	GRAY , Position A , Lead Length 020 Inches					
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>PW3520-60 CLASS III LOW LIFT WALKIE PALLET PLATFORM</b>															
24 VOLTS , 34.44 X 6.69 X 999.00 Weight Minimum 360 Connector SB175 GRAY , Position A , Lead Length 020 Inches															
	24	100T07	300	7.0	33.81	6.56	23.25	590	M1801210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L07	255	5.9	33.81	6.56	23.25	600	M1901208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085F07	255	5.9	33.81	6.56	23.25	578	M1501208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	33.81	6.56	23.25	554	M1601208507G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
<b>WE2300-25 CLASS III LOW LIFT WALKIE PALLET PLATFORM</b>															
12 VOLTS , 31.12 X 7.94 X 999.00 Weight Minimum 644 Connector SB350 GRAY , Position A , Lead Length 020 Inches															
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.69	6.56	23.25	533	M1800610013A1	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.69	6.56	23.25	533	M1800610013A1	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.69	6.56	23.25	535	M1900608513A1	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.69	6.56	23.25	535	M1900608513A1	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.69	6.56	23.25	508	M1600608513A1	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.69	6.56	23.25	508	M1600608513A1	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
<b>WE2300-30 CLASS III LOW LIFT WALKIE PALLET PLATFORM</b>															
12 VOLTS , 32.50 X 8.50 X 24.70 Weight Minimum 644 Connector SB350 GRAY , Position A , Lead Length 020 Inches															
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.69	6.56	23.25	533	M1800610013A1	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.69	6.56	23.25	533	M1800610013A1	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.69	6.56	23.25	535	M1900608513A1	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.69	6.56	23.25	535	M1900608513A1	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.69	6.56	23.25	508	M1600608513A1	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.69	6.56	23.25	508	M1600608513A1	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
PW3520-80	CLASS III LOW LIFT WALKIE PALLET PLATFORM							24 VOLTS , 31.12 X 13.19 X 999.00		Weight Minimum 815	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PW3520-80	CLASS III LOW LIFT WALKIE PALLET PLATFORM							24 VOLTS , 34.44 X 6.69 X 999.00		Weight Minimum 360	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	100T07	300	7.0	33.81	6.56	23.25	590	M1801210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	33.81	6.56	23.25	600	M1901208507G	N	(CALL)	SCR20012260S1H	(CALL)	(CALL)	(CALL)	
	24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085F07	255	5.9	33.81	6.56	23.25	578	M1501208507G	N	(CALL)	SCR20012260S1H	(CALL)	(CALL)	(CALL)	
	24	085C07	255	5.9	33.81	6.56	23.25	554	M1601208507G	Y	(CALL)	SCR20012260S1H	(CALL)	(CALL)	(CALL)	
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PE4000-60	CLASS III LOW-LIFT WALKIE RIDER PALLET							24 VOLTS , 31.12 X 13.19 X 31.62		Weight Minimum 975	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L11	625	14.6	30.69	12.94	31.00	1260	M1901212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F11	625	14.6	30.69	12.94	31.00	1283	M1501212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C11	625	14.6	30.69	12.94	31.00	1226	M1601212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
PE4000-60	CLASS III LOW-LIFT WALKIE RIDER PALLET							24 VOLTS , 34.44 X 6.69 X 31.62		Weight Minimum 360	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	100T07	300	7.0	33.81	6.56	23.25	590	M1801210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	33.81	6.56	23.25	600	M1901208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085F07	255	5.9	33.81	6.56	23.25	578	M1501208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C07	255	5.9	33.81	6.56	23.25	554	M1601208507G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PE4000-80	CLASS III LOW-LIFT WALKIE RIDER PALLET							24 VOLTS , 31.12 X 13.19 X 31.62		Weight Minimum 975	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L11	625	14.6	30.69	12.94	31.00	1260	M1901212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F11	625	14.6	30.69	12.94	31.00	1283	M1501212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C11	625	14.6	30.69	12.94	31.00	1226	M1601212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PE4500-80	CLASS III LOW-LIFT WALKIE RIDER PALLET							24 VOLTS , 34.44 X 6.69 X 31.62		Weight Minimum 360	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	100T07	300	7.0	33.81	6.56	23.25	590	M1801210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	33.81	6.56	23.25	600	M1901208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085F07	255	5.9	33.81	6.56	23.25	578	M1501208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C07	255	5.9	33.81	6.56	23.25	554	M1601208507G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PE4500-60	CLASS III LOW-LIFT WALKIE RIDER PALLET							24 VOLTS , 31.12 X 13.19 X 31.62		Weight Minimum 975	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L11	625	14.6	30.69	12.94	31.00	1260	M1901212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F11	625	14.6	30.69	12.94	31.00	1283	M1501212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C11	625	14.6	30.69	12.94	31.00	1226	M1601212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
PE4500-60	CLASS III LOW-LIFT WALKIE RIDER PALLET							24 VOLTS , 34.44 X 6.69 X 31.62		Weight Minimum 360	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	100T07	300	7.0	33.81	6.56	23.25	590	M1801210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	33.81	6.56	23.25	600	M1901208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085F07	255	5.9	33.81	6.56	23.25	578	M1501208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C07	255	5.9	33.81	6.56	23.25	554	M1601208507G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PE4500-80	CLASS III LOW-LIFT WALKIE RIDER PALLET							24 VOLTS , 31.12 X 13.19 X 31.62		Weight Minimum 975	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L11	625	14.6	30.69	12.94	31.00	1260	M1901212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F11	625	14.6	30.69	12.94	31.00	1283	M1501212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C11	625	14.6	30.69	12.94	31.00	1226	M1601212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PE4500-80	CLASS III LOW-LIFT WALKIE RIDER PALLET							24 VOLTS , 34.44 X 6.69 X 31.62		Weight Minimum 360	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	100T07	300	7.0	33.81	6.56	23.25	590	M1801210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	33.81	6.56	23.25	600	M1901208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085F07	255	5.9	33.81	6.56	23.25	578	M1501208507G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C07	255	5.9	33.81	6.56	23.25	554	M1601208507G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PR4500-60	CLASS III LOW LIFT WALKIE RIDER/PALLET							24 VOLTS , 31.12 X 13.19 X 999.00		Weight Minimum 975	Connector SB175	GRAY , Position A , Lead Length 022 Inches				
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L11	625	14.6	30.69	12.94	31.00	1260	M1901212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
PR4500-80	CLASS III LOW LIFT WALKIE RIDER/PALLET							24 VOLTS , 31.12 X 13.19 X 999.00		Weight Minimum 975	Connector SB175	GRAY , Position A , Lead Length 022 Inches				
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L11	625	14.6	30.69	12.94	31.00	1260	M1901212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F11	625	14.6	30.69	12.94	31.00	1283	M1501212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C11	625	14.6	30.69	12.94	31.00	1226	M1601212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PC4500-60	CLASS III LOW-LIFT WALKIE RIDER CENTER CONTROL							24 VOLTS , 31.12 X 13.19 X 31.62		Weight Minimum 975	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F11	625	14.6	30.69	12.94	31.00	1283	M1501212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C11	625	14.6	30.69	12.94	31.00	1226	M1601212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
PC4500-80	CLASS III LOW-LIFT WALKIE RIDER CENTER CONTROL							24 VOLTS , 31.12 X 13.19 X 31.62		Weight Minimum 975	Connector SB175	GRAY , Position A , Lead Length 020 Inches				
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L11	625	14.6	30.69	12.94	31.00	1260	M1901212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F11	625	14.6	30.69	12.94	31.00	1283	M1501212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C11	625	14.6	30.69	12.94	31.00	1226	M1601212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>TR3600</b>	<b>CLASS III TRACTOR / TUGGER</b>			<b>24 VOLTS , 31.12 X 13.19 X 31.62</b>											
											<b>Weight Minimum 975</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
<b>20WBTF</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b>			<b>24 VOLTS , 31.75 X 13.12 X 23.25</b>											
											<b>Weight Minimum 975</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position A , Lead Length 017 Inches</b>	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>20WB</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b>			<b>24 VOLTS , 31.75 X 13.12 X 23.25</b>											
											<b>Weight Minimum 975</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position A , Lead Length 017 Inches</b>	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>20WBTL</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b>			<b>24 VOLTS , 31.75 X 13.12 X 23.25</b>											
											<b>Weight Minimum 975</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position A , Lead Length 017 Inches</b>	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>30WBTF</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b>			<b>24 VOLTS , 31.75 X 13.12 X 23.25</b>											
											<b>Weight Minimum 975</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position A , Lead Length 017 Inches</b>	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>30WBTL</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b>			<b>24 VOLTS , 31.75 X 13.12 X 23.25</b>											
											<b>Weight Minimum 975</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position A , Lead Length 017 Inches</b>	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>30WBTT</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b>			<b>24 VOLTS , 31.75 X 13.12 X 23.25</b>											
											<b>Weight Minimum 975</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position A , Lead Length 017 Inches</b>	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>40WBTF</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b>			<b>24 VOLTS , 31.75 X 13.12 X 23.25</b>											
											<b>Weight Minimum 975</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position A , Lead Length 017 Inches</b>	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
40WBTL	CLASS III WALKIE HIGH LIFT COUNTERBALANCED			24 VOLTS , 31.75 X 13.12 X 23.25			Weight Minimum 975		Connector SB175	GRAY	, Position A , Lead Length 017 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
40WBTT	CLASS III WALKIE HIGH LIFT COUNTERBALANCED			24 VOLTS , 31.75 X 13.12 X 23.25			Weight Minimum 975		Connector SB175	GRAY	, Position A , Lead Length 017 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
SHR5520-25	CLASS III WALKIE HIGH LIFT STRADLE			24 VOLTS , 34.37 X 6.62 X 24.80			Weight Minimum 510		Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	24	085C07	255	5.9	34.25	6.56	22.63	543	M2601208507GA	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
SHR5520-30	CLASS III WALKIE HIGH LIFT STRADLE			24 VOLTS , 34.37 X 6.62 X 24.80			Weight Minimum 510		Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	24	085C07	255	5.9	34.25	6.56	22.63	543	M2601208507GA	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
SX3000-30	CLASS III WALKIE HIGH LIFT STRADLE			24 VOLTS , 26.40 X 9.10 X 23.62			Weight Minimum 360		Connector SB175	GRAY	, Position A/B, Lead Length 020 Inches				
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)			(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.63	22.63	532	M2601208507D	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
SH5520-40	CLASS III WALKIE HIGH LIFT STRADLE			24 VOLTS , 34.37 X 6.62 X 24.80			Weight Minimum 510		Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	24	085C07	255	5.9	34.25	6.56	22.63	543	M2601208507GA	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
SH5540-40	CLASS III WALKIE HIGH LIFT STRADLE			24 VOLTS , 31.10 X 13.12 X 24.80			Weight Minimum 975		Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	24	100T13	600	14.0	30.81	12.88	22.63	1075	M2801210013A7A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.81	12.88	22.63	1010	M2601208513A7A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G09	400	9.4	31.00	12.88	23.00	1000	M8901210009NPP7	N	(CALL)			(CALL)	(CALL)
SHR5540-35	CLASS III WALKIE HIGH LIFT STRADLE			24 VOLTS , 31.10 X 13.12 X 24.80			Weight Minimum 975		Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	24	100T13	600	14.0	30.81	12.88	22.63	1075	M2801210013A7A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.81	12.88	22.63	1010	M2601208513A7A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G09	400	9.4	31.00	12.88	23.00	1000	M8901210009NPP7	N	(CALL)			(CALL)	(CALL)
SP3580F	CLASS II ORDER PICKER			24 VOLTS , 36.25 X 14.25 X 31.00			Weight Minimum 1520		Connector SB350	RED	, Position A , Lead Length 020 Inches				
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.25	14.06	30.50	1734	M2901212515A6	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	170C11	850	19.8	35.25	13.31	30.50	1645	M2601217011D	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	055B31	825	19.4	36.75	14.00	30.69	1600	M2101205531FB25	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
SP3505-30	CLASS II ORDER PICKER		24 VOLTS , 31.75 X 13.12 X 23.25 Weight Minimum 975 Connector SB175 GRAY , Position A , Lead Length 020 Inches												
	24	100T13	600	14.0	30.81	12.88	22.63	1075	M2801210013A7A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.81	12.88	22.63	1010	M2601208513A7A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G09	400	9.4	31.00	12.88	23.00	1000	M8901210009NPP7	N	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
SP3510-30	CLASS II ORDER PICKER		24 VOLTS , 36.25 X 14.25 X 31.00 Weight Minimum 1520 Connector SB350 RED , Position A , Lead Length 020 Inches												
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.25	14.06	30.50	1734	M2901212515A6	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	170C11	850	19.8	35.25	13.31	30.50	1645	M2601217011D	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	055B31	825	19.4	36.75	14.00	30.69	1600	M2101205531FB25	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
SP3520-30	CLASS II ORDER PICKER		24 VOLTS , 36.25 X 14.25 X 31.00 Weight Minimum 1520 Connector SB350 RED , Position A , Lead Length 020 Inches												
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.25	14.06	30.50	1734	M2901212515A6	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	170C11	850	19.8	35.25	13.31	30.50	1645	M2601217011D	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	055B31	825	19.4	36.75	14.00	30.69	1600	M2101205531FB25	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
SP3550H-30	CLASS II ORDER PICKER		24 VOLTS , 36.25 X 14.25 X 31.00 Weight Minimum 1520 Connector SB350 RED , Position A , Lead Length 020 Inches												
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.25	14.06	30.50	1734	M2901212515A6	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	170C11	850	19.8	35.25	13.31	30.50	1645	M2601217011D	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	055B31	825	19.4	36.75	14.00	30.69	1600	M2101205531FB25	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
SP3570F	CLASS II ORDER PICKER		24 VOLTS , 36.25 X 14.25 X 31.00 Weight Minimum 1520 Connector SB350 RED , Position A , Lead Length 020 Inches												
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.25	14.06	30.50	1734	M2901212515A6	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	170C11	850	19.8	35.25	13.31	30.50	1645	M2601217011D	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	055B31	825	19.4	36.75	14.00	30.69	1600	M2101205531FB25	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
RR5715-35	NARROW AISLE REACH TRUCK		24 VOLTS , 38.38 X 14.25 X 31.00 Weight Minimum 1600 Connector SB350 RED , Position A , Lead Length 009 Inches												
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)	(CALL)	SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)	(CALL)	SCR200121050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
RR5715-35	NARROW AISLE REACH TRUCK		24 VOLTS , 38.38 X 16.25 X 31.00													Weight Minimum 1880	Connector SB350	RED	, Position A	, Lead Length 009 Inches
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)					
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
RR5715-40	NARROW AISLE REACH TRUCK		24 VOLTS , 38.38 X 14.25 X 31.00													Weight Minimum 1600	Connector SB350	RED	, Position A	, Lead Length 011 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
RR5715-40	NARROW AISLE REACH TRUCK		24 VOLTS , 38.38 X 16.25 X 31.00													Weight Minimum 1880	Connector SB350	RED	, Position A	, Lead Length 011 Inches
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)					
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
RR5725-45	CLASS II NARROW AISLE REACH		36 VOLTS , 38.38 X 16.25 X 31.00													Weight Minimum 2000	Connector SB350	GRAY	, Position A	, Lead Length 011 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)					
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
RR5725-45	CLASS II NARROW AISLE REACH		36 VOLTS , 38.38 X 18.00 X 31.00													Weight Minimum 2280	Connector SB350	GRAY	, Position A	, Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)					
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)					
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)					
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)					
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)					
RR5725-45	CLASS II NARROW AISLE REACH		36 VOLTS , 38.38 X 20.75 X 31.00													Weight Minimum 2600	Connector SB350	GRAY	, Position A	, Lead Length 011 Inches
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)					
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)					
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)					
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)					
RD5725-30	CLASS II NARROW AISLE REACH		36 VOLTS , 38.38 X 14.25 X 31.00													Weight Minimum 1600	Connector SB350	GRAY	, Position A	, Lead Length 011 Inches
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
RD5725-30	CLASS II NARROW AISLE REACH		36 VOLTS , 38.38 X 16.25 X 31.00													Weight Minimum 2000	Connector SB350	GRAY	, Position A	, Lead Length 011 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)					
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>RD5725-30</b>	<b>CLASS II NARROW AISLE REACH</b>			<b>36 VOLTS , 38.38 X 18.00 X 31.00</b>												
											<b>Weight Minimum 2280</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 011 Inches</b>		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
<b>RD5725-30</b>	<b>CLASS II NARROW AISLE REACH</b>			<b>36 VOLTS , 38.38 X 20.75 X 31.00</b>												
											<b>Weight Minimum 2600</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 011 Inches</b>		
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
<b>RR5795S-45</b>	<b>CLASS II NARROW AISLE REACH</b>			<b>36 VOLTS , 38.38 X 16.25 X 31.00</b>												
											<b>Weight Minimum 2000</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 011 Inches</b>		
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>RR5795S-45</b>	<b>CLASS II NARROW AISLE REACH</b>			<b>36 VOLTS , 38.38 X 18.00 X 31.00</b>												
											<b>Weight Minimum 2280</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 011 Inches</b>		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
<b>RR5795S-45</b>	<b>CLASS II NARROW AISLE REACH</b>			<b>36 VOLTS , 38.38 X 20.75 X 31.00</b>												
											<b>Weight Minimum 2600</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 011 Inches</b>		
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
<b>RM6095S</b>	<b>CLASS II NARROW AISLE REACH MONOLIFT MAST</b>			<b>36 VOLTS , 38.38 X 20.75 X 31.00</b>												
											<b>Weight Minimum 2600</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 011 Inches</b>		
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>RMD6095S</b>	<b>CLASS II NARROW AISLE REACH MONOLIFT MAST</b>							<b>36 VOLTS , 38.38 X 20.75 X 31.00</b>		<b>Weight Minimum 2600</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 011 Inches</b>				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
<b>SR5285H</b>	<b>CLASS II NARROW AISLE REACH</b>							<b>48 VOLTS , 48.15 X 19.64 X 30.56</b>		<b>Weight Minimum 2736</b>	<b>Connector SB350</b>	<b>BLUE , Position N/A, Lead Length 000 Inches</b>				
	48	125F15	875	40.7	48.00	19.34	30.50	3160	M2502412515E6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	125C15	875	40.7	48.00	19.34	30.50	3050	M2602412515E6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
<b>SR5000</b>	<b>CLASS II NARROW AISLE MOVING MAST COLD STORAGE</b>							<b>48 VOLTS , 46.97 X 19.64 X 30.56</b>		<b>Weight Minimum 2736</b>	<b>Connector SB350</b>	<b>BLUE , Position N/A, Lead Length 000 Inches</b>				
	48	140T15	980	45.6	48.00	19.34	30.50	3380	M2802414015E6	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	125L15	875	40.7	48.00	19.34	30.50	3230	M2902412515E6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	125F15	875	40.7	48.00	19.34	30.50	3160	M2502412515E6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	125C15	875	40.7	48.00	19.34	30.50	3050	M2602412515E6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
<b>SR5000</b>	<b>CLASS II NARROW AISLE MOVING MAST COLD STORAGE</b>							<b>48 VOLTS , 48.15 X 19.64 X 30.56</b>		<b>Weight Minimum 2736</b>	<b>Connector SB350</b>	<b>BLUE , Position N/A, Lead Length 000 Inches</b>				
	48	140T15	980	45.6	48.00	19.34	30.50	3380	M2802414015E6	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	125L15	875	40.7	48.00	19.34	30.50	3230	M2902412515E6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	125F15	875	40.7	48.00	19.34	30.50	3160	M2502412515E6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	125C15	875	40.7	48.00	19.34	30.50	3050	M2602412515E6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
<b>RD5795S</b>	<b>CLASS II NARROW AISLE DOUBLE REACH</b>							<b>36 VOLTS , 38.38 X 16.25 X 31.00</b>		<b>Weight Minimum 2000</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 009 Inches</b>				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>RD5795S</b>	<b>CLASS II NARROW AISLE DOUBLE REACH</b>							<b>36 VOLTS , 38.69 X 18.00 X 31.00</b>		<b>Weight Minimum 2280</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 009 Inches</b>				
	36	140T15	980	34.2	38.31	17.75	31.00	2469	M1801814015B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
<b>RD5795S</b>	<b>CLASS II NARROW AISLE DOUBLE REACH</b>							<b>36 VOLTS , 38.69 X 20.75 X 31.00</b>		<b>Weight Minimum 2800</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 009 Inches</b>				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
<b>40TS</b>	<b>CLASS II VERY NARROW AISLE TURRET</b>							<b>72 VOLTS , 38.38 X 18.00 X 31.00</b>		<b>Weight Minimum 2085</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 009 Inches</b>				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
TSP6000	CLASS II VERY NARROW AISLE TURRET											48 VOLTS , 44.50 X 24.69 X 31.00	Weight Minimum 2900	Connector SB350	BLUE , Position A , Lead Length 015 Inches		
	48	140T15	980	45.6	43.38	23.63	30.50	3388	M2802414015A	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	125F15	875	40.7	43.00	23.63	30.50	3181	M2502412515B11	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)		
	48	125F15	875	40.7	43.38	23.63	30.50	3162	M2502412515A	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)		
	48	125C15	875	40.7	43.00	23.63	30.50	3179	M2602412515B11	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)		
TSP6000	CLASS II VERY NARROW AISLE TURRET											48 VOLTS , 44.50 X 28.12 X 31.00	Weight Minimum 3140	Connector SB350	BLUE , Position A , Lead Length 015 Inches		
	48	140T17	1120	52.1	38.44	26.88	30.50	3862	M2802414017B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	125L17	1000	46.6	38.44	26.88	30.50	3741	M2902412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	125F17	1000	46.6	38.44	26.88	30.50	3763	M2502412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	125C17	1000	46.6	38.44	26.88	30.50	3636	M2602412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
TSP6000	CLASS II VERY NARROW AISLE TURRET											48 VOLTS , 44.50 X 33.75 X 31.00	Weight Minimum 3880	Connector SB350	BLUE , Position A , Lead Length 015 Inches		
	48	140T21	1400	65.2	38.50	33.00	30.50	4334	M2802414021B	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)		
	48	125L21	1250	58.2	44.25	33.00	30.50	4543	M2902412521B6	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)		
	48	125F23	1375	64.0	44.53	32.03	30.50	5069	M2502412523Z	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)		
	48	125C21	1250	58.2	38.50	33.00	30.50	4322	M2602412521B	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)		
TSP7000	CLASS II VERY NARROW AISLE TURRET 72 VOLTS											72 VOLTS , 44.50 X 39.12 X 31.00	Weight Minimum 2280	Connector SB350	GREY , Position A , Lead Length 015 Inches		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
30TSP-48	CLASS II VERY NARROW AISLE TURRET											48 VOLTS , 38.75 X 27.00 X 31.00	Weight Minimum 3140	Connector SB350	GRAY , Position A , Lead Length 009 Inches		
	48	140T17	1120	52.1	38.44	26.88	30.50	3862	M2802414017B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	125L17	1000	46.6	38.44	26.88	30.50	3741	M2902412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	125F17	1000	46.6	38.44	26.88	30.50	3763	M2502412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	125C17	1000	46.6	38.44	26.88	30.50	3636	M2602412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
30TSP-48	CLASS II VERY NARROW AISLE TURRET											48 VOLTS , 38.75 X 33.00 X 31.00	Weight Minimum 3800	Connector SB350	GRAY , Position A , Lead Length 009 Inches		
	48	125C19	1125	52.4	38.44	32.25	30.50	4043	M2602412519B6	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	105B21	1050	49.4	39.61	31.89	30.86	4080	M2102410521B781	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
30TSP-72	CLASS II VERY NARROW AISLE TURRET											72 VOLTS , 38.38 X 15.88 X 31.00	Weight Minimum 1770	Connector SB350	GRAY , Position A , Lead Length 009 Inches		
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
30TSP-72	CLASS II VERY NARROW AISLE TURRET											72 VOLTS , 38.44 X 13.50 X 31.00	Weight Minimum 1610	Connector SB350	GRAY , Position A , Lead Length 009 Inches		
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
30TSP-72	CLASS II VERY NARROW AISLE TURRET											72 VOLTS , 38.69 X 18.00 X 31.00				Weight Minimum 2085	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
SC5210-30	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 38.81 X 16.63 X 22.63				Weight Minimum 1475	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	085C13	510	17.8	38.00	15.50	22.63	1425	M2601808513B	Y	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)			
SC5220-30	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 38.81 X 20.87 X 22.63				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	060B23	660	23.3	38.50	19.62	23.69	1975	M2101806023B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
SC5220-30	CLASS I 3 WHEEL COUNTERBALANCED											48 VOLTS , 38.81 X 20.87 X 22.63				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
SC5220-35	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 38.81 X 20.87 X 22.63				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	060B23	660	23.3	38.50	19.62	23.69	1975	M2101806023B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
SC5220-35	CLASS I 3 WHEEL COUNTERBALANCED											48 VOLTS , 38.81 X 20.87 X 22.63				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
SC5240-35	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 38.81 X 25.13 X 22.63				Weight Minimum 2250	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C19	765	26.7	38.44	23.75	22.63	2315	M2601808519B725	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
SC5240-35	CLASS I 3 WHEEL COUNTERBALANCED											48 VOLTS , 38.81 X 25.13 X 22.63				Weight Minimum 2250	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
SC5245-40	CLASS I 3 WHEEL COUNTERBALANCED											36 VOLTS , 38.81 X 25.13 X 22.63				Weight Minimum 2250	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C19	765	26.7	38.44	23.75	22.63	2315	M2601808519B725	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
SC5245-40	CLASS I 3 WHEEL COUNTERBALANCED											48 VOLTS , 38.81 X 25.13 X 22.63				Weight Minimum 2250	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
FC4510-40	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 38.69 X 27.25 X 23.35				Weight Minimum 2630	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F23	935	32.7	38.44	27.00	23.12	2760	M2501808523B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085C23	935	32.7	38.44	27.00	23.12	2716	M2601808523B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
FC4510-40	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 38.69 X 27.25 X 23.35				Weight Minimum 2630	Connector SB350	BLUE , Position A , Lead Length 018 Inches
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C17	680	31.7	38.25	27.00	22.88	2684	M2602408517B725	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
FC4510-50	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 38.69 X 27.25 X 23.35				Weight Minimum 2630	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F23	935	32.7	38.44	27.00	23.12	2760	M2501808523B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085C23	935	32.7	38.44	27.00	23.12	2716	M2601808523B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
FC4510-50	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 38.69 X 27.25 X 23.35				Weight Minimum 2630	Connector SB350	BLUE , Position A , Lead Length 018 Inches
	48	085C17	680	31.7	38.25	27.00	22.88	2684	M2602408517B725	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
FC4515-40	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 38.69 X 27.25 X 23.35				Weight Minimum 2630	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F23	935	32.7	38.44	27.00	23.12	2760	M2501808523B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085C23	935	32.7	38.44	27.00	23.12	2716	M2601808523B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
FC4515-40	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 38.69 X 27.25 X 23.35				Weight Minimum 2630	Connector SB350	BLUE , Position A , Lead Length 018 Inches
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C17	680	31.7	38.25	27.00	22.88	2684	M2602408517B725	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
FC4515-50	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 38.69 X 27.25 X 23.35				Weight Minimum 2630	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L23	935	32.7	38.44	27.00	23.12	2781	M2901808523B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085F23	935	32.7	38.44	27.00	23.12	2760	M2501808523B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085C23	935	32.7	38.44	27.00	23.12	2716	M2601808523B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
FC4515-50	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 38.69 X 27.25 X 23.35				Weight Minimum 2630	Connector SB350	BLUE , Position A , Lead Length 018 Inches
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C17	680	31.7	38.25	27.00	22.88	2684	M2602408517B725	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
FC4520-40	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 32.94 X 23.35											Weight Minimum 2800	Connector SB350	GRAY	, Position A , Lead Length 018 Inches
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
FC4520-40	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 32.94 X 23.35											Weight Minimum 2800	Connector SB350	BLUE	, Position A , Lead Length 018 Inches
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
FC4520-50	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 32.94 X 23.35											Weight Minimum 2800	Connector SB350	GRAY	, Position A , Lead Length 018 Inches
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
FC4520-50	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 32.94 X 23.35											Weight Minimum 2800	Connector SB350	BLUE	, Position A , Lead Length 018 Inches
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
FC4520-55	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 32.94 X 23.35											Weight Minimum 2800	Connector SB350	GRAY	, Position A , Lead Length 018 Inches
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
FC4520-55	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 32.94 X 23.35											Weight Minimum 2800	Connector SB350	BLUE	, Position A , Lead Length 018 Inches
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
FC4520-60	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 32.94 X 23.35											Weight Minimum 2800	Connector SB350	GRAY	, Position A , Lead Length 018 Inches
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
FC4520-60	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 32.94 X 23.35												
											Weight Minimum 2800	Connector SB350	BLUE	, Position A , Lead Length 018 Inches		
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
FC4525-40	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 32.94 X 23.35												
											Weight Minimum 2800	Connector SB350	GRAY	, Position A , Lead Length 018 Inches		
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
FC4525-40	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 32.94 X 23.35												
											Weight Minimum 2800	Connector SB350	BLUE	, Position A , Lead Length 018 Inches		
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
FC4525-50	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 32.94 X 23.35												
											Weight Minimum 2800	Connector SB350	GRAY	, Position A , Lead Length 018 Inches		
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
FC4525-50	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 32.94 X 23.35												
											Weight Minimum 2800	Connector SB350	BLUE	, Position A , Lead Length 018 Inches		
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
FC4525-55	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 32.94 X 23.35												
											Weight Minimum 2800	Connector SB350	GRAY	, Position A , Lead Length 018 Inches		
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
FC4525-55	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 32.94 X 23.35												
											Weight Minimum 2800	Connector SB350	BLUE	, Position A , Lead Length 018 Inches		
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
FC4525-60	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 32.94 X 23.35												
											Weight Minimum 2800	Connector SB350	GRAY	, Position A , Lead Length 018 Inches		
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
FC4525-60	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 32.94 X 23.35												
											Weight Minimum 2800	Connector SB350	BLUE	, Position A , Lead Length 018 Inches		
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
FC4540-50	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 36.38 X 23.35												
											Weight Minimum 3100	Connector SB350	GRAY	, Position A , Lead Length 018 Inches		
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)	
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
FC4540-50	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 36.38 X 23.35												
											Weight Minimum 3100	Connector SB350	BLUE	, Position A , Lead Length 018 Inches		
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
FC4540-55	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 36.38 X 23.35												
											Weight Minimum 3100	Connector SB350	GRAY	, Position A , Lead Length 018 Inches		
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)	
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
FC4540-55	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 36.38 X 23.35												
											Weight Minimum 3100	Connector SB350	BLUE	, Position A , Lead Length 018 Inches		
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
FC4540-60	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 36.38 X 23.35												
											Weight Minimum 3100	Connector SB350	GRAY	, Position A , Lead Length 018 Inches		
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)	
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
FC4540-60	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 38.69 X 36.38 X 23.35												
											Weight Minimum 3100	Connector SB350	BLUE	, Position A , Lead Length 018 Inches		
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
FC4545-50	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 38.69 X 36.38 X 23.35												
											Weight Minimum 3100	Connector SB350	GRAY	, Position A , Lead Length 018 Inches		
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)	
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
FC4545-50	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 38.69 X 36.38 X 23.35				Weight Minimum 3100	Connector SB350	BLUE , Position A , Lead Length 018 Inches
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)			
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
FC4545-55	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 38.69 X 36.38 X 23.35				Weight Minimum 3100	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)			
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
FC4545-55	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 38.69 X 36.38 X 23.35				Weight Minimum 3100	Connector SB350	BLUE , Position A , Lead Length 018 Inches
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)			
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
FC4545-60	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 38.69 X 36.38 X 23.35				Weight Minimum 3100	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)			
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
FC4545-60	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 38.69 X 36.38 X 23.35				Weight Minimum 3100	Connector SB350	BLUE , Position A , Lead Length 018 Inches
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)			
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
RC5510-30	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 13.60 X 31.00				Weight Minimum 1710	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
RC5515-30	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 13.60 X 31.00				Weight Minimum 1710	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
RC5520-30	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 15.88 X 31.00				Weight Minimum 1990	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
RC5525-30	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 15.88 X 31.00				Weight Minimum 1990	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
RC5530-30	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 18.20 X 31.00				Weight Minimum 2280	Connector SB350	GRAY , Position A , Lead Length 009 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
RC5530-35	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 18.20 X 31.00		Weight Minimum 2280	Connector SB350	GRAY	, Position A , Lead Length 009 Inches	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
RC5535-30	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 18.20 X 31.00		Weight Minimum 2280	Connector SB350	GRAY	, Position A , Lead Length 009 Inches	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
RC5535-35	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 18.20 X 31.00		Weight Minimum 2280	Connector SB350	GRAY	, Position A , Lead Length 009 Inches	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
RC5540-40	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 20.50 X 31.00		Weight Minimum 2600	Connector SB350	GRAY	, Position A , Lead Length 009 Inches	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
RC5545-40	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.56 X 20.50 X 31.00		Weight Minimum 2600	Connector SB350	GRAY	, Position A , Lead Length 009 Inches	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)