

| TRUCK MODEL | VOLT                                      | BATTERY TYPE | CAPACITY 6 HOUR RATE |                                   | BATTERY DIMENSIONS |               |                    | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP                                      | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|---|--------------|----------------------|-----------------------------------|--------------------|---------------|--------------------|------------------|----------------------|--|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|             |   |              | A.H.                 | KwH                               | X in. (Length)     | Y in. (Width) | Z in. (Height)     |                  |                      |  |                    |                            |                           |                        |                        |
| WP2340-45   | CLASS III LOW LIFT WALKIE PALLET PLATFORM |              |                      | 24 VOLTS , 25.75 X 9.10 X 26.00   |                    |               | Weight Minimum 330 |                  | Connector SB175      | GRAY , Position A , Lead Length 020 Inches |                    |                            |                           |                        |                        |
|             | 24  | 100T07       | 300                  | 7.0                               | 25.38              | 8.69          | 23.25              | 601              | M1801210007D         | Y  | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24  | 085L07       | 255                  | 5.9                               | 25.38              | 8.69          | 23.25              | 585              | M1901208507D         | Y  | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24  | 085C07       | 255                  | 5.9                               | 25.38              | 8.69          | 23.25              | 565              | M1601208507D         | Y  | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24  | 090G07       | 270                  | 6.4                               | 24.00              | 8.64          | 25.36              | 582              | M8901209007E059      | Y  | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
| WP2345-45   | CLASS III LOW LIFT WALKIE PALLET PLATFORM |              |                      | 24 VOLTS , 25.75 X 9.10 X 26.00   |                    |               | Weight Minimum 330 |                  | Connector SB175      | GRAY , Position A , Lead Length 020 Inches |                    |                            |                           |                        |                        |
|             | 24  | 100T07       | 300                  | 7.0                               | 25.38              | 8.69          | 23.25              | 601              | M1801210007D         | Y  | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24  | 085L07       | 255                  | 5.9                               | 25.38              | 8.69          | 23.25              | 585              | M1901208507D         | Y  | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24  | 085C07       | 255                  | 5.9                               | 25.38              | 8.69          | 23.25              | 565              | M1601208507D         | Y  | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|             | 24  | 090G07       | 270                  | 6.4                               | 24.00              | 8.64          | 25.36              | 582              | M8901209007E059      | Y  | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
| PW3510-60   | CLASS III LOW LIFT WALKIE PALLET PLATFORM |              |                      | 12 VOLTS , 31.12 X 7.94 X 999.00  |                    |               | Weight Minimum 400 |                  | Connector SB350      | GRAY , Position A , Lead Length 020 Inches |                    |                            |                           |                        |                        |
|             | 12  | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25              | 543              | M1800610013A         | N  | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 100T13       | 600                  | 7.0                               | 30.44              | 7.63          | 23.25              | 543              | M1800610013A         | N  | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 100T13       | 600                  | 7.0                               | 30.69              | 6.56          | 23.25              | 533              | M1800610013A1        | N  | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 100T13       | 600                  | 7.0                               | 30.69              | 6.56          | 23.25              | 533              | M1800610013A1        | N  | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085L13       | 510                  | 5.9                               | 30.69              | 6.56          | 23.25              | 535              | M1900608513A1        | N  | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085L13       | 510                  | 5.9                               | 30.69              | 6.56          | 23.25              | 535              | M1900608513A1        | N  | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25              | 523              | M1900608513A         | N  | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085L13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25              | 523              | M1900608513A         | N  | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25              | 534              | M1500608513A         | N  | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085F13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25              | 534              | M1500608513A         | N  | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25              | 513              | M1600608513A         | Y  | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085C13       | 510                  | 5.9                               | 30.44              | 7.63          | 23.25              | 513              | M1600608513A         | Y  | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085C13       | 510                  | 5.9                               | 30.69              | 6.56          | 23.25              | 508              | M1600608513A1        | Y  | (CALL)             | SCR20006600S1H             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 085C13       | 510                  | 5.9                               | 30.69              | 6.56          | 23.25              | 508              | M1600608513A1        | Y  | (CALL)             | SCR20006600S1L             | SCR20006600T1H            | (CALL)                 | (CALL)                 |
|             | 12  | 100G09       | 400                  | 4.7                               | 30.88              | 7.75          | 23.98              | 500              | M8900610009APP       | Y  | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
| PW3520-60   | CLASS III LOW LIFT WALKIE PALLET PLATFORM |              |                      | 24 VOLTS , 31.12 X 13.19 X 999.00 |                    |               | Weight Minimum 815 |                  | Connector SB175      | GRAY , Position A , Lead Length 020 Inches |                    |                            |                           |                        |                        |
|             | 24  | 140T13       | 840                  | 19.6                              | 30.63              | 12.81         | 31.00              | 1435             | M1801214013A         | Y  | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 100T13       | 600                  | 14.0                              | 30.63              | 12.69         | 23.25              | 1020             | M1801210013A         | Y  | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 085L13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25              | 983              | M1901208513A         | Y  | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 125L13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00              | 1358             | M1901212513A         | Y  | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 100F13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13              | 1149             | M1501210013A         | Y  | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 125F13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00              | 1383             | M1501212513A         | Y  | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 085F13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25              | 1001             | M1501208513A         | Y  | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 100C13       | 600                  | 14.0                              | 30.63              | 12.69         | 26.13              | 1107             | M1601210013A         | Y  | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 125C13       | 750                  | 17.5                              | 30.63              | 12.81         | 31.00              | 1341             | M1601212513A         | Y  | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 085C13       | 510                  | 11.9                              | 30.82              | 12.88         | 23.25              | 993              | M1601208513A25C      | Y  | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 085C13       | 510                  | 11.9                              | 30.63              | 12.69         | 23.25              | 966              | M1601208513A         | Y  | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 105B15       | 735                  | 17.3                              | 30.73              | 13.00         | 30.53              | 1415             | M2101210515N         | N  | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|             | 24  | 100G11       | 500                  | 11.8                              | 30.70              | 12.75         | 28.42              | 1035             | M8901210011NPP059    | Y  | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|             | 24  | 100G11       | 500                  | 11.8                              | 30.69              | 12.88         | 26.40              | 1075             | M8901210011N059      | Y  | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL   | VOLT | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|---|------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|   |      |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| PW3520-60 CLASS III LOW LIFT WALKIE PALLET PLATFORM 24 VOLTS , 34.44 X 6.69 X 999.00 Weight Minimum 360 Connector SB175 GRAY , Position A , Lead Length 020 Inches  |      |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|   | 24   | 100T07       | 300                  | 7.0  | 33.81              | 6.56          | 23.25          | 590              | M1801210007G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 140T07       | 420                  | 9.8  | 33.88              | 6.63          | 31.00          | 856              | M1801214007G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085L07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 600              | M1901208507G         | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|   | 24   | 125L07       | 375                  | 8.7  | 33.88              | 6.63          | 31.00          | 840              | M1901212507G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085F07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 578              | M1501208507G         | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|   | 24   | 085C07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 554              | M1601208507G         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|   | 24   | 100C07       | 300                  | 7.0  | 33.81              | 6.63          | 26.13          | 624              | M1601210007G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 125C07       | 375                  | 8.7  | 33.88              | 6.63          | 31.00          | 802              | M1601212507G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
| PW3520-80 CLASS III LOW LIFT WALKIE PALLET PLATFORM 24 VOLTS , 31.12 X 13.19 X 999.00 Weight Minimum 815 Connector SB175 GRAY , Position A , Lead Length 020 Inches |      |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|   | 24   | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 100T13       | 600                  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085L13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 983              | M1901208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 100F13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1149             | M1501210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085F13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 1001             | M1501208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 100C13       | 600                  | 14.0 | 30.63              | 12.69         | 26.13          | 1107             | M1601210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085C13       | 510                  | 11.9 | 30.63              | 12.69         | 23.25          | 966              | M1601208513A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 105B15       | 735                  | 17.3 | 30.73              | 13.00         | 30.53          | 1415             | M2101210515N         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 100G11       | 500                  | 11.8 | 30.70              | 12.75         | 28.42          | 1035             | M8901210011NPP059    | Y     | (CALL)             |                            |                           | (CALL)                 | (CALL)                 |
|   | 24   | 100G11       | 500                  | 11.8 | 30.69              | 12.88         | 26.40          | 1075             | M8901210011N059      | Y     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
| PW3520-80 CLASS III LOW LIFT WALKIE PALLET PLATFORM 24 VOLTS , 34.44 X 6.69 X 999.00 Weight Minimum 360 Connector SB175 GRAY , Position A , Lead Length 020 Inches  |      |              |                      |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|   | 24   | 100T07       | 300                  | 7.0  | 33.81              | 6.56          | 23.25          | 590              | M1801210007G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 140T07       | 420                  | 9.8  | 33.88              | 6.63          | 31.00          | 856              | M1801214007G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085L07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 600              | M1901208507G         | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|   | 24   | 125L07       | 375                  | 8.7  | 33.88              | 6.63          | 31.00          | 840              | M1901212507G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 085F07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 578              | M1501208507G         | N     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|   | 24   | 085C07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 554              | M1601208507G         | Y     | (CALL)             | SCR20012260S1H             |                           | (CALL)                 | (CALL)                 |
|   | 24   | 100C07       | 300                  | 7.0  | 33.81              | 6.63          | 26.13          | 624              | M1601210007G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |
|   | 24   | 125C07       | 375                  | 8.7  | 33.88              | 6.63          | 31.00          | 802              | M1601212507G         | N     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                                   | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.)                 | BATTERY MODEL NUMBER | Q-SHP              | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)                 | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |  |
|-------------|--|--------------|----------------------|------|--------------------|---------------|----------------|----------------------------------|----------------------|--------------------|--------------------|--|---------------------------|------------------------|------------------------|--|
|             |  |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                                  |                      |                    |                    |  |                           |                        |                        |  |
| PE4000-60   | CLASS III LOW-LIFT WALKIE RIDER PALLET |              |                      |      |                    |               |                | 24 VOLTS , 31.12 X 13.19 X 31.62 |                      | Weight Minimum 975 | Connector SB175    | GRAY , Position A , Lead Length 020 Inches |                           |                        |                        |  |
|             | 24                                     | 140T11       | 700                  | 16.3 | 30.69              | 12.94         | 31.00          | 1302                             | M1801214011A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435                             | M1801214013A         | Y                  | (CALL)             | SCR20012965S1H                             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013                             | M1901208513A25C      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1260                             | M1901212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358                             | M1901212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125F11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1283                             | M1501212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383                             | M1501212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1226                             | M1601212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341                             | M1601212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993                              | M1601208513A25C      | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 105B15       | 735                  | 17.3 | 30.73              | 13.00         | 30.53          | 1415                             | M2101210515N         | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100G11       | 500                  | 11.8 | 30.70              | 12.75         | 28.42          | 1035                             | M8901210011NPP059    | Y                  | (CALL)             | (CALL)                                     | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100G11       | 500                  | 11.8 | 30.69              | 12.88         | 26.40          | 1075                             | M8901210011N059      | Y                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| PE4000-60   | CLASS III LOW-LIFT WALKIE RIDER PALLET |              |                      |      |                    |               |                | 24 VOLTS , 34.44 X 6.69 X 31.62  |                      | Weight Minimum 360 | Connector SB175    | GRAY , Position A , Lead Length 020 Inches |                           |                        |                        |  |
|             | 24                                     | 100T07       | 300                  | 7.0  | 33.81              | 6.56          | 23.25          | 590                              | M1801210007G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 140T07       | 420                  | 9.8  | 33.88              | 6.63          | 31.00          | 856                              | M1801214007G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085L07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 600                              | M1901208507G         | N                  | (CALL)             | SCR20012260S1H                             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L07       | 375                  | 8.7  | 33.88              | 6.63          | 31.00          | 840                              | M1901212507G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085F07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 578                              | M1501208507G         | N                  | (CALL)             | SCR20012260S1H                             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085C07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 554                              | M1601208507G         | Y                  | (CALL)             | SCR20012260S1H                             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100C07       | 300                  | 7.0  | 33.81              | 6.63          | 26.13          | 624                              | M1601210007G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C07       | 375                  | 8.7  | 33.88              | 6.63          | 31.00          | 802                              | M1601212507G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| PE4000-80   | CLASS III LOW-LIFT WALKIE RIDER PALLET |              |                      |      |                    |               |                | 24 VOLTS , 31.12 X 13.19 X 31.62 |                      | Weight Minimum 975 | Connector SB175    | GRAY , Position A , Lead Length 020 Inches |                           |                        |                        |  |
|             | 24                                     | 140T11       | 700                  | 16.3 | 30.69              | 12.94         | 31.00          | 1302                             | M1801214011A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435                             | M1801214013A         | Y                  | (CALL)             | SCR20012965S1H                             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013                             | M1901208513A25C      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1260                             | M1901212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358                             | M1901212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125F11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1283                             | M1501212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383                             | M1501212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1226                             | M1601212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341                             | M1601212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993                              | M1601208513A25C      | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 105B15       | 735                  | 17.3 | 30.73              | 13.00         | 30.53          | 1415                             | M2101210515N         | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100G11       | 500                  | 11.8 | 30.70              | 12.75         | 28.42          | 1035                             | M8901210011NPP059    | Y                  | (CALL)             | (CALL)                                     | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100G11       | 500                  | 11.8 | 30.69              | 12.88         | 26.40          | 1075                             | M8901210011N059      | Y                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| PE4000-80   | CLASS III LOW-LIFT WALKIE RIDER PALLET |              |                      |      |                    |               |                | 24 VOLTS , 34.44 X 6.69 X 31.62  |                      | Weight Minimum 360 | Connector SB175    | GRAY , Position A , Lead Length 020 Inches |                           |                        |                        |  |
|             | 24                                     | 100T07       | 300                  | 7.0  | 33.81              | 6.56          | 23.25          | 590                              | M1801210007G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 140T07       | 420                  | 9.8  | 33.88              | 6.63          | 31.00          | 856                              | M1801214007G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085L07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 600                              | M1901208507G         | N                  | (CALL)             | SCR20012260S1H                             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L07       | 375                  | 8.7  | 33.88              | 6.63          | 31.00          | 840                              | M1901212507G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085F07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 578                              | M1501208507G         | N                  | (CALL)             | SCR20012260S1H                             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085C07       | 255                  | 5.9  | 33.81              | 6.56          | 23.25          | 554                              | M1601208507G         | Y                  | (CALL)             | SCR20012260S1H                             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100C07       | 300                  | 7.0  | 33.81              | 6.63          | 26.13          | 624                              | M1601210007G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C07       | 375                  | 8.7  | 33.88              | 6.63          | 31.00          | 802                              | M1601212507G         | N                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                                   | BATTERY TYPE | CAPACITY 6 HOUR RATE |                                  | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP           | BATTERY LIST PRICE                         | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |  |
|-------------|--|--------------|----------------------|----------------------------------|--------------------|---------------|----------------|------------------|----------------------|-----------------|--|----------------------------|---------------------------|------------------------|------------------------|--|
|             |  |              | A.H.                 | KwH                              | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |                 |  |                            |                           |                        |                        |  |
| PE4500-60   | CLASS III LOW-LIFT WALKIE RIDER PALLET |              |                      | 24 VOLTS , 31.12 X 13.19 X 31.62 |                    |               |                |                  | Weight Minimum 975   | Connector SB175 | GRAY , Position A , Lead Length 020 Inches |                            |                           |                        |                        |  |
|             | 24                                     | 140T11       | 700                  | 16.3                             | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 140T13       | 840                  | 19.6                             | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y               | (CALL)                                     | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085L13       | 510                  | 11.9                             | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N               | (CALL)                                     | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L11       | 625                  | 14.6                             | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L13       | 750                  | 17.5                             | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125F11       | 625                  | 14.6                             | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125F13       | 750                  | 17.5                             | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C11       | 625                  | 14.6                             | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C13       | 750                  | 17.5                             | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085C13       | 510                  | 11.9                             | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y               | (CALL)                                     | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 105B15       | 735                  | 17.3                             | 30.73              | 13.00         | 30.53          | 1415             | M2101210515N         | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100G11       | 500                  | 11.8                             | 30.70              | 12.75         | 28.42          | 1035             | M8901210011NPP059    | Y               | (CALL)                                     | (CALL)                     | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100G11       | 500                  | 11.8                             | 30.69              | 12.88         | 26.40          | 1075             | M8901210011N059      | Y               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| PE4500-60   | CLASS III LOW-LIFT WALKIE RIDER PALLET |              |                      | 24 VOLTS , 34.44 X 6.69 X 31.62  |                    |               |                |                  | Weight Minimum 360   | Connector SB175 | GRAY , Position A , Lead Length 020 Inches |                            |                           |                        |                        |  |
|             | 24                                     | 100T07       | 300                  | 7.0                              | 33.81              | 6.56          | 23.25          | 590              | M1801210007G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 140T07       | 420                  | 9.8                              | 33.88              | 6.63          | 31.00          | 856              | M1801214007G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085L07       | 255                  | 5.9                              | 33.81              | 6.56          | 23.25          | 600              | M1901208507G         | N               | (CALL)                                     | SCR20012260S1H             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L07       | 375                  | 8.7                              | 33.88              | 6.63          | 31.00          | 840              | M1901212507G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085F07       | 255                  | 5.9                              | 33.81              | 6.56          | 23.25          | 578              | M1501208507G         | N               | (CALL)                                     | SCR20012260S1H             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085C07       | 255                  | 5.9                              | 33.81              | 6.56          | 23.25          | 554              | M1601208507G         | Y               | (CALL)                                     | SCR20012260S1H             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100C07       | 300                  | 7.0                              | 33.81              | 6.63          | 26.13          | 624              | M1601210007G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C07       | 375                  | 8.7                              | 33.88              | 6.63          | 31.00          | 802              | M1601212507G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| PE4500-80   | CLASS III LOW-LIFT WALKIE RIDER PALLET |              |                      | 24 VOLTS , 31.12 X 13.19 X 31.62 |                    |               |                |                  | Weight Minimum 975   | Connector SB175 | GRAY , Position A , Lead Length 020 Inches |                            |                           |                        |                        |  |
|             | 24                                     | 140T11       | 700                  | 16.3                             | 30.69              | 12.94         | 31.00          | 1302             | M1801214011A6        | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 140T13       | 840                  | 19.6                             | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y               | (CALL)                                     | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085L13       | 510                  | 11.9                             | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N               | (CALL)                                     | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L11       | 625                  | 14.6                             | 30.69              | 12.94         | 31.00          | 1260             | M1901212511A6        | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L13       | 750                  | 17.5                             | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125F11       | 625                  | 14.6                             | 30.69              | 12.94         | 31.00          | 1283             | M1501212511A6        | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125F13       | 750                  | 17.5                             | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C11       | 625                  | 14.6                             | 30.69              | 12.94         | 31.00          | 1226             | M1601212511A6        | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C13       | 750                  | 17.5                             | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085C13       | 510                  | 11.9                             | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y               | (CALL)                                     | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 105B15       | 735                  | 17.3                             | 30.73              | 13.00         | 30.53          | 1415             | M2101210515N         | N               | (CALL)                                     | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100G11       | 500                  | 11.8                             | 30.70              | 12.75         | 28.42          | 1035             | M8901210011NPP059    | Y               | (CALL)                                     | (CALL)                     | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100G11       | 500                  | 11.8                             | 30.69              | 12.88         | 26.40          | 1075             | M8901210011N059      | Y               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| PE4500-80   | CLASS III LOW-LIFT WALKIE RIDER PALLET |              |                      | 24 VOLTS , 34.44 X 6.69 X 31.62  |                    |               |                |                  | Weight Minimum 360   | Connector SB175 | GRAY , Position A , Lead Length 020 Inches |                            |                           |                        |                        |  |
|             | 24                                     | 100T07       | 300                  | 7.0                              | 33.81              | 6.56          | 23.25          | 590              | M1801210007G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 140T07       | 420                  | 9.8                              | 33.88              | 6.63          | 31.00          | 856              | M1801214007G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085L07       | 255                  | 5.9                              | 33.81              | 6.56          | 23.25          | 600              | M1901208507G         | N               | (CALL)                                     | SCR20012260S1H             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125L07       | 375                  | 8.7                              | 33.88              | 6.63          | 31.00          | 840              | M1901212507G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085F07       | 255                  | 5.9                              | 33.81              | 6.56          | 23.25          | 578              | M1501208507G         | N               | (CALL)                                     | SCR20012260S1H             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 085C07       | 255                  | 5.9                              | 33.81              | 6.56          | 23.25          | 554              | M1601208507G         | Y               | (CALL)                                     | SCR20012260S1H             | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 100C07       | 300                  | 7.0                              | 33.81              | 6.63          | 26.13          | 624              | M1601210007G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
|             | 24                                     | 125C07       | 375                  | 8.7                              | 33.88              | 6.63          | 31.00          | 802              | M1601212507G         | N               | (CALL)                                     | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT   | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.)                  | BATTERY MODEL NUMBER | Q-SHP              | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)                 | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |  |
|-------------|--|--------------|----------------------|------|--------------------|---------------|----------------|-----------------------------------|----------------------|--------------------|--------------------|--|---------------------------|------------------------|------------------------|--|
|             |  |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                                   |                      |                    |                    |  |                           |                        |                        |  |
| PR4500-60   | CLASS III LOW LIFT WALKIE RIDER/PALLET         |              |                      |      |                    |               |                | 24 VOLTS , 31.12 X 13.19 X 999.00 |                      | Weight Minimum 975 | Connector SB175    | GRAY , Position A , Lead Length 022 Inches |                           |                        |                        |  |
|             | 24   | 140T11       | 700                  | 16.3 | 30.69              | 12.94         | 31.00          | 1302                              | M1801214011A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435                              | M1801214013A         | Y                  | (CALL)             | SCR20012965S1H                             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013                              | M1901208513A25C      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1260                              | M1901212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358                              | M1901212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1283                              | M1501212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383                              | M1501212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1226                              | M1601212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341                              | M1601212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993                               | M1601208513A25C      | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 105B15       | 735                  | 17.3 | 30.73              | 13.00         | 30.53          | 1415                              | M2101210515N         | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.70              | 12.75         | 28.42          | 1035                              | M8901210011NPP059    | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.69              | 12.88         | 26.40          | 1075                              | M8901210011N059      | Y                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| PR4500-80   | CLASS III LOW LIFT WALKIE RIDER/PALLET         |              |                      |      |                    |               |                | 24 VOLTS , 31.12 X 13.19 X 999.00 |                      | Weight Minimum 975 | Connector SB175    | GRAY , Position A , Lead Length 022 Inches |                           |                        |                        |  |
|             | 24   | 140T11       | 700                  | 16.3 | 30.69              | 12.94         | 31.00          | 1302                              | M1801214011A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435                              | M1801214013A         | Y                  | (CALL)             | SCR20012965S1H                             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013                              | M1901208513A25C      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1260                              | M1901212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358                              | M1901212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1283                              | M1501212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383                              | M1501212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1226                              | M1601212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341                              | M1601212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993                               | M1601208513A25C      | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 105B15       | 735                  | 17.3 | 30.73              | 13.00         | 30.53          | 1415                              | M2101210515N         | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.70              | 12.75         | 28.42          | 1035                              | M8901210011NPP059    | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.69              | 12.88         | 26.40          | 1075                              | M8901210011N059      | Y                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| PC4500-60   | CLASS III LOW-LIFT WALKIE RIDER CENTER CONTROL |              |                      |      |                    |               |                | 24 VOLTS , 31.12 X 13.19 X 31.62  |                      | Weight Minimum 975 | Connector SB175    | GRAY , Position A , Lead Length 020 Inches |                           |                        |                        |  |
|             | 24   | 140T11       | 700                  | 16.3 | 30.69              | 12.94         | 31.00          | 1302                              | M1801214011A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435                              | M1801214013A         | Y                  | (CALL)             | SCR20012965S1H                             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013                              | M1901208513A25C      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1260                              | M1901212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358                              | M1901212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1283                              | M1501212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383                              | M1501212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1226                              | M1601212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341                              | M1601212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993                               | M1601208513A25C      | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 105B15       | 735                  | 17.3 | 30.73              | 13.00         | 30.53          | 1415                              | M2101210515N         | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.70              | 12.75         | 28.42          | 1035                              | M8901210011NPP059    | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.69              | 12.88         | 26.40          | 1075                              | M8901210011N059      | Y                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT   | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.)                 | BATTERY MODEL NUMBER | Q-SHP              | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)                 | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |  |
|-------------|--|--------------|----------------------|------|--------------------|---------------|----------------|----------------------------------|----------------------|--------------------|--------------------|--|---------------------------|------------------------|------------------------|--|
|             |  |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                                  |                      |                    |                    |  |                           |                        |                        |  |
| PC4500-80   | CLASS III LOW-LIFT WALKIE RIDER CENTER CONTROL |              |                      |      |                    |               |                | 24 VOLTS , 31.12 X 13.19 X 31.62 |                      | Weight Minimum 975 | Connector SB175    | GRAY , Position A , Lead Length 020 Inches |                           |                        |                        |  |
|             | 24   | 140T11       | 700                  | 16.3 | 30.69              | 12.94         | 31.00          | 1302                             | M1801214011A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435                             | M1801214013A         | Y                  | (CALL)             | SCR20012965S1H                             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013                             | M1901208513A25C      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1260                             | M1901212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358                             | M1901212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1283                             | M1501212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383                             | M1501212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C11       | 625                  | 14.6 | 30.69              | 12.94         | 31.00          | 1226                             | M1601212511A6        | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341                             | M1601212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993                              | M1601208513A25C      | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 105B15       | 735                  | 17.3 | 30.73              | 13.00         | 30.53          | 1415                             | M2101210515N         | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.70              | 12.75         | 28.42          | 1035                             | M8901210011NPP059    | Y                  | (CALL)             | (CALL)                                     | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.69              | 12.88         | 26.40          | 1075                             | M8901210011N059      | Y                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| TR          | CLASS III TRACTOR / TUGGER                     |              |                      |      |                    |               |                | 24 VOLTS , 31.75 X 13.12 X 23.25 |                      | Weight Minimum 975 | Connector SB175    | GRAY , Position B , Lead Length 020 Inches |                           |                        |                        |  |
|             | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013                             | M1901208513A25C      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993                              | M1601208513A25C      | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 105B11       | 525                  | 12.3 | 30.85              | 12.88         | 22.83          | 1040                             | M2101210511N         | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 105B11       | 525                  | 12.3 | 30.88              | 12.88         | 22.95          | 1090                             | M2101210511N059      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G09       | 400                  | 9.4  | 31.00              | 12.88         | 23.00          | 1000                             | M8901210009NPP7      | N                  | (CALL)             | (CALL)                                     | (CALL)                    | (CALL)                 | (CALL)                 |  |
| TR3520      | CLASS III TRACTOR / TUGGER                     |              |                      |      |                    |               |                | 24 VOLTS , 31.12 X 13.19 X 31.62 |                      | Weight Minimum 975 | Connector SB175    | GRAY , Position B , Lead Length 020 Inches |                           |                        |                        |  |
|             | 24   | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435                             | M1801214013A         | Y                  | (CALL)             | SCR20012965S1H                             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013                             | M1901208513A25C      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358                             | M1901212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383                             | M1501212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341                             | M1601212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993                              | M1601208513A25C      | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 105B15       | 735                  | 17.3 | 30.73              | 13.00         | 30.53          | 1415                             | M2101210515N         | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.70              | 12.75         | 28.42          | 1035                             | M8901210011NPP059    | Y                  | (CALL)             | (CALL)                                     | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.69              | 12.88         | 26.40          | 1075                             | M8901210011N059      | Y                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |
| TR3540      | CLASS III TRACTOR / TUGGER                     |              |                      |      |                    |               |                | 24 VOLTS , 31.12 X 13.19 X 31.62 |                      | Weight Minimum 975 | Connector SB175    | GRAY , Position B , Lead Length 020 Inches |                           |                        |                        |  |
|             | 24   | 140T13       | 840                  | 19.6 | 30.63              | 12.81         | 31.00          | 1435                             | M1801214013A         | Y                  | (CALL)             | SCR20012965S1H                             | SCR20012865T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013                             | M1901208513A25C      | N                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125L13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1358                             | M1901212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125F13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1383                             | M1501212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 125C13       | 750                  | 17.5 | 30.63              | 12.81         | 31.00          | 1341                             | M1601212513A         | Y                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993                              | M1601208513A25C      | Y                  | (CALL)             | SCR20012600S1H                             | SCR20012600T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 105B15       | 735                  | 17.3 | 30.73              | 13.00         | 30.53          | 1415                             | M2101210515N         | N                  | (CALL)             | SCR20012750S1H                             | SCR20012750T1H            | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.70              | 12.75         | 28.42          | 1035                             | M8901210011NPP059    | Y                  | (CALL)             | (CALL)                                     | (CALL)                    | (CALL)                 | (CALL)                 |  |
|             | 24   | 100G11       | 500                  | 11.8 | 30.69              | 12.88         | 26.40          | 1075                             | M8901210011N059      | Y                  | (CALL)             | SCR20012475S1H                             | SCR20012475T1H            | (CALL)                 | (CALL)                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL   | VOLT  | BATTERY TYPE | CAPACITY 6 HOUR RATE |   | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE    |                        |             |  |
|---------------|---|--------------|----------------------|---|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|---------------------------|------------------------|-------------|--|
|               |   |              | A.H.                 | KwH                                     | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                           |                        |             |  |
| <b>TR3560</b> | <b>CLASS III TRACTOR / TUGGER</b>                 |              |                      | <b>24 VOLTS , 31.12 X 13.19 X 31.62</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 975</b> | <b>Connector SB175</b> | <b>GRAY</b> | <b>, Position B , Lead Length 020 Inches</b> |
|               | 24  | 140T13       | 840                  | 19.6                                    | 30.63              | 12.81         | 31.00          | 1435             | M1801214013A         | Y     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085L13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 125L13       | 750                  | 17.5                                    | 30.63              | 12.81         | 31.00          | 1358             | M1901212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 125F13       | 750                  | 17.5                                    | 30.63              | 12.81         | 31.00          | 1383             | M1501212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 125C13       | 750                  | 17.5                                    | 30.63              | 12.81         | 31.00          | 1341             | M1601212513A         | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085C13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 105B15       | 735                  | 17.3                                    | 30.73              | 13.00         | 30.53          | 1415             | M2101210515N         | N     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 100G11       | 500                  | 11.8                                    | 30.70              | 12.75         | 28.42          | 1035             | M8901210011NPP059    | Y     | (CALL)             | SCR20012750S1H             | SCR20012750T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 100G11       | 500                  | 11.8                                    | 30.69              | 12.88         | 26.40          | 1075             | M8901210011N059      | Y     | (CALL)             | SCR20012475S1H             | SCR20012475T1H            | (CALL)                 | (CALL)                    |                        |             |  |
| <b>20WBTF</b> | <b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b> |              |                      | <b>24 VOLTS , 31.75 X 13.12 X 23.25</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 975</b> | <b>Connector SB175</b> | <b>GRAY</b> | <b>, Position A , Lead Length 017 Inches</b> |
|               | 24  | 100T13       | 600                  | 14.0                                    | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085L13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085C13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
| <b>20WBTL</b> | <b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b> |              |                      | <b>24 VOLTS , 31.75 X 13.12 X 23.25</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 975</b> | <b>Connector SB175</b> | <b>GRAY</b> | <b>, Position A , Lead Length 017 Inches</b> |
|               | 24  | 100T13       | 600                  | 14.0                                    | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085L13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085C13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
| <b>30WBTF</b> | <b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b> |              |                      | <b>24 VOLTS , 31.75 X 13.12 X 23.25</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 975</b> | <b>Connector SB175</b> | <b>GRAY</b> | <b>, Position A , Lead Length 017 Inches</b> |
|               | 24  | 100T13       | 600                  | 14.0                                    | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085L13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085C13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
| <b>30WBTL</b> | <b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b> |              |                      | <b>24 VOLTS , 31.75 X 13.12 X 23.25</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 975</b> | <b>Connector SB175</b> | <b>GRAY</b> | <b>, Position A , Lead Length 017 Inches</b> |
|               | 24  | 100T13       | 600                  | 14.0                                    | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085L13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085C13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
| <b>30WBTT</b> | <b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b> |              |                      | <b>24 VOLTS , 31.75 X 13.12 X 23.25</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 975</b> | <b>Connector SB175</b> | <b>GRAY</b> | <b>, Position A , Lead Length 017 Inches</b> |
|               | 24  | 100T13       | 600                  | 14.0                                    | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085L13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085C13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
| <b>40WBTF</b> | <b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b> |              |                      | <b>24 VOLTS , 31.75 X 13.12 X 23.25</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 975</b> | <b>Connector SB175</b> | <b>GRAY</b> | <b>, Position A , Lead Length 017 Inches</b> |
|               | 24  | 100T13       | 600                  | 14.0                                    | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085L13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085C13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
| <b>40WBTL</b> | <b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED</b> |              |                      | <b>24 VOLTS , 31.75 X 13.12 X 23.25</b> |                    |               |                |                  |                      |       |                    |                            |                           |                        | <b>Weight Minimum 975</b> | <b>Connector SB175</b> | <b>GRAY</b> | <b>, Position A , Lead Length 017 Inches</b> |
|               | 24  | 100T13       | 600                  | 14.0                                    | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085L13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |
|               | 24  | 085C13       | 510                  | 11.9                                    | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)             | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                    |                        |             |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                                       | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE               | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE                 |  |
|-------------|--|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|----------------------------------|----------------------------|---------------------------|------------------------|--|--|
|             |  |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                                  |                            |                           |                        |  |  |
| 40WBTT      | CLASS III WALKIE HIGH LIFT COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 24 VOLTS , 31.75 X 13.12 X 23.25 | Weight Minimum 975         | Connector SB175           | GRAY                   | , Position A , Lead Length 017 Inches  |  |
|             | 24   | 100T13       | 600                  | 14.0 | 30.63              | 12.69         | 23.25          | 1020             | M1801210013A         | Y     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 085L13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 1013             | M1901208513A25C      | N     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.82              | 12.88         | 23.25          | 993              | M1601208513A25C      | Y     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
| SHR5520-25  | CLASS III WALKIE HIGH LIFT STRADLE         |              |                      |      |                    |               |                |                  |                      |       | 24 VOLTS , 34.37 X 6.62 X 24.80  | Weight Minimum 510         | Connector SB175           | GRAY                   | , Position B , Lead Length 020 Inches  |  |
|             | 24   | 085C07       | 255                  | 5.9  | 34.25              | 6.56          | 22.63          | 543              | M2601208507GA        | N     | (CALL)                           | SCR20012260S1H             |                           | (CALL)                 | (CALL)                                 |  |
| SHR5520-30  | CLASS III WALKIE HIGH LIFT STRADLE         |              |                      |      |                    |               |                |                  |                      |       | 24 VOLTS , 34.37 X 6.62 X 24.80  | Weight Minimum 510         | Connector SB175           | GRAY                   | , Position B , Lead Length 020 Inches  |  |
|             | 24   | 085C07       | 255                  | 5.9  | 34.25              | 6.56          | 22.63          | 543              | M2601208507GA        | N     | (CALL)                           | SCR20012260S1H             |                           | (CALL)                 | (CALL)                                 |  |
| SX3000-30   | CLASS III WALKIE HIGH LIFT STRADLE         |              |                      |      |                    |               |                |                  |                      |       | 24 VOLTS , 26.40 X 9.10 X 23.62  | Weight Minimum 360         | Connector SB175           | GRAY                   | , Position A/B, Lead Length 020 Inches |  |
|             | 24   | 100T07       | 300                  | 7.0  | 25.38              | 8.69          | 23.25          | 601              | M1801210007D         | Y     | (CALL)                           | SCR20012260S1H             |                           | (CALL)                 | (CALL)                                 |  |
|             | 24   | 085L07       | 255                  | 5.9  | 25.38              | 8.69          | 23.25          | 585              | M1901208507D         | Y     | (CALL)                           | SCR20012260S1H             |                           | (CALL)                 | (CALL)                                 |  |
|             | 24   | 085C07       | 255                  | 5.9  | 25.38              | 8.69          | 23.25          | 565              | M1601208507D         | Y     | (CALL)                           | SCR20012260S1H             |                           | (CALL)                 | (CALL)                                 |  |
|             | 24   | 085C05       | 170                  | 4.0  | 25.38              | 8.63          | 23.25          | 486              | M1601208505FFPC      | N     | (CALL)                           |                            |                           | (CALL)                 | (CALL)                                 |  |
|             | 24   | 085C07       | 255                  | 5.9  | 25.38              | 8.63          | 22.63          | 532              | M2601208507D         | N     | (CALL)                           | SCR20012260S1H             |                           | (CALL)                 | (CALL)                                 |  |
| SH5520-40   | CLASS III WALKIE HIGH LIFT STRADLE         |              |                      |      |                    |               |                |                  |                      |       | 24 VOLTS , 34.37 X 6.62 X 24.80  | Weight Minimum 510         | Connector SB175           | GRAY                   | , Position B , Lead Length 020 Inches  |  |
|             | 24   | 085C07       | 255                  | 5.9  | 34.25              | 6.56          | 22.63          | 543              | M2601208507GA        | N     | (CALL)                           | SCR20012260S1H             |                           | (CALL)                 | (CALL)                                 |  |
| SH5540-40   | CLASS III WALKIE HIGH LIFT STRADLE         |              |                      |      |                    |               |                |                  |                      |       | 24 VOLTS , 31.10 X 13.12 X 24.80 | Weight Minimum 975         | Connector SB175           | GRAY                   | , Position B , Lead Length 020 Inches  |  |
|             | 24   | 100T13       | 600                  | 14.0 | 30.81              | 12.88         | 22.63          | 1075             | M2801210013A7A       | N     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.81              | 12.88         | 22.63          | 1010             | M2601208513A7A       | Y     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 105B11       | 525                  | 12.3 | 30.85              | 12.88         | 22.83          | 1040             | M2101210511N         | Y     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 100G09       | 400                  | 9.4  | 31.00              | 12.88         | 23.00          | 1000             | M8901210009NPP7      | N     | (CALL)                           |                            |                           | (CALL)                 | (CALL)                                 |  |
| SHR5540-35  | CLASS III WALKIE HIGH LIFT STRADLE         |              |                      |      |                    |               |                |                  |                      |       | 24 VOLTS , 31.10 X 13.12 X 24.80 | Weight Minimum 975         | Connector SB175           | GRAY                   | , Position B , Lead Length 020 Inches  |  |
|             | 24   | 100T13       | 600                  | 14.0 | 30.81              | 12.88         | 22.63          | 1075             | M2801210013A7A       | N     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.81              | 12.88         | 22.63          | 1010             | M2601208513A7A       | Y     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 105B11       | 525                  | 12.3 | 30.85              | 12.88         | 22.83          | 1040             | M2101210511N         | Y     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 100G09       | 400                  | 9.4  | 31.00              | 12.88         | 23.00          | 1000             | M8901210009NPP7      | N     | (CALL)                           |                            |                           | (CALL)                 | (CALL)                                 |  |
| SP3580F     | CLASS II ORDER PICKER                      |              |                      |      |                    |               |                |                  |                      |       | 24 VOLTS , 36.25 X 14.25 X 31.00 | Weight Minimum 1520        | Connector SB350           | RED                    | , Position A , Lead Length 020 Inches  |  |
|             | 24   | 140T15       | 980                  | 22.8 | 35.25              | 14.00         | 30.50          | 1810             | M2801214015A6        | Y     | (CALL)                           |                            | SCR200121050T1H           | (CALL)                 | (CALL)                                 |  |
|             | 24   | 125L15       | 875                  | 20.4 | 35.25              | 14.06         | 30.50          | 1734             | M2901212515A6        | N     | (CALL)                           | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 125F15       | 875                  | 20.4 | 35.25              | 14.00         | 30.50          | 1747             | M2501212515A6        | Y     | (CALL)                           | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 125C15       | 875                  | 20.4 | 35.25              | 14.00         | 30.50          | 1700             | M2601212515A6        | Y     | (CALL)                           | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 170C11       | 850                  | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)                           | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 055B31       | 825                  | 19.4 | 36.75              | 14.00         | 30.69          | 1600             | M2101205531FB25      | N     | (CALL)                           | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                                 |  |
| SP3505-30   | CLASS II ORDER PICKER                      |              |                      |      |                    |               |                |                  |                      |       | 24 VOLTS , 31.75 X 13.12 X 23.25 | Weight Minimum 975         | Connector SB175           | GRAY                   | , Position A , Lead Length 020 Inches  |  |
|             | 24   | 100T13       | 600                  | 14.0 | 30.81              | 12.88         | 22.63          | 1075             | M2801210013A7A       | N     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 085C13       | 510                  | 11.9 | 30.81              | 12.88         | 22.63          | 1010             | M2601208513A7A       | Y     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 105B11       | 525                  | 12.3 | 30.85              | 12.88         | 22.83          | 1040             | M2101210511N         | Y     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 105B11       | 525                  | 12.3 | 30.88              | 12.88         | 22.95          | 1090             | M2101210511N059      | N     | (CALL)                           | SCR20012600S1H             | SCR20012600T1H            | (CALL)                 | (CALL)                                 |  |
|             | 24   | 100G09       | 400                  | 9.4  | 31.00              | 12.88         | 23.00          | 1000             | M8901210009NPP7      | N     | (CALL)                           |                            |                           | (CALL)                 | (CALL)                                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



| TRUCK MODEL | VOLT                        | BATTERY TYPE | CAPACITY 6 HOUR RATE  |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|-----------------------------|--------------|---|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|
|             |                             |              | A.H.  | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |
| SP3510-30   | CLASS II ORDER PICKER       |              | 24 VOLTS , 36.25 X 14.25 X 31.00 Weight Minimum 1520 Connector SB350 RED , Position A , Lead Length 020 Inches  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                          | 140T15       | 980   | 22.8 | 35.25              | 14.00         | 30.50          | 1810             | M2801214015A6        | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 125L15       | 875   | 20.4 | 35.25              | 14.06         | 30.50          | 1734             | M2901212515A6        | N     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125F15       | 875   | 20.4 | 35.25              | 14.00         | 30.50          | 1747             | M2501212515A6        | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125C15       | 875   | 20.4 | 35.25              | 14.00         | 30.50          | 1700             | M2601212515A6        | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 170C11       | 850   | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 055B31       | 825   | 19.4 | 36.75              | 14.00         | 30.69          | 1600             | M2101205531FB25      | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
| SP3520-30   | CLASS II ORDER PICKER       |              | 24 VOLTS , 36.25 X 14.25 X 31.00 Weight Minimum 1520 Connector SB350 RED , Position A , Lead Length 020 Inches  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                          | 140T15       | 980   | 22.8 | 35.25              | 14.00         | 30.50          | 1810             | M2801214015A6        | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 125L15       | 875   | 20.4 | 35.25              | 14.06         | 30.50          | 1734             | M2901212515A6        | N     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125F15       | 875   | 20.4 | 35.25              | 14.00         | 30.50          | 1747             | M2501212515A6        | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125C15       | 875   | 20.4 | 35.25              | 14.00         | 30.50          | 1700             | M2601212515A6        | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 170C11       | 850   | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 055B31       | 825   | 19.4 | 36.75              | 14.00         | 30.69          | 1600             | M2101205531FB25      | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
| SP3550H-30  | CLASS II ORDER PICKER       |              | 24 VOLTS , 36.25 X 14.25 X 31.00 Weight Minimum 1520 Connector SB350 RED , Position A , Lead Length 020 Inches  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                          | 140T15       | 980   | 22.8 | 35.25              | 14.00         | 30.50          | 1810             | M2801214015A6        | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 125L15       | 875   | 20.4 | 35.25              | 14.06         | 30.50          | 1734             | M2901212515A6        | N     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125F15       | 875   | 20.4 | 35.25              | 14.00         | 30.50          | 1747             | M2501212515A6        | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125C15       | 875   | 20.4 | 35.25              | 14.00         | 30.50          | 1700             | M2601212515A6        | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 170C11       | 850   | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 055B31       | 825   | 19.4 | 36.75              | 14.00         | 30.69          | 1600             | M2101205531FB25      | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
| SP3570F     | CLASS II ORDER PICKER       |              | 24 VOLTS , 36.25 X 14.25 X 31.00 Weight Minimum 1520 Connector SB350 RED , Position A , Lead Length 020 Inches  |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 24                          | 140T15       | 980   | 22.8 | 35.25              | 14.00         | 30.50          | 1810             | M2801214015A6        | Y     | (CALL)             |                            | SCR200121050T1H           | (CALL)                 | (CALL)                 |
|             | 24                          | 125L15       | 875   | 20.4 | 35.25              | 14.06         | 30.50          | 1734             | M2901212515A6        | N     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125F15       | 875   | 20.4 | 35.25              | 14.00         | 30.50          | 1747             | M2501212515A6        | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 125C15       | 875   | 20.4 | 35.25              | 14.00         | 30.50          | 1700             | M2601212515A6        | Y     | (CALL)             | SCR20012965S1H             | SCR20012965T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 170C11       | 850   | 19.8 | 35.25              | 13.31         | 30.50          | 1645             | M2601217011D         | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
|             | 24                          | 055B31       | 825   | 19.4 | 36.75              | 14.00         | 30.69          | 1600             | M2101205531FB25      | N     | (CALL)             | SCR20012965S1H             | SCR20012865T1H            | (CALL)                 | (CALL)                 |
| RR5725-45   | CLASS II NARROW AISLE REACH |              | 36 VOLTS , 38.38 X 16.25 X 31.00 Weight Minimum 2000 Connector SB350 GRAY , Position A , Lead Length 011 Inches |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 36                          | 140T13       | 840   | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 125L13       | 750   | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 045B31       | 675   | 23.8 | 39.25              | 15.99         | 30.69          | 2070             | M2101804531B37       | Y     | (CALL)             | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                 |
| RR5725-45   | CLASS II NARROW AISLE REACH |              | 36 VOLTS , 38.38 X 18.00 X 31.00 Weight Minimum 2280 Connector SB350 GRAY , Position A , Lead Length 011 Inches |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 36                          | 140T15       | 980   | 34.2 | 38.25              | 17.81         | 30.50          | 2492             | M2801814015B         | Y     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |
|             | 36                          | 125L15       | 875   | 30.6 | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | (CALL)             | SCR20018965S1H             | SCR20018965T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 125F15       | 875   | 30.6 | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | (CALL)             | SCR20018965S1H             | SCR20018965T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 125C15       | 875   | 30.6 | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | (CALL)             | SCR20018965S1H             | SCR20018965T1H            | (CALL)                 | (CALL)                 |
|             | 36                          | 055B31       | 825   | 29.1 | 39.50              | 18.04         | 30.69          | 2380             | M2101805531B         | N     | (CALL)             | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                 |
| RR5725-45   | CLASS II NARROW AISLE REACH |              | 36 VOLTS , 38.38 X 20.75 X 31.00 Weight Minimum 2600 Connector SB350 GRAY , Position A , Lead Length 011 Inches |      |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        |
|             | 36                          | 140T17       | 1120  | 39.1 | 38.31              | 20.13         | 30.50          | 2843             | M2801814017B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |
|             | 36                          | 125F17       | 1000  | 34.9 | 38.31              | 20.13         | 30.50          | 2762             | M2501812517B         | Y     | (CALL)             | SCR200181050T1H            | SCR200181050T1H           | (CALL)                 | (CALL)                 |
|             | 36                          | 125C17       | 1000  | 34.9 | 38.31              | 20.13         | 30.50          | 2673             | M2601812517B         | Y     | (CALL)             | SCR200181050T1H            | SCR200181050T1H           | (CALL)                 | (CALL)                 |
|             | 36                          | 060B31       | 900   | 31.8 | 39.50              | 19.41         | 30.69          | 2600             | M2101806031B         | Y     | (CALL)             | SCR20018965S1H             | SCR20018965T1H            | (CALL)                 | (CALL)                 |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                                       | BATTERY TYPE | CAPACITY 6 HOUR RATE |                                  | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1)                    | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |
|-------------|--|--------------|----------------------|----------------------------------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|--|------------------------|------------------------|
|             |  |              | A.H.                 | KwH                              | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |  |                        |                        |
| SR5285H     | CLASS II NARROW AISLE REACH                |              |                      | 48 VOLTS , 48.15 X 19.64 X 30.56 |                    |               |                |                  |                      |       |                    |                            |  |                        |                        |
|             | 48   | 125F15       | 875                  | 40.7                             | 48.00              | 19.34         | 30.50          | 3160             | M2502412515E6        | N     | ( CALL )           | Connector SB350            | BLUE , Position N/A , Lead Length 000 Inches | ( CALL )               | ( CALL )               |
|             | 48   | 125C15       | 875                  | 40.7                             | 48.00              | 19.34         | 30.50          | 3050             | M2602412515E6        | N     | ( CALL )           | Connector SB350            | BLUE , Position N/A , Lead Length 000 Inches | ( CALL )               | ( CALL )               |
| RD5795S     | CLASS II NARROW AISLE DOUBLE REACH         |              |                      | 36 VOLTS , 38.38 X 16.25 X 31.00 |                    |               |                |                  |                      |       |                    |                            |  |                        |                        |
|             | 36   | 140T13       | 840                  | 29.3                             | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125L13       | 750                  | 26.2                             | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125F13       | 750                  | 26.2                             | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125C13       | 750                  | 26.2                             | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
| RD5795S     | CLASS II NARROW AISLE DOUBLE REACH         |              |                      | 36 VOLTS , 38.69 X 18.00 X 31.00 |                    |               |                |                  |                      |       |                    |                            |  |                        |                        |
|             | 36   | 140T15       | 980                  | 34.2                             | 38.31              | 17.75         | 31.00          | 2469             | M1801814015B         | N     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125L15       | 875                  | 30.6                             | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125F15       | 875                  | 30.6                             | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125C15       | 875                  | 30.6                             | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 055B31       | 825                  | 29.1                             | 39.50              | 18.04         | 30.69          | 2380             | M2101805531B         | N     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
| RD5795S     | CLASS II NARROW AISLE DOUBLE REACH         |              |                      | 36 VOLTS , 38.69 X 20.75 X 31.00 |                    |               |                |                  |                      |       |                    |                            |  |                        |                        |
|             | 36   | 140T17       | 1120                 | 39.1                             | 38.31              | 20.13         | 30.50          | 2843             | M2801814017B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125L17       | 1000                 | 34.9                             | 38.31              | 20.13         | 30.50          | 2711             | M2901812517B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
| 40TS        | CLASS II VERY NARROW AISLE TURRET          |              |                      | 72 VOLTS , 38.38 X 18.00 X 31.00 |                    |               |                |                  |                      |       |                    |                            |  |                        |                        |
|             | 36   | 140T15       | 980                  | 34.2                             | 38.25              | 17.81         | 30.50          | 2492             | M2801814015B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125L15       | 875                  | 30.6                             | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125F15       | 875                  | 30.6                             | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125C15       | 875                  | 30.6                             | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | ( CALL )           | Connector SB350            | GRAY , Position A , Lead Length 009 Inches   | ( CALL )               | ( CALL )               |
| TSP6000     | CLASS II VERY NARROW AISLE TURRET          |              |                      | 48 VOLTS , 44.50 X 24.69 X 31.00 |                    |               |                |                  |                      |       |                    |                            |  |                        |                        |
|             | 48   | 140T15       | 980                  | 45.6                             | 43.38              | 23.63         | 30.50          | 3388             | M2802414015A         | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 48   | 125F15       | 875                  | 40.7                             | 43.00              | 23.63         | 30.50          | 3181             | M2502412515B11       | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 48   | 125F15       | 875                  | 40.7                             | 43.38              | 23.63         | 30.50          | 3162             | M2502412515A         | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 48   | 125C15       | 875                  | 40.7                             | 43.00              | 23.63         | 30.50          | 3179             | M2602412515B11       | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
| TSP6000     | CLASS II VERY NARROW AISLE TURRET          |              |                      | 48 VOLTS , 44.50 X 28.12 X 31.00 |                    |               |                |                  |                      |       |                    |                            |  |                        |                        |
|             | 48   | 140T17       | 1120                 | 52.1                             | 38.44              | 26.88         | 30.50          | 3862             | M2802414017B         | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 48   | 125L17       | 1000                 | 46.6                             | 38.44              | 26.88         | 30.50          | 3741             | M2902412517B         | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 48   | 125F17       | 1000                 | 46.6                             | 38.44              | 26.88         | 30.50          | 3763             | M2502412517B         | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 48   | 125C17       | 1000                 | 46.6                             | 38.44              | 26.88         | 30.50          | 3636             | M2602412517B         | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
| TSP6000     | CLASS II VERY NARROW AISLE TURRET          |              |                      | 48 VOLTS , 44.50 X 33.75 X 31.00 |                    |               |                |                  |                      |       |                    |                            |  |                        |                        |
|             | 48   | 140T21       | 1400                 | 65.2                             | 38.50              | 33.00         | 30.50          | 4334             | M2802414021B         | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 48   | 125L21       | 1250                 | 58.2                             | 44.25              | 33.00         | 30.50          | 4543             | M2902412521B6        | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 48   | 125C21       | 1250                 | 58.2                             | 38.50              | 33.00         | 30.50          | 4322             | M2602412521B         | N     | ( CALL )           | Connector SB350            | BLUE , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
| TSP7000     | CLASS II VERY NARROW AISLE TURRET 72 VOLTS |              |                      | 72 VOLTS , 44.50 X 39.12 X 31.00 |                    |               |                |                  |                      |       |                    |                            |  |                        |                        |
|             | 36   | 140T15       | 980                  | 34.2                             | 38.25              | 17.81         | 30.50          | 2492             | M2801814015B         | Y     | ( CALL )           | Connector SB350            | GREY , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125L15       | 875                  | 30.6                             | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | ( CALL )           | Connector SB350            | GREY , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125F15       | 875                  | 30.6                             | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | ( CALL )           | Connector SB350            | GREY , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |
|             | 36   | 125C15       | 875                  | 30.6                             | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | ( CALL )           | Connector SB350            | GREY , Position A , Lead Length 015 Inches   | ( CALL )               | ( CALL )               |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                                | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE               | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE                     | T-1 CHARGER LIST PRICE |  |
|-------------|-------------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|----------------------------------|----------------------------|---------------------------|--|------------------------|--|
|             |                                     |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                                  |                            |                           |  |                        |  |
| 30TSP-48    | CLASS II VERY NARROW AISLE TURRET   |              |                      |      |                    |               |                |                  |                      |       | 48 VOLTS , 38.75 X 27.00 X 31.00 | Weight Minimum 3140        | Connector SB350           | GRAY , Position A , Lead Length 009 Inches |                        |  |
|             | 48                                  | 140T17       | 1120                 | 52.1 | 38.44              | 26.88         | 30.50          | 3862             | M2802414017B         | N     | (CALL)                           | SCR200241200T1H            | SCR200241050T1H           | (CALL)                                     | (CALL)                 |  |
|             | 48                                  | 125L17       | 1000                 | 46.6 | 38.44              | 26.88         | 30.50          | 3741             | M2902412517B         | N     | (CALL)                           | SCR200241050T1H            | SCR200241050T1H           | (CALL)                                     | (CALL)                 |  |
|             | 48                                  | 125F17       | 1000                 | 46.6 | 38.44              | 26.88         | 30.50          | 3763             | M2502412517B         | N     | (CALL)                           | SCR200241050T1H            | SCR200241050T1H           | (CALL)                                     | (CALL)                 |  |
|             | 48                                  | 125C17       | 1000                 | 46.6 | 38.44              | 26.88         | 30.50          | 3636             | M2602412517B         | N     | (CALL)                           | SCR200241050T1H            | SCR200241050T1H           | (CALL)                                     | (CALL)                 |  |
| 30TSP-48    | CLASS II VERY NARROW AISLE TURRET   |              |                      |      |                    |               |                |                  |                      |       | 48 VOLTS , 38.75 X 33.00 X 31.00 | Weight Minimum 3800        | Connector SB350           | GRAY , Position A , Lead Length 009 Inches |                        |  |
|             | 48                                  | 125C19       | 1125                 | 52.4 | 38.44              | 32.25         | 30.50          | 4043             | M2602412519B6        | N     | (CALL)                           | SCR200241200T1H            | SCR200181050T1H           | (CALL)                                     | (CALL)                 |  |
|             | 48                                  | 105B21       | 1050                 | 49.4 | 39.61              | 31.89         | 30.86          | 4080             | M2102410521B781      | N     | (CALL)                           | SCR200181050T1H            | SCR200181050T1H           | (CALL)                                     | (CALL)                 |  |
| 30TSP-72    | CLASS II VERY NARROW AISLE TURRET   |              |                      |      |                    |               |                |                  |                      |       | 72 VOLTS , 38.38 X 15.88 X 31.00 | Weight Minimum 1770        | Connector SB350           | GRAY , Position A , Lead Length 009 Inches |                        |  |
|             | 36                                  | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)                           | SCR20018865S1H             | SCR20018865T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
| 30TSP-72    | CLASS II VERY NARROW AISLE TURRET   |              |                      |      |                    |               |                |                  |                      |       | 72 VOLTS , 38.44 X 13.50 X 31.00 | Weight Minimum 1610        | Connector SB350           | GRAY , Position A , Lead Length 009 Inches |                        |  |
|             | 36                                  | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 125F11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1792             | M2501812511B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 125C11       | 625                  | 21.8 | 38.01              | 13.25         | 30.50          | 1705             | M2601812511B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
| 30TSP-72    | CLASS II VERY NARROW AISLE TURRET   |              |                      |      |                    |               |                |                  |                      |       | 72 VOLTS , 38.69 X 18.00 X 31.00 | Weight Minimum 2085        | Connector SB350           | GRAY , Position A , Lead Length 009 Inches |                        |  |
|             | 36                                  | 140T15       | 980                  | 34.2 | 38.25              | 17.81         | 30.50          | 2492             | M2801814015B         | Y     | (CALL)                           | SCR200181050T1H            | SCR20018965T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 125L15       | 875                  | 30.6 | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | (CALL)                           | SCR20018965S1H             | SCR20018965T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 125F15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | (CALL)                           | SCR20018965S1H             | SCR20018965T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 125C15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | (CALL)                           | SCR20018965S1H             | SCR20018965T1H            | (CALL)                                     | (CALL)                 |  |
| SC4510-30   | CLASS I THREE WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.81 X 16.01 X 22.80 | Weight Minimum 1475        | Connector SB350           | GRAY , Position A , Lead Length 009 Inches |                        |  |
|             | 36                                  | 060B15       | 420                  | 14.8 | 38.50              | 15.57         | 22.63          | 1545             | M2101806015ZA7       | N     | (CALL)                           | SCR20018475S1H             | SCR20018475T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 060B15       | 420                  | 14.8 | 38.50              | 15.57         | 22.63          | 1545             | M2101806015ZA7       | N     | (CALL)                           | SCR20018475S1H             | SCR20018475T1H            | (CALL)                                     | (CALL)                 |  |
| SC4520-30   | CLASS I 3 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.81 X 20.50 X 22.80 | Weight Minimum 1850        | Connector SB350           | GRAY , Position A , Lead Length 009 Inches |                        |  |
|             | 36                                  | 100T17       | 800                  | 27.9 | 38.25              | 19.94         | 22.63          | 2049             | M2801810017B         | Y     | (CALL)                           | SCR20018865S1H             | SCR20018865T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 085L17       | 680                  | 23.7 | 38.25              | 19.94         | 22.63          | 1963             | M2901808517B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 085F17       | 680                  | 23.7 | 38.25              | 19.94         | 22.63          | 2014             | M2501808517B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 085C17       | 680                  | 23.7 | 38.25              | 19.94         | 22.63          | 1933             | M2601808517B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 060B23       | 660                  | 23.3 | 38.50              | 19.62         | 23.69          | 1975             | M2101806023B0        | N     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
| SC4520-35   | CLASS I 3 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.81 X 20.50 X 22.80 | Weight Minimum 1850        | Connector SB350           | GRAY , Position A , Lead Length 009 Inches |                        |  |
|             | 36                                  | 100T17       | 800                  | 27.9 | 38.25              | 19.94         | 22.63          | 2049             | M2801810017B         | Y     | (CALL)                           | SCR20018865S1H             | SCR20018865T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 085L17       | 680                  | 23.7 | 38.25              | 19.94         | 22.63          | 1963             | M2901808517B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 085F17       | 680                  | 23.7 | 38.25              | 19.94         | 22.63          | 2014             | M2501808517B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 085C17       | 680                  | 23.7 | 38.25              | 19.94         | 22.63          | 1933             | M2601808517B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |
|             | 36                                  | 060B23       | 660                  | 23.3 | 38.50              | 19.62         | 23.69          | 1975             | M2101806023B0        | N     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                                     | (CALL)                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                                | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)       | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                     |                 |  |
|-------------|-------------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------------|---------------------------|------------------------|------------------------|---------------------|-----------------|--|
|             |                                     |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                                  |                           |                        |                        |                     |                 |  |
| SC4540-35   | CLASS I 3 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.81 X 24.88 X 22.80 |                           |                        |                        | Weight Minimum 2250 | Connector SB350 | GRAY , Position A , Lead Length 009 Inches |
|             | 36                                  | 100T21       | 1000                 | 34.9 | 38.25              | 24.56         | 22.63          | 2455             | M2801810021B         | Y     | ( CALL )           |                                  | SCR200181050T1H           | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085L21       | 850                  | 29.7 | 38.25              | 24.56         | 22.63          | 2350             | M2901808521B         | Y     | ( CALL )           | SCR20018865S1H                   | SCR20018865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085F21       | 850                  | 29.7 | 38.25              | 24.56         | 22.63          | 2411             | M2501808521B         | Y     | ( CALL )           | SCR20018865S1H                   | SCR20018865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085C21       | 850                  | 29.7 | 38.25              | 24.56         | 22.63          | 2314             | M2601808521B         | Y     | ( CALL )           | SCR20018865S1H                   | SCR20018865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
| SC4540-40   | CLASS I 3 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.81 X 24.88 X 22.80 |                           |                        |                        | Weight Minimum 2250 | Connector SB350 | GRAY , Position A , Lead Length 009 Inches |
|             | 36                                  | 100T21       | 1000                 | 34.9 | 38.25              | 24.56         | 22.63          | 2455             | M2801810021B         | Y     | ( CALL )           |                                  | SCR200181050T1H           | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085L21       | 850                  | 29.7 | 38.25              | 24.56         | 22.63          | 2350             | M2901808521B         | Y     | ( CALL )           | SCR20018865S1H                   | SCR20018865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085F21       | 850                  | 29.7 | 38.25              | 24.56         | 22.63          | 2411             | M2501808521B         | Y     | ( CALL )           | SCR20018865S1H                   | SCR20018865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085C21       | 850                  | 29.7 | 38.25              | 24.56         | 22.63          | 2314             | M2601808521B         | Y     | ( CALL )           | SCR20018865S1H                   | SCR20018865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085C19       | 765                  | 26.7 | 38.44              | 23.75         | 22.63          | 2315             | M2601808519B725      | N     | ( CALL )           | SCR20018865S1H                   | SCR20018865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
| SC4510-30   | CLASS I THREE WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.81 X 16.01 X 22.80 |                           |                        |                        | Weight Minimum 1475 | Connector SB350 | GRAY , Position A , Lead Length 009 Inches |
|             | 36                                  | 060B15       | 420                  | 14.8 | 38.50              | 15.57         | 22.63          | 1545             | M2101806015ZA7       | N     | ( CALL )           | SCR20018475S1H                   | SCR20018475T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 060B15       | 420                  | 14.8 | 38.50              | 15.57         | 22.63          | 1545             | M2101806015ZA7       | N     | ( CALL )           | SCR20018475S1H                   | SCR20018475T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
| FC4510-40   | CLASS I 4 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 27.25 X 23.35 |                           |                        |                        | Weight Minimum 2630 | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36                                  | 100T23       | 1100                 | 38.4 | 38.25              | 26.88         | 22.63          | 2685             | M2801810023B         | N     | ( CALL )           |                                  | SCR200181200T1H           | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085F23       | 935                  | 32.7 | 38.44              | 27.00         | 23.12          | 2760             | M2501808523B7        | N     | ( CALL )           |                                  | SCR20018965T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085C23       | 935                  | 32.7 | 38.44              | 27.00         | 23.12          | 2716             | M2601808523B7        | N     | ( CALL )           |                                  | SCR20018965T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
| FC4510-40   | CLASS I 4 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 27.25 X 23.35 |                           |                        |                        | Weight Minimum 2630 | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48                                  | 100T17       | 800                  | 37.2 | 38.38              | 26.69         | 22.63          | 2700             | M2802410017B         | N     | ( CALL )           |                                  | SCR20024865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 48                                  | 085C17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2684             | M2602408517B725      | N     | ( CALL )           |                                  | SCR20024750T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
| FC4510-50   | CLASS I 4 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 27.25 X 23.35 |                           |                        |                        | Weight Minimum 2630 | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36                                  | 100T23       | 1100                 | 38.4 | 38.25              | 26.88         | 22.63          | 2685             | M2801810023B         | N     | ( CALL )           |                                  | SCR200181200T1H           | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085F23       | 935                  | 32.7 | 38.44              | 27.00         | 23.12          | 2760             | M2501808523B7        | N     | ( CALL )           |                                  | SCR20018965T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085C23       | 935                  | 32.7 | 38.44              | 27.00         | 23.12          | 2716             | M2601808523B7        | N     | ( CALL )           |                                  | SCR20018965T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
| FC4510-50   | CLASS I 4 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 27.25 X 23.35 |                           |                        |                        | Weight Minimum 2630 | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48                                  | 100T17       | 800                  | 37.2 | 38.38              | 26.69         | 22.63          | 2700             | M2802410017B         | N     | ( CALL )           |                                  | SCR20024865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 48                                  | 085C17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2684             | M2602408517B725      | N     | ( CALL )           |                                  | SCR20024750T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
| FC4515-40   | CLASS I 4 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 27.25 X 23.35 |                           |                        |                        | Weight Minimum 2630 | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36                                  | 100T23       | 1100                 | 38.4 | 38.25              | 26.88         | 22.63          | 2685             | M2801810023B         | N     | ( CALL )           |                                  | SCR200181200T1H           | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085F23       | 935                  | 32.7 | 38.44              | 27.00         | 23.12          | 2760             | M2501808523B7        | N     | ( CALL )           |                                  | SCR20018965T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 36                                  | 085C23       | 935                  | 32.7 | 38.44              | 27.00         | 23.12          | 2716             | M2601808523B7        | N     | ( CALL )           |                                  | SCR20018965T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
| FC4515-40   | CLASS I 4 WHEEL COUNTERBALANCED     |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 27.25 X 23.35 |                           |                        |                        | Weight Minimum 2630 | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48                                  | 100T17       | 800                  | 37.2 | 38.38              | 26.69         | 22.63          | 2700             | M2802410017B         | N     | ( CALL )           |                                  | SCR20024865T1H            | ( CALL )               | ( CALL )               |                     |                 |  |
|             | 48                                  | 085C17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2684             | M2602408517B725      | N     | ( CALL )           |                                  | SCR20024750T1H            | ( CALL )               | ( CALL )               |                     |                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                            | BATTERY TYPE | CAPACITY 6 HOUR RATE |                                  | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                     |                 |      |                                       |
|-------------|---------------------------------|--------------|----------------------|----------------------------------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|---------------------|-----------------|------|---------------------------------------|
|             |                                 |              | A.H.                 | KwH                              | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |                     |                 |      |                                       |
| FC4515-50   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 36 VOLTS , 38.69 X 27.25 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | Weight Minimum 2630 | Connector SB350 | GRAY | , Position A , Lead Length 018 Inches |
|             | 36                              | 100T23       | 1100                 | 38.4                             | 38.25              | 26.88         | 22.63          | 2685             | M2801810023B         | N     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085F23       | 935                  | 32.7                             | 38.44              | 27.00         | 23.12          | 2760             | M2501808523B7        | N     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085F23       | 935                  | 32.7                             | 38.44              | 27.00         | 23.12          | 2760             | M2501808523B7        | N     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085C23       | 935                  | 32.7                             | 38.44              | 27.00         | 23.12          | 2716             | M2601808523B7        | N     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085C23       | 935                  | 32.7                             | 38.44              | 27.00         | 23.12          | 2716             | M2601808523B7        | N     | (CALL)             |                            | SCR20018965T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
| FC4515-50   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 48 VOLTS , 38.69 X 27.25 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | Weight Minimum 2630 | Connector SB350 | BLUE | , Position A , Lead Length 018 Inches |
|             | 48                              | 100T17       | 800                  | 37.2                             | 38.38              | 26.69         | 22.63          | 2700             | M2802410017B         | N     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 48                              | 085C17       | 680                  | 31.7                             | 38.25              | 27.00         | 22.88          | 2684             | M2602408517B725      | N     | (CALL)             |                            | SCR20024750T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
| FC4520-40   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 36 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | Weight Minimum 2800 | Connector SB350 | GRAY | , Position A , Lead Length 018 Inches |
|             | 36                              | 100T27       | 1300                 | 45.4                             | 38.44              | 31.50         | 22.63          | 3127             | M2801810027B         | Y     | (CALL)             |                            | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085L27       | 1105                 | 38.6                             | 38.25              | 31.50         | 22.63          | 3003             | M2901808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085F27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 3086             | M2501808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085C27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 2960             | M2601808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 105B21       | 1050                 | 37.0                             | 38.61              | 32.50         | 22.05          | 3075             | M2101810521B059      | N     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
| FC4520-40   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 48 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | Weight Minimum 2800 | Connector SB350 | BLUE | , Position A , Lead Length 018 Inches |
|             | 48                              | 100T21       | 1000                 | 46.6                             | 38.25              | 32.63         | 22.63          | 3293             | M2802410021B         | Y     | (CALL)             |                            | SCR200241050T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 48                              | 085L21       | 850                  | 39.6                             | 38.38              | 32.69         | 22.63          | 3157             | M2902408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 48                              | 085F21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3211             | M2502408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 48                              | 085C21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3087             | M2602408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 48                              | 105B15       | 735                  | 34.6                             | 39.25              | 30.19         | 22.54          | 3090             | M2102410515B75981    | N     | (CALL)             |                            | SCR20024750T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
| FC4520-50   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 36 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | Weight Minimum 2800 | Connector SB350 | GRAY | , Position A , Lead Length 018 Inches |
|             | 36                              | 100T27       | 1300                 | 45.4                             | 38.44              | 31.50         | 22.63          | 3127             | M2801810027B         | Y     | (CALL)             |                            | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085L27       | 1105                 | 38.6                             | 38.25              | 31.50         | 22.63          | 3003             | M2901808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085F27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 3086             | M2501808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085C27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 2960             | M2601808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 105B21       | 1050                 | 37.0                             | 38.61              | 32.50         | 22.05          | 3075             | M2101810521B059      | N     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
| FC4520-50   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 48 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | Weight Minimum 2800 | Connector SB350 | BLUE | , Position A , Lead Length 018 Inches |
|             | 48                              | 100T21       | 1000                 | 46.6                             | 38.25              | 32.63         | 22.63          | 3293             | M2802410021B         | Y     | (CALL)             |                            | SCR200241050T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 48                              | 085L21       | 850                  | 39.6                             | 38.38              | 32.69         | 22.63          | 3157             | M2902408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 48                              | 085F21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3211             | M2502408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 48                              | 085C21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3087             | M2602408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 48                              | 105B15       | 735                  | 34.6                             | 39.25              | 30.19         | 22.54          | 3090             | M2102410515B75981    | N     | (CALL)             |                            | SCR20024750T1H            | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
| FC4520-55   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 36 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        |                        | Weight Minimum 2800 | Connector SB350 | GRAY | , Position A , Lead Length 018 Inches |
|             | 36                              | 100T27       | 1300                 | 45.4                             | 38.44              | 31.50         | 22.63          | 3127             | M2801810027B         | Y     | (CALL)             |                            | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085L27       | 1105                 | 38.6                             | 38.25              | 31.50         | 22.63          | 3003             | M2901808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085F27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 3086             | M2501808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 085C27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 2960             | M2601808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |
|             | 36                              | 105B21       | 1050                 | 37.0                             | 38.61              | 32.50         | 22.05          | 3075             | M2101810521B059      | N     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |                     |                 |      |                                       |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                            | BATTERY TYPE | CAPACITY 6 HOUR RATE |                                  | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                 |  |
|-------------|---------------------------------|--------------|----------------------|----------------------------------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------|---------------------------|------------------------|------------------------|-----------------|--|
|             |                                 |              | A.H.                 | KwH                              | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                            |                           |                        |                        |                 |  |
| FC4520-55   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 48 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 2800    | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48                              | 100T21       | 1000                 | 46.6                             | 38.25              | 32.63         | 22.63          | 3293             | M2802410021B         | Y     | (CALL)             |                            | SCR200241050T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085L21       | 850                  | 39.6                             | 38.38              | 32.69         | 22.63          | 3157             | M2902408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085F21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3211             | M2502408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085C21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3087             | M2602408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 105B15       | 735                  | 34.6                             | 39.25              | 30.19         | 22.54          | 3090             | M2102410515B75981    | N     | (CALL)             |                            | SCR20024750T1H            | (CALL)                 | (CALL)                 |                 |  |
| FC4520-60   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 36 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 2800    | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36                              | 100T27       | 1300                 | 45.4                             | 38.44              | 31.50         | 22.63          | 3127             | M2801810027B         | Y     | (CALL)             |                            | SCR200181450T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 085L27       | 1105                 | 38.6                             | 38.25              | 31.50         | 22.63          | 3003             | M2901808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 085F27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 3086             | M2501808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 085C27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 2960             | M2601808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 105B21       | 1050                 | 37.0                             | 38.61              | 32.50         | 22.05          | 3075             | M2101810521B059      | N     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |                 |  |
| FC4520-60   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 48 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 2800    | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48                              | 100T21       | 1000                 | 46.6                             | 38.25              | 32.63         | 22.63          | 3293             | M2802410021B         | Y     | (CALL)             |                            | SCR200241050T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085L21       | 850                  | 39.6                             | 38.38              | 32.69         | 22.63          | 3157             | M2902408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085F21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3211             | M2502408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085C21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3087             | M2602408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 105B15       | 735                  | 34.6                             | 39.25              | 30.19         | 22.54          | 3090             | M2102410515B75981    | N     | (CALL)             |                            | SCR20024750T1H            | (CALL)                 | (CALL)                 |                 |  |
| FC4525-40   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 36 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 2800    | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36                              | 100T27       | 1300                 | 45.4                             | 38.44              | 31.50         | 22.63          | 3127             | M2801810027B         | Y     | (CALL)             |                            | SCR200181450T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 085L27       | 1105                 | 38.6                             | 38.25              | 31.50         | 22.63          | 3003             | M2901808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 085F27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 3086             | M2501808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 085C27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 2960             | M2601808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 105B21       | 1050                 | 37.0                             | 38.61              | 32.50         | 22.05          | 3075             | M2101810521B059      | N     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |                 |  |
| FC4525-40   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 48 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 2800    | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48                              | 100T21       | 1000                 | 46.6                             | 38.25              | 32.63         | 22.63          | 3293             | M2802410021B         | Y     | (CALL)             |                            | SCR200241050T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085L21       | 850                  | 39.6                             | 38.38              | 32.69         | 22.63          | 3157             | M2902408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085F21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3211             | M2502408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085C21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3087             | M2602408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 105B15       | 735                  | 34.6                             | 39.25              | 30.19         | 22.54          | 3090             | M2102410515B75981    | N     | (CALL)             |                            | SCR20024750T1H            | (CALL)                 | (CALL)                 |                 |  |
| FC4525-50   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 36 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 2800    | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36                              | 100T27       | 1300                 | 45.4                             | 38.44              | 31.50         | 22.63          | 3127             | M2801810027B         | Y     | (CALL)             |                            | SCR200181450T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 085L27       | 1105                 | 38.6                             | 38.25              | 31.50         | 22.63          | 3003             | M2901808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 085F27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 3086             | M2501808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 085C27       | 1105                 | 38.6                             | 38.44              | 31.50         | 22.63          | 2960             | M2601808527B         | Y     | (CALL)             |                            | SCR200181200T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 36                              | 105B21       | 1050                 | 37.0                             | 38.61              | 32.50         | 22.05          | 3075             | M2101810521B059      | N     | (CALL)             |                            | SCR200181050T1H           | (CALL)                 | (CALL)                 |                 |  |
| FC4525-50   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      | 48 VOLTS , 38.69 X 32.94 X 23.35 |                    |               |                |                  |                      |       |                    |                            |                           |                        | Weight Minimum 2800    | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48                              | 100T21       | 1000                 | 46.6                             | 38.25              | 32.63         | 22.63          | 3293             | M2802410021B         | Y     | (CALL)             |                            | SCR200241050T1H           | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085L21       | 850                  | 39.6                             | 38.38              | 32.69         | 22.63          | 3157             | M2902408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085F21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3211             | M2502408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 085C21       | 850                  | 39.6                             | 38.25              | 32.63         | 22.63          | 3087             | M2602408521B         | Y     | (CALL)             |                            | SCR20024865T1H            | (CALL)                 | (CALL)                 |                 |  |
|             | 48                              | 105B15       | 735                  | 34.6                             | 39.25              | 30.19         | 22.54          | 3090             | M2102410515B75981    | N     | (CALL)             |                            | SCR20024750T1H            | (CALL)                 | (CALL)                 |                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT                            | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)       | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |      |                                       |  |
|-------------|---------------------------------|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------------|---------------------------|------------------------|------------------------|------|---------------------------------------|--|
|             |                                 |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                                  |                           |                        |                        |      |                                       |  |
| FC4525-55   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 32.94 X 23.35 |                           | Weight Minimum 2800    | Connector SB350        | GRAY | , Position A , Lead Length 018 Inches |  |
|             | 36                              | 100T27       | 1300                 | 45.4 | 38.44              | 31.50         | 22.63          | 3127             | M2801810027B         | Y     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085L27       | 1105                 | 38.6 | 38.25              | 31.50         | 22.63          | 3003             | M2901808527B         | Y     | (CALL)             |                                  | SCR200181200T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085F27       | 1105                 | 38.6 | 38.44              | 31.50         | 22.63          | 3086             | M2501808527B         | Y     | (CALL)             |                                  | SCR200181200T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085C27       | 1105                 | 38.6 | 38.44              | 31.50         | 22.63          | 2960             | M2601808527B         | Y     | (CALL)             |                                  | SCR200181200T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 105B21       | 1050                 | 37.0 | 38.61              | 32.50         | 22.05          | 3075             | M2101810521B059      | N     | (CALL)             |                                  | SCR200181050T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
| FC4525-55   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 32.94 X 23.35 |                           | Weight Minimum 2800    | Connector SB350        | BLUE | , Position A , Lead Length 018 Inches |  |
|             | 48                              | 100T21       | 1000                 | 46.6 | 38.25              | 32.63         | 22.63          | 3293             | M2802410021B         | Y     | (CALL)             |                                  | SCR200241050T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085L21       | 850                  | 39.6 | 38.38              | 32.69         | 22.63          | 3157             | M2902408521B         | Y     | (CALL)             |                                  | SCR20024865T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085F21       | 850                  | 39.6 | 38.25              | 32.63         | 22.63          | 3211             | M2502408521B         | Y     | (CALL)             |                                  | SCR20024865T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085C21       | 850                  | 39.6 | 38.25              | 32.63         | 22.63          | 3087             | M2602408521B         | Y     | (CALL)             |                                  | SCR20024865T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 105B15       | 735                  | 34.6 | 39.25              | 30.19         | 22.54          | 3090             | M2102410515B75981    | N     | (CALL)             |                                  | SCR20024750T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
| FC4525-60   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 32.94 X 23.35 |                           | Weight Minimum 2800    | Connector SB350        | GRAY | , Position A , Lead Length 018 Inches |  |
|             | 36                              | 100T27       | 1300                 | 45.4 | 38.44              | 31.50         | 22.63          | 3127             | M2801810027B         | Y     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085L27       | 1105                 | 38.6 | 38.25              | 31.50         | 22.63          | 3003             | M2901808527B         | Y     | (CALL)             |                                  | SCR200181200T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085F27       | 1105                 | 38.6 | 38.44              | 31.50         | 22.63          | 3086             | M2501808527B         | Y     | (CALL)             |                                  | SCR200181200T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085C27       | 1105                 | 38.6 | 38.44              | 31.50         | 22.63          | 2960             | M2601808527B         | Y     | (CALL)             |                                  | SCR200181200T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 105B21       | 1050                 | 37.0 | 38.61              | 32.50         | 22.05          | 3075             | M2101810521B059      | N     | (CALL)             |                                  | SCR200181050T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
| FC4525-60   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 32.94 X 23.35 |                           | Weight Minimum 2800    | Connector SB350        | BLUE | , Position A , Lead Length 018 Inches |  |
|             | 48                              | 100T21       | 1000                 | 46.6 | 38.25              | 32.63         | 22.63          | 3293             | M2802410021B         | Y     | (CALL)             |                                  | SCR200241050T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085L21       | 850                  | 39.6 | 38.38              | 32.69         | 22.63          | 3157             | M2902408521B         | Y     | (CALL)             |                                  | SCR20024865T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085F21       | 850                  | 39.6 | 38.25              | 32.63         | 22.63          | 3211             | M2502408521B         | Y     | (CALL)             |                                  | SCR20024865T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085C21       | 850                  | 39.6 | 38.25              | 32.63         | 22.63          | 3087             | M2602408521B         | Y     | (CALL)             |                                  | SCR20024865T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 105B15       | 735                  | 34.6 | 39.25              | 30.19         | 22.54          | 3090             | M2102410515B75981    | N     | (CALL)             |                                  | SCR20024750T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
| FC4540-50   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 36.38 X 23.35 |                           | Weight Minimum 3100    | Connector SB350        | GRAY | , Position A , Lead Length 018 Inches |  |
|             | 36                              | 100T31       | 1500                 | 52.4 | 38.44              | 36.13         | 22.63          | 3730             | M2801810031B         | N     | (CALL)             |                                  | SCR200181700T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085F31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3742             | M2501808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085C31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3514             | M2601808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
| FC4540-50   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 36.38 X 23.35 |                           | Weight Minimum 3100    | Connector SB350        | BLUE | , Position A , Lead Length 018 Inches |  |
|             | 48                              | 100T23       | 1100                 | 51.2 | 38.44              | 35.88         | 22.63          | 3688             | M2802410023B         | N     | (CALL)             |                                  | SCR200241200T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085F23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3626             | M2502408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085C23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3458             | M2602408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
| FC4540-55   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 36.38 X 23.35 |                           | Weight Minimum 3100    | Connector SB350        | GRAY | , Position A , Lead Length 018 Inches |  |
|             | 36                              | 100T31       | 1500                 | 52.4 | 38.44              | 36.13         | 22.63          | 3730             | M2801810031B         | N     | (CALL)             |                                  | SCR200181700T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085F31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3742             | M2501808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 36                              | 085C31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3514             | M2601808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
| FC4540-55   | CLASS I 4 WHEEL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 36.38 X 23.35 |                           | Weight Minimum 3100    | Connector SB350        | BLUE | , Position A , Lead Length 018 Inches |  |
|             | 48                              | 100T23       | 1100                 | 51.2 | 38.44              | 35.88         | 22.63          | 3688             | M2802410023B         | N     | (CALL)             |                                  | SCR200241200T1H           | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085F23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3626             | M2502408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |      |                                       |  |
|             | 48                              | 085C23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3458             | M2602408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |      |                                       |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

| TRUCK MODEL | VOLT   | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)       | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                     |                 |  |
|-------------|--|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|----------------------------------|---------------------------|------------------------|------------------------|---------------------|-----------------|--|
|             |  |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |                                  |                           |                        |                        |                     |                 |  |
| FC4540-60   | CLASS I 4 WHEEL COUNTERBALANCED              |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 36.38 X 23.35 |                           |                        |                        | Weight Minimum 3100 | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36   | 100T31       | 1500                 | 52.4 | 38.44              | 36.13         | 22.63          | 3730             | M2801810031B         | N     | (CALL)             |                                  | SCR200181700T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 36   | 085F31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3742             | M2501808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 36   | 085C31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3514             | M2601808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
| FC4540-60   | CLASS I 4 WHEEL COUNTERBALANCED              |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 36.38 X 23.35 |                           |                        |                        | Weight Minimum 3100 | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48   | 100T23       | 1100                 | 51.2 | 38.44              | 35.88         | 22.63          | 3688             | M2802410023B         | N     | (CALL)             |                                  | SCR200241200T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 48   | 085F23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3626             | M2502408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 48   | 085C23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3458             | M2602408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |                     |                 |  |
| FC4545-50   | CLASS I 4 WHEEL COUNTERBALANCED              |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 36.38 X 23.35 |                           |                        |                        | Weight Minimum 3100 | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36   | 100T31       | 1500                 | 52.4 | 38.44              | 36.13         | 22.63          | 3730             | M2801810031B         | N     | (CALL)             |                                  | SCR200181700T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 36   | 085F31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3742             | M2501808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 36   | 085C31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3514             | M2601808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
| FC4545-50   | CLASS I 4 WHEEL COUNTERBALANCED              |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 36.38 X 23.35 |                           |                        |                        | Weight Minimum 3100 | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48   | 100T23       | 1100                 | 51.2 | 38.44              | 35.88         | 22.63          | 3688             | M2802410023B         | N     | (CALL)             |                                  | SCR200241200T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 48   | 085F23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3626             | M2502408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 48   | 085C23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3458             | M2602408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |                     |                 |  |
| FC4545-55   | CLASS I 4 WHEEL COUNTERBALANCED              |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 36.38 X 23.35 |                           |                        |                        | Weight Minimum 3100 | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36   | 100T31       | 1500                 | 52.4 | 38.44              | 36.13         | 22.63          | 3730             | M2801810031B         | N     | (CALL)             |                                  | SCR200181700T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 36   | 085F31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3742             | M2501808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 36   | 085C31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3514             | M2601808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
| FC4545-55   | CLASS I 4 WHEEL COUNTERBALANCED              |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 36.38 X 23.35 |                           |                        |                        | Weight Minimum 3100 | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48   | 100T23       | 1100                 | 51.2 | 38.44              | 35.88         | 22.63          | 3688             | M2802410023B         | N     | (CALL)             |                                  | SCR200241200T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 48   | 085F23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3626             | M2502408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 48   | 085C23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3458             | M2602408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |                     |                 |  |
| FC4545-60   | CLASS I 4 WHEEL COUNTERBALANCED              |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.69 X 36.38 X 23.35 |                           |                        |                        | Weight Minimum 3100 | Connector SB350 | GRAY , Position A , Lead Length 018 Inches |
|             | 36   | 100T31       | 1500                 | 52.4 | 38.44              | 36.13         | 22.63          | 3730             | M2801810031B         | N     | (CALL)             |                                  | SCR200181700T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 36   | 085F31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3742             | M2501808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 36   | 085C31       | 1275                 | 44.5 | 38.44              | 36.13         | 22.63          | 3514             | M2601808531B         | N     | (CALL)             |                                  | SCR200181450T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
| FC4545-60   | CLASS I 4 WHEEL COUNTERBALANCED              |              |                      |      |                    |               |                |                  |                      |       |                    | 48 VOLTS , 38.69 X 36.38 X 23.35 |                           |                        |                        | Weight Minimum 3100 | Connector SB350 | BLUE , Position A , Lead Length 018 Inches |
|             | 48   | 100T23       | 1100                 | 51.2 | 38.44              | 35.88         | 22.63          | 3688             | M2802410023B         | N     | (CALL)             |                                  | SCR200241200T1H           | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 48   | 085F23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3626             | M2502408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |                     |                 |  |
|             | 48   | 085C23       | 935                  | 43.5 | 38.44              | 35.88         | 22.63          | 3458             | M2602408523B         | N     | (CALL)             |                                  | SCR20024965T1H            | (CALL)                 | (CALL)                 |                     |                 |  |
| RC5510-30   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.56 X 13.60 X 31.00 |                           |                        |                        | Weight Minimum 1710 | Connector SB350 | GRAY , Position A , Lead Length 009 Inches |
|             | 36   | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                   | SCR20018750T1H            | (CALL)                 | (CALL)                 |                     |                 |  |
| RC5515-30   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       |                    | 36 VOLTS , 38.56 X 13.60 X 31.00 |                           |                        |                        | Weight Minimum 1710 | Connector SB350 | GRAY , Position A , Lead Length 009 Inches |
|             | 36   | 140T11       | 700                  | 24.4 | 38.11              | 13.25         | 30.50          | 1811             | M2801814011B         | Y     | (CALL)             | SCR20018750S1H                   | SCR20018750T1H            | (CALL)                 | (CALL)                 |                     |                 |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



| TRUCK MODEL | VOLT   | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE               | SINGLE PHASE CHARGER (S-1) | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE                |  |
|-------------|--|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|----------------------------------|----------------------------|---------------------------|------------------------|---------------------------------------|--|
|             |  |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                                  |                            |                           |                        |                                       |  |
| RC5520-30   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.56 X 15.88 X 31.00 | Weight Minimum 1990        | Connector SB350           | GRAY                   | , Position A , Lead Length 009 Inches |  |
|             | 36   | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)                           | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                                |  |
| RC5525-30   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.56 X 15.88 X 31.00 | Weight Minimum 1990        | Connector SB350           | GRAY                   | , Position A , Lead Length 009 Inches |  |
|             | 36   | 140T13       | 840                  | 29.3 | 37.94              | 15.63         | 30.50          | 2166             | M2801814013B         | Y     | (CALL)                           | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125L13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2090             | M2901812513B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125F13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2113             | M2501812513B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125C13       | 750                  | 26.2 | 37.94              | 15.63         | 30.50          | 2046             | M2601812513B         | Y     | (CALL)                           | SCR20018750S1H             | SCR20018750T1H            | (CALL)                 | (CALL)                                |  |
| RC5530-30   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.56 X 18.20 X 31.00 | Weight Minimum 2280        | Connector SB350           | GRAY                   | , Position A , Lead Length 009 Inches |  |
|             | 36   | 140T15       | 980                  | 34.2 | 38.25              | 17.81         | 30.50          | 2492             | M2801814015B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125L15       | 875                  | 30.6 | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125F15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125C15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 055B31       | 825                  | 29.1 | 39.50              | 18.04         | 30.69          | 2380             | M2101805531B         | N     | (CALL)                           | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                                |  |
| RC5530-35   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.56 X 18.20 X 31.00 | Weight Minimum 2280        | Connector SB350           | GRAY                   | , Position A , Lead Length 009 Inches |  |
|             | 36   | 140T15       | 980                  | 34.2 | 38.25              | 17.81         | 30.50          | 2492             | M2801814015B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125L15       | 875                  | 30.6 | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125F15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125C15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 055B31       | 825                  | 29.1 | 39.50              | 18.04         | 30.69          | 2380             | M2101805531B         | N     | (CALL)                           | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                                |  |
| RC5535-30   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.56 X 18.20 X 31.00 | Weight Minimum 2280        | Connector SB350           | GRAY                   | , Position A , Lead Length 009 Inches |  |
|             | 36   | 140T15       | 980                  | 34.2 | 38.25              | 17.81         | 30.50          | 2492             | M2801814015B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125L15       | 875                  | 30.6 | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125F15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125C15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 055B31       | 825                  | 29.1 | 39.50              | 18.04         | 30.69          | 2380             | M2101805531B         | N     | (CALL)                           | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                                |  |
| RC5535-35   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.56 X 18.20 X 31.00 | Weight Minimum 2280        | Connector SB350           | GRAY                   | , Position A , Lead Length 009 Inches |  |
|             | 36   | 140T15       | 980                  | 34.2 | 38.25              | 17.81         | 30.50          | 2492             | M2801814015B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125L15       | 875                  | 30.6 | 38.25              | 17.81         | 30.50          | 2383             | M2901812515B         | N     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125F15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2417             | M2501812515B         | Y     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 125C15       | 875                  | 30.6 | 38.31              | 17.88         | 30.50          | 2340             | M2601812515B         | Y     | (CALL)                           |                            | SCR20018965T1H            | (CALL)                 | (CALL)                                |  |
|             | 36   | 055B31       | 825                  | 29.1 | 39.50              | 18.04         | 30.69          | 2380             | M2101805531B         | N     | (CALL)                           | SCR20018865S1H             | SCR20018865T1H            | (CALL)                 | (CALL)                                |  |
| RC5540-40   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.56 X 20.50 X 31.00 | Weight Minimum 2600        | Connector SB350           | GRAY                   | , Position A , Lead Length 009 Inches |  |
|             | 36   | 140T17       | 1120                 | 39.1 | 38.31              | 20.13         | 30.50          | 2843             | M2801814017B         | Y     | (CALL)                           |                            | SCR200181200T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125L17       | 1000                 | 34.9 | 38.31              | 20.13         | 30.50          | 2711             | M2901812517B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125F17       | 1000                 | 34.9 | 38.31              | 20.13         | 30.50          | 2762             | M2501812517B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125C17       | 1000                 | 34.9 | 38.31              | 20.13         | 30.50          | 2673             | M2601812517B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |
| RC5545-40   | CLASS I STAND-UP END CONTROL COUNTERBALANCED |              |                      |      |                    |               |                |                  |                      |       | 36 VOLTS , 38.56 X 20.50 X 31.00 | Weight Minimum 2600        | Connector SB350           | GRAY                   | , Position A , Lead Length 009 Inches |  |
|             | 36   | 140T17       | 1120                 | 39.1 | 38.31              | 20.13         | 30.50          | 2843             | M2801814017B         | Y     | (CALL)                           |                            | SCR200181200T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125L17       | 1000                 | 34.9 | 38.31              | 20.13         | 30.50          | 2711             | M2901812517B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125F17       | 1000                 | 34.9 | 38.31              | 20.13         | 30.50          | 2762             | M2501812517B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |
|             | 36   | 125C17       | 1000                 | 34.9 | 38.31              | 20.13         | 30.50          | 2673             | M2601812517B         | Y     | (CALL)                           |                            | SCR200181050T1H           | (CALL)                 | (CALL)                                |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)