

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>B15R-5</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>							<b>24 VOLTS , 33.30 X 19.80 X 25.50</b>		<b>Weight Minimum 1488</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>				
	24	100T13	600	14.0	32.75	17.38	22.63	1501	M2801210013D7	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T15	700	16.3	32.75	19.25	22.63	1686	M2801210015D7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	32.75	17.38	22.63	1438	M2901208513D7	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L15	595	13.9	32.75	19.25	22.63	1615	M2901208515D7	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F15	595	13.9	32.75	19.25	22.63	1631	M2501208515D7	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	32.75	17.38	22.63	1403	M2601208513D7	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C15	595	13.9	32.75	19.25	22.63	1576	M2601208515D7	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>B15T-5</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>							<b>36 VOLTS , 38.90 X 20.80 X 26.70</b>		<b>Weight Minimum 1544</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>				
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>B15T-5</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>							<b>48 VOLTS , 38.90 X 20.80 X 26.70</b>		<b>Weight Minimum 1544</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 040 Inches</b>				
	48	100T11	500	23.3	37.69	17.50	22.63	1750	M2802410011BA	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085L11	425	19.8	37.69	17.50	22.63	1698	M2902408511BA	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
	48	085C11	425	19.8	37.69	17.50	22.63	1648	M2602408511BA	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
<b>B18T-5</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>							<b>36 VOLTS , 38.90 X 25.10 X 26.70</b>		<b>Weight Minimum 1764</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>				
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
<b>B18T-5</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>							<b>48 VOLTS , 38.90 X 25.10 X 26.70</b>		<b>Weight Minimum 1764</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 040 Inches</b>				
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
<b>B20T-5</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>							<b>36 VOLTS , 38.90 X 25.10 X 26.70</b>		<b>Weight Minimum 2315</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>				
	36	100T21	1000	34.9	38.50	24.56	22.63	2584	M2801810021B7B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	085L21	850	29.7	38.50	24.56	22.63	2466	M2901808521B7B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F21	850	29.7	38.50	24.56	22.63	2574	M2501808521B7B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C21	850	29.7	38.50	24.56	22.63	2430	M2601808521B7B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
<b>B20T-5</b>	<b>CLASS I 3 WHEEL COUNTERBALANCED</b>							<b>48 VOLTS , 38.90 X 25.10 X 26.70</b>		<b>Weight Minimum 2315</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>				
	48	100T15	700	32.6	38.31	23.63	23.63	2628	M2802410015B7B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085L15	595	27.7	38.31	23.63	23.63	2520	M2902408515B7B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085F15	595	27.7	38.31	23.63	23.63	2614	M2502408515B7B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085C15	595	27.7	38.31	23.63	23.63	2473	M2602408515B7B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>B16/18/20X</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>48 VOLTS , 39.00 X 25.00 X 26.70</b>											
											Weight Minimum 2313	Connector SB350	GRAY	, Position B , Lead Length 018 Inches	
	48	100T15	700	32.6	38.31	23.63	23.63	2628	M2802410015B7B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085L15	595	27.7	38.31	23.63	23.63	2520	M2902408515B7B	N	( CALL )		SCR20024600T1H	( CALL )	( CALL )
	48	085F15	595	27.7	38.31	23.63	23.63	2614	M2502408515B7B	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	085C15	595	27.7	28.31	23.63	23.63	2473	M2602408515B7B	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
<b>BC15/18/20SC</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>36 VOLTS , 36.20 X 27.60 X 25.70</b>											
											Weight Minimum 1852	Connector SB350	GRAY	, Position B , Lead Length 018 Inches	
	36	100T17	800	27.9	32.00	26.63	22.63	2065	M2801810017J	N	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	085L17	680	23.7	32.00	26.63	22.63	2032	M2901808517J	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	085C17	680	23.7	32.00	26.50	22.63	1957	M2601808517J	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
<b>BC15/18/20SC</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>48 VOLTS , 36.20 X 27.60 X 25.70</b>											
											Weight Minimum 2490	Connector SB350	GRAY	, Position B , Lead Length 018 Inches	
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
<b>BC20S</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>36 VOLTS , 40.00 X 30.50 X 24.00</b>											
											Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 018 Inches	
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
<b>BC20S</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>48 VOLTS , 40.00 X 30.50 X 24.00</b>											
											Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 018 Inches	
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	23.25	2954	M1902408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
<b>BC25S</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>36 VOLTS , 40.00 X 30.50 X 24.00</b>											
											Weight Minimum 2800	Connector SB350	GRAY	, Position B , Lead Length 018 Inches	
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L25	1020	35.6	38.69	29.69	22.88	3362	M2901808525B7	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.69	29.69	22.88	3064	M2501808525B7	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085C25	1020	35.6	38.69	29.69	22.88	2999	M2601808525B7	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
<b>BC25S</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>			<b>48 VOLTS , 40.00 X 30.50 X 24.00</b>											
											Weight Minimum 2800	Connector SB350	GRAY	, Position B , Lead Length 018 Inches	
	48	100T19	900	41.9	38.50	30.00	22.62	3106	M2802410019B7	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.50	30.00	22.62	2974	M2902408519B7	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.50	30.00	22.62	3106	M2502408519B7	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C19	765	35.6	38.50	30.00	22.62	2900	M2602408519B7	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
BC25SE	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 40.0 X 34.4 X 24.00 Weight Minimum 2800 Connector SB350 GRAY , Position B , Lead Length 018 Inches											
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
BC25SE	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 40.0 X 34.4 X 24.00 Weight Minimum 2800 Connector SB350 GRAY , Position B , Lead Length 018 Inches											
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
BC30S	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 40.0 X 34.4 X 24.00 Weight Minimum 3000 Connector SB350 GRAY , Position B , Lead Length 018 Inches											
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
BC30S	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 40.0 X 34.4 X 24.00 Weight Minimum 3000 Connector SB350 GRAY , Position B , Lead Length 018 Inches											
	48	100T21	1000	46.6	38.25	33.25	22.63	3401	M2802410021B7B	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	085L21	850	39.6	38.25	33.25	22.63	3243	M2902408521B7B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C21	850	39.6	38.25	33.25	22.63	3216	M2602408521B7B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C21	850	39.6	38.31	32.57	22.88	3143	M2602408521B7	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
BC32S	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 40.0 X 34.4 X 24.00 Weight Minimum 3000 Connector SB350 GRAY , Position B , Lead Length 018 Inches											
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
BC32S	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 40.0 X 34.4 X 24.00 Weight Minimum 3000 Connector SB350 GRAY , Position B , Lead Length 018 Inches											
	48	085C21	850	39.6	38.31	32.57	22.88	3143	M2602408521B7	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
B20S	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 40.7 X 35.2 X 20.80 Weight Minimum 2447 Connector SB350 GRAY , Position D , Lead Length 030 Inches											
	48	060C21	600	27.9	38.44	32.75	19.50	2768	M2602406021B7	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
B25S	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 40.7 X 35.2 X 20.80 Weight Minimum 2447 Connector SB350 GRAY , Position D , Lead Length 030 Inches											
	48	060C21	600	27.9	38.44	32.75	19.50	2768	M2602406021B7	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
B30S	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 40.7 X 41.1 X 20.80 Weight Minimum 3175 Connector SB350 GRAY , Position D , Lead Length 030 Inches											
	48	060C25	720	33.5	38.88	38.50	19.13	3265	M2602406025C7	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
B32S	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 40.7 X 41.1 X 20.80 Weight Minimum 3175 Connector SB350 GRAY , Position D , Lead Length 030 Inches											
	48	060C25	720	33.5	38.88	38.50	19.13	3265	M2602406025C7	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
<b>B22X</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>											<b>80 VOLTS , 40.90 X 28.40 X 30.80</b>				<b>Weight Minimum 3439</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>
	80	140T09	560	43.5	40.00	27.50	30.50	3986	M2804014009X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
	80	125L09	500	38.8	40.00	27.50	30.50	3902	M2904012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
	80	125F09	500	38.8	40.00	27.50	30.50	3995	M2504012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
	80	125C09	500	38.8	40.00	27.50	30.50	3835	M2604012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
<b>B25X</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>											<b>80 VOLTS , 40.90 X 28.40 X 30.80</b>				<b>Weight Minimum 3439</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>
	80	140T09	560	43.5	40.00	27.50	30.50	3986	M2804014009X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
	80	125L09	500	38.8	40.00	27.50	30.50	3902	M2904012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
	80	125F09	500	38.8	40.00	27.50	30.50	3995	M2504012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
	80	125C09	500	38.8	40.00	27.50	30.50	3835	M2604012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
<b>B30X</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>											<b>80 VOLTS , 40.90 X 34.10 X 30.80</b>				<b>Weight Minimum 4123</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>
	80	125L11	625	48.5	40.05	32.71	30.50	4662	M2904012511X76A	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125F11	625	48.5	40.05	32.71	30.50	4862	M2504012511X76A	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125C11	625	48.5	40.05	32.71	30.50	4581	M2604012511X76A	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
<b>B35X</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>											<b>80 VOLTS , 40.90 X 34.10 X 30.80</b>				<b>Weight Minimum 4123</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>
	80	125L11	625	48.5	40.05	32.71	30.50	4662	M2904012511X76A	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125F11	625	48.5	40.05	32.71	30.50	4862	M2504012511X76A	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125C11	625	48.5	40.05	32.71	30.50	4581	M2604012511X76A	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
<b>B40X</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>											<b>80 VOLTS , 40.90 X 39.60 X 33.00</b>				<b>Weight Minimum 4762</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>
	80	140T13	750	58.2	40.00	38.63	30.50	5322	M2804014013X7	N	( CALL )		SCR20040865T1H	( CALL )	( CALL )			
	80	125L13	750	58.2	40.00	38.63	30.50	5122	M2904012513X7	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125F13	750	58.2	40.00	38.63	30.50	5382	M2504012513X7	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125C13	750	58.2	40.00	38.63	30.50	5054	M2604012513X7	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
<b>B45X</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>											<b>80 VOLTS , 40.90 X 39.60 X 33.00</b>				<b>Weight Minimum 4762</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>
	80	140T13	750	58.2	40.00	38.63	30.50	5322	M2804014013X7	N	( CALL )		SCR20040865T1H	( CALL )	( CALL )			
	80	125L13	750	58.2	40.00	38.63	30.50	5122	M2904012513X7	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125F13	750	58.2	40.00	38.63	30.50	5382	M2504012513X7	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125C13	750	58.2	40.00	38.63	30.50	5054	M2604012513X7	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
<b>B50X</b>	<b>CLASS I 4 WHEEL COUNTERBALANCED</b>											<b>80 VOLTS , 40.90 X 39.60 X 33.00</b>				<b>Weight Minimum 4762</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>
	80	140T13	750	58.2	40.00	38.63	30.50	5322	M2804014013X7	N	( CALL )		SCR20040865T1H	( CALL )	( CALL )			
	80	125L13	750	58.2	40.00	38.63	30.50	5122	M2904012513X7	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125F13	750	58.2	40.00	38.63	30.50	5382	M2504012513X7	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
	80	125C13	750	58.2	40.00	38.63	30.50	5054	M2604012513X7	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			