

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>T5XT</b>	<b>TOW TRACTORS</b>		<b>24 VOLTS , 32.00 X 13.40 X 31.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F11	625	14.6	30.69	12.94	31.00	1283	M1501212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C11	625	14.6	30.69	12.94	31.00	1226	M1601212511A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T11	700	16.3	30.69	12.94	31.00	1302	M1801214011A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>C60Z</b>	<b>CENTER RIDER</b>		<b>24 VOLTS , 31.30 X 13.40 X 999.00 Weight Minimum 500 Connector SB175 RED , Position B , Lead Length 016 Inches</b>												
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>C80Z</b>	<b>CENTER RIDER</b>		<b>24 VOLTS , 31.30 X 13.30 X 999.00 Weight Minimum 500 Connector SB175 RED , Position B , Lead Length 016 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>B60ZAC</b>	<b>CLASS III LOW-LIFT WALKIE/RIDER PALLET</b>		<b>24 VOLTS , 31.25 X 9.00 X 31.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
<b>B60ZAC</b>	<b>CLASS III LOW-LIFT WALKIE/RIDER PALLET</b>		<b>24 VOLTS , 31.25 X 13.40 X 31.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>B80ZAC</b>	<b>CLASS III LOW-LIFT WALKIE/RIDER PALLET</b>			<b>24 VOLTS , 31.25 X 13.40 X 999.00</b>					<b>Weight Minimum 536</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>T5Z</b>	<b>CLASS III TRACTOR/TUGGER</b>			<b>24 VOLTS , 31.30 X 13.40 X 999.00</b>					<b>Weight Minimum 500</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>				
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>T7Z</b>	<b>CLASS III TRACTOR/TUGGER</b>			<b>24 VOLTS , 31.30 X 13.30 X 999.00</b>					<b>Weight Minimum 500</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>CA60XT</b>	<b>RIDER</b>			<b>24 VOLTS , 32.00 X 13.40 X 31.00</b>					<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>YELLOW</b>	<b>, Position B , Lead Length 015 Inches</b>				
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>CA80XT</b>	<b>RIDER</b>			<b>24 VOLTS , 32.00 X 13.40 X 31.00</b>					<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>YELLOW</b>	<b>, Position B , Lead Length 015 Inches</b>				
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
<b>W20ZA</b>	<b>STRADDLE STACKER, 2000 LB</b>			<b>24 VOLTS , 27.80 X 8.10 X 999.00</b>											<b>Weight Minimum 310</b>	<b>Connector SBX175</b>	<b>RED</b>	<b>, Position N/A, Lead Length 020 Inches</b>
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	100C05	200	4.7	25.25	6.50	25.63	455	M1601210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	CHP	195	.0	27.30	7.50	26.45	400	M90004S24CHPX	Y	(CALL)	(CALL)		(CALL)	(CALL)			
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
<b>W25ZA</b>	<b>STRADDLE STACKER, 2500 LB</b>			<b>24 VOLTS , 27.80 X 9.10 X 999.00</b>											<b>Weight Minimum 350</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)	(CALL)		(CALL)	(CALL)			
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	CHP	195	.0	27.30	7.50	26.45	400	M90004S24CHPX	Y	(CALL)	(CALL)		(CALL)	(CALL)			
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
<b>W45Z</b>	<b>WALKIE PALLET TRUCK</b>			<b>12 VOLTS , 31.60 X 8.10 X 999.00</b>											<b>Weight Minimum 300</b>	<b>Connector SB175</b>	<b>YELLOW</b>	<b>, Position B , Lead Length 020 Inches</b>
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)			
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)			
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)			
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)			
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)	(CALL)		(CALL)	(CALL)			
	12	085C11	425	4.9	30.56	7.75	23.25	461	M1600608511A6	N	(CALL)	SCR20006475S1H	SCR20006475T1H	(CALL)	(CALL)			
	12	085C11	425	4.9	30.56	7.75	23.25	461	M1600608511A6	N	(CALL)	SCR20006475S1L	SCR20006475T1H	(CALL)	(CALL)			
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)			
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)			
<b>W45Z</b>	<b>WALKIE PALLET TRUCK</b>			<b>24 VOLTS , 28.50 X 9.10 X 999.00</b>											<b>Weight Minimum 410</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	090G07	270	6.4	27.00	8.70	27.88	615	M8901209007E0	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C07	255	5.9	27.75	8.63	23.25	587	M1601208507D625	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085L07	255	5.9	27.75	8.63	23.25	620	M1901208507D625	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>W65Z</b>	<b>WALKIE PALLET TRUCK</b>		<b>12 VOLTS , 32.00 X 9.00 X 31.00</b>										<b>Weight Minimum 305</b>	<b>Connector SB175</b>	<b>YELLOW , Position B , Lead Length 020 Inches</b>	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	125F13	750	8.7	30.56	7.69	31.00	709	M1500612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)	
	12	125C13	750	8.7	30.56	7.69	31.00	708	M1600612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)	
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)			(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	125L13	750	8.7	30.56	7.69	31.00	740	M1900612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)	
<b>B40XL</b>	<b>WALKIES</b>		<b>24 VOLTS , 31.90 X 13.60 X 23.90</b>										<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED , Position B , Lead Length 015 Inches</b>	
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>B60XL</b>	<b>WALKIES</b>		<b>24 VOLTS , 31.90 X 13.60 X 23.90</b>										<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED , Position B , Lead Length 015 Inches</b>	
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>W40XL</b>	<b>WALKIES</b>		<b>12 VOLTS , 31.90 X 8.30 X 23.90</b>										<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>YELLOW , Position B , Lead Length 015 Inches</b>	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
<b>W40XL</b>	<b>WALKIES</b>		<b>24 VOLTS , 32.00 X 13.50 X 32.00</b>										<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED , Position B , Lead Length 015 Inches</b>	
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
W40XT	WALKIES		24 VOLTS , 25.75 X 6.88 X 999.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
W40XT	WALKIES		24 VOLTS , 28.75 X 7.80 X 999.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	090G05	180	4.2	28.00	6.52	25.42	525	M8901209005GPP0	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
W40XT	WALKIES		24 VOLTS , 29.50 X 7.80 X 999.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	090G05	180	4.2	28.00	6.52	25.42	525	M8901209005GPP0	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	CHP	195	.0	27.30	7.50	26.45	400	M90004S24CHPX	Y	(CALL)			(CALL)	(CALL)
W45XT	WALKIES		12 VOLTS , 31.75 X 8.10 X 999.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 015 Inches												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)			(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
W45XT	WALKIES		24 VOLTS , 31.75 X 8.10 X 999.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 015 Inches												
	24	045B11	225	5.3	31.67	6.63	24.07	560	M2101204511M	Y	(CALL)	SCR20024260S1H		(CALL)	(CALL)
W45XT	WALKIES		24 VOLTS , 31.75 X 9.10 X 999.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 015 Inches												
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475T1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
W60XL	WALKIES		12 VOLTS , 31.90 X 8.30 X 23.90 Weight Minimum 0 Connector SB175 YELLOW , Position B , Lead Length 015 Inches												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>W60XL</b>	<b>WALKIES</b>							<b>24 VOLTS , 32.00 X 13.50 X 32.00</b>		<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED , Position B , Lead Length 015 Inches</b>			
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>W60XT</b>	<b>WALKIES</b>							<b>12 VOLTS , 32.00 X 9.00 X 31.00</b>		<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>YELLOW , Position B , Lead Length 020 Inches</b>			
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	125F13	750	8.7	30.56	7.69	31.00	709	M1500612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
	12	125C13	750	8.7	30.56	7.69	31.00	708	M1600612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)			(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	140T13	840	9.8	30.56	7.69	31.00	755	M1800614013A	N	(CALL)	SCR20006865S1H	SCR20006865T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	125L13	750	8.7	30.56	7.69	31.00	740	M1900612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
<b>W60XT</b>	<b>WALKIES</b>							<b>24 VOLTS , 32.00 X 9.00 X 31.00</b>		<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED , Position B , Lead Length 020 Inches</b>			
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
<b>W60XT</b>	<b>WALKIES</b>							<b>24 VOLTS , 32.00 X 13.40 X 31.00</b>		<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED , Position B , Lead Length 020 Inches</b>			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>W80XT</b>	<b>WALKIES</b>		<b>24 VOLTS , 32.00 X 13.40 X 31.00</b>						<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>B60XT</b>	<b>WALKIES, RIDERS</b>		<b>24 VOLTS , 32.00 X 9.00 X 31.00</b>						<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>				
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H	(CALL)	(CALL)	(CALL)	
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H	(CALL)	(CALL)	(CALL)	
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H	(CALL)	(CALL)	(CALL)	
<b>B60XT</b>	<b>WALKIES, RIDERS</b>		<b>24 VOLTS , 32.00 X 13.40 X 31.00</b>						<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100C13	600	14.0	30.69	13.00	26.81	1141	M3401210013A12	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>B60Z</b>	<b>WALKIES, RIDERS</b>		<b>24 VOLTS , 32.00 X 9.00 X 31.00</b>						<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>				
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H	(CALL)	(CALL)	(CALL)	
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H	(CALL)	(CALL)	(CALL)	
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H	(CALL)	(CALL)	(CALL)	
<b>B60Z</b>	<b>WALKIES, RIDERS</b>		<b>24 VOLTS , 32.00 X 13.40 X 31.00</b>						<b>Weight Minimum 0</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>				
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>B80XT</b>	<b>WALKIES, RIDERS</b>		<b>24 VOLTS , 32.00 X 9.00 X 31.00</b>												
			<b>Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
<b>B80XT</b>	<b>WALKIES, RIDERS</b>		<b>24 VOLTS , 32.00 X 13.40 X 31.00</b>												
			<b>Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>B80Z</b>	<b>WALKIES, RIDERS</b>		<b>24 VOLTS , 32.00 X 13.40 X 999.00</b>												
			<b>Weight Minimum 536 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>C60XT</b>	<b>WALKIES, RIDERS</b>		<b>24 VOLTS , 32.00 X 13.40 X 31.00</b>												
			<b>Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>C80XT</b>	<b>WALKIES, RIDERS</b>		<b>24 VOLTS , 32.00 X 13.40 X 31.00 Weight Minimum 0 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>E30HSD</b>	<b>CLASS I STAND UP COUNTERBALANCED</b>		<b>36 VOLTS , 38.60 X 16.30 X 31.10 Weight Minimum 1800 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>E30HSD</b>	<b>CLASS I STAND UP COUNTERBALANCED</b>		<b>36 VOLTS , 38.60 X 18.30 X 31.10 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	(CALL)	SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	(CALL)	SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	(CALL)	SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	(CALL)	SCR20018965T1H	(CALL)	(CALL)
<b>E35HSD</b>	<b>CLASS I STAND UP COUNTERBALANCED</b>		<b>36 VOLTS , 38.60 X 18.30 X 31.10 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	(CALL)	SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	(CALL)	SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	(CALL)	SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	(CALL)	SCR20018965T1H	(CALL)	(CALL)
<b>E35HSD</b>	<b>CLASS I STAND UP COUNTERBALANCED</b>		<b>36 VOLTS , 38.60 X 20.80 X 31.10 Weight Minimum 2500 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	(CALL)	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	(CALL)	SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	(CALL)	SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	(CALL)	SCR20018965T1H	(CALL)	(CALL)
<b>E40HSD</b>	<b>CLASS I STAND UP COUNTERBALANCED</b>		<b>36 VOLTS , 38.60 X 20.80 X 31.10 Weight Minimum 2500 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	(CALL)	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	(CALL)	SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	(CALL)	SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	(CALL)	SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
<b>R30XMF2</b>	<b>CLASS II FURNITURE ORDER PICKER</b>											<b>24 VOLTS , 38.90 X 14.60 X 30.80</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B</b>	<b>, Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
<b>R30XMA2</b>	<b>CLASS II ORDER PICKER</b>											<b>24 VOLTS , 39.00 X 14.60 X 31.50</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B</b>	<b>, Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
<b>R30XMA2</b>	<b>CLASS II ORDER PICKER</b>											<b>36 VOLTS , 39.00 X 14.60 X 31.50</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B</b>	<b>, Lead Length 016 Inches</b>
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
<b>R30XMS2</b>	<b>CLASS II ORDER PICKER</b>											<b>24 VOLTS , 36.00 X 13.50 X 24.71</b>				<b>Weight Minimum 1025</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B</b>	<b>, Lead Length 016 Inches</b>
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085F15	595	13.9	35.06	12.88	22.50	1127	M2501208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085C15	595	13.9	35.06	12.88	22.50	1076	M2601208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	100T15	700	16.3	35.06	12.88	22.50	1145	M2801210015A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	085L15	595	13.9	35.06	12.88	22.50	1109	M2901208515A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
<b>R30XM2</b>	<b>CLASS II ORDER PICKER</b>											<b>24 VOLTS , 38.90 X 14.60 X 30.80</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B</b>	<b>, Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)					
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
<b>R30XM2</b>	<b>CLASS II ORDER PICKER</b>											<b>36 VOLTS , 38.90 X 14.60 X 30.80</b>				<b>Weight Minimum 1800</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B</b>	<b>, Lead Length 016 Inches</b>
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	125C11	625	21.8	38.00	14.00	30.50	1875	M2601812511B7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
<b>V30ZMU-MEDWHBASE</b>	<b>CLASS II VERY NARROW AISLE TURRET</b>											<b>48 VOLTS , 44.40 X 21.30 X 31.00</b>				<b>Weight Minimum 2976</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B</b>	<b>, Lead Length 030 Inches</b>
	48	125F13	750	34.9	44.13	20.63	30.50	3295	M2502412513B7	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	125C13	750	34.9	44.13	20.63	30.50	3159	M2602412513B7	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	140T13	840	39.1	44.13	20.63	30.50	3312	M2802414013B7	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
	48	125L13	750	34.9	44.13	20.63	30.50	3167	M2902412513B7	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
<b>V35XMU</b>	<b>CLASS II VERY NARROW AISLE TURRET</b>											<b>72 VOLTS , 40.75 X 28.74 X 37.40</b>				<b>Weight Minimum 3520</b>	<b>Connector SB350</b>	<b>GREEN</b>	<b>, Position B</b>	<b>, Lead Length 030 Inches</b>
	72	125C11	625	43.7	40.23	27.92	34.57	3640	M2603612511B741	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)					

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>W20XTC</b>	<b>COUNTERBALANCED STACKERS</b>			<b>24 VOLTS , 31.87 X 13.38 X 999.00</b>					<b>Weight Minimum 400</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>				
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>W30XTC</b>	<b>COUNTERBALANCED STACKERS</b>			<b>24 VOLTS , 31.87 X 13.38 X 999.00</b>					<b>Weight Minimum 400</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>				
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>W40XTC</b>	<b>COUNTERBALANCED STACKERS</b>			<b>24 VOLTS , 31.87 X 13.38 X 999.00</b>					<b>Weight Minimum 400</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>				
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>R40EH</b>	<b>HI-RACKER</b>			<b>72 VOLTS , 42.40 X 17.40 X 31.50</b>					<b>Weight Minimum 4000</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 040 Inches</b>				
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>E30FR</b>	<b>LIFT TRUCK</b>			<b>24 VOLTS , 38.75 X 15.50 X 31.62</b>					<b>Weight Minimum 1925</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position D , Lead Length 009 Inches</b>				
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)	
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
<b>E30FR</b>	<b>LIFT TRUCK</b>			<b>36 VOLTS , 38.75 X 16.12 X 31.62</b>					<b>Weight Minimum 1925</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position D , Lead Length 009 Inches</b>				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>E35FR</b>	<b>LIFT TRUCK</b>		<b>36 VOLTS , 38.75 X 16.12 X 31.62 Weight Minimum 1925 Connector SB350 GRAY , Position D , Lead Length 009 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>E40FR</b>	<b>LIFT TRUCK</b>		<b>36 VOLTS , 38.88 X 20.60 X 31.62 Weight Minimum 2700 Connector SB350 GRAY , Position D , Lead Length 009 Inches</b>												
	36	060B31	900	31.8	39.63	19.47	31.31	2790	M2101806031B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
<b>E50FR</b>	<b>LIFT TRUCK</b>		<b>36 VOLTS , 38.88 X 20.60 X 31.62 Weight Minimum 2700 Connector SB350 GRAY , Position D , Lead Length 009 Inches</b>												
	36	060B31	900	31.8	39.63	19.47	31.31	2790	M2101806031B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
<b>N30AH</b>	<b>MAN-DOWN</b>		<b>36 VOLTS , 39.87 X 39.76 X 23.15 Weight Minimum 3417 Connector SB350 GRAY , Position B , Lead Length 016 Inches</b>												
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
<b>N30AH</b>	<b>MAN-DOWN</b>		<b>36 VOLTS , 39.87 X 39.76 X 24.57 Weight Minimum 3417 Connector SB350 GRAY , Position B , Lead Length 016 Inches</b>												
	36	085C33	1360	47.5	38.44	38.38	23.25	3816	M1601808533B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F33	1360	47.5	38.44	38.38	23.25	3998	M1501808533B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>N30AH</b>	<b>MAN-DOWN</b>		<b>48 VOLTS , 39.87 X 39.76 X 23.15 Weight Minimum 3417 Connector SB350 BLUE , Position B , Lead Length 016 Inches</b>												
	48	085C25	1020	47.5	38.94	38.38	22.63	3657	M2602408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T25	1200	55.9	38.94	38.38	22.63	3904	M2802410025B	Y	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	085L25	1020	47.5	38.94	38.38	22.63	3850	M2902408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
<b>N30AH</b>	<b>MAN-DOWN</b>		<b>48 VOLTS , 39.87 X 39.76 X 24.57 Weight Minimum 3417 Connector SB350 BLUE , Position B , Lead Length 016 Inches</b>												
	48	085C25	1020	47.5	38.88	38.44	23.25	3851	M1602408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
<b>N25XMDR</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>		<b>24 VOLTS , 38.88 X 14.60 X 31.18 Weight Minimum 1500 Connector SB350 RED , Position B , Lead Length 016 Inches</b>												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
<b>N25XMDR</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>		<b>24 VOLTS , 38.88 X 16.60 X 31.18 Weight Minimum 1600 Connector SB350 RED , Position B , Lead Length 016 Inches</b>												
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>N25XMDR</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N25XMDR</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N25XMDR3</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>N25XMDR3</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1600</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)				
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
<b>N25XMDR3</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N25XMDR3</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N30XMXDR</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 18.80 X 31.50</b>				<b>Weight Minimum 2200</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>N30XMXDR</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 21.10 X 31.50</b>				<b>Weight Minimum 2600</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>N30XMXDR3</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 18.80 X 31.50</b>				<b>Weight Minimum 2200</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>N30XMXDR3</b>	<b>NARROW-AISLE DOUBLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 21.10 X 31.50</b>				<b>Weight Minimum 2600</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>N30XMDR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N30XMDR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 18.75 X 31.18</b>				<b>Weight Minimum 2200</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>N30XMDR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 21.10 X 31.50</b>				<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>N30XMDR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>N30XMDR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 18.75 X 31.18</b>				<b>Weight Minimum 2200</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>N30XMDR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 21.10 X 31.50</b>				<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>N30XMR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 12.50 X 31.18</b>				<b>Weight Minimum 1250</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
<b>N30XMR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>N30XMR2</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 12.50 X 31.18</b>				<b>Weight Minimum 1250</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
<b>N30XMR2</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>N30XMR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 12.50 X 31.18</b>				<b>Weight Minimum 1250</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>N30XMR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>N40XMR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>N40XMR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1600</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)				
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
<b>N40XMR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1550</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N40XMR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N40XMR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>N40XMR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1600</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)				
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>N40XMR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1550</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N40XMR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N45XMR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N45XMR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 18.75 X 31.18</b>				<b>Weight Minimum 2200</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
<b>N45XMR</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 21.12 X 31.18</b>				<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
<b>N45XMR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100C13	600	21.0	38.13	15.63	26.56	1749	M3401810013B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N45XMR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 18.75 X 31.18</b>				<b>Weight Minimum 2200</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>N45XMR3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 21.12 X 31.18</b>				<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>N50XMA</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 12.50 X 31.18</b>				<b>Weight Minimum 1250</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
<b>N50XMA</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>N50XMA</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1600</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)				
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
<b>N50XMA</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1550</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N50XMA</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N50XMA3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 12.50 X 31.18</b>				<b>Weight Minimum 1250</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>N50XMA3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>N50XMA3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>24 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1600</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)				
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
<b>N50XMA3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 14.60 X 31.18</b>				<b>Weight Minimum 1550</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>N50XMA3</b>	<b>NARROW-AISLE REACH TRUCKS</b>											<b>36 VOLTS , 38.88 X 16.60 X 31.18</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>R30XM</b>	<b>ORDER PICKER</b>											<b>24 VOLTS , 38.90 X 14.60 X 30.80</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>R30XM</b>	<b>ORDER PICKER</b>											<b>36 VOLTS , 38.90 X 14.60 X 30.80</b>				<b>Weight Minimum 1800</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>R30XMA</b>	<b>ORDER PICKER</b>											<b>24 VOLTS , 38.90 X 14.60 X 30.80</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
<b>R30XMF</b>	<b>ORDER PICKER</b>		<b>24 VOLTS , 38.90 X 14.60 X 30.80</b>													<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)				(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)				(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)				(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)				(CALL)	(CALL)				
<b>R30ES</b>	<b>ORDERPICKER TRUCKS</b>		<b>24 VOLTS , 36.00 X 13.50 X 24.71</b>													<b>Weight Minimum 1025</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>	
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085F15	595	13.9	35.06	12.88	22.50	1127	M2501208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085C15	595	13.9	35.06	12.88	22.50	1076	M2601208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	100T15	700	16.3	35.06	12.88	22.50	1145	M2801210015A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	085L15	595	13.9	35.06	12.88	22.50	1109	M2901208515A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
<b>R30F</b>	<b>ORDERPICKER TRUCKS</b>		<b>24 VOLTS , 39.00 X 14.60 X 31.50</b>													<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)				(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)				(CALL)	(CALL)				
	24	060B29	840	19.8	38.50	14.19	30.80	1635	M2101206029FB0	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)					
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)				(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)				(CALL)	(CALL)				
<b>R30F</b>	<b>ORDERPICKER TRUCKS</b>		<b>36 VOLTS , 39.00 X 14.60 X 31.50</b>													<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>	
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
<b>R30FA</b>	<b>ORDERPICKER TRUCKS</b>		<b>24 VOLTS , 39.00 X 14.60 X 31.50</b>													<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)				(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)				(CALL)	(CALL)				
	24	060B29	840	19.8	38.50	14.19	30.80	1635	M2101206029FB0	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)					
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)				(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)				(CALL)	(CALL)				
<b>R30FF</b>	<b>ORDERPICKER TRUCKS</b>		<b>24 VOLTS , 39.00 X 14.60 X 31.50</b>													<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)				(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)				(CALL)	(CALL)				
	24	060B29	840	19.8	38.50	14.19	30.80	1635	M2101206029FB0	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)					
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)				(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)				(CALL)	(CALL)				
<b>R30XMS</b>	<b>ORDERPICKER TRUCKS</b>		<b>24 VOLTS , 36.00 X 13.50 X 24.71</b>													<b>Weight Minimum 1025</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>	
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085F15	595	13.9	35.06	12.88	22.50	1127	M2501208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085C15	595	13.9	35.06	12.88	22.50	1076	M2601208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	100T15	700	16.3	35.06	12.88	22.50	1145	M2801210015A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	085L15	595	13.9	35.06	12.88	22.50	1109	M2901208515A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>R30CH</b>	<b>RACKLOADER</b>		<b>36 VOLTS , 39.00 X 23.80 X 999.00</b>													
	36	125C19	1125	39.3	38.31	22.38	31.00	3028	M1601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125C19	1125	39.3	38.44	22.50	31.63	3050	M3401812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
<b>N30FR</b>	<b>REACH TRUCKS</b>		<b>24 VOLTS , 39.00 X 12.50 X 31.50</b>													
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
<b>N30FR</b>	<b>REACH TRUCKS</b>		<b>24 VOLTS , 39.00 X 14.60 X 31.50</b>													
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
<b>N40FR</b>	<b>REACH TRUCKS</b>		<b>24 VOLTS , 39.00 X 14.60 X 31.50</b>													
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
<b>N40FR</b>	<b>REACH TRUCKS</b>		<b>24 VOLTS , 39.00 X 16.60 X 31.50</b>													
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)	
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
<b>N40FR</b>	<b>REACH TRUCKS</b>		<b>36 VOLTS , 39.00 X 14.60 X 31.50</b>													
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>N40FR</b>	<b>REACH TRUCKS</b>		<b>36 VOLTS , 39.00 X 16.60 X 31.50</b>													
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>N45FR</b>	<b>REACH TRUCKS</b>		<b>24 VOLTS , 39.00 X 16.60 X 31.50</b>													
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)	
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
N45FR	REACH TRUCKS		36 VOLTS , 39.00 X 16.60 X 31.50 Weight Minimum 1850 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
N45FR	REACH TRUCKS		36 VOLTS , 39.00 X 18.75 X 31.50 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
N45FR	REACH TRUCKS		36 VOLTS , 39.00 X 21.12 X 31.50 Weight Minimum 2500 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
N45MXR	REACH TRUCKS		36 VOLTS , 39.00 X 18.75 X 31.50 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
N45MXR	REACH TRUCKS		36 VOLTS , 39.00 X 21.12 X 31.50 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
N45MXR3	REACH TRUCKS		36 VOLTS , 39.00 X 18.75 X 31.50 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
N45MXR3	REACH TRUCKS		36 VOLTS , 39.00 X 21.12 X 31.50 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
N50FA	REACH TRUCKS		24 VOLTS , 39.00 X 14.60 X 31.50												
											Weight Minimum 1500	Connector SB350	RED	, Position B , Lead Length 016 Inches	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	( CALL )		SCR200121050T1H	( CALL )	( CALL )
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	( CALL )		SCR200121050T1H	( CALL )	( CALL )
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	( CALL )	SCR20012965S1H	SCR20012965T1H	( CALL )	( CALL )
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	( CALL )		SCR200121200T1H	( CALL )	( CALL )
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	( CALL )		SCR200121050T1H	( CALL )	( CALL )
N50FA	REACH TRUCKS		24 VOLTS , 39.00 X 16.60 X 31.50												
											Weight Minimum 1650	Connector SB350	RED	, Position B , Lead Length 016 Inches	
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	( CALL )		SCR200121200T1H	( CALL )	( CALL )
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	( CALL )		SCR200121200T1H	( CALL )	( CALL )
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	( CALL )		SCR200121200T1H	( CALL )	( CALL )
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	( CALL )		SCR200121450T1H	( CALL )	( CALL )
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	( CALL )		SCR200121200T1H	( CALL )	( CALL )
N50FA	REACH TRUCKS		36 VOLTS , 39.00 X 14.60 X 31.50												
											Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 016 Inches	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
N50FA	REACH TRUCKS		36 VOLTS , 39.00 X 16.60 X 31.50												
											Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 016 Inches	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
E30ER	STAND-UP END CONTROL		36 VOLTS , 38.69 X 16.00 X 32.00												
											Weight Minimum 1925	Connector SB350	GRAY	, Position A , Lead Length 008 Inches	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
E40ER	STAND-UP END CONTROL		36 VOLTS , 38.69 X 20.75 X 32.00												
											Weight Minimum 2700	Connector SB350	GRAY	, Position A , Lead Length 008 Inches	
	36	060B31	900	31.8	39.63	19.47	31.31	2790	M2101806031B7	N	( CALL )		SCR20018965T1H	( CALL )	( CALL )
E50ER	STAND-UP END CONTROL		36 VOLTS , 38.69 X 20.75 X 32.00												
											Weight Minimum 2700	Connector SB350	GRAY	, Position A , Lead Length 008 Inches	
	36	060B31	900	31.8	39.63	19.47	31.31	2790	M2101806031B7	N	( CALL )		SCR20018965T1H	( CALL )	( CALL )
W20XTA	STRADDLE STACKERS		24 VOLTS , 35.40 X 8.12 X 999.00												
											Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches	
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	( CALL )	SCR20012475S1H	SCR20012475T1H	( CALL )	( CALL )
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	( CALL )	SCR20012475S1H	SCR20012475T1H	( CALL )	( CALL )
	24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	( CALL )	SCR20012475S1H	SCR20012475T1H	( CALL )	( CALL )
	24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	( CALL )	SCR20012475S1H	SCR20012475T1H	( CALL )	( CALL )
W20XTA	STRADDLE STACKERS		24 VOLTS , 35.40 X 13.50 X 999.00												
											Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches	
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )
	24	085C13	510	11.9	34.50	12.94	23.25	980	M1601208513A625	N	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>W20XTR</b>	<b>STRADDLE STACKERS</b>														
24 VOLTS , 35.40 X 13.50 X 999.00											Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches	
24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	085C13	510	11.9	34.50	12.94	23.25	980	M1601208513A625	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>W30XTR</b>	<b>STRADDLE STACKERS</b>														
24 VOLTS , 35.40 X 13.50 X 999.00											Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches	
24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	085C13	510	11.9	34.50	12.94	23.25	980	M1601208513A625	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>W30ZA</b>	<b>STRADDLE STACKER</b>														
24 VOLTS , 33.00 X 13.50 X 999.00											Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches	
24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>W30XTA</b>	<b>STRADDLE STACKERS</b>														
24 VOLTS , 35.40 X 8.12 X 999.00											Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches	
24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
<b>W30XTA</b>	<b>STRADDLE STACKERS</b>														
24 VOLTS , 35.40 X 13.50 X 999.00											Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches	
24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	085C13	510	11.9	34.50	12.94	23.25	980	M1601208513A625	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>W40XTA</b>	<b>STRADDLE STACKERS</b>														
24 VOLTS , 35.40 X 8.12 X 999.00											Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches	
24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
<b>W40XTA</b>	<b>STRADDLE STACKERS</b>														
24 VOLTS , 35.40 X 13.50 X 999.00											Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches	
24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	085C13	510	11.9	34.50	12.94	23.25	980	M1601208513A625	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>N30XMH</b>	<b>TURRET TRUCK</b>														
36 VOLTS , 39.87 X 39.76 X 24.41											Weight Minimum 3420	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	(CALL)	SCR200181450T1H	SCR200181450T1H	(CALL)	(CALL)	
36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	(CALL)	SCR200181450T1H	SCR200181450T1H	(CALL)	(CALL)	
36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)	SCR200181700T1H	SCR200181700T1H	(CALL)	(CALL)	
36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)	
<b>N30XMH</b>	<b>TURRET TRUCK</b>														
48 VOLTS , 39.87 X 39.76 X 24.41											Weight Minimum 3420	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
48	085C25	1020	47.5	38.94	38.38	22.63	3657	M2602408525B	N	(CALL)	SCR200241050T1H	SCR200241050T1H	(CALL)	(CALL)	
48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	(CALL)	SCR20024965T1H	SCR20024965T1H	(CALL)	(CALL)	
48	100T25	1200	55.9	38.94	38.38	22.63	3904	M2802410025B	Y	(CALL)	SCR200241200T1H	SCR200241200T1H	(CALL)	(CALL)	
48	085L25	1020	47.5	38.94	38.38	22.63	3850	M2902408525B	N	(CALL)	SCR200241050T1H	SCR200241050T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
V30XMU	TURRET TRUCK		48 VOLTS , 44.76 X 21.65 X 33.46										Weight Minimum 2640	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	125F13	750	34.9	44.13	20.63	30.50	3295	M2502412513B7	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	125C13	750	34.9	44.13	20.63	30.50	3159	M2602412513B7	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	060B23	660	31.0	44.12	21.09	32.00	2725	M2102406023B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	140T13	840	39.1	44.13	20.63	30.50	3312	M2802414013B7	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	125C13	750	34.9	43.00	20.75	31.63	2800	M3402412513K17	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
E100Z	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE		36 VOLTS , 44.10 X 45.70 X 23.15										Weight Minimum 4000	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)	
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)	
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)	
E25Z	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE		36 VOLTS , 34.57 X 27.36 X 24.13										Weight Minimum 1750	Connector SB350	GRAY	, Position A , Lead Length 030 Inches
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
E25Z	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE		36 VOLTS , 35.79 X 27.36 X 24.13										Weight Minimum 1750	Connector SB350	GRAY	, Position A , Lead Length 030 Inches
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
E25Z	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE		48 VOLTS , 34.57 X 27.36 X 24.13										Weight Minimum 1750	Connector SB350	BLUE	, Position A , Lead Length 030 Inches
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
E25Z	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE		48 VOLTS , 35.79 X 27.36 X 24.13										Weight Minimum 1750	Connector SB350	BLUE	, Position A , Lead Length 030 Inches
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
E30Z	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE		36 VOLTS , 34.57 X 27.36 X 24.13										Weight Minimum 1850	Connector SB350	GRAY	, Position A , Lead Length 030 Inches
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
E30Z	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE		36 VOLTS , 35.79 X 27.36 X 24.13										Weight Minimum 1850	Connector SB350	GRAY	, Position A , Lead Length 030 Inches
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
E30Z	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE		48 VOLTS , 34.57 X 27.36 X 24.13										Weight Minimum 1850	Connector SB350	BLUE	, Position A , Lead Length 030 Inches
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	34.00	27.00	23.81	2026	M3402408513A6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
<b>E30Z</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 35.79 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	BLUE , Position A , Lead Length 030 Inches
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
<b>E35Z</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 34.57 X 27.36 X 24.29				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 030 Inches
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
<b>E35Z</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 35.79 X 27.36 X 24.29				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 030 Inches
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
<b>E35Z</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 34.57 X 27.36 X 24.29				Weight Minimum 1850	Connector SB350	BLUE , Position A , Lead Length 030 Inches
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
<b>E35Z</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 35.79 X 27.36 X 24.29				Weight Minimum 1850	Connector SB350	BLUE , Position A , Lead Length 030 Inches
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
<b>E40ZS</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 34.57 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 030 Inches
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
<b>E40ZS</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 35.79 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 030 Inches
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
<b>E40ZS</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 34.57 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	BLUE , Position A , Lead Length 030 Inches
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
<b>E40ZS</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 35.79 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	BLUE , Position A , Lead Length 030 Inches
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
<b>E80Z</b>	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 44.10 X 39.20 X 23.15				Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>E80Z</b>	<b>CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE</b>											<b>36 VOLTS , 45.20 X 39.20 X 24.60</b>				
												Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
<b>E80Z</b>	<b>CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE</b>											<b>48 VOLTS , 44.10 X 39.20 X 23.15</b>				
												Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches		
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027B	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )	
<b>E80Z</b>	<b>CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE</b>											<b>48 VOLTS , 45.20 X 39.20 X 24.60</b>				
												Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches		
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )	
<b>E100XL</b>	<b>CLASS III LOW-LIFT WALKIE PALLET</b>											<b>36 VOLTS , 44.10 X 45.70 X 23.15</b>				
												Weight Minimum 4000	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
<b>E80BS</b>	<b>SIT-DOWN</b>											<b>36 VOLTS , 40.30 X 39.60 X 23.30</b>				
												Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
<b>J40XL</b>	<b>SIT-DOWN FOUR WHEEL - XL</b>											<b>36 VOLTS , 39.87 X 33.15 X 23.15</b>				
												Weight Minimum 2900	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )	
<b>J40XL</b>	<b>SIT-DOWN FOUR WHEEL - XL</b>											<b>36 VOLTS , 39.87 X 33.15 X 24.57</b>				
												Weight Minimum 2900	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	085F27	1105	38.6	38.44	31.62	23.25	3172	M1501808527B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	085C27	1105	38.6	38.44	31.62	23.25	3050	M1601808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	100T27	1300	45.4	38.44	31.62	23.25	3250	M1801810027B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
<b>J40XL</b>	<b>SIT-DOWN FOUR WHEEL - XL</b>											<b>36 VOLTS , 39.87 X 39.76 X 23.15</b>				
												Weight Minimum 3420	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
<b>J40XL</b>	<b>SIT-DOWN FOUR WHEEL - XL</b>											<b>36 VOLTS , 39.87 X 39.76 X 24.57</b>				
												Weight Minimum 3420	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	085C33	1360	47.5	38.44	38.38	23.25	3816	M1601808533B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085F33	1360	47.5	38.44	38.38	23.25	3998	M1501808533B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
<b>J40XL</b>	<b>SIT-DOWN FOUR WHEEL - XL</b>											<b>48 VOLTS , 39.87 X 33.15 X 23.15</b>				
												Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 030 Inches		
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )	
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
J40XL	SIT-DOWN FOUR WHEEL - XL											48 VOLTS , 39.87 X 33.15 X 24.57				Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085F21	850	39.6	38.25	32.75	23.25	3311	M1502408521B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.75	23.25	3180	M1602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.75	23.50	3199	M3402408521K	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	48	100T21	1000	46.6	38.25	32.75	23.25	3405	M1802410021B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
J40XL	SIT-DOWN FOUR WHEEL - XL											48 VOLTS , 39.87 X 39.76 X 23.15				Weight Minimum 3420	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085C25	1020	47.5	38.94	38.38	22.63	3657	M2602408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	100T25	1200	55.9	38.94	38.38	22.63	3904	M2802410025B	Y	(CALL)		SCR200241200T1H	(CALL)	(CALL)			
	48	085L25	1020	47.5	38.94	38.38	22.63	3850	M2902408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
J40XL	SIT-DOWN FOUR WHEEL - XL											48 VOLTS , 39.87 X 39.76 X 24.57				Weight Minimum 3420	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085C25	1020	47.5	38.88	38.44	23.25	3851	M1602408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
J50XL	SIT-DOWN FOUR WHEEL - XL											36 VOLTS , 39.87 X 33.15 X 23.15				Weight Minimum 2900	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
J50XL	SIT-DOWN FOUR WHEEL - XL											36 VOLTS , 39.87 X 33.15 X 24.57				Weight Minimum 2900	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F27	1105	38.6	38.44	31.62	23.25	3172	M1501808527B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C27	1105	38.6	38.44	31.62	23.25	3050	M1601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	100T27	1300	45.4	38.44	31.62	23.25	3250	M1801810027B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
J50XL	SIT-DOWN FOUR WHEEL - XL											36 VOLTS , 39.87 X 39.76 X 23.15				Weight Minimum 3420	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)			
J50XL	SIT-DOWN FOUR WHEEL - XL											36 VOLTS , 39.87 X 39.76 X 24.57				Weight Minimum 3420	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	38.44	38.38	23.25	3816	M1601808533B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085F33	1360	47.5	38.44	38.38	23.25	3998	M1501808533B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
J50XL	SIT-DOWN FOUR WHEEL - XL											48 VOLTS , 39.87 X 33.15 X 23.15				Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
J50XL	SIT-DOWN FOUR WHEEL - XL											48 VOLTS , 39.87 X 33.15 X 24.57				Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085F21	850	39.6	38.25	32.75	23.25	3311	M1502408521B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.75	23.25	3180	M1602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	100T21	1000	46.6	38.25	32.75	23.25	3405	M1802410021B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
J50XL	SIT-DOWN FOUR WHEEL - XL											48 VOLTS , 39.87 X 39.76 X 23.15				Weight Minimum 3420	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085C25	1020	47.5	38.94	38.38	22.63	3657	M2602408525B	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )				
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )				
	48	100T25	1200	55.9	38.94	38.38	22.63	3904	M2802410025B	Y	( CALL )		SCR200241200T1H	( CALL )	( CALL )				
	48	085L25	1020	47.5	38.94	38.38	22.63	3850	M2902408525B	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )				
J50XL	SIT-DOWN FOUR WHEEL - XL											48 VOLTS , 39.87 X 39.76 X 24.57				Weight Minimum 3420	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085C25	1020	47.5	38.88	38.44	23.25	3851	M1602408525C	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )				
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )				
J60XL	SIT-DOWN FOUR WHEEL - XL											36 VOLTS , 39.87 X 39.76 X 23.15				Weight Minimum 3420	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )				
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )				
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )				
J60XL	SIT-DOWN FOUR WHEEL - XL											36 VOLTS , 39.87 X 39.76 X 24.57				Weight Minimum 3420	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	38.44	38.38	23.25	3816	M1601808533B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )				
	36	085F33	1360	47.5	38.44	38.38	23.25	3998	M1501808533B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )				
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )				
J60XL	SIT-DOWN FOUR WHEEL - XL											48 VOLTS , 39.87 X 39.76 X 23.15				Weight Minimum 3420	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085C25	1020	47.5	38.94	38.38	22.63	3657	M2602408525B	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )				
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )				
	48	100T25	1200	55.9	38.94	38.38	22.63	3904	M2802410025B	Y	( CALL )		SCR200241200T1H	( CALL )	( CALL )				
	48	085L25	1020	47.5	38.94	38.38	22.63	3850	M2902408525B	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )				
J60XL	SIT-DOWN FOUR WHEEL - XL											48 VOLTS , 39.87 X 39.76 X 24.57				Weight Minimum 3420	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085C25	1020	47.5	38.88	38.44	23.25	3851	M1602408525C	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )				
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )				
A30XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											24 VOLTS , 32.90 X 19.72 X 26.60				Weight Minimum 1370	Connector SB350	RED	, Position A , Lead Length 009 Inches
	24	085C21	850	19.8	32.88	19.19	22.63	1543	M2601208521C	N	( CALL )	SCR20012965S1H	SCR20012865T1H	( CALL )	( CALL )				
	24	105B19	945	22.2	32.00	19.56	25.46	1800	M2101210519F	N	( CALL )	SCR20012965S1H	SCR20012965T1H	( CALL )	( CALL )				
E100XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 44.10 X 45.70 X 23.15				Weight Minimum 4000	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )				
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )				
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )				
E100XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 44.10 X 45.70 X 23.15				Weight Minimum 4000	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )				
	48	085C29	1190	55.4	44.90	43.00	22.62	4585	M2602408529C25	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )				
E100XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 45.00 X 45.70 X 24.29				Weight Minimum 4000	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085C33	1360	63.3	44.88	44.63	23.25	4976	M1602408533W	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )				
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )				
	48	085C31	1275	59.4	44.63	42.44	22.75	4631	M2602408531W	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
E100XLS	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			36 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3600		Connector SB350	GRAY	, Position B , Lead Length 030 Inches						
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
E100XLS	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			36 VOLTS , 45.00 X 39.20 X 24.29		Weight Minimum 3600		Connector SB350	GRAY	, Position B , Lead Length 030 Inches						
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
E100XLS	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			48 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3600		Connector SB350	BLUE	, Position B , Lead Length 030 Inches						
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
E100XLS	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			48 VOLTS , 45.00 X 39.20 X 24.29		Weight Minimum 3600		Connector SB350	BLUE	, Position B , Lead Length 030 Inches						
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
E100XL2	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			36 VOLTS , 44.10 X 45.70 X 23.15		Weight Minimum 4000		Connector SB350	GRAY	, Position B , Lead Length 030 Inches						
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
E100XL2	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			48 VOLTS , 45.00 X 45.70 X 24.29		Weight Minimum 4000		Connector SB350	BLUE	, Position B , Lead Length 030 Inches						
	48	085C33	1360	63.3	44.88	44.63	23.25	4976	M1602408533W	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
E100XL2S	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			36 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3600		Connector SB350	GRAY	, Position B , Lead Length 030 Inches						
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
E100XL2S	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			36 VOLTS , 45.00 X 39.20 X 24.29		Weight Minimum 3600		Connector SB350	GRAY	, Position B , Lead Length 030 Inches						
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
E100XL2S	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			48 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3600		Connector SB350	BLUE	, Position B , Lead Length 030 Inches						
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
E100XL2S	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			48 VOLTS , 45.00 X 39.20 X 24.29		Weight Minimum 3600		Connector SB350	BLUE	, Position B , Lead Length 030 Inches						
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
E100XL3	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
			48 VOLTS , 45.00 X 45.70 X 24.29		Weight Minimum 4000		Connector SB350	BLUE	, Position B , Lead Length 030 Inches						
	48	085C33	1360	63.3	44.88	44.63	23.25	4976	M1602408533W	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>E100XL3S</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			36 VOLTS , 45.20 X 39.20 X 24.60					36			Weight Minimum 3600	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
<b>E100XL3S</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			48 VOLTS , 45.00 X 39.20 X 24.57					48			Weight Minimum 3400	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	24	100T13	600	14.0	31.50	13.00	23.25	1020	M1801210013A0644	N	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )
	48	100T25	1200	55.9	38.88	38.44	23.12	4150	M2802410025C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )
<b>E100XL3S</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			48 VOLTS , 45.20 X 39.20 X 24.60					48			Weight Minimum 3600	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085C25	1020	47.5	38.88	38.44	23.12	3911	M2602408525C	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	085F25	1020	47.5	38.88	38.44	23.12	4150	M2502408525C	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	085L25	1020	47.5	38.88	38.44	23.12	3958	M2902408525C	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
<b>E100ZS</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			36 VOLTS , 44.10 X 39.20 X 23.15					36			Weight Minimum 3600	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
<b>E100ZS</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			48 VOLTS , 44.10 X 39.20 X 23.15					48			Weight Minimum 3600	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027B	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )
<b>E120XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			36 VOLTS , 44.10 X 45.70 X 23.15					36			Weight Minimum 4230	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )
<b>E120XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			48 VOLTS , 44.10 X 45.70 X 23.15					48			Weight Minimum 4230	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	085C29	1190	55.4	44.90	43.00	22.62	4585	M2602408529C25	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
<b>E120XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			48 VOLTS , 45.00 X 45.70 X 24.29					48			Weight Minimum 4230	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085C33	1360	63.3	44.88	44.63	23.25	4976	M1602408533W	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
<b>E120XL2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			36 VOLTS , 44.10 X 45.70 X 23.15					36			Weight Minimum 4230	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )
<b>E120XL2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>														
			48 VOLTS , 44.10 X 45.70 X 23.15					48			Weight Minimum 4230	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
E120XL2	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	(CALL)	Connector SB350	BLUE	, Position B	, Lead Length 030 Inches
E120XL3	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	(CALL)	Connector SB350	GRAY	, Position B	, Lead Length 030 Inches
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
E120XL3	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	(CALL)	Connector SB350	BLUE	, Position B	, Lead Length 030 Inches
	48	085C29	1190	55.4	44.90	43.00	22.62	4585	M2602408529C25	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	085C31	1275	59.4	44.63	42.44	22.75	4631	M2602408531W	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
E120XL3	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	(CALL)	Connector SB350	BLUE	, Position B	, Lead Length 030 Inches
E120Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	(CALL)	Connector SB350	GRAY	, Position B	, Lead Length 030 Inches
E120Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	(CALL)	Connector SB350	BLUE	, Position B	, Lead Length 030 Inches
	48	085C29	1190	55.4	44.90	43.00	22.62	4585	M2602408529C25	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
E120Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	(CALL)	Connector SB350	GRAY	, Position B	, Lead Length 030 Inches
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
E25XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	Connector SB350	GRAY	, Position A	, Lead Length 020 Inches
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)		SCR20018750S1H	SCR20018750T1H	(CALL) (CALL)
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)		SCR20018750S1H	SCR20018750T1H	(CALL) (CALL)
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)		SCR20018865S1H	SCR20018865T1H	(CALL) (CALL)
E25XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	Connector SB350	GRAY	, Position A	, Lead Length 020 Inches
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)		SCR20018865S1H	SCR20018865T1H	(CALL) (CALL)
E25XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	Connector SB350	BLUE	, Position A	, Lead Length 020 Inches
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)		SCR20024600S1H	SCR20024600T1H	(CALL) (CALL)
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)		SCR20024600S1H	SCR20024600T1H	(CALL) (CALL)
E25XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED														
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	Connector SB350	BLUE	, Position A	, Lead Length 020 Inches
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024600S1H	SCR20024600T1H	(CALL) (CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>E25XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 34.57 X 27.36 X 24.13</b>				<b>Weight Minimum 1750</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 020 Inches</b>	
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>E25XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 35.79 X 27.36 X 24.00</b>				<b>Weight Minimum 1750</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 020 Inches</b>	
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
<b>E25XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 34.57 X 27.36 X 24.13</b>				<b>Weight Minimum 1750</b>	<b>Connector SB350</b>	<b>BLUE , Position A , Lead Length 020 Inches</b>	
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
<b>E25XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 35.79 X 27.36 X 24.00</b>				<b>Weight Minimum 1750</b>	<b>Connector SB350</b>	<b>BLUE , Position A , Lead Length 020 Inches</b>	
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)				
<b>E25XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 34.57 X 27.36 X 24.13</b>				<b>Weight Minimum 1750</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 020 Inches</b>	
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>E25XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 35.79 X 27.36 X 24.00</b>				<b>Weight Minimum 1750</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 020 Inches</b>	
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
<b>E25XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 34.57 X 27.36 X 24.13</b>				<b>Weight Minimum 1750</b>	<b>Connector SB350</b>	<b>BLUE , Position A , Lead Length 020 Inches</b>	
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
<b>E25XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 35.79 X 27.36 X 24.00</b>				<b>Weight Minimum 1750</b>	<b>Connector SB350</b>	<b>BLUE , Position A , Lead Length 020 Inches</b>	
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)				
<b>E30XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 35.16 X 27.32 X 23.15</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 020 Inches</b>	
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
<b>E30XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 35.79 X 27.32 X 24.57</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 020 Inches</b>	
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>E30XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	48 VOLTS , 35.16 X 27.32 X 23.15											Weight Minimum 1850	Connector SB350	BLUE	, Position A , Lead Length 020 Inches	
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
<b>E30XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	48 VOLTS , 35.79 X 27.32 X 24.57											Weight Minimum 1850	Connector SB350	BLUE	, Position A , Lead Length 020 Inches	
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
<b>E30XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	36 VOLTS , 34.57 X 27.36 X 24.13											Weight Minimum 1850	Connector SB350	GRAY	, Position A , Lead Length 020 Inches	
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>E30XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	36 VOLTS , 35.79 X 27.36 X 24.00											Weight Minimum 1850	Connector SB350	GRAY	, Position A , Lead Length 020 Inches	
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
<b>E30XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	48 VOLTS , 34.57 X 27.36 X 24.13											Weight Minimum 1850	Connector SB350	BLUE	, Position A , Lead Length 020 Inches	
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
<b>E30XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	48 VOLTS , 35.79 X 27.36 X 24.00											Weight Minimum 1850	Connector SB350	BLUE	, Position A , Lead Length 020 Inches	
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
<b>E30XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	36 VOLTS , 34.57 X 27.36 X 24.13											Weight Minimum 1850	Connector SB350	GRAY	, Position A , Lead Length 020 Inches	
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>E30XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	36 VOLTS , 35.79 X 27.36 X 24.00											Weight Minimum 1850	Connector SB350	GRAY	, Position A , Lead Length 020 Inches	
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
<b>E30XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	48 VOLTS , 34.57 X 27.36 X 24.13											Weight Minimum 1850	Connector SB350	BLUE	, Position A , Lead Length 020 Inches	
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
<b>E30XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>															
	48 VOLTS , 35.79 X 27.36 X 24.00											Weight Minimum 1850	Connector SB350	BLUE	, Position A , Lead Length 020 Inches	
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>E35XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 35.16 X 27.32 X 23.15</b>				<b>Weight Minimum 2020</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 020 Inches</b>
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C19	765	26.7	34.88	25.81	22.63	2168	M2601808519VA	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
<b>E35XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 35.79 X 27.32 X 24.57</b>				<b>Weight Minimum 2020</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 020 Inches</b>
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
<b>E35XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 35.16 X 27.32 X 23.15</b>				<b>Weight Minimum 2020</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position A , Lead Length 020 Inches</b>
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
<b>E35XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 35.79 X 27.32 X 24.57</b>				<b>Weight Minimum 2020</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position A , Lead Length 020 Inches</b>
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)				
<b>E35XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 34.57 X 27.36 X 24.13</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 020 Inches</b>
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>E35XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 35.79 X 27.36 X 24.00</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 020 Inches</b>
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)				
<b>E35XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 34.57 X 27.36 X 24.13</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position A , Lead Length 020 Inches</b>
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
<b>E35XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 35.79 X 27.36 X 24.00</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position A , Lead Length 020 Inches</b>
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)				
<b>E35XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 34.57 X 27.36 X 24.13</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 020 Inches</b>
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	31.94	26.82	23.82	1980	M3401808517H625	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
E35XM2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 35.79 X 27.36 X 24.00				Weight Minimum 1850	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	105B13	630	22.2	35.00	25.62	22.38	1954	M2101810513K	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
E35XM2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 34.57 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
E35XM2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 35.79 X 27.36 X 24.00				Weight Minimum 1850	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
E40XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 39.87 X 27.32 X 23.15				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
E40XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 39.87 X 27.32 X 24.29				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085C23	935	32.7	38.44	27.00	23.25	2608	M1601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)				
	36	085C23	935	32.7	38.31	27.00	23.25	2640	M1601808523B2	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100T23	1100	38.4	38.44	27.00	23.25	2775	M1801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
E40XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 39.87 X 33.11 X 23.15				Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
E40XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 39.87 X 33.11 X 24.29				Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.62	23.25	3172	M1501808527B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.44	31.62	23.25	3050	M1601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.31	31.50	23.81	3060	M3401808527B2	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.62	23.25	3250	M1801810027B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
E40XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 39.87 X 27.32 X 23.15				Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
E40XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 39.87 X 27.32 X 24.29				Weight Minimum 2300	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085C17	680	31.7	38.31	26.75	23.25	2605	M1602408517B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	100T17	800	37.2	38.31	26.75	23.25	2619	M1802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
E40XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 39.87 X 33.11 X 23.15				Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
E40XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 39.87 X 33.11 X 24.29				Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085F21	850	39.6	38.25	32.75	23.25	3311	M1502408521B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.75	23.25	3180	M1602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	100T21	1000	46.6	38.25	32.75	23.25	3405	M1802410021B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
E40XM	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 34.57 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 020 Inches
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
E40XM	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 35.79 X 27.36 X 24.00				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 020 Inches
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
E40XM	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 34.57 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	BLUE , Position A , Lead Length 020 Inches
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
E40XM	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 35.79 X 27.36 X 24.00				Weight Minimum 1850	Connector SB350	BLUE , Position A , Lead Length 020 Inches
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
E40XM2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 34.57 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 020 Inches
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
E40XM2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 35.79 X 27.36 X 24.00				Weight Minimum 1850	Connector SB350	GRAY , Position A , Lead Length 020 Inches
	36	085C19	765	26.7	35.18	25.81	23.25	2238	M1601808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	100T19	900	31.4	35.18	25.81	23.25	2399	M1801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
E40XM2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 34.57 X 27.36 X 24.13				Weight Minimum 1850	Connector SB350	BLUE , Position A , Lead Length 020 Inches
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>E40XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 35.79 X 27.36 X 24.00</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position A , Lead Length 020 Inches</b>
	48	085C15	595	27.7	35.31	25.50	23.25	2209	M1602408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T15	700	32.6	35.31	25.50	23.25	2380	M1802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
<b>E45XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 33.11 X 23.15</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>E45XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 33.11 X 24.29</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.62	23.25	3172	M1501808527B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.44	31.62	23.25	3050	M1601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.31	31.50	23.81	3060	M3401808527B2	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.62	23.25	3250	M1801810027B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
<b>E45XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.11 X 23.15</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>E45XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.11 X 24.29</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.75	23.25	3311	M1502408521B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.75	23.25	3180	M1602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.75	23.25	3405	M1802410021B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
<b>E45XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>E45XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>E45XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	060B23	660	31.0	38.50	26.93	23.82	2520	M2102406023DB	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>E45XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>E45XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>E45XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>E45XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	060B23	660	31.0	38.50	26.93	23.82	2520	M2102406023DB	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>E45XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>E45Z</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
E45Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 33.15 X 24.41			Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.31	31.50	23.81	3099	M3401808527B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
E45Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED			48 VOLTS , 39.87 X 27.36 X 24.41			Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	060B23	660	31.0	38.50	26.93	23.82	2520	M2102406023DB	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
E45Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED			48 VOLTS , 39.87 X 33.15 X 24.41			Weight Minimum 2900	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.75	23.50	3199	M3402408521K	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
E50XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 27.32 X 23.15			Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
E50XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 27.32 X 24.29			Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085C23	935	32.7	38.44	27.00	23.25	2608	M1601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.31	27.00	23.25	2640	M1601808523B2	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	27.00	23.81	2674	M3401808523B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.44	27.00	23.25	2775	M1801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
E50XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 33.11 X 23.15			Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
E50XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 33.11 X 24.29			Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.62	23.25	3172	M1501808527B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.62	23.25	3050	M1601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.31	31.50	23.81	3060	M3401808527B2	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.62	23.25	3250	M1801810027B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
<b>E50XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 27.32 X 23.15</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>	
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)					
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					
<b>E50XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 27.32 X 24.29</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>	
	48	085C17	680	31.7	38.31	26.75	23.25	2605	M1602408517B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	100T17	800	37.2	38.31	26.75	23.25	2619	M1802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
<b>E50XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.11 X 23.15</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>	
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)					
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
<b>E50XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.11 X 24.29</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>	
	48	085F21	850	39.6	38.25	32.75	23.25	3311	M1502408521B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
	48	085C21	850	39.6	38.25	32.75	23.25	3180	M1602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
	48	100T21	1000	46.6	38.25	32.75	23.25	3405	M1802410021B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)					
<b>E50XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>	
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)					
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)					
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)					
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)					
<b>E50XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>	
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)					
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)					
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)					
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)					
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)					
<b>E50XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>	
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	060B23	660	31.0	38.50	26.93	23.82	2520	M2102406023DB	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)					

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>E50XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>E50XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>E50XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>E50XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	060B23	660	31.0	38.50	26.93	23.82	2520	M2102406023DB	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>E50XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>E50Z</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 27.36 X 24.41</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)				
	36	085C23	935	32.7	38.25	27.00	23.81	2674	M3401808523B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>E50Z</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
E50Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED			48 VOLTS , 39.87 X 27.36 X 24.41			Weight Minimum 2300		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	060B23	660	31.0	38.50	26.93	23.82	2520	M2102406023DB	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.31	26.75	23.81	2675	M3402408517K	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
E50Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED			48 VOLTS , 39.87 X 33.15 X 24.41			Weight Minimum 2900		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
E55XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 27.32 X 23.15			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
E55XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 27.32 X 24.29			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C23	935	32.7	38.44	27.00	23.25	2608	M1601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.31	27.00	23.25	2640	M1601808523B2	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.44	27.00	23.25	2775	M1801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
E55XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 33.11 X 23.15			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
E55XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 33.11 X 24.29			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.62	23.25	3172	M1501808527B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.62	23.25	3050	M1601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.31	31.50	23.81	3060	M3401808527B2	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.62	23.25	3250	M1801810027B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
E55XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			48 VOLTS , 39.87 X 27.32 X 23.15			Weight Minimum 2300		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>E55XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 27.32 X 24.29</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085C17	680	31.7	38.31	26.75	23.25	2605	M1602408517B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100T17	800	37.2	38.31	26.75	23.25	2619	M1802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>E55XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.11 X 23.15</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>E55XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.11 X 24.29</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.75	23.25	3311	M1502408521B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.75	23.25	3180	M1602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.75	23.25	3405	M1802410021B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
<b>E55XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>E55XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
<b>E55XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>E55XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 33.15 X 24.41</b>				<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
E55Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 33.15 X 24.41			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
E55Z	SIT-DOWN FOUR WHEEL COUNTER BALANCED			48 VOLTS , 39.87 X 33.15 X 24.41			Weight Minimum 2900		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.75	23.50	3199	M3402408521K	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
E60XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 33.11 X 23.15			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
E60XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 33.11 X 24.29			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.62	23.25	3172	M1501808527B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.62	23.25	3050	M1601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.31	31.50	23.81	3060	M3401808527B2	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.62	23.25	3250	M1801810027B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
E60XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			48 VOLTS , 39.87 X 33.11 X 23.15			Weight Minimum 2900		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
E60XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED			48 VOLTS , 39.87 X 33.11 X 24.29			Weight Minimum 2900		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.75	23.25	3311	M1502408521B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.75	23.25	3180	M1602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.75	23.25	3405	M1802410021B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
E60XM	SIT-DOWN FOUR WHEEL COUNTER BALANCED			36 VOLTS , 39.87 X 33.15 X 24.41			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>E60XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>			<b>48 VOLTS , 39.87 X 33.15 X 24.41</b>			<b>Weight Minimum 2900</b>		<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
<b>E60XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>			<b>36 VOLTS , 39.87 X 33.15 X 24.41</b>			<b>Weight Minimum 2900</b>		<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>				
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>E60XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>			<b>48 VOLTS , 39.87 X 33.15 X 24.41</b>			<b>Weight Minimum 2900</b>		<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
<b>E60Z</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>			<b>36 VOLTS , 39.87 X 33.15 X 24.41</b>			<b>Weight Minimum 2900</b>		<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>				
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.31	31.50	23.81	3099	M3401808527B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>E60Z</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>			<b>48 VOLTS , 39.87 X 33.15 X 24.41</b>			<b>Weight Minimum 2900</b>		<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
<b>E65XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>			<b>36 VOLTS , 39.87 X 39.76 X 24.41</b>			<b>Weight Minimum 3420</b>		<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>				
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>E65XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>			<b>48 VOLTS , 39.87 X 39.76 X 24.41</b>			<b>Weight Minimum 3420</b>		<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>				
	48	085C25	1020	47.5	38.88	38.44	23.25	3851	M1602408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>E65XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 39.76 X 24.41</b>				<b>Weight Minimum 3420</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>	
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)				
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>E65XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 39.76 X 24.41</b>				<b>Weight Minimum 3420</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>	
	48	085C25	1020	47.5	38.94	38.38	22.63	3657	M2602408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	100T25	1200	55.9	38.94	38.38	22.63	3904	M2802410025B	Y	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	085L25	1020	47.5	38.94	38.38	22.63	3850	M2902408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
<b>E65Z</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 39.76 X 24.41</b>				<b>Weight Minimum 3420</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>	
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085C33	1360	47.5	38.31	38.44	23.81	3791	M3401808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)				
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>E65Z</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 39.76 X 24.41</b>				<b>Weight Minimum 3420</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>	
	48	085C25	1020	47.5	38.94	38.38	22.63	3657	M2602408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	085C25	1020	47.5	38.88	38.44	23.25	3851	M1602408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	100T25	1200	55.9	38.94	38.38	22.63	3904	M2802410025B	Y	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	085L25	1020	47.5	38.94	38.38	22.63	3850	M2902408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
<b>E70XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 44.10 X 39.20 X 23.15</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
<b>E70XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 45.00 X 39.20 X 24.57</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>	
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
<b>E70XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 44.10 X 39.20 X 23.15</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>	
	24	100T13	600	14.0	31.50	13.00	23.25	1020	M1801210013A0644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	48	100T25	1200	55.9	38.88	38.44	23.12	4150	M2802410025C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	24	100T13	600	14.0	31.50	13.00	23.25	1020	M1801210013A0644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	48	100T25	1200	55.9	38.88	38.44	23.12	4150	M2802410025C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	24	100T13	600	14.0	31.50	13.00	23.25	1020	M1801210013A0644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	48	100T25	1200	55.9	38.88	38.44	23.12	4150	M2802410025C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	085L25	1020	47.5	38.88	38.44	23.12	3958	M2902408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>E70XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 45.00 X 39.20 X 24.57</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	24	100T13	600	14.0	31.50	13.00	23.25	1020	M1801210013A0644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	48	100T25	1200	55.9	38.88	38.44	23.12	4150	M2802410025C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)				
<b>E70XL2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 44.10 X 39.20 X 23.15</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
<b>E70XL2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 45.00 X 39.20 X 24.57</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
<b>E70XL2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 44.10 X 39.20 X 23.15</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
<b>E70XL2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 45.00 X 39.20 X 24.57</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)				
<b>E70XL3</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 44.10 X 39.20 X 23.15</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085C29	1190	41.6	43.00	38.50	22.62	3640	M2601808529A76	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
<b>E70XL3</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 44.10 X 39.20 X 23.15</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)				
<b>E70XL3</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 45.20 X 39.20 X 24.57</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)				
<b>E80XL</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 44.10 X 39.20 X 23.15</b>				<b>Weight Minimum 3400</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
E80XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 45.00 X 39.20 X 24.57				Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
E80XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 44.10 X 39.20 X 23.15				Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )			
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
E80XL	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 45.00 X 39.20 X 24.57				Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )			
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )			
E80XL2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 44.10 X 39.20 X 23.15				Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
E80XL2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 45.00 X 39.20 X 24.57				Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
E80XL2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 44.10 X 39.20 X 23.15				Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )			
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027B	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )			
E80XL2	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 45.00 X 39.20 X 24.57				Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )			
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )			
E80XL3	SIT-DOWN FOUR WHEEL COUNTER BALANCED											36 VOLTS , 44.10 X 39.20 X 23.15				Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085C29	1190	41.6	43.00	38.50	22.62	3640	M2601808529A76	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
E80XL3	SIT-DOWN FOUR WHEEL COUNTER BALANCED											48 VOLTS , 44.10 X 39.20 X 23.15				Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )			
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027B	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>E80XL3</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 45.20 X 39.20 X 24.57</b>				
											Weight Minimum 3400	Connector SB350	BLUE	, Position B , Lead Length 030 Inches		
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )	
<b>J40XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 38.80 X 28.30 X 30.90</b>				
											Weight Minimum 3720	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	125C23	1375	48.0	38.50	27.75	30.50	3786	M2601812523B7	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	140T23	1540	53.8	38.50	27.75	30.50	3990	M2801814023B7	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
<b>J40XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 38.80 X 28.30 X 30.90</b>				
											Weight Minimum 3720	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	125C23	1375	48.0	38.50	27.75	30.50	3786	M2601812523B7	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	140T23	1540	53.8	38.50	27.75	30.50	3990	M2801814023B7	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
<b>J50XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 38.80 X 28.30 X 30.90</b>				
											Weight Minimum 3720	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	125C23	1375	48.0	38.50	27.75	30.50	3786	M2601812523B7	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	140T23	1540	53.8	38.50	27.75	30.50	3990	M2801814023B7	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
<b>J50XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 38.80 X 28.30 X 30.90</b>				
											Weight Minimum 3720	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	125C23	1375	48.0	38.50	27.75	30.50	3786	M2601812523B7	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	140T23	1540	53.8	38.50	27.75	30.50	3990	M2801814023B7	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
<b>J60XM</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 38.80 X 33.90 X 30.90</b>				
											Weight Minimum 4456	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	125C25	1500	52.4	38.43	33.31	30.50	4625	M2601812525B725	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
<b>J60XM2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 38.80 X 33.90 X 30.90</b>				
											Weight Minimum 4456	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	125C25	1500	52.4	38.43	33.31	30.50	4625	M2601812525B725	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
<b>N30XMH2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 39.76 X 24.41</b>				
											Weight Minimum 3420	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
<b>N30XMH2</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>48 VOLTS , 39.87 X 39.76 X 24.41</b>				
											Weight Minimum 3420	Connector SB350	BLUE	, Position B , Lead Length 030 Inches		
	48	085C25	1020	47.5	38.88	38.44	23.25	3851	M1602408525C	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )	
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
<b>V30ZMD</b>	<b>SIT-DOWN FOUR WHEEL COUNTER BALANCED</b>											<b>36 VOLTS , 39.87 X 39.76 X 24.41</b>				
											Weight Minimum 3420	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )	
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
V30ZMD	SIT-DOWN FOUR WHEEL COUNTER BALANCED			48 VOLTS , 39.87 X 39.76 X 24.41												
											Weight Minimum 3420	Connector SB350	BLUE	, Position B , Lead Length 030 Inches		
	48	085C25	1020	47.5	38.94	38.38	22.63	3657	M2602408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085C25	1020	47.5	38.88	38.44	23.25	3851	M1602408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	060B31	900	42.3	38.69	38.61	22.50	3605	M2102406031BB781	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	100T25	1200	55.9	38.94	38.38	22.63	3904	M2802410025B	Y	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085L25	1020	47.5	38.94	38.38	22.63	3850	M2902408525B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
J30XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED			36 VOLTS , 39.00 X 16.70 X 23.10												
											Weight Minimum 1300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	085C13	510	17.8	38.00	15.50	22.63	1425	M2601808513B	Y	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
	36	100T13	600	21.0	38.00	15.50	22.63	1516	M2801810013B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
	36	085L13	510	17.8	38.00	15.50	22.63	1452	M2901808513B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
J30XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED			36 VOLTS , 39.00 X 16.70 X 26.10												
											Weight Minimum 1800	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	100C13	600	21.0	38.38	16.06	25.63	1860	M2601810013B7	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
	36	050G21	500	17.6	38.61	16.00	26.00	1890	M8901805021B14	N	(CALL)		SCR20018475T1H	(CALL)	(CALL)	
J30XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED			36 VOLTS , 39.00 X 21.50 X 23.10												
											Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	060B21	600	21.2	38.50	20.75	24.50	2077	M2101806021B7	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
J30XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED			36 VOLTS , 39.00 X 21.50 X 26.10												
											Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	060B25	720	25.4	38.50	20.34	25.69	2130	M2101806025B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
J30XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED			48 VOLTS , 39.00 X 21.50 X 23.10												
											Weight Minimum 1700	Connector SB350	BLUE	, Position B , Lead Length 030 Inches		
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
J30XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED			48 VOLTS , 39.00 X 21.50 X 26.10												
											Weight Minimum 2000	Connector SB350	BLUE	, Position B , Lead Length 030 Inches		
	48	100C13	600	27.9	38.50	20.63	25.63	2201	M2602410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
J30ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED			36 VOLTS , 39.00 X 21.50 X 23.10												
											Weight Minimum 1700	Connector SB350	GRAY	, Position A , Lead Length 025 Inches		
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	060B21	600	21.2	38.50	20.75	24.50	2077	M2101806021B7	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
J30ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED			36 VOLTS , 39.00 X 21.50 X 26.10												
											Weight Minimum 2000	Connector SB350	GRAY	, Position A , Lead Length 025 Inches		
	36	060B25	720	25.4	38.50	20.34	25.69	2130	M2101806025B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
J30ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 21.50 X 23.10				Weight Minimum 1700	Connector SB350	BLUE , Position A , Lead Length 025 Inches
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
J30ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 21.50 X 26.10				Weight Minimum 2000	Connector SB350	BLUE , Position A , Lead Length 025 Inches
	48	100C13	600	27.9	38.50	20.63	25.63	2201	M2602410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
J35XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)			
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
J35XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085C21	850	29.7	38.31	24.56	24.30	2560	M3401808521B72	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
J35XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
J35XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2400	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
J35XMT2	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)			
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
J35XMT2	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085C21	850	29.7	38.31	24.56	24.30	2560	M3401808521B72	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
J35XMT2	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
J35XMT2	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2400	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
J35ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	GRAY	, Position A , Lead Length 025 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
J35ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2500	Connector SB350	GRAY	, Position A , Lead Length 025 Inches
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	085C21	850	29.7	38.31	24.56	24.30	2560	M3401808521B72	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
J35ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	BLUE	, Position A , Lead Length 025 Inches
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
J35ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2500	Connector SB350	BLUE	, Position A , Lead Length 025 Inches
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
J40XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
J40XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
J40XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
J40XMT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2400	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
J40ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	GRAY	, Position A , Lead Length 025 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
J40ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											36 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2500	Connector SB350	GRAY	, Position A , Lead Length 025 Inches
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	085C21	850	29.7	38.31	24.56	24.30	2560	M3401808521B72	N	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				
J40ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 23.10				Weight Minimum 2100	Connector SB350	BLUE	, Position A , Lead Length 025 Inches
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )				
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )				
J40ZT	SIT-DOWN THREE WHEEL COUNTER BALANCED											48 VOLTS , 39.00 X 25.20 X 26.10				Weight Minimum 2500	Connector SB350	BLUE	, Position A , Lead Length 025 Inches
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )				
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )				
J40Z	4 WHEEL SIT DOWN											80 VOLTS , 40.60 X 28.30 X 30.90				Weight Minimum 3720	Connector SBE320	BLACK	, Position A , Lead Length 012 Inches
	80	140T09	560	43.5	40.00	27.50	30.50	3985	M2804014009X7625	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )				
J50Z	4 WHEEL SIT DOWN											80 VOLTS , 40.60 X 28.30 X 30.90				Weight Minimum 3720	Connector SBE320	BLACK	, Position A , Lead Length 012 Inches
	80	125C09	500	38.8	40.00	27.50	30.50	3835	M2604012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )				
	80	125F09	500	38.8	40.00	27.50	30.50	3995	M2504012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )				
	80	125L09	500	38.8	40.00	27.50	30.50	3902	M2904012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )				
	80	140T09	560	43.5	40.00	27.50	30.50	3986	M2804014009X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )				
J50Z	4 WHEEL SIT DOWN											80 VOLTS , 40.60 X 33.90 X 30.90				Weight Minimum 4456	Connector SBE320	BLACK	, Position A , Lead Length 012 Inches
	80	140T11	700	54.3	40.50	33.21	30.50	4674	M2804014011X7625	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )				
	80	125C11	625	48.5	40.05	32.71	30.50	4581	M2604012511X76A	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )				
	80	125F11	625	48.5	40.05	32.71	30.50	4862	M2504012511X76A	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )				
J60Z	4 WHEEL SIT DOWN											80 VOLTS , 40.60 X 33.90 X 30.90				Weight Minimum 4456	Connector SBE320	BLACK	, Position A , Lead Length 012 Inches
	80	140T11	700	54.3	40.50	33.21	30.50	4674	M2804014011X7625	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )				
J65Z	4 WHEEL SIT DOWN											80 VOLTS , 40.60 X 33.90 X 30.90				Weight Minimum 4456	Connector SBE320	BLACK	, Position A , Lead Length 012 Inches
	80	140T11	700	54.3	40.50	33.21	30.50	4674	M2804014011X7625	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)