

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
10BOP	CLASS II ORDER PICKER		36 VOLTS , 38.20 X 14.30 X 31.10 Weight Minimum 1322 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
10BOP	CLASS II ORDER PICKER		48 VOLTS , 38.20 X 14.30 X 31.10 Weight Minimum 1322 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	48	140T07	420	19.6	38.00	11.75	30.50	1590	M2802414007A	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
	48	125L07	375	17.5	38.00	11.75	30.50	1520	M2902412507A	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
	48	125F07	375	17.5	38.00	11.75	30.50	1535	M2502412507A	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
	48	125C07	375	17.5	38.00	11.75	30.50	1480	M2602412507A	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
13BOP	CLASS II ORDER PICKER		36 VOLTS , 38.20 X 16.30 X 31.10 Weight Minimum 1609 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
13BOP	CLASS II ORDER PICKER		48 VOLTS , 38.20 X 16.30 X 31.10 Weight Minimum 1609 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	48	125F09	500	23.3	38.13	14.63	30.50	1882	M2502412509B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125C09	500	23.3	38.13	14.63	30.50	1819	M2602412509B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
15BRP-7	CLASS II REACH TRUCK		36 VOLTS , 38.38 X 17.99 X 30.98 Weight Minimum 2280 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
15BRP-7	CLASS II REACH TRUCK		36 VOLTS , 38.38 X 20.70 X 30.98 Weight Minimum 2280 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
18BRP-7	CLASS II NARROW AISLE REACH		36 VOLTS , 38.38 X 14.25 X 30.98 Weight Minimum 1598 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
18BRP-7	CLASS II NARROW AISLE REACH		36 VOLTS , 38.38 X 16.25 X 30.98 Weight Minimum 1598 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
20BRP-7	CLASS II NARROW AISLE REACH										36 VOLTS , 38.38 X 16.25 X 30.98		Weight Minimum 1878	Connector SB350	GRAY , Position B , Lead Length 020 Inches	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
20BRP-7	CLASS II NARROW AISLE REACH										36 VOLTS , 38.38 X 17.99 X 30.98		Weight Minimum 1878	Connector SB350	GRAY , Position B , Lead Length 020 Inches	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
23BRP-7	CLASS II NARROW AISLE REACH										36 VOLTS , 38.38 X 17.99 X 30.98		Weight Minimum 2280	Connector SB350	GRAY , Position B , Lead Length 020 Inches	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
23BRP-7	CLASS II NARROW AISLE REACH										36 VOLTS , 38.38 X 20.70 X 30.98		Weight Minimum 2280	Connector SB350	GRAY , Position B , Lead Length 020 Inches	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
18BR-7	CLASS II NARROW AISLE MOVING MAST										48 VOLTS , 39.10 X 14.90 X 22.90		Weight Minimum 1230	Connector SB350	GRAY , Position B , Lead Length 036 Inches	
	48	085T09	340	15.8	37.88	14.88	21.63	1430	M2802408509B	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
	48	085C09	340	15.8	38.00	14.58	22.63	1333	M2602408509B37	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
20BR-7	CLASS II NARROW AISLE MOVING MAST										48 VOLTS , 39.10 X 14.90 X 22.90		Weight Minimum 1230	Connector SB350	GRAY , Position B , Lead Length 036 Inches	
	48	085T09	340	15.8	37.88	14.88	21.63	1430	M2802408509B	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
	48	085C09	340	15.8	38.00	14.58	22.63	1333	M2602408509B37	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
25BR-7	CLASS II NARROW AISLE MOVING MAST										48 VOLTS , 39.10 X 14.90 X 22.90		Weight Minimum 1230	Connector SB350	GRAY , Position B , Lead Length 036 Inches	
	48	085T09	340	15.8	37.88	14.88	21.63	1430	M2802408509B	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
	48	085C09	340	15.8	38.00	14.58	22.63	1333	M2602408509B37	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
15BT-7	CLASS I 3 WHEEL COUNTERBALANCED										36 VOLTS , 39.00 X 21.50 X 25.00		Weight Minimum 1565	Connector SB350	GRAY , Position B , Lead Length 018 Inches	
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
15BT-7	CLASS I 3 WHEEL COUNTERBALANCED										48 VOLTS , 39.00 X 21.50 X 25.00		Weight Minimum 1565	Connector SB350	GRAY , Position B , Lead Length 018 Inches	
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
18BT-7	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.00 X 24.80 X 25.00			Weight Minimum 1841		Connector SB350	GRAY	, Position B , Lead Length 018 Inches				
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
18BT-7	CLASS I 3 WHEEL COUNTERBALANCED			48 VOLTS , 39.00 X 24.80 X 25.00			Weight Minimum 1841		Connector SB350	GRAY	, Position B , Lead Length 018 Inches				
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
20BT-7	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.00 X 24.80 X 25.00			Weight Minimum 1841		Connector SB350	GRAY	, Position B , Lead Length 018 Inches				
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
20BT-7	CLASS I 3 WHEEL COUNTERBALANCED			48 VOLTS , 39.00 X 24.80 X 25.00			Weight Minimum 1841		Connector SB350	GRAY	, Position B , Lead Length 018 Inches				
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
16B-7	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.00 X 21.50 X 25.00			Weight Minimum 1565		Connector SB350	GRAY	, Position B , Lead Length 018 Inches				
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
16B-7	CLASS I 3 WHEEL COUNTERBALANCED			48 VOLTS , 39.00 X 21.50 X 25.00			Weight Minimum 1565		Connector SB350	GRAY	, Position B , Lead Length 018 Inches				
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
18B-7	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.00 X 24.80 X 25.00			Weight Minimum 1841		Connector SB350	GRAY	, Position B , Lead Length 018 Inches				
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
18B-7	CLASS I 3 WHEEL COUNTERBALANCED			48 VOLTS , 39.00 X 24.80 X 25.00			Weight Minimum 1841		Connector SB350	GRAY	, Position B , Lead Length 018 Inches				
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
20BC-7	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.76 X 30.55 X 23.62				Weight Minimum 2490	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
20BC-7	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.76 X 30.55 X 23.62				Weight Minimum 2490	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
25BC-7	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.76 X 30.55 X 23.62				Weight Minimum 2490	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100C25	1200	41.9	38.50	29.50	25.63	3231	M2601810025B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
25BC-7	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.76 X 30.55 X 23.62				Weight Minimum 2490	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
30BC-7	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.76 X 34.49 X 23.62				Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
30BC-7	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.76 X 30.55 X 23.62				Weight Minimum 3086	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
32BC-7	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 39.76 X 34.49 X 23.62				Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
32BC-7	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 39.76 X 30.55 X 23.62				Weight Minimum 3086	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
22B-7	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 42.13 X 31.73 X 21.26				Weight Minimum 2292	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	36	060C27	780	27.2	38.25	31.50	19.13	2512	M2601806027C7	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)			
22B-7	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 42.13 X 31.73 X 21.26				Weight Minimum 2292	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	48	105B13	630	29.6	35.55	31.39	20.78	2455	M2102410513E81	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
25B-7	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 42.13 X 31.73 X 21.26				Weight Minimum 2425	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	36	060C27	780	27.2	38.25	31.50	19.13	2512	M2601806027C7	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
25B-7	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 42.13 X 31.73 X 21.26				Weight Minimum 2425	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	48	105B13	630	29.6	35.55	31.39	20.78	2455	M2102410513E81	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
30B-7	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 42.13 X 39.37 X 21.26				Weight Minimum 2800	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	36	060C33	960	33.5	38.38	38.44	18.13	2828	M2601806033B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
30B-7	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 42.13 X 39.37 X 21.26				Weight Minimum 2800	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	48	060C27	780	36.3	41.75	38.44	18.50	3072	M2602406027C	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
32B-7	CLASS I 4 WHEEL COUNTERBALANCED											36 VOLTS , 42.13 X 39.37 X 21.26				Weight Minimum 2800	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	36	060C33	960	33.5	38.38	38.44	18.13	2828	M2601806033B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
32B-7	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 42.13 X 39.37 X 21.26				Weight Minimum 2800	Connector SB350	GRAY , Position B , Lead Length 018 Inches
	48	060C27	780	36.3	41.75	38.44	18.50	3072	M2602406027C	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
35B-7	CLASS I 4 WHEEL COUNTERBALANCED											80 VOLTS , 40.67 X 33.82 X 31.10				Weight Minimum 3925	Connector SBE320	BLACK , Position B , Lead Length 030 Inches
	80	140T11	700	54.3	40.25	33.00	30.50	4310	M2804014011X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125L11	625	48.5	40.25	33.10	30.50	4375	M2904012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125F11	625	48.5	40.25	33.00	30.50	4312	M2504012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125C11	625	48.5	40.25	33.00	30.50	4031	M2604012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
40B-7	CLASS I 4 WHEEL COUNTERBALANCED											80 VOLTS , 40.67 X 39.53 X 31.10				Weight Minimum 4620	Connector SBE320	BLACK , Position B , Lead Length 030 Inches
	80	140T13	840	65.2	40.35	39.21	30.28	5073	M2804014013X	N	(CALL)		SCR20040865T1H	(CALL)	(CALL)			
	80	125L13	750	58.2	40.35	39.21	30.28	4777	M2904012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125F13	750	58.2	40.35	39.21	30.28	5025	M2504012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			
	80	125C13	750	58.2	40.35	39.21	30.28	4751	M2604012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
45B-7	CLASS I 4 WHEEL COUNTERBALANCED			80 VOLTS , 40.67 X 39.53 X 31.10 Weight Minimum 4620 Connector SBE320 BLACK , Position B , Lead Length 030 Inches											
	80	140T13	840	65.2	40.35	39.21	30.28	5073	M2804014013X	N	(CALL)		SCR20040865T1H	(CALL)	(CALL)
	80	125L13	750	58.2	40.35	39.21	30.28	4777	M2904012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125F13	750	58.2	40.35	39.21	30.28	5025	M2504012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125C13	750	58.2	40.35	39.21	30.28	4751	M2604012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
50B-7	CLASS I 4 WHEEL COUNTERBALANCED			80 VOLTS , 40.67 X 39.53 X 31.10 Weight Minimum 4620 Connector SBE320 BLACK , Position B , Lead Length 030 Inches											
	80	140T13	840	65.2	40.35	39.21	30.28	5073	M2804014013X	N	(CALL)		SCR20040865T1H	(CALL)	(CALL)
	80	125L13	750	58.2	40.35	39.21	30.28	4777	M2904012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125F13	750	58.2	40.35	39.21	30.28	5025	M2504012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125C13	750	58.2	40.35	39.21	30.28	4751	M2604012513X	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
22BHA	CLASS I 4 WHEEL COUNTERBALANCED			80 VOLTS , 40.35 X 27.87 X 30.86 Weight Minimum 3234 Connector SBE320 BLACK , Position B , Lead Length 018 Inches											
	80	125L09	500	38.8	40.00	27.50	30.50	3520	M2904012509X76	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)
	80	125F09	500	38.8	40.00	27.50	30.50	3579	M2504012509X50	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)
	80	125C09	500	38.8	40.00	27.50	30.50	3369	M2604012509X76	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)
	80	125C09	500	38.8	40.40	27.75	30.50	3458	M2604012509X50	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)
25BHA-7	CLASS I 4 WHEEL COUNTERBALANCED			80 VOLTS , 40.35 X 27.87 X 30.86 Weight Minimum 3234 Connector SBE320 BLACK , Position B , Lead Length 018 Inches											
	80	140T09	560	43.5	40.00	27.50	30.50	3985	M2804014009X7625	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)
	80	125L09	500	38.8	40.00	27.50	30.50	3520	M2904012509X76	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)
	80	125F09	500	38.8	40.00	27.50	30.50	3579	M2504012509X50	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)
	80	125C09	500	38.8	40.00	27.50	30.50	3369	M2604012509X76	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)
	80	125C09	500	38.8	40.40	27.75	30.50	3458	M2604012509X50	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)
30BHA-7	CLASS I 4 WHEEL COUNTERBALANCED			80 VOLTS , 40.35 X 33.54 X 30.86 Weight Minimum 3925 Connector SBE320 BLACK , Position B , Lead Length 018 Inches											
	80	140T11	700	54.3	40.25	33.00	30.50	4310	M2804014011X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125L11	625	48.5	40.25	33.10	30.50	4375	M2904012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125F11	625	48.5	40.25	33.00	30.50	4312	M2504012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
	80	125C11	625	48.5	40.25	33.00	30.50	4031	M2604012511X76	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)