

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
EJE120/EJE225,NO COVER	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)										24 VOLTS , 25.74 X 9.37 X 26.57		Weight Minimum 155	Connector SB175	GRAY	, Position B , Lead Length 018 Inches
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085C07	255	5.9	25.38	8.69	23.25	570	M1601208507D44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	MSB	195	.0	25.25	8.50	25.26	400	M90004S24CHPTM	N	(CALL)			(CALL)	(CALL)	
EJE120E,NO COVER	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)										24 VOLTS , 32.28 X 9.37 X 26.57		Weight Minimum 375	Connector SB175	GRAY	, Position B , Lead Length 018 Inches
	24	100T07	300	7.0	31.75	8.90	23.25	550	M1801210007D00644	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	31.75	8.90	23.25	550	M1901208507D00644	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085F07	255	5.9	31.75	8.90	23.25	635	M1501208507D00644	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C07	255	5.9	31.75	8.90	23.25	525	M1601208507D00644	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
EJE120/EJE225,WITH COVER	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)										24 VOLTS , 25.74 X 9.37 X 23.62		Weight Minimum 155	Connector SB175	GRAY	, Position B , Lead Length 018 Inches
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085C07	255	5.9	25.38	8.69	23.25	570	M1601208507D44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
EJE225E	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)										24 VOLTS , 32.00 X 13.58 X 31.29		Weight Minimum 948	Connector SB175	GRAY	, Position B , Lead Length 018 Inches
	24	140T13	840	19.6	31.50	13.00	31.00	1400	M1801214013A0644	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	31.50	13.00	23.25	1020	M1901208513A0644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	31.50	13.00	31.00	1352	M1901212513A0644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	31.50	13.00	23.25	1010	M1501208513A0644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	31.50	13.00	31.00	1428	M1501212513A00644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	31.50	13.00	23.25	995	M1601208513A0644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	31.50	13.00	31.00	1372	M1601212513A00644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
ECR327/336	CLASS III LOW-LIFT WALKIE RIDER/PALLET										24 VOLTS , 32.00 X 13.58 X 31.29		Weight Minimum 933	Connector SB175	GRAY	, Position A , Lead Length 018 Inches
	24	140T13	840	19.6	31.50	13.00	31.00	1408	M1801214013A00644	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	31.50	13.00	23.25	1035	M1801210013A00644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	31.50	13.00	31.00	1372	M1901212513A00644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	31.50	13.00	23.25	1012	M1501208513A00644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	31.50	13.00	31.00	1428	M1501212513A00644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	31.50	13.00	23.25	979	M1601208513A00644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	31.50	13.00	31.00	1372	M1601212513A00644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
EZS350NA	CLASS III TOW TRACTOR										24 VOLTS , 31.49 X 13.11 X 30.90		Weight Minimum 1025	Connector SB175	GRAY	, Position B , Lead Length 018 Inches
	24	125C13	750	17.5	30.82	12.81	30.25	1380	M2601212513A5944	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.81	30.25	1051	M2601208513A5944	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
EZS570NA	CLASS III TOW TRACTOR										48 VOLTS , 32.16 X 16.20 X 24.70		Weight Minimum 1210	Connector REMA320	BLACK	, Position A , Lead Length 016 Inches
	48	100T07	300	14.0	32.00	15.50	23.00	1357	M2802410007Z5044	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
	48	085L07	255	11.9	32.00	15.50	23.00	1297	M2902408507Z5044	N	(CALL)	SCR20024260S1H		(CALL)	(CALL)	
	48	085F07	255	11.9	32.00	15.50	23.00	1307	M2502408507Z5044	N	(CALL)	SCR20024260S1H		(CALL)	(CALL)	
	48	085C07	255	11.9	32.00	15.50	23.00	1263	M2602408507Z5044	N	(CALL)	SCR20024260S1H		(CALL)	(CALL)	
EJCB12	CLASS III WALKIE STACKER										24 VOLTS , 25.70 X 8.35 X 27.36		Weight Minimum 523	Connector SB175	GRAY	, Position A , Lead Length 032 Inches
	24	100T05	200	4.7	25.25	7.81	22.63	540	M2801210005G744	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L05	170	4.0	25.25	7.81	22.63	523	M2901208505G744	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085F05	170	4.0	25.25	7.80	22.63	527	M2501208505G744	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C05	170	4.0	25.25	7.81	22.63	514	M2601208505G744	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
EJC14/B16	CLASS III WALKIE HIGHLIFT STRADDLE										24 VOLTS , 25.70 X 11.50 X 27.36	Weight Minimum 536	Connector SB175	GRAY	, Position A , Lead Length 032 Inches	
	24	100T09	400	9.3	25.27	10.88	22.63	743	M2801210009D44A	N	(CALL)			(CALL)	(CALL)	
	24	085L09	340	7.9	25.27	10.88	22.63	713	M2901208509D44A	N	(CALL)			(CALL)	(CALL)	
	24	085F09	340	7.9	25.27	10.88	22.63	720	M2501208509D44A	N	(CALL)			(CALL)	(CALL)	
	24	085C09	340	7.9	25.27	10.88	22.63	696	M2601208509D44A	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
EJC214/216	CLASS III FORK-OVER WALKIE HIGHLIFT STRADDLE										24 VOLTS , 24.92 X 11.50 X 27.36	Weight Minimum 635	Connector SB175	GRAY	, Position A , Lead Length 018 Inches	
	24	100T07	300	7.0	24.00	10.25	22.63	690	M2801210007T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100T07	300	7.0	24.00	10.25	22.63	690	M2801210007T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	24.00	10.25	23.63	667	M2901208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	24.00	10.25	23.63	667	M2901208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085F07	255	5.9	24.00	10.25	22.63	672	M2501208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C07	255	5.9	24.00	10.25	22.63	462	M2601208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
EKS110	CLASS II ORDER PICKER										24 VOLTS , 25.00 X 14.00 X 30.87	Weight Minimum 1047	Connector EBC160	BLACK	, Position A , Lead Length 016 Inches	
	24	125C09	500	11.6	24.50	14.00	30.50	1129	M2601212509A44	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
EKS208	CLASS II ORDER PICKER										24 VOLTS , 33.27 X 17.72 X 32.17	Weight Minimum 2000	Connector EBC320	BLACK	, Position B , Lead Length 016 Inches	
	24	140T13	840	19.6	32.75	17.13	30.50	2150	M2801214013A7D44	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	32.75	17.13	30.50	2105	M2501212513A7D44	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
EKS208	CLASS II ORDER PICKER										48 VOLTS , 33.27 X 17.72 X 32.17	Weight Minimum 2000	Connector REMA320	BLACK	, Position AB , Lead Length 025 Inches	
	48	140T09	560	26.1	33.10	17.10	30.50	2121	M2802414009SB44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	125L09	500	23.3	33.10	17.10	30.50	2046	M2902412509SB44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
EKS308	CLASS II ORDER PICKER										24 VOLTS , 37.20 X 21.26 X 32.17	Weight Minimum 2000	Connector EBC320	BLACK	, Position A , Lead Length 025 Inches	
	24	140T17	1120	26.1	36.25	20.63	30.50	2163	M2801214017C744	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	36.25	20.63	30.50	2104	M2501212517C744	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
EKS308	CLASS II ORDER PICKER										36 VOLTS , 37.20 X 21.26 X 32.17	Weight Minimum 2000	Connector EBC320	BLACK	, Position A , Lead Length 025 Inches	
	36	140T13	840	29.3	36.19	19.25	30.50	2151	M2801814013A6A44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	36.19	19.25	30.05	2179	M2501812513A6A44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EKS308	CLASS II ORDER PICKER										48 VOLTS , 21.26 X 37.20 X 32.17	Weight Minimum 2000	Connector EBC320	BLACK	, Position AB , Lead Length 025 Inches	
	48	140T09	560	26.1	36.25	20.50	30.50	2125	M2802414009M644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	125L09	500	23.3	36.25	20.50	30.50	2030	M2902412509M644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
ETR130/135/140	CLASS II NARROW AISLE REACH										24 VOLTS , 38.60 X 14.25 X 31.65	Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 025 Inches	
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
ETR130/135/140	CLASS II NARROW AISLE REACH										24 VOLTS , 38.60 X 16.25 X 31.65	Weight Minimum 2000	Connector SB350	RED	, Position B , Lead Length 025 Inches	
	24	140T19	1260	29.3	38.19	15.00	30.50	2054	M2801214019B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L19	1125	26.2	38.19	15.00	30.50	1963	M2901212519B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2084	M2501212519B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
ETR230	CLASS II NARROW AISLE REACH											36 VOLTS , 38.60 X 14.25 X 31.65				Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T11	700	24.4	38.01	13.25	30.50	1765	M2801814011B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125L11	625	21.8	38.00	13.25	30.50	1720	M2901812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1759	M2501812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.01	13.25	30.50	1692	M2601812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ETR230/235/340/340P/345/345P	CLASS II NARROW AISLE REACH											36 VOLTS , 38.60 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
ETR235/340/340P/345/345P	CLASS II NARROW AISLE REACH											36 VOLTS , 38.60 X 18.25 X 31.65				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
ETR340/340P/345/345P	CLASS II NARROW AISLE REACH											36 VOLTS , 38.60 X 21.25 X 31.65				Weight Minimum 2600	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
ETR125D	CLASS II DOUBLE REACH											24 VOLTS , 38.60 X 14.25 X 31.65				Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 025 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
ETR125D	CLASS II NARROW AISLE STRADDLE											24 VOLTS , 38.60 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	24	140T19	1260	29.3	38.19	15.00	30.50	2054	M2801214019B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L19	1125	26.2	38.19	15.00	30.50	1963	M2901212519B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
ETR225D	CLASS II DOUBLE REACH											36 VOLTS , 38.60 X 14.25 X 31.65				Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T11	700	24.4	38.01	13.25	30.50	1765	M2801814011B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1759	M2501812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.01	13.25	30.50	1692	M2601812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ETR225D/230D/230DP	CLASS II DOUBLE REACH											36 VOLTS , 38.60 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ETR230D/230DP	CLASS II DOUBLE REACH											36 VOLTS , 38.60 X 18.25 X 31.65				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



Jungheinrich Lift Trucks 2012 Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ETR230D/230DP	CLASS II DOUBLE REACH		36 VOLTS , 38.60 X 21.25 X 31.65 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ETV110/112	CLASS II NARROW AISLE REACH		48 VOLTS , 40.75 X 13.90 X 30.87 Weight Minimum 1562 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T07	420	19.6	40.25	13.25	30.50		M2802414007A644	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
	48	125L07	375	17.5	40.25	13.25	30.50		M2902412507A644	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
	48	125C07	375	17.5	40.25	13.25	30.50	1608	M2602412507A644	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
ETV110/112	CLASS II NARROW AISLE REACH		48 VOLTS , 40.75 X 17.49 X 30.87 Weight Minimum 1962 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T09	560	26.1	40.25	17.00	30.50	2223	M2802414009B44A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125L09	500	23.3	40.25	17.00	30.50	2141	M2902412509B44A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125C09	500	23.3	40.25	17.00	30.50	2098	M2602412509B44A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ETV214/216	CLASS II NARROW AISLE REACH		48 VOLTS , 48.15 X 13.97 X 30.87 Weight Minimum 1967 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T09	560	26.1	47.25	13.50	30.50	2151	M2802414009Y44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125L09	500	23.3	47.25	13.50	30.50	2195	M2902412509Y44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125C09	500	23.3	47.25	13.50	30.50	2101	M2602412509Y44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ETV214/216	CLASS II NARROW AISLE REACH		48 VOLTS , 48.15 X 16.81 X 30.87 Weight Minimum 2344 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	125C11	625	29.1	47.25	16.25	30.50	2496	M2602412511U44	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
ETVC16&20/Q20&25/320&325	CLASS II NARROW AISLE REACH		48 VOLTS , 48.15 X 14.10 X 30.87 Weight Minimum 1967 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T09	560	26.1	47.25	13.50	30.50	2151	M2802414009Y44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125L09	500	23.3	47.25	13.50	30.50	2195	M2902412509Y44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125C09	500	23.3	47.25	13.50	30.50	2101	M2602412509Y44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ETVC16&20/Q20&25/320&325	CLASS II NARROW AISLE REACH		48 VOLTS , 48.15 X 16.90 X 30.87 Weight Minimum 2344 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	125C11	625	29.1	47.25	16.25	30.50	2496	M2602412511U44	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
ETVQ20&25/320&325	CLASS II NARROW AISLE REACH		48 VOLTS , 48.15 X 19.76 X 30.87 Weight Minimum 2736 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T13	840	39.1	47.25	19.16	30.50	2987	M2802414013E644	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	125C13	750	34.9	47.25	19.16	30.50	2883	M2602412513E644	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
ETM214/216	CLASS II NARROW AISLE REACH		48 VOLTS , 40.75 X 13.89 X 30.87 Weight Minimum 1560 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T07	420	19.6	40.25	13.25	30.50		M2802414007A644	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
	48	125L07	375	17.5	40.25	13.25	30.50		M2902412507A644	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
	48	125C07	375	17.5	40.25	13.25	30.50	1608	M2602412507A644	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
ETM214/216	CLASS II NARROW AISLE REACH		48 VOLTS , 40.75 X 17.44 X 30.87 Weight Minimum 1962 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T09	560	26.1	40.25	17.00	30.50	2223	M2802414009B44A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125L09	500	23.3	40.25	17.00	30.50	2141	M2902412509B44A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125C09	500	23.3	40.25	17.00	30.50	2098	M2602412509B44A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ETM214/216	CLASS II NARROW AISLE REACH		48 VOLTS , 40.75 X 20.98 X 30.87 Weight Minimum 2344 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T13	840	39.1	40.25	20.62	30.50	2989	M2802414013B644	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	125L13	750	34.9	40.25	20.62	30.50	2872	M2902412513B644	N	(CALL)			(CALL)	(CALL)
	48	125F13	750	34.9	40.25	20.62	30.50	2822	M2502412513B644	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100C13	600	27.9	40.25	20.62	30.50	2380	M2602410013B644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ETM320/325	CLASS II NARROW AISLE REACH		48 VOLTS , 40.75 X 17.49 X 30.87 Weight Minimum 1962 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T09	560	26.1	40.25	17.00	30.50	2223	M2802414009B44A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125L09	500	23.3	40.25	17.00	30.50	2141	M2902412509B44A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	125C09	500	23.3	40.25	17.00	30.50	2098	M2602412509B44A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ETM320/325	CLASS II NARROW AISLE REACH		48 VOLTS , 40.75 X 21.10 X 30.87 Weight Minimum 2334 Connector EBC320 BLACK , Position A , Lead Length 025 Inches												
	48	140T13	840	39.1	40.25	20.62	30.50	2989	M2802414013B644	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	125L13	750	34.9	40.25	20.62	30.50	2872	M2902412513B644	N	(CALL)			(CALL)	(CALL)
	48	125F13	750	34.9	40.25	20.62	30.50	2822	M2502412513B644	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100C13	600	27.9	40.25	20.62	30.50	2380	M2602410013B644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ETB130/140	CLASS II NARROW AISLE STRADDLE		24 VOLTS , 38.60 X 14.25 X 31.65 Weight Minimum 1600 Connector SB350 RED , Position B , Lead Length 025 Inches												
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
ETB130/140	CLASS II NARROW AISLE STRADDLE		24 VOLTS , 38.60 X 16.25 X 31.65 Weight Minimum 2000 Connector SB350 RED , Position B , Lead Length 025 Inches												
	24	125F19	1125	26.2	38.19	15.00	30.50	2084	M2501212519B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
ETB230	CLASS II NARROW AISLE STRADDLE		36 VOLTS , 38.60 X 14.25 X 31.65 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	140T11	700	24.4	38.01	13.25	30.50	1765	M2801814011B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1720	M2901812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1759	M2501812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1692	M2601812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ETB230/340	CLASS II NARROW AISLE STRADDLE		36 VOLTS , 38.60 X 16.25 X 31.65 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ETB340	CLASS II NARROW AISLE STRADDLE		36 VOLTS , 38.60 X 18.25 X 31.65 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.31	17.88	30.50	2367	M2901812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EKX410	CLASS II VERY NARROW AISLE (TURRET)		48 VOLTS , 42.13 X 25.24 X 27.28 Weight Minimum 2116 Connector EBC320 BLACK , Position B , Lead Length 016 Inches												
	48	085L15	595	27.7	40.00	24.00	24.00	2288	M2902408515B644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	40.00	24.00	24.00	2193	M2602408515B644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
EKX513	CLASS II VERY NARROW AISLE (TURRET)											80 VOLTS , 42.13 X 24.33 X 36.02				Weight Minimum 2593	Connector EBC320	BLACK	, Position B , Lead Length 016 Inches
	80	140T09	560	43.5	40.56	23.58	30.50	3336	M2804014009JX44	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125L09	500	38.8	40.56	23.58	30.50	3138	M2904012509JX44	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125C09	500	38.8	41.00	24.00	30.50	3100	M2604012509JX44	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
EKX515K	CLASS II VERY NARROW AISLE (TURRET)											80 VOLTS , 42.13 X 28.27 X 36.02				Weight Minimum 3263	Connector EBC320	BLACK	, Position B , Lead Length 016 Inches
	80	140T11	700	54.3	41.25	27.75	30.28		M2804014011AH644	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125L11	625	48.5	41.25	27.75	30.28		M2904012511AH644	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125F11	625	48.5	41.25	27.75	30.28	3895	M2504012511AH644	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125C11	625	48.5	41.25	27.75	30.28	3700	M2604012511AH644	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
EKX515	CLASS II VERY NARROW AISLE (TURRET)											80 VOLTS , 42.13 X 39.92 X 36.02				Weight Minimum 4561	Connector EBC320	BLACK	, Position B , Lead Length 016 Inches
	80	140T15	980	76.0	41.00	39.38	30.50	5713	M2804014015K44	N	(CALL)			(CALL)	(CALL)				
	80	125L15	875	67.9	41.00	39.38	30.50	5475	M2904012515K44	N	(CALL)			(CALL)	(CALL)				
	80	125C15	875	67.9	41.00	39.38	30.50	5332	M2604012515K44	N	(CALL)		SCR20040865T1H	(CALL)	(CALL)				
EFX410/413	CLASS II VERY NARROW AISLE (TURRET)											48 VOLTS , 42.13 X 25.24 X 24.69				Weight Minimum 2116	Connector EBC320	BLACK	, Position B , Lead Length 016 Inches
	48	100T15	700	32.6	40.00	24.00	24.00	2326	M2802410015B644	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085L15	595	27.7	40.00	24.00	24.00	2288	M2902408515B644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	40.00	24.00	24.00	2193	M2602408515B644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
EFG110K	CLASS I 3 WHEEL COUNTERBALANCED											24 VOLTS , 32.68 X 10.75 X 24.68				Weight Minimum 779	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	24	100T09	400	9.3	32.56	10.50	22.63	905	M2801210009P44	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	100T11	500	11.6	32.60	10.75	22.62	879	M2801210011J44	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
EFG110	CLASS I 3 WHEEL COUNTERBALANCED											24 VOLTS , 32.68 X 12.87 X 24.68				Weight Minimum 932	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	24	100T13	600	14.0	32.63	12.88	22.63	1070	M2801210013A7B44	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100T13	600	14.0	32.63	12.88	22.63	1070	M2801210013A7B44	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085C13	510	11.9	32.63	12.88	22.63	982	M2601208513A7B44	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
EFG113	CLASS I 3 WHEEL COUNTERBALANCED											24 VOLTS , 32.68 X 17.13 X 24.69				Weight Minimum 1257	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	24	100T13	600	14.0	32.56	16.88	22.63	1320	M2801210013A76	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085L13	510	11.9	32.56	16.88	22.63	1294	M2901208513A76	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
EFG115	CLASS I 3 WHEEL COUNTERBALANCED											24 VOLTS , 32.68 X 19.25 X 24.68				Weight Minimum 1416	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	24	085C21	850	19.8	32.63	19.19	22.63	1551	M2601208521C44	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)				
EFG213/215	CLASS I 3 WHEEL COUNTERBALANCED											48 VOLTS , 32.68 X 20.55 X 24.69				Weight Minimum 1483	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	48	100T09	400	18.6	32.56	20.38	23.38	1615	M2802410009Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
EFG216K/218K	CLASS I 3 WHEEL COUNTERBALANCED											48 VOLTS , 32.68 X 24.80 X 24.69				Weight Minimum 1793	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	48	100T11	500	23.3	32.00	24.38	22.62	1942	M2802410011Z6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085L11	425	19.8	32.00	24.38	22.62	1878	M2902408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085F11	425	19.8	32.00	24.38	22.62	1949	M2502408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085C11	425	19.8	32.00	24.50	22.62	1835	M2602408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
EFG216/218/220	CLASS I 3 WHEEL COUNTERBALANCED											48 VOLTS , 32.68 X 29.06 X 24.69				Weight Minimum 2122	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	48	100T13	600	27.9	32.56	28.88	22.63	2386	M2802410013Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085L13	510	23.7	32.75	29.00	22.62	2303	M2902408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C13	510	23.7	32.63	29.00	22.63	2253	M2602408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
EFG316K/318K	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 32.68 X 24.80 X 24.69				Weight Minimum 1793	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	48	100T11	500	23.3	32.00	24.38	22.62	1942	M2802410011Z6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085L11	425	19.8	32.00	24.38	22.62	1878	M2902408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085F11	425	19.8	32.00	24.38	22.62	1949	M2502408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	085C11	425	19.8	32.00	24.50	22.62	1835	M2602408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
EFG316/318/320	CLASS I 4 WHEEL COUNTERBALANCED											48 VOLTS , 32.68 X 29.06 X 24.69				Weight Minimum 2122	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	48	100T13	600	27.9	32.56	28.88	22.63	2386	M2802410013Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085L13	510	23.7	32.75	29.00	22.62	2303	M2902408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C13	510	23.7	32.63	29.00	22.63	2253	M2602408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
EFG425K	CLASS I 4 WHEEL COUNTERBALANCED											80 VOLTS , 40.47 X 27.99 X 30.87				Weight Minimum 3263	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	80	125C11	625	48.5	40.35	27.88	30.28	3685	M2604012511XM44	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
EFG425/430/535	CLASS I 4 WHEEL COUNTERBALANCED											80 VOLTS , 40.47 X 33.66 X 30.87				Weight Minimum 4436	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	80	125F11	625	48.5	40.25	33.00	30.50	4312	M2504012511X7644	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
EFG540/545/550	CLASS I 4 WHEEL COUNTERBALANCED											80 VOLTS , 40.47 X 39.33 X 30.87				Weight Minimum 4562	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches
	80	125C13	750	58.2	40.35	39.21	30.28	4727	M2604012513X44	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
ETG230/235	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.60 X 14.25 X 31.70				Weight Minimum 1700	Connector SB350	GRAY	, Position C , Lead Length 020 Inches
	36	140T11	700	24.4	38.06	13.50	30.50	1972	M2801814011B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125L11	625	21.8	38.25	13.50	30.50	1825	M2901812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.06	13.50	30.50	1899	M2501812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.00	13.25	30.50	1836	M2601812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ETG230/235	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.60 X 16.25 X 31.70				Weight Minimum 2000	Connector SB350	GRAY	, Position C , Lead Length 020 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ETG230/235/340	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.60 X 18.25 X 31.70				Weight Minimum 2300	Connector SB350	GRAY	, Position C , Lead Length 020 Inches
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.31	17.88	30.50	2367	M2901812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ETG340/350/355	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 21.25 X 31.70			Weight Minimum 2600	Connector SB350	GRAY , Position C , Lead Length 020 Inches						
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2668	M2901812517B44	N	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
ETG350/355	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 23.75 X 31.70			Weight Minimum 2900	Connector SB350	GRAY , Position C , Lead Length 020 Inches						
	36	140T19	1260	44.0	38.31	22.38	30.50	3098	M2801814019B44	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	
	36	125F19	1125	39.3	38.31	22.38	30.50	3143	M2501812519B44	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	
	36	125C19	1125	39.3	38.31	22.38	30.50	2961	M2601812519B44	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)