

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
EJE120/EJE225,NO COVER	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)					24 VOLTS , 25.74 X 9.37 X 26.57			Weight Minimum 155	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.69	23.25	570	M1601208507D44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	MSB	195	.0	25.25	8.50	25.26	400	M90004S24CHPTM	N	(CALL)			(CALL)	(CALL)
EJE120E,NO COVER	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)					24 VOLTS , 32.28 X 9.37 X 26.57			Weight Minimum 375	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	100T07	300	7.0	31.75	8.90	23.25	550	M1801210007D00644	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	31.75	8.90	23.25	550	M1901208507D00644	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
EJE120/EJE225,WITH COVER	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)					24 VOLTS , 25.74 X 9.37 X 23.62			Weight Minimum 155	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.69	23.25	570	M1601208507D44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
EJE225E	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)					24 VOLTS , 32.00 X 13.58 X 31.29			Weight Minimum 948	Connector SB175	GRAY	, Position B , Lead Length 018 Inches			
	24	140T13	840	19.6	31.50	13.00	31.00	1400	M1801214013A0644	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	085L13	510	11.9	31.50	13.00	23.25	1020	M1901208513A0644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
ECR327/336	CLASS III LOW-LIFT WALKIE RIDER/PALLET					24 VOLTS , 32.00 X 13.58 X 31.29			Weight Minimum 933	Connector SB175	GRAY	, Position A , Lead Length 018 Inches			
	24	100T13	600	14.0	31.50	13.00	23.25	1035	M1801210013A00644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	31.50	13.00	31.00	1428	M1501212513A00644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	31.50	13.00	31.00	1372	M1601212513A00644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
EJCB14/B16	CLASS III WALKIE HIGHLIFT STRADDLE					24 VOLTS , 25.70 X 11.50 X 27.36			Weight Minimum 536	Connector SB175	GRAY	, Position A , Lead Length 032 Inches			
	24	100T09	400	9.3	25.27	10.88	22.63	743	M2801210009D44A	N	(CALL)			(CALL)	(CALL)
	24	085L09	340	7.9	25.27	10.88	22.63	713	M2901208509D44A	N	(CALL)			(CALL)	(CALL)
	24	085F09	340	7.9	25.27	10.88	22.63	720	M2501208509D44A	N	(CALL)			(CALL)	(CALL)
	24	085C09	340	7.9	25.27	10.88	22.63	696	M2601208509D44A	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
EJC214/216	CLASS III FORK-OVER WALKIE HIGHLIFT STRADDLE					24 VOLTS , 24.92 X 11.50 X 27.36			Weight Minimum 635	Connector SB175	GRAY	, Position A , Lead Length 018 Inches			
	24	100T07	300	7.0	24.00	10.25	22.63	690	M2801210007T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	24.00	10.25	23.63	667	M2901208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	24.00	10.25	23.63	667	M2901208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F07	255	5.9	24.00	10.25	22.63	672	M2501208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	24.00	10.25	22.63	462	M2601208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
EJE120(OLDSERIES)	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)					24 VOLTS , 25.30 X 8.70 X 25.60			Weight Minimum 220	Connector SB175	GRAY	, Position A , Lead Length 016 Inches			
	24	090G07	270	6.4	24.00	8.64	25.36	582	M8901209007E059	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	MSB	195	.0	25.25	8.50	25.26	400	M90004S24CHPTM	N	(CALL)			(CALL)	(CALL)
EJE120LARGE(W/LG)	CLASS III LOW-LFT WALKIE PALLET (PLATFORM)					24 VOLTS , 31.18 X 9.37 X 26.57			Weight Minimum 374	Connector SB175	GRAY	, Position A , Lead Length 018 Inches			
	24	085L07	255	5.9	30.68	8.90	23.25	550	M1901208507D25644	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F07	255	5.9	30.68	8.90	23.25	618	M1501208507D25644	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.68	8.90	23.25	596	M1601208507D25644	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
ECR327/336	CLASS III LOW-LIFT WALKIE RIDER/PALLET					24 VOLTS , 32.00 X 13.58 X 31.29			Weight Minimum 933	Connector SB175	GRAY	, Position A , Lead Length 018 Inches			
	24	100T13	600	14.0	31.50	13.00	23.25	1035	M1801210013A00644	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	31.50	13.00	31.00	1428	M1501212513A00644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	31.50	13.00	31.00	1372	M1601212513A00644	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
EJCB14/B16	CLASS III WALKIE HIGHLIFT STRADDLE											24 VOLTS , 25.70 X 11.50 X 27.36				Weight Minimum 536	Connector SB175	GRAY	, Position A , Lead Length 032 Inches
	24	100T09	400	9.3	25.27	10.88	22.63	743	M2801210009D44A	N	(CALL)			(CALL)	(CALL)				
	24	085L09	340	7.9	25.27	10.88	22.63	713	M2901208509D44A	N	(CALL)			(CALL)	(CALL)				
	24	085F09	340	7.9	25.27	10.88	22.63	720	M2501208509D44A	N	(CALL)			(CALL)	(CALL)				
	24	085C09	340	7.9	25.27	10.88	22.63	696	M2601208509D44A	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
EJC214/216	CLASS III FORK-OVER WALKIE HIGHLIFT STRADDLE											24 VOLTS , 24.92 X 11.50 X 27.36				Weight Minimum 635	Connector SB175	GRAY	, Position A , Lead Length 018 Inches
	24	100T07	300	7.0	24.00	10.25	22.63	690	M2801210007T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085L07	255	5.9	24.00	10.25	23.63	667	M2901208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085L07	255	5.9	24.00	10.25	23.63	667	M2901208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085F07	255	5.9	24.00	10.25	22.63	672	M2501208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
	24	085C07	255	5.9	24.00	10.25	22.63	462	M2601208507T44	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)				
ETR135	CLASS II NARROW AISLE REACH											24 VOLTS , 38.58 X 14.25 X 31.65				Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
ETR135	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ETR135	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 18.25 X 31.65				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
ETR230	CLASS II NARROW AISLE REACH											24 VOLTS , 38.60 X 14.25 X 31.65				Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
ETR235/340/340P/345/345P	CLASS II NARROW AISLE REACH											24 VOLTS , 38.60 X 14.25 X 31.65				Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
ETR235/340/340P/345/345P	CLASS II NARROW AISLE REACH											36 VOLTS , 38.60 X 16.25 X 31.65				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ETR125D	CLASS II DOUBLE REACH											36 VOLTS , 38.58 X 14.25 X 31.65				Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 025 Inches
	36	140T11	700	24.4	38.01	13.25	30.50	1765	M2801814011B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1759	M2501812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.01	13.25	30.50	1692	M2601812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



Jungheinrich Lift Trucks Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
ETR125D	CLASS II NARROW AISLE STRADDLE											36 VOLTS , 38.60 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
ETR225D	CLASS II DOUBLE REACH											24 VOLTS , 38.58 X 14.25 X 31.65				Weight Minimum 1700	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)	SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)				
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)				
ETR225D	CLASS II NARROW AISLE REACH											36 VOLTS , 38.60 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
ETVC16&20/Q20&25/320&325	CLASS II NARROW AISLE REACH											48 VOLTS , 48.15 X 14.10 X 30.87				Weight Minimum 1967	Connector EBC320	BLACK , Position A , Lead Length 025 Inches
	48	140T09	560	26.1	47.25	13.50	30.50	2151	M2802414009Y44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	125L09	500	23.3	47.25	13.50	30.50	2195	M2902412509Y44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	125C09	500	23.3	47.25	13.50	30.50	2101	M2602412509Y44	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
ETB340	CLASS II NARROW AISLE STRADDLE											24 VOLTS , 38.60 X 14.25 X 31.65				Weight Minimum 1700	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)	SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)				
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)				
EFX410/413	CLASS II VERY NARROW AISLE (TURRET)											48 VOLTS , 42.13 X 25.24 X 24.69				Weight Minimum 2116	Connector EBC320	BLACK , Position B , Lead Length 016 Inches
	48	100T15	700	32.6	40.00	24.00	24.00	2326	M2802410015B644	N	(CALL)	SCR20024750T1H	(CALL)	(CALL)				
	48	085L15	595	27.7	40.00	24.00	24.00	2288	M2902408515B644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C15	595	27.7	40.00	24.00	24.00	2193	M2602408515B644	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
EFG110	CLASS I 3 WHEEL COUNTERBALANCED											24 VOLTS , 32.68 X 12.87 X 24.68				Weight Minimum 932	Connector EBC320	BLACK , Position A , Lead Length 016 Inches
	24	100T13	600	14.0	32.63	12.88	22.63	1070	M2801210013A7B44	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	100T13	600	14.0	32.63	12.88	22.63	1070	M2801210013A7B44	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
EFG113	CLASS I 3 WHEEL COUNTERBALANCED											24 VOLTS , 32.68 X 17.13 X 24.69				Weight Minimum 1257	Connector EBC320	BLACK , Position A , Lead Length 016 Inches
	24	100T13	600	14.0	32.56	16.88	22.63	1320	M2801210013A76	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	32.56	16.88	22.63	1294	M2901208513A76	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
ETG235	CLASS I STAND-UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.60 X 14.25 X 31.70				Weight Minimum 1700	Connector SB350	GRAY , Position C , Lead Length 020 Inches
	72	125L15	875	61.1	76.38	17.88	31.00	4800	M1903612515J	N	(CALL)	SCR20036865T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
ETG235	CLASS I STAND-UP END CONTROL COUNTERBALANCED							36 VOLTS , 38.60 X 16.25 X 31.70		Weight Minimum 2000	Connector SB350	GRAY , Position C , Lead Length 020 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2166	M2801814013B2844	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.56	2081	M2901812513B2844	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2193	M2501812513B2844	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2045	M2601812513B2844	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EKS230/EKS230P	CLASS II ORDER PICKER							24 VOLTS , 38.62 X 13.25 X 32.25		Weight Minimum 920	Connector SB350	RED , Position C , Lead Length 012 Inches				
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B44	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)	
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B44	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125F15	875	20.4	38.18	11.98	30.50	1635	M2501212515B44	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125C15	875	20.4	38.18	11.98	30.50	1563	M2601212515B44	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
EKS230/EKS230P	CLASS II ORDER PICKER							24 VOLTS , 38.62 X 14.25 X 32.25		Weight Minimum 1242	Connector SB350	RED , Position C , Lead Length 012 Inches				
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)	
EKS230	CLASS II ORDER PICKER							24 VOLTS , 38.62 X 14.25 X 32.25		Weight Minimum 1242	Connector SB350	RED , Position C , Lead Length 012 Inches				
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)	
EKS230P	CLASS II ORDER PICKER							24 VOLTS , 38.62 X 14.25 X 32.25		Weight Minimum 920	Connector SB350	RED , Position C , Lead Length 012 Inches				
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)	
EKS330P	CLASS II ORDER PICKER							36 VOLTS , 38.62 X 14.25 X 32.25		Weight Minimum 1600	Connector SB350	GRAY , Position C , Lead Length 012 Inches				
	36	140T11	700	24.4	38.01	13.25	30.50	1765	M2801814011B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L11	625	21.8	38.00	13.25	30.50	1720	M2901812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1759	M2501812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.01	13.25	30.50	1692	M2601812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
ETR345	CLASS II NARROW AISLE REACH							36 VOLTS , 38.58 X 16.25 X 31.65		Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 025 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ETR345	CLASS II NARROW AISLE REACH			36 VOLTS , 38.58 X 18.25 X 31.65			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.31	17.88	30.50	2367	M2901812515B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
ETR345	CLASS II NARROW AISLE REACH			36 VOLTS , 38.58 X 21.25 X 31.65			Weight Minimum 2600		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
ETR345P	CLASS II NARROW AISLE REACH			36 VOLTS , 38.58 X 16.25 X 31.65			Weight Minimum 2000		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ETR345P	CLASS II NARROW AISLE REACH			36 VOLTS , 38.58 X 18.25 X 31.65			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
ETR345P	CLASS II NARROW AISLE REACH			36 VOLTS , 38.58 X 21.25 X 31.65			Weight Minimum 2600		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
ETB140	CLASS II NARROW AISLE STRADDLE			24 VOLTS , 38.58 X 14.25 X 31.65			Weight Minimum 1700		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)	SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)	
ETB140	CLASS II NARROW AISLE STRADDLE			36 VOLTS , 38.58 X 16.25 X 31.65			Weight Minimum 2000		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ETB140	CLASS II NARROW AISLE STRADDLE			36 VOLTS , 38.58 X 18.25 X 31.65			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.31	17.88	30.50	2367	M2901812515B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
ETR235	CLASS II NARROW AISLE REACH			24 VOLTS , 38.58 X 14.25 X 31.65			Weight Minimum 1700		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ETR340	CLASS II NARROW AISLE REACH		24 VOLTS , 38.58 X 14.25 X 31.65												
											Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
ETR340	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65												
											Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ETR340	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 18.25 X 31.65												
											Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ETR340P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65												
											Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ETR340P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 18.25 X 31.65												
											Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ETR340P	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 21.25 X 31.65												
											Weight Minimum 2600	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ETR345	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 16.25 X 31.65												
											Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ETR345	CLASS II NARROW AISLE REACH		36 VOLTS , 38.58 X 18.25 X 31.65												
											Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.31	17.88	30.50	2367	M2901812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
ETR345	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 21.25 X 31.65				Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
ETR230DP	CLASS II DOUBLE REACH											36 VOLTS , 38.58 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
ETR230DP	CLASS II DOUBLE REACH											36 VOLTS , 38.58 X 18.25 X 31.65				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
ETR230DP	CLASS II DOUBLE REACH											36 VOLTS , 38.58 X 21.25 X 31.65				Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
ETR130	CLASS II NARROW AISLE REACH											24 VOLTS , 38.58 X 14.25 X 31.65				Weight Minimum 910	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)			
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)			
ETR130	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 14.25 X 31.65				Weight Minimum 1700	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	140T11	700	24.4	38.01	13.25	30.50	1765	M2801814011B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125L11	625	21.8	38.00	13.25	30.50	1720	M2901812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F11	625	21.8	38.01	13.25	30.50	1759	M2501812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C11	625	21.8	38.01	13.25	30.50	1692	M2601812511B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
ETR140	CLASS II NARROW AISLE REACH											24 VOLTS , 38.58 X 14.25 X 31.65				Weight Minimum 1700	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1842	M2801214017B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)			
	24	125L17	1000	23.3	38.13	13.44	30.50	1765	M2901212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)			
	24	125F17	1000	23.3	38.13	13.44	30.50	1870	M2501212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)			
	24	125C17	1000	23.3	38.13	13.44	30.50	1746	M2601212517B44	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)			
ETR140	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 16.25 X 31.65				Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2158	M2801814013B44	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F13	750	26.2	37.94	15.63	30.50	2185	M2501812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C13	750	26.2	37.94	15.63	30.50	2048	M2601812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
ETR140	CLASS II NARROW AISLE REACH											36 VOLTS , 38.58 X 18.25 X 31.65				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 025 Inches
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ETR140	CLASS II NARROW AISLE REACH			36 VOLTS , 38.58 X 21.25 X 31.65											
											Weight Minimum 2600	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ETR140	CLASS II NARROW AISLE STRADDLE			24 VOLTS , 38.58 X 16.25 X 31.65											
											Weight Minimum 910	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	24	140T19	1260	29.3	38.19	15.00	30.50	2054	M2801214019B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	1963	M2901212519B44	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
ETG340	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 18.25 X 31.70											
											Weight Minimum 2300	Connector SB350	GRAY	, Position C , Lead Length 020 Inches	
	36	140T15	980	34.2	38.31	17.88	30.50	2477	M2801814015B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.31	17.88	30.50	2367	M2901812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2502	M2501812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2048	M2601812515B44	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ETG350	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 21.25 X 31.70											
											Weight Minimum 2600	Connector SB350	GRAY	, Position C , Lead Length 020 Inches	
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2668	M2901812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ETG355	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 21.25 X 31.70											
											Weight Minimum 2600	Connector SB350	GRAY	, Position C , Lead Length 020 Inches	
	36	140T17	1120	39.1	38.31	20.13	30.50	2784	M2801814017B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2827	M2501812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2640	M2601812517B44	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ETG355	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 23.75 X 31.70											
											Weight Minimum 2900	Connector SB350	GRAY	, Position C , Lead Length 020 Inches	
	36	140T19	1260	44.0	38.31	22.38	30.50	3098	M2801814019B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125F19	1125	39.3	38.31	22.38	30.50	3143	M2501812519B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125C19	1125	39.3	38.31	22.38	30.50	2961	M2601812519B44	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ETG630	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 16.25 X 31.60											
											Weight Minimum 2000	Connector SB350	GRAY	, Position C , Lead Length 020 Inches	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B44	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
EFG213/215	CLASS I 3 WHEEL COUNTERBALANCED			48 VOLTS , 32.68 X 20.55 X 24.69											
											Weight Minimum 1483	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches	
	48	100T09	400	18.6	32.56	20.38	23.38	1615	M2802410009Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
EFG216/218/220	CLASS I 3 WHEEL COUNTERBALANCED			48 VOLTS , 32.68 X 29.06 X 24.69											
											Weight Minimum 2122	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches	
	48	100T13	600	27.9	32.56	28.88	22.63	2386	M2802410013Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	32.75	29.00	22.62	2303	M2902408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	32.63	29.00	22.63	2253	M2602408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
EFG316/318/320	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 32.68 X 29.06 X 24.69											
											Weight Minimum 2122	Connector EBC320	BLACK	, Position A , Lead Length 016 Inches	
	48	100T13	600	27.9	32.56	28.88	22.63	2386	M2802410013Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	32.75	29.00	22.62	2303	M2902408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	32.63	29.00	22.63	2253	M2602408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



Jungheinrich Lift Trucks Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
EFG316K/318K	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 32.68 X 24.80 X 24.69 Weight Minimum 1793 Connector EBC320 BLACK , Position A , Lead Length 016 Inches											
	48	100T11	500	23.3	32.00	24.38	22.62	1942	M2802410011Z6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L11	425	19.8	32.00	24.38	22.62	1878	M2902408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
	48	085F11	425	19.8	32.00	24.38	22.62	1949	M2502408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
	48	085C11	425	19.8	32.00	24.50	22.62	1835	M2602408511Z6	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
EFG425K	CLASS I 4 WHEEL COUNTERBALANCED			80 VOLTS , 40.47 X 27.99 X 30.87 Weight Minimum 3263 Connector EBC320 BLACK , Position A , Lead Length 016 Inches											
	80	125C11	625	48.5	40.35	27.88	30.28	3685	M2604012511XM44	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)
EFG540/545/550	CLASS I 4 WHEEL COUNTERBALANCED			80 VOLTS , 40.47 X 39.33 X 30.87 Weight Minimum 4562 Connector EBC320 BLACK , Position A , Lead Length 016 Inches											
	80	125C13	750	58.2	40.35	39.21	30.28	4727	M2604012513X44	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)