

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
FB15MU-12	CLASS I AM50 3 WHEEL COUNTERBALANCED SERIES										48 VOLTS , 38.50 X 21.38 X 25.79	Weight Minimum 1590	Connector SB350	GRAY , Position A , Lead Length 010 Inches		
	48	100T13	600	27.9	38.13	20.82	22.63	2056	M2802410013B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.13	20.82	22.63	1927	M2602408513B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
FB18MU-12	CLASS I AM50 3 WHEEL COUNTERBALANCED SERIES										48 VOLTS , 38.50 X 21.38 X 25.79	Weight Minimum 1590	Connector SB350	GRAY , Position A , Lead Length 010 Inches		
	48	100T13	600	27.9	38.13	20.82	22.63	2056	M2802410013B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.13	20.82	22.63	1927	M2602408513B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
FB20MU-12	CLASS I AM50 3 WHEEL COUNTERBALANCED SERIES										48 VOLTS , 38.50 X 21.38 X 25.79	Weight Minimum 1680	Connector SB350	GRAY , Position A , Lead Length 010 Inches		
	48	100T13	600	27.9	38.13	20.82	22.63	2056	M2802410013B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.13	20.82	22.63	1927	M2602408513B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
FB15U-12	CLASS I AE50 4 WHEEL COUNTERBALANCED SERIES										48 VOLTS , 38.50 X 21.38 X 25.79	Weight Minimum 1590	Connector SB350	GRAY , Position A , Lead Length 010 Inches		
	48	100T13	600	27.9	38.13	20.82	22.63	2056	M2802410013B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.13	20.82	22.63	1927	M2602408513B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
FB18U-12	CLASS I AE50 4 WHEEL COUNTERBALANCED SERIES										48 VOLTS , 38.50 X 21.38 X 25.79	Weight Minimum 1590	Connector SB350	GRAY , Position A , Lead Length 010 Inches		
	48	100T13	600	27.9	38.13	20.82	22.63	2056	M2802410013B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.13	20.82	22.63	1927	M2602408513B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
FB20AU-12	CLASS I AE50 4 WHEEL COUNTERBALANCED SERIES										48 VOLTS , 38.50 X 21.38 X 25.79	Weight Minimum 1680	Connector SB350	GRAY , Position A , Lead Length 010 Inches		
	48	100T13	600	27.9	38.13	20.82	22.63	2056	M2802410013B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.13	20.82	22.63	1927	M2602408513B65	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
FB20SH-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES										36 VOLTS , 38.80 X 29.10 X 23.80	Weight Minimum 2430	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
FB20SH-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES										48 VOLTS , 38.80 X 29.10 X 23.80	Weight Minimum 2430	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
FB20SHG-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES										36 VOLTS , 38.80 X 36.20 X 23.80	Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
FB20SHG-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES										48 VOLTS , 38.80 X 36.20 X 23.80	Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
FB25SH-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES			36 VOLTS , 38.80 X 29.10 X 23.80			Weight Minimum 2430		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
FB25SH-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES			48 VOLTS , 38.80 X 29.10 X 23.80			Weight Minimum 2430		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
FB25SHG-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES			36 VOLTS , 38.80 X 36.20 X 23.80			Weight Minimum 3000		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
FB25SHG-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES			48 VOLTS , 38.80 X 36.20 X 23.80			Weight Minimum 3000		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
FB30SH-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES			36 VOLTS , 38.80 X 36.20 X 23.80			Weight Minimum 3000		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
FB30SH-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES			48 VOLTS , 38.80 X 36.20 X 23.80			Weight Minimum 3000		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
FB32SH-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES			36 VOLTS , 38.80 X 36.20 X 23.80			Weight Minimum 3000		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
FB32SH-6	CLASS I BBX 4 WHEEL COUNTERBALANCED SERIES			48 VOLTS , 38.80 X 36.20 X 23.80			Weight Minimum 3000		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
FB35ZSH-1	CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES											36 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3490	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)	
FB35ZSH-1	CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES											48 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3490	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
FB35ZSHH-1	CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES											36 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3490	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)	
FB35ZSHH-1	CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES											48 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3490	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
FB35SH-1	CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES											36 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3585	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)	
FB35SH-1	CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES											48 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3585	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
FB35SHH-1	CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES											36 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3585	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)	
FB35SHH-1	CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES											48 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3585	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
FB45SH-1	CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES											36 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3450	Connector SB350	GRAY , Position A , Lead Length 018 Inches
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
FB45SH-1			CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES			48 VOLTS , 44.90 X 39.60 X 24.00			Weight Minimum 3450	Connector SB350	GRAY	, Position A , Lead Length 018 Inches			
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
FB45SHH-1			CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES			36 VOLTS , 44.90 X 39.60 X 24.00			Weight Minimum 3450	Connector SB350	GRAY	, Position A , Lead Length 018 Inches			
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)
FB45SHH-1			CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES			48 VOLTS , 44.90 X 39.60 X 24.00			Weight Minimum 3450	Connector SB350	GRAY	, Position A , Lead Length 018 Inches			
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
FB55SH-1			CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES			36 VOLTS , 44.90 X 39.60 X 24.00			Weight Minimum 4250	Connector SB350	GRAY	, Position A , Lead Length 018 Inches			
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)
FB55SH-1			CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES			48 VOLTS , 44.90 X 39.60 X 24.00			Weight Minimum 4250	Connector SB350	GRAY	, Position A , Lead Length 018 Inches			
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
FB55SHH-1			CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES			36 VOLTS , 44.90 X 39.60 X 24.00			Weight Minimum 4250	Connector SB350	GRAY	, Position A , Lead Length 018 Inches			
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)
FB55SHH-1			CLASS I CBX 4 WHEEL COUNTERBALANCED SERIES			48 VOLTS , 44.90 X 39.60 X 24.00			Weight Minimum 4250	Connector SB350	GRAY	, Position A , Lead Length 018 Inches			
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
FS15SH-1			CLASS I ASX SERIES STAND UO END CONTROL COUNTERBALANCE			36 VOLTS , 38.70 X 16.10 X 31.50			Weight Minimum 1925	Connector SB350	GRAY	, Position D , Lead Length 009 Inches			
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
FS17SH-1			CLASS I ASX SERIES STAND UP END CONTROL COUNTERBALANCE			36 VOLTS , 38.70 X 18.10 X 31.50			Weight Minimum 2175	Connector SB350	GRAY	, Position D , Lead Length 009 Inches			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
FS18SH-1	CLASS I ASX SERIES STAND UP END CONTROL COUNTERBALANCE											36 VOLTS , 38.70 X 16.10 X 31.50	Weight Minimum 1925	Connector SB350	GRAY , Position D , Lead Length 009 Inches		
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
FS15S-1	CLASS I ASX SERIES STAND UP END CONTROL COUNTERBALANCE											36 VOLTS , 38.70 X 16.10 X 31.50	Weight Minimum 1925	Connector SB350	GRAY , Position D , Lead Length 009 Inches		
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
FS18S-1	CLASS I ASX SERIES STAND UP END CONTROL COUNTERBALANCE											36 VOLTS , 38.70 X 16.10 X 31.50	Weight Minimum 1925	Connector SB350	GRAY , Position D , Lead Length 009 Inches		
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
FS20S-1	CLASS I ASX SERIES STAND UP END CONTROL COUNTERBALANCE											36 VOLTS , 38.70 X 20.70 X 31.50	Weight Minimum 2700	Connector SB350	GRAY , Position D , Lead Length 009 Inches		
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
FS19SH-1	CLASS I BSX SERIES STAND UP END CONTROL COUNTERBALANCE											36 VOLTS , 38.70 X 18.10 X 31.50	Weight Minimum 2175	Connector SB350	GRAY , Position D , Lead Length 009 Inches		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
FS20SH-1	CLASS I BSX SERIES STAND UP END CONTROL COUNTERBALANCE											36 VOLTS , 38.70 X 20.70 X 31.50	Weight Minimum 2700	Connector SB350	GRAY , Position D , Lead Length 009 Inches		
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
FS23SH-1	CLASS I BSX SERIES STAND UP END CONTROL COUNTERBALANCE											36 VOLTS , 38.70 X 20.70 X 31.50	Weight Minimum 2700	Connector SB350	GRAY , Position D , Lead Length 009 Inches		
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
FS25SH-1	CLASS I BSX SERIES STAND UP END CONTROL COUNTERBALANCE											36 VOLTS , 38.70 X 20.70 X 31.50	Weight Minimum 2700	Connector SB350	GRAY , Position D , Lead Length 009 Inches		
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
FS28SH-1	CLASS I BSX SERIES STAND UP END CONTROL COUNTERBALANCE											36 VOLTS , 38.70 X 20.70 X 31.50	Weight Minimum 2700	Connector SB350	GRAY , Position D , Lead Length 009 Inches		
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)