

| TRUCK MODEL         | VOLT   | BATTERY TYPE | CAPACITY 6 HOUR RATE |      | BATTERY DIMENSIONS |               |                | BATT. WT. (LBS.) | BATTERY MODEL NUMBER | Q-SHP | BATTERY LIST PRICE | SINGLE PHASE CHARGER (S-1)              | THREE PHASE CHARGER (T-1) | S-1 CHARGER LIST PRICE | T-1 CHARGER LIST PRICE |                            |                        |   |  |
|---------------------|--|--------------|----------------------|------|--------------------|---------------|----------------|------------------|----------------------|-------|--------------------|---|---------------------------|------------------------|------------------------|----------------------------|------------------------|---|--|
|                     |  |              | A.H.                 | KwH  | X in. (Length)     | Y in. (Width) | Z in. (Height) |                  |                      |       |                    |   |                           |                        |                        |                            |                        |   |  |
| <b>P30E90D</b>      | <b>PivotMast Lift Truck</b>                  |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.75 X 32.38 X 23.88</b> |                           |                        |                        | <b>Weight Minimum 3250</b> | <b>Connector SB350</b> | <b>GRAY , Position A , Lead Length 018 Inches</b> |  |
|                     | 36   | 085C27       | 1105                 | 38.6 | 38.44              | 31.50         | 22.63          | 2960             | M2601808527B         | Y     | (CALL)             |   | SCR200181200T1H           | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 36   | 085F27       | 1105                 | 38.6 | 38.44              | 31.50         | 22.63          | 3086             | M2501808527B         | Y     | (CALL)             |   | SCR200181200T1H           | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 36   | 100T27       | 1300                 | 45.4 | 38.44              | 31.50         | 22.63          | 3127             | M2801810027B         | Y     | (CALL)             |   | SCR200181450T1H           | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>P30E-90D</b>     | <b>PIVOTMAST 3,000 LBS</b>                   |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 39.13 X 33.88 X 26.88</b> |                           |                        |                        | <b>Weight Minimum 3250</b> | <b>Connector SB350</b> | <b>BLUE , Position A , Lead Length 018 Inches</b> |  |
|                     | 48   | 100C21       | 1000                 | 46.6 | 38.43              | 32.93         | 25.62          | 3664             | M2602410021B         | N     | (CALL)             |   | SCR200241050T1H           | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>P40E-90D</b>     | <b>VERY NARROW AISLE, PIVOTMAST</b>          |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 39.13 X 33.88 X 26.88</b> |                           |                        |                        | <b>Weight Minimum 3250</b> | <b>Connector SB350</b> | <b>BLUE , Position A , Lead Length 018 Inches</b> |  |
|                     | 48   | 100C21       | 1000                 | 46.6 | 38.43              | 32.93         | 25.62          | 3664             | M2602410021B         | N     | (CALL)             |   | SCR200241050T1H           | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 100T21       | 1000                 | 46.6 | 38.25              | 32.63         | 22.63          | 3293             | M2802410021B         | Y     | (CALL)             |   | SCR200241050T1H           | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>B25/B30</b>      | <b>Bendi 180D 2500# and 3000# Lift Truck</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 38.75 X 27.50 X 23.00</b> |                           |                        |                        | <b>Weight Minimum 2600</b> | <b>Connector SB350</b> | <b>BLUE , Position C , Lead Length 020 Inches</b> |  |
|                     | 48   | 100T17       | 800                  | 37.2 | 38.38              | 26.69         | 22.63          | 2700             | M2802410017B         | N     | (CALL)             |   | SCR20024865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085C17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2684             | M2602408517B725      | N     | (CALL)             |   | SCR20024750T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085L17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2661             | M2902408517B725AU    | N     | (CALL)             |   | SCR20024750T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>B35/B40</b>      | <b>Bendi 180D 3500# and 4000# Lift Truck</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 38.75 X 27.50 X 23.00</b> |                           |                        |                        | <b>Weight Minimum 2600</b> | <b>Connector SB350</b> | <b>BLUE , Position A , Lead Length 012 Inches</b> |  |
|                     | 48   | 100T17       | 800                  | 37.2 | 38.38              | 26.69         | 22.63          | 2700             | M2802410017B         | N     | (CALL)             |   | SCR20024865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085C17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2684             | M2602408517B725      | N     | (CALL)             |   | SCR20024750T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085L17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2661             | M2902408517B725AU    | N     | (CALL)             |   | SCR20024750T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>B35/B40</b>      | <b>Bendi 180D 3500# and 4000# Lift Truck</b> |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 44.75 X 26.00 X 23.00</b> |                           |                        |                        | <b>Weight Minimum 2600</b> | <b>Connector SB350</b> | <b>BLUE , Position A , Lead Length 012 Inches</b> |  |
|                     | 48   | 085C19       | 765                  | 35.6 | 44.44              | 25.63         | 22.63          | 2832             | M2602408519A         | N     | (CALL)             |   | SCR20024865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085F19       | 765                  | 35.6 | 44.44              | 25.63         | 22.63          | 2930             | M2502408519A         | N     | (CALL)             |   | SCR20024865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>B45</b>          | <b>Bendi 180D 4500# Lift Truck</b>           |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 38.75 X 27.50 X 23.00</b> |                           |                        |                        | <b>Weight Minimum 2600</b> | <b>Connector SB350</b> | <b>BLUE , Position A , Lead Length 012 Inches</b> |  |
|                     | 48   | 100T17       | 800                  | 37.2 | 38.38              | 26.69         | 22.63          | 2700             | M2802410017B         | N     | (CALL)             |   | SCR20024865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085C17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2684             | M2602408517B725      | N     | (CALL)             |   | SCR20024750T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085L17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2661             | M2902408517B725AU    | N     | (CALL)             |   | SCR20024750T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>B45</b>          | <b>Bendi 180D 4500# Lift Truck</b>           |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 44.75 X 26.00 X 23.00</b> |                           |                        |                        | <b>Weight Minimum 2600</b> | <b>Connector SB350</b> | <b>BLUE , Position A , Lead Length 012 Inches</b> |  |
|                     | 48   | 085C19       | 765                  | 35.6 | 44.44              | 25.63         | 22.63          | 2832             | M2602408519A         | N     | (CALL)             |   | SCR20024865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085F19       | 765                  | 35.6 | 44.44              | 25.63         | 22.63          | 2930             | M2502408519A         | N     | (CALL)             |   | SCR20024865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>SLT-30/35</b>    | <b>Drexel SwingMast Lift Truck</b>           |              |                      |      |                    |               |                |                  |                      |       |                    | <b>36 VOLTS , 38.63 X 21.75 X 27.00</b> |                           |                        |                        | <b>Weight Minimum 2100</b> | <b>Connector SB350</b> | <b>GRAY , Position B , Lead Length 025 Inches</b> |  |
|                     | 36   | 100C17       | 800                  | 27.9 | 38.19              | 20.00         | 25.62          | 2156             | M2601810017B         | Y     | (CALL)             | SCR20018865S1H                          | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 36   | 100F17       | 800                  | 27.9 | 38.19              | 20.00         | 25.63          | 2272             | M2501810017B         | Y     | (CALL)             | SCR20018865S1H                          | SCR20018865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>SLT-35-HLC</b>   | <b>Drexel SwingMast Lift Truck</b>           |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 38.63 X 26.50 X 27.00</b> |                           |                        |                        | <b>Weight Minimum 2650</b> | <b>Connector SB350</b> | <b>GRAY , Position B , Lead Length 036 Inches</b> |  |
|                     | 48   | 100C15       | 700                  | 32.6 | 38.31              | 24.63         | 25.63          | 2727             | M2602410015B7        | N     | (CALL)             |   | SCR20024750T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>B30/42E-180D</b> | <b>FOUR WHEEL SWING MAST</b>                 |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 38.75 X 27.50 X 23.00</b> |                           |                        |                        | <b>Weight Minimum 2600</b> | <b>Connector SB350</b> | <b>BLUE , Position A , Lead Length 012 Inches</b> |  |
|                     | 48   | 060B21       | 600                  | 28.2 | 38.50              | 27.25         | 23.11          | 2666             | M2102406021DB75982   | N     | (CALL)             | SCR20024600S1H                          | SCR20024600T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085C17       | 680                  | 31.7 | 38.25              | 27.00         | 22.88          | 2684             | M2602408517B725      | N     | (CALL)             |   | SCR20024750T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
| <b>B40AC</b>        | <b>FOUR WHEEL SWING MAST</b>                 |              |                      |      |                    |               |                |                  |                      |       |                    | <b>48 VOLTS , 44.75 X 26.00 X 23.00</b> |                           |                        |                        | <b>Weight Minimum 2600</b> | <b>Connector SB350</b> | <b>BLUE , Position A , Lead Length 012 Inches</b> |  |
|                     | 48   | 085C19       | 765                  | 35.6 | 44.44              | 25.63         | 22.63          | 2832             | M2602408519A         | N     | (CALL)             |   | SCR20024865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |
|                     | 48   | 085F19       | 765                  | 35.6 | 44.44              | 25.63         | 22.63          | 2930             | M2502408519A         | N     | (CALL)             |   | SCR20024865T1H            | (CALL)                 | (CALL)                 |                            |                        |   |  |

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)