



Linde Baker 2012 Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
R1411"	CLASS II ORDER PICKER																			
	48	125C07	375	17.5	47.50	10.75	30.50	1690	M2602412507R76	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)					
												48 VOLTS , 48.15 X 11.14 X 30.87				Weight Minimum 1575	Connector SB350	BLUE	, Position B	, Lead Length 024 Inches
R1611"	CLASS II ORDER PICKER																			
	48	125C07	375	17.5	47.50	10.75	30.50	1690	M2602412507R76	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)					
												48 VOLTS , 48.15 X 11.14 X 30.87				Weight Minimum 1575	Connector SB350	BLUE	, Position B	, Lead Length 024 Inches
R20N17"	CLASS II REACH																			
	48	140T13	840	39.1	38.13	20.68	30.50	2900	M2802414013B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
	48	125F13	750	34.9	38.31	20.69	30.50	2792	M2502412513B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	125C13	750	34.9	38.13	20.68	30.50	2727	M2602412513B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)					
	48	140T13	840	39.1	38.13	20.68	30.50	2900	M2802414013B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)					
												48 VOLTS , 40.75 X 21.00 X 30.87				Weight Minimum 1965	Connector SB350	BLUE	, Position B	, Lead Length 030 Inches

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)