

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>ETR</b>	<b>PALLET</b>				<b>24 VOLTS , 32.75 X 13.50 X 31.00</b>				<b>Weight Minimum 850</b>		<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position A , Lead Length 021 Inches</b>			
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
<b>PPTW</b>	<b>PALLET</b>				<b>12 VOLTS , 31.50 X 8.25 X 40.00</b>				<b>Weight Minimum 450</b>		<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>			
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)	
<b>PPTW</b>	<b>PALLET</b>				<b>24 VOLTS , 31.50 X 13.50 X 40.00</b>				<b>Weight Minimum 975</b>		<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>BW</b>	<b>PALLET TRUCK</b>				<b>12 VOLTS , 31.50 X 8.25 X 40.00</b>				<b>Weight Minimum 450</b>		<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>			
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
<b>BW</b>	<b>PALLET TRUCK</b>				<b>24 VOLTS , 31.50 X 13.50 X 40.00</b>				<b>Weight Minimum 975</b>		<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>			
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>GAWR</b>	<b>PALLET TRUCK</b>				<b>12 VOLTS , 31.50 X 8.25 X 999.00</b>				<b>Weight Minimum 450</b>		<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>			
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)	
<b>GAWR</b>	<b>PALLET TRUCK</b>				<b>24 VOLTS , 31.50 X 13.50 X 999.00</b>				<b>Weight Minimum 975</b>		<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>MTW</b>	<b>PALLET TRUCK</b>				<b>12 VOLTS , 31.12 X 8.25 X 40.00</b>				<b>Weight Minimum 450</b>		<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>			
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Linde Baker Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
<b>MTW</b>	<b>PALLET TRUCK</b>		<b>24 VOLTS , 31.12 X 13.50 X 40.00</b>														
			<b>Weight Minimum 975</b>											<b>Connector SB175</b>		<b>GRAY , Position B , Lead Length 018 Inches</b>	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
<b>MTWR</b>	<b>PALLET TRUCK</b>		<b>12 VOLTS , 31.12 X 8.25 X 40.00</b>														
			<b>Weight Minimum 450</b>											<b>Connector SB175</b>		<b>GRAY , Position B , Lead Length 018 Inches</b>	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)		
<b>MTWR</b>	<b>PALLET TRUCK</b>		<b>24 VOLTS , 31.12 X 13.50 X 40.00</b>														
			<b>Weight Minimum 975</b>											<b>Connector SB175</b>		<b>GRAY , Position B , Lead Length 018 Inches</b>	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
<b>EGU20</b>	<b>WALKIE</b>		<b>24 VOLTS , 26.00 X 9.00 X 26.00</b>														
			<b>Weight Minimum 450</b>											<b>Connector SB175</b>		<b>RED , Position A , Lead Length 021 Inches</b>	
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)		
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)			(CALL)	(CALL)		
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)		
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)		
	24	MSB	195	.0	25.25	8.50	25.26	400	M90004S24CHPTM	N	(CALL)			(CALL)	(CALL)		
<b>EXU20</b>	<b>WALKIE</b>		<b>24 VOLTS , 26.00 X 9.00 X 26.00</b>														
			<b>Weight Minimum 450</b>											<b>Connector SB175</b>		<b>RED , Position A , Lead Length 021 Inches</b>	
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)		
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)			(CALL)	(CALL)		
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)		
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)		
	24	MSB	195	.0	25.25	8.50	25.26	400	M90004S24CHPTM	N	(CALL)			(CALL)	(CALL)		
<b>BW40FL</b>	<b>WALKIE PALLET TRUCK</b>		<b>24 VOLTS , 27.40 X 9.95 X 26.20</b>														
			<b>Weight Minimum 0</b>											<b>Connector SB175</b>		<b>GRAY , Position B , Lead Length 018 Inches</b>	
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)		
	24	100C07	300	7.0	25.52	8.75	26.00	652	M1601210007D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)		
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)		
	24	CHP	195	.0	25.50	8.69	26.16	400	M90004S24CHPC	N	(CALL)			(CALL)	(CALL)		
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)		
<b>BW60</b>	<b>WALKIE PALLET TRUCK</b>		<b>12 VOLTS , 31.50 X 8.25 X 999.00</b>														
			<b>Weight Minimum 450</b>											<b>Connector SB175</b>		<b>GRAY , Position B , Lead Length 018 Inches</b>	
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)		
<b>BW60</b>	<b>WALKIE PALLET TRUCK</b>		<b>24 VOLTS , 31.50 X 13.50 X 999.00</b>														
			<b>Weight Minimum 900</b>											<b>Connector SB175</b>		<b>GRAY , Position B , Lead Length 018 Inches</b>	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>BWR80</b>	<b>WALKIE PALLET TRUCK</b>		<b>24 VOLTS , 31.50 X 13.50 X 999.00 Weight Minimum 900 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>BWR40</b>	<b>WALKIE RIDER</b>		<b>12 VOLTS , 31.50 X 8.25 X 999.00 Weight Minimum 450 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
<b>BWR40</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 31.50 X 13.50 X 999.00 Weight Minimum 900 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>BWR60</b>	<b>WALKIE RIDER</b>		<b>12 VOLTS , 31.50 X 8.25 X 999.00 Weight Minimum 450 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
<b>BWR60</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 31.50 X 13.50 X 999.00 Weight Minimum 900 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>BWR80</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 31.50 X 13.50 X 999.00 Weight Minimum 900 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ECR60/80		WALKIE RIDER			24 VOLTS , 32.75 X 13.50 X 31.00						Weight Minimum 850	Connector SB175	GRAY	, Position A , Lead Length 021 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
EWR60		WALKIE RIDER			12 VOLTS , 31.50 X 8.25 X 40.00						Weight Minimum 450	Connector SB175	YELLOW	, Position A , Lead Length 021 Inches	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
EWR60		WALKIE RIDER			24 VOLTS , 31.50 X 13.50 X 40.00						Weight Minimum 900	Connector SB175	RED	, Position A , Lead Length 021 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
EWR80		WALKIE RIDER			12 VOLTS , 31.50 X 8.25 X 40.00						Weight Minimum 450	Connector SB175	YELLOW	, Position A , Lead Length 021 Inches	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
EWR80		WALKIE RIDER			24 VOLTS , 31.50 X 13.50 X 40.00						Weight Minimum 900	Connector SB175	RED	, Position A , Lead Length 021 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
EWS40		WALKIE RIDER			12 VOLTS , 32.50 X 8.25 X 40.00						Weight Minimum 625	Connector SB175	GRAY	, Position B , Lead Length 021 Inches	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
EWS40		WALKIE RIDER			24 VOLTS , 32.50 X 13.50 X 40.00						Weight Minimum 975	Connector SB175	GRAY	, Position B , Lead Length 021 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
EWX30		WALKIE RIDER			24 VOLTS , 32.50 X 13.50 X 40.00						Weight Minimum 975	Connector SB175	GRAY	, Position B , Lead Length 021 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
EW60		WALKIE RIDER			12 VOLTS , 31.50 X 8.25 X 40.00						Weight Minimum 450	Connector SB175	YELLOW	, Position A , Lead Length 021 Inches	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
EW60		WALKIE RIDER			24 VOLTS , 31.50 X 9.00 X 40.00						Weight Minimum 450	Connector SB175	YELLOW	, Position A , Lead Length 021 Inches	
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
EW60		WALKIE RIDER			24 VOLTS , 31.50 X 13.50 X 40.00						Weight Minimum 900	Connector SB175	RED	, Position A , Lead Length 021 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
EW80		WALKIE RIDER			12 VOLTS , 31.50 X 8.25 X 40.00						Weight Minimum 450	Connector SB175	YELLOW	, Position A , Lead Length 021 Inches	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
EW80		WALKIE RIDER			24 VOLTS , 31.50 X 13.50 X 40.00						Weight Minimum 900	Connector SB175	RED	, Position A , Lead Length 021 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
GAW		WALKIE RIDER			12 VOLTS , 31.50 X 8.25 X 40.00						Weight Minimum 450	Connector SB175	GRAY	, Position B , Lead Length 018 Inches	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
GAW		WALKIE RIDER			24 VOLTS , 31.50 X 13.50 X 40.00						Weight Minimum 975	Connector SB175	GRAY	, Position B , Lead Length 018 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>MTPW</b>	<b>WALKIE RIDER</b>		<b>12 VOLTS , 31.50 X 8.25 X 40.00 Weight Minimum 450 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
<b>MTPW</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 31.50 X 13.50 X 40.00 Weight Minimum 975 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>PALWR60</b>	<b>WALKIE RIDER</b>		<b>12 VOLTS , 31.50 X 8.25 X 999.00 Weight Minimum 450 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
<b>PALWR60</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 31.50 X 13.50 X 999.00 Weight Minimum 900 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>PALWR80</b>	<b>WALKIE RIDER</b>		<b>12 VOLTS , 31.50 X 8.25 X 999.00 Weight Minimum 450 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
<b>PALWR80</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 31.50 X 13.50 X 999.00 Weight Minimum 900 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>PALW60</b>	<b>WALKIE RIDER</b>		<b>12 VOLTS , 31.50 X 8.25 X 40.00 Weight Minimum 450 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
<b>PALW60</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 31.50 X 13.50 X 40.00 Weight Minimum 975 Connector SB175 GRAY , Position B , Lead Length 021 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>PALW80</b>	<b>WALKIE RIDER</b>		<b>12 VOLTS , 31.50 X 8.25 X 40.00 Weight Minimum 450 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
<b>PALW80</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 31.50 X 13.50 X 40.00 Weight Minimum 975 Connector SB175 GRAY , Position B , Lead Length 021 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>PPT-WR</b>	<b>WALKIE RIDER</b>		<b>12 VOLTS , 31.50 X 8.25 X 999.00 Weight Minimum 450 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G09	400	4.7	30.88	7.75	23.98	500	M8900610009APP	Y	(CALL)			(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
<b>PPT-WR</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 31.50 X 13.50 X 999.00 Weight Minimum 900 Connector SB175 GRAY , Position B , Lead Length 018 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>WC2013"</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 32.75 X 13.50 X 31.00 Weight Minimum 850 Connector SB175 GRAY , Position A , Lead Length 021 Inches</b>												
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>WC3013"</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 32.75 X 13.50 X 31.00 Weight Minimum 850 Connector SB175 GRAY , Position A , Lead Length 021 Inches</b>												
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>WC4013"</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 32.75 X 13.50 X 31.00 Weight Minimum 850 Connector SB175 GRAY , Position A , Lead Length 021 Inches</b>												
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>WTT</b>	<b>WALKIE RIDER</b>		<b>24 VOLTS , 32.75 X 13.50 X 31.00 Weight Minimum 850 Connector SB175 GRAY , Position A , Lead Length 021 Inches</b>												
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>EW80</b>	<b>WALKIE RIDER SHIMS REQUIRED WITH THIS BATTERY</b>		<b>24 VOLTS , 31.50 X 9.00 X 40.00 Weight Minimum 450 Connector SB175 YELLOW , Position A , Lead Length 021 Inches</b>												
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>BRT30D</b>	<b>DEEP REACH</b>		<b>36 VOLTS , 39.50 X 16.60 X 31.80</b>												
			<b>Weight Minimum 1800</b>		<b>Connector SB350</b>			<b>GRAY</b>		<b>, Position B , Lead Length 024 Inches</b>					
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>BRT30D</b>	<b>DEEP REACH</b>		<b>36 VOLTS , 39.50 X 21.20 X 31.80</b>												
			<b>Weight Minimum 2400</b>		<b>Connector SB350</b>			<b>GRAY</b>		<b>, Position B , Lead Length 024 Inches</b>					
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>BRT45D</b>	<b>HEAVY DUTY DEEP REACH</b>		<b>36 VOLTS , 39.50 X 21.20 X 31.80</b>												
			<b>Weight Minimum 2400</b>		<b>Connector SB350</b>			<b>GRAY</b>		<b>, Position B , Lead Length 024 Inches</b>					
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>BRT45</b>	<b>HEAVY DUTY REACH</b>		<b>36 VOLTS , 39.50 X 16.60 X 31.80</b>												
			<b>Weight Minimum 1800</b>		<b>Connector SB350</b>			<b>GRAY</b>		<b>, Position B , Lead Length 024 Inches</b>					
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>MX-30</b>	<b>ORDER PICKER</b>		<b>72 VOLTS , 38.10 X 16.00 X 34.00</b>												
			<b>Weight Minimum 4120</b>		<b>Connector SB350</b>			<b>BLUE</b>		<b>, Position N/A, Lead Length 036 Inches</b>					
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
<b>R1411"</b>	<b>ORDER PICKER</b>		<b>48 VOLTS , 48.15 X 11.14 X 30.87</b>												
			<b>Weight Minimum 1653</b>		<b>Connector SB350</b>			<b>BLUE</b>		<b>, Position B , Lead Length 024 Inches</b>					
	48	125C07	375	17.5	47.50	10.75	30.50	1690	M2602412507R76	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
<b>R1611"</b>	<b>ORDER PICKER</b>		<b>48 VOLTS , 48.15 X 11.14 X 30.87</b>												
			<b>Weight Minimum 1653</b>		<b>Connector SB350</b>			<b>BLUE</b>		<b>, Position B , Lead Length 024 Inches</b>					
	48	125C07	375	17.5	47.50	10.75	30.50	1690	M2602412507R76	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
<b>BOP30</b>	<b>ORDER SELECTOR</b>		<b>24 VOLTS , 36.50 X 14.60 X 31.50</b>												
			<b>Weight Minimum 1600</b>		<b>Connector SB350</b>			<b>RED</b>		<b>, Position A , Lead Length 030 Inches</b>					
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
<b>BOS15</b>	<b>ORDER SELECTOR</b>		<b>24 VOLTS , 37.00 X 14.60 X 31.50</b>												
			<b>Weight Minimum 1600</b>		<b>Connector SB350</b>			<b>RED</b>		<b>, Position A , Lead Length 030 Inches</b>					
	24	125F15	875	20.4	35.25	13.06	30.50	1662	M2501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	13.06	30.50	1606	M2601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.25	13.06	30.50	1702	M2801214015A	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
<b>R16N/R20N17"</b>	<b>REACH</b>		<b>48 VOLTS , 40.75 X 17.44 X 30.87</b>												
			<b>Weight Minimum 2065</b>		<b>Connector SB350</b>			<b>BLUE</b>		<b>, Position B , Lead Length 024 Inches</b>					
	48	125C11	625	29.1	38.06	17.38	30.50	2267	M2602412511B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>R20N21*</b>	<b>REACH</b>							<b>48 VOLTS , 40.75 X 21.00 X 30.87</b>		<b>Weight Minimum 2462</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 024 Inches</b>		
	48	125F13	750	34.9	38.31	20.69	30.50	2792	M2502412513B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	125C13	750	34.9	38.13	20.68	30.50	2727	M2602412513B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	140T13	840	39.1	38.13	20.68	30.50	2900	M2802414013B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
<b>BSC35</b>	<b>STANDUP COUNTERBALANCED</b>							<b>36 VOLTS , 39.25 X 21.25 X 32.00</b>		<b>Weight Minimum 2400</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 024 Inches</b>		
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>BRT35</b>	<b>STRADDLE REACH</b>							<b>24 VOLTS , 39.50 X 14.60 X 31.80</b>		<b>Weight Minimum 1425</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 024 Inches</b>		
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
<b>BRT35</b>	<b>STRADDLE REACH</b>							<b>36 VOLTS , 39.50 X 16.60 X 31.80</b>		<b>Weight Minimum 1800</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 024 Inches</b>		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>BST40</b>	<b>STRADDLE REACH</b>							<b>24 VOLTS , 39.50 X 14.60 X 31.80</b>		<b>Weight Minimum 1425</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 024 Inches</b>		
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
<b>BST40</b>	<b>STRADDLE REACH</b>							<b>36 VOLTS , 39.50 X 16.60 X 31.80</b>		<b>Weight Minimum 1800</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 024 Inches</b>		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>BTMAMX20</b>	<b>VERY NARROW AISLE - MAN ALOFT TRUCK</b>							<b>48 VOLTS , 40.50 X 25.10 X 34.00</b>		<b>Weight Minimum 2930</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 024 Inches</b>		
	48	125F15	875	40.7	38.31	23.62	30.50	3170	M2502412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	125C15	875	40.7	38.31	23.62	30.50	3084	M2602412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	140T15	980	45.6	38.31	23.62	30.50	3283	M2802414015B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
<b>BTMDZ12</b>	<b>VERY NARROW AISLE - MAN DOWN TRUCK</b>							<b>48 VOLTS , 44.90 X 24.25 X 32.95</b>		<b>Weight Minimum 2860</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 018 Inches</b>		
	48	125F15	875	40.7	38.31	23.62	30.50	3170	M2502412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	125C15	875	40.7	38.31	23.62	30.50	3084	M2602412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	140T15	980	45.6	38.31	23.62	30.50	3283	M2802414015B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
<b>BTMDZ15</b>	<b>VERY NARROW AISLE - MAN DOWN TRUCK</b>							<b>48 VOLTS , 44.90 X 24.25 X 32.95</b>		<b>Weight Minimum 2860</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 018 Inches</b>		
	48	125F15	875	40.7	38.31	23.62	30.50	3170	M2502412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	125C15	875	40.7	38.31	23.62	30.50	3084	M2602412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	140T15	980	45.6	38.31	23.62	30.50	3283	M2802414015B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Linde Baker Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
346SeriesE18/E20	3-Wheel Sit-down Rider		36 VOLTS , 38.98 X 25.59 X 25.91 Weight Minimum 2161 Connector SB350 GRAY , Position A , Lead Length 024 Inches												
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
346SeriesE18/E20	3-Wheel Sit-down Rider		48 VOLTS , 38.31 X 12.36 X 25.63 Weight Minimum 2647 Connector SB350 BLUE , Position A , Lead Length 024 Inches												
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
346SeriesE18/E20	3-Wheel Sit-down Rider		48 VOLTS , 38.31 X 23.63 X 25.63 Weight Minimum 2161 Connector SB350 GRAY , Position A , Lead Length 024 Inches												
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
346SeriesE18/E20	3-Wheel Sit-down Rider		480 VOLTS , 38.31 X 12.36 X 25.63 Weight Minimum 2647 Connector SB350 GRAY , Position A , Lead Length 024 Inches												
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
E18C	COUNTERBALANCE - 3 WHEEL		48 VOLTS , 33.00 X 29.50 X 24.50 Weight Minimum 2233 Connector SB350 BLUE , Position A , Lead Length 030 Inches												
	48	085C13	510	23.7	32.63	29.00	22.63	2253	M2602408513Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T13	600	27.9	32.56	28.88	22.63	2386	M2802410013Z25	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
BFE40	FOUR WHEEL		48 VOLTS , 39.10 X 21.50 X 31.20 Weight Minimum 2700 Connector SB350 BLUE , Position A , Lead Length 030 Inches												
	48	125F13	750	34.9	38.31	20.69	30.50	2792	M2502412513B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	125C13	750	34.9	38.13	20.68	30.50	2727	M2602412513B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	140T13	840	39.1	38.13	20.68	30.50	2900	M2802414013B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
BFE50	FOUR WHEEL		36 VOLTS , 39.10 X 24.80 X 31.20 Weight Minimum 2683 Connector SB350 GRAY , Position A , Lead Length 030 Inches												
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
BFE50	FOUR WHEEL		48 VOLTS , 39.10 X 24.80 X 31.20 Weight Minimum 2683 Connector SB350 BLUE , Position A , Lead Length 030 Inches												
	48	125F15	875	40.7	38.31	23.62	30.50	3170	M2502412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	125C15	875	40.7	38.31	23.62	30.50	3084	M2602412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	140T15	980	45.6	38.31	23.62	30.50	3283	M2802414015B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
BFE60	FOUR WHEEL		36 VOLTS , 39.10 X 30.30 X 31.20 Weight Minimum 3350 Connector SB350 GRAY , Position A , Lead Length 030 Inches												
	36	125C23	1375	48.0	38.44	26.88	30.50	3573	M2601812523B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
BFE60	FOUR WHEEL		48 VOLTS , 39.10 X 30.30 X 31.20 Weight Minimum 3350 Connector SB350 BLUE , Position A , Lead Length 030 Inches												
	48	125C17	1000	46.6	38.44	26.88	30.50	3636	M2602412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	125F17	1000	46.6	38.44	26.88	30.50	3763	M2502412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	140T17	1120	52.1	38.44	26.88	30.50	3862	M2802414017B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
BFE80	FOUR WHEEL		36 VOLTS , 39.10 X 35.20 X 31.20 Weight Minimum 3770 Connector SB350 GRAY , Position A , Lead Length 030 Inches												
	36	100C29	1400	48.9	38.93	33.87	25.63	3842	M2601810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
BFE80	FOUR WHEEL							48 VOLTS , 39.10 X 35.20 X 31.20		Weight Minimum 3770	Connector SB350	BLUE	, Position A , Lead Length 030 Inches		
	48	125C19	1125	52.4	38.44	29.75	30.50	3967	M2602412519B	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
E20B	FOUR WHEEL							36 VOLTS , 39.10 X 21.50 X 31.20		Weight Minimum 2439	Connector SB350	GRAY	, Position A , Lead Length 030 Inches		
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
E20B	FOUR WHEEL							48 VOLTS , 39.10 X 21.50 X 31.20		Weight Minimum 2439	Connector SB350	BLUE	, Position A , Lead Length 030 Inches		
	48	125F13	750	34.9	38.31	20.69	30.50	2792	M2502412513B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	125C13	750	34.9	38.13	20.68	30.50	2727	M2602412513B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	140T13	840	39.1	38.13	20.68	30.50	2900	M2802414013B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
E30B	FOUR WHEEL							36 VOLTS , 39.10 X 30.30 X 31.20		Weight Minimum 3350	Connector SB350	GRAY	, Position A , Lead Length 030 Inches		
	36	125C23	1375	48.0	38.44	26.88	30.50	3573	M2601812523B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
E30B	FOUR WHEEL							48 VOLTS , 39.10 X 30.30 X 31.20		Weight Minimum 3350	Connector SB350	BLUE	, Position A , Lead Length 030 Inches		
	48	125C17	1000	46.6	38.44	26.88	30.50	3636	M2602412517B	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	125F17	1000	46.6	38.44	26.88	30.50	3763	M2502412517B	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	140T17	1120	52.1	38.44	26.88	30.50	3862	M2802414017B	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
E20P	FOUR WHEEL SIT-DOWN							48 VOLTS , 33.00 X 25.90 X 31.25		Weight Minimum 2465	Connector SB350	BLUE	, Position A , Lead Length 030 Inches		
	48	125C13	750	34.9	32.25	25.63	30.50	2734	M2602412513A6	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
BTE/S30	3-WHEEL SIT DOWN RIDER							36 VOLTS , 32.67 X 29.29 X 25.82		Weight Minimum 2215	Connector SB350	GRAY	, Position A , Lead Length 030 Inches		
	36	100C17	800	27.9	31.93	26.62	25.62	2210	M2601810017J	N	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
BTE/S35	3-WHEEL SIT DOWN RIDER							36 VOLTS , 32.67 X 28.30 X 25.82		Weight Minimum 2215	Connector SB350	GRAY	, Position A , Lead Length 030 Inches		
	36	100C17	800	27.9	31.93	26.62	25.62	2210	M2601810017J	N	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
BTE30	3-WHEEL SIT DOWN RIDER							24 VOLTS , 32.67 X 20.10 X 26.80		Weight Minimum 1525	Connector SB350	RED	, Position A , Lead Length 030 Inches		
	24	100C19	900	21.0	29.75	19.38	25.63	1648	M2601210019C	N	( CALL )	SCR20012965S1H	SCR20012965T1H	( CALL )	( CALL )
E15	3-WHEEL SIT DOWN RIDER							24 VOLTS , 33.00 X 20.25 X 26.00		Weight Minimum 1525	Connector SB350	RED	, Position A , Lead Length 030 Inches		
	24	100C19	900	21.0	29.75	19.38	25.63	1648	M2601210019C	N	( CALL )	SCR20012965S1H	SCR20012965T1H	( CALL )	( CALL )
E15S	3-WHEEL SIT DOWN RIDER							36 VOLTS , 33.00 X 29.50 X 26.00		Weight Minimum 2215	Connector SB350	GRAY	, Position A , Lead Length 030 Inches		
	36	100C17	800	27.9	31.93	26.62	25.62	2210	M2601810017J	N	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
E15S	3-WHEEL SIT DOWN RIDER							48 VOLTS , 33.00 X 29.50 X 26.00		Weight Minimum 2215	Connector SB350	BLUE	, Position A , Lead Length 030 Inches		
	48	100C13	600	27.9	32.25	28.00	25.63	2449	M2602410013A6A	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	100F13	600	27.9	32.25	28.00	25.63	2552	M2502410013A6A	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
E16	3-WHEEL SIT DOWN RIDER							36 VOLTS , 33.00 X 28.50 X 26.00		Weight Minimum 2215	Connector SB350	GRAY	, Position A , Lead Length 030 Inches		
	36	100C17	800	27.9	31.93	26.62	25.62	2210	M2601810017J	N	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
E16	3-WHEEL SIT DOWN RIDER							48 VOLTS , 33.00 X 28.50 X 26.00		Weight Minimum 2215	Connector SB350	BLUE	, Position A , Lead Length 030 Inches		
	48	100C13	600	27.9	32.25	28.00	25.63	2449	M2602410013A6A	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	100F13	600	27.9	32.25	28.00	25.63	2552	M2502410013A6A	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
E20C28"	4 Wheel Sit-Down		36 VOLTS , 38.70 X 27.80 X 23.40		Weight Minimum 1942			Connector SB350	GRAY	, Position A , Lead Length 030 Inches						
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
E20C28"	4 Wheel Sit-Down		48 VOLTS , 38.70 X 27.80 X 23.40		Weight Minimum 1942			Connector SB350	BLUE	, Position A , Lead Length 030 Inches						
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
E20C30"	4 Wheel Sit-Down		36 VOLTS , 38.70 X 30.30 X 23.40		Weight Minimum 2740			Connector SB350	GRAY	, Position A , Lead Length 030 Inches						
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
E20C30"	4 Wheel Sit-Down		48 VOLTS , 38.70 X 30.30 X 23.40		Weight Minimum 2740			Connector SB350	BLUE	, Position A , Lead Length 030 Inches						
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
E25C28"	4 Wheel Sit-Down		36 VOLTS , 38.70 X 27.80 X 23.40		Weight Minimum 1942			Connector SB350	GRAY	, Position A , Lead Length 030 Inches						
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
E25C28"	4 Wheel Sit-Down		48 VOLTS , 38.70 X 27.80 X 23.40		Weight Minimum 1942			Connector SB350	BLUE	, Position A , Lead Length 030 Inches						
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
E25C30"	4 Wheel Sit-Down		36 VOLTS , 38.70 X 30.30 X 23.40		Weight Minimum 2740			Connector SB350	GRAY	, Position A , Lead Length 030 Inches						
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
E25C30"	4 Wheel Sit-Down		48 VOLTS , 38.70 X 30.30 X 23.40		Weight Minimum 2740			Connector SB350	BLUE	, Position A , Lead Length 030 Inches						
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>E25C34"</b>	<b>4 Wheel Sit-Down</b>		<b>36 VOLTS , 38.70 X 34.30 X 23.40 Weight Minimum 3060 Connector SB350 GRAY , Position A , Lead Length 030 Inches</b>												
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
<b>E25C34"</b>	<b>4 Wheel Sit-Down</b>		<b>48 VOLTS , 38.70 X 34.30 X 23.40 Weight Minimum 3060 Connector SB350 BLUE , Position A , Lead Length 030 Inches</b>												
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
<b>E30C30"</b>	<b>4 Wheel Sit-Down</b>		<b>36 VOLTS , 38.70 X 30.30 X 23.40 Weight Minimum 2740 Connector SB350 GRAY , Position A , Lead Length 030 Inches</b>												
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
<b>E30C30"</b>	<b>4 Wheel Sit-Down</b>		<b>48 VOLTS , 38.70 X 30.30 X 23.40 Weight Minimum 2740 Connector SB350 BLUE , Position A , Lead Length 030 Inches</b>												
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
<b>E30C34"</b>	<b>4 Wheel Sit-Down</b>		<b>36 VOLTS , 38.70 X 34.30 X 23.40 Weight Minimum 3060 Connector SB350 GRAY , Position A , Lead Length 030 Inches</b>												
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
<b>E30C34"</b>	<b>4 Wheel Sit-Down</b>		<b>48 VOLTS , 38.70 X 34.30 X 23.40 Weight Minimum 3060 Connector SB350 BLUE , Position A , Lead Length 030 Inches</b>												
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
<b>E25P/600,E25S/600</b>	<b>4 WHEEL</b>		<b>80 VOLTS , 40.70 X 33.90 X 33.00 Weight Minimum 4127 Connector SB350 YELLOW , Position A , Lead Length 030 Inches</b>												
	80	125C11	625	48.5	40.50	33.21	30.50	4180	M2604012511X7625	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)