

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
PW23 / PW30 (NO COVER)	CLASS III LOW-LIFT WALKIE PALLET (PLATFORM)		24 VOLTS , 25.74 X 9.37 X 26.57			Weight Minimum 155		Connector SB175		GRAY , Position B , Lead Length 018 Inches					
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	MSB	195	.0	25.25	8.50	25.26	400	M90004S24CHPTM	N	(CALL)			(CALL)	(CALL)
PW30L (NO COVER)	CLASS III LOW-LIFT WALKIE PALLET (PLATFORM)		24 VOLTS , 32.00 X 13.58 X 31.29			Weight Minimum 431		Connector SB175		GRAY , Position B , Lead Length 018 Inches					
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	MSB	195	.0	25.25	8.50	25.26	400	M90004S24CHPTM	N	(CALL)			(CALL)	(CALL)
PMWR30 / PMWR30N / PMWR40	CLASS III LOW-LIFT WALKIE RIDER/PALLET		24 VOLTS , 32.00 X 13.58 X 31.29			Weight Minimum 933		Connector SB175		GRAY , Position B , Lead Length 018 Inches					
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B13	630	14.8	30.88	12.88	26.73	1250	M2101210513N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
PWT13	CLASS III WALKIE HIGHLIFT STRADDLE		24 VOLTS , 25.70 X 8.35 X 27.36			Weight Minimum 536		Connector SB175		GRAY , Position A , Lead Length 032 Inches					
	24	085L05	170	4.0	25.25	7.81	22.63	523	M2901208505G7	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T05	200	4.7	25.25	7.81	22.63	540	M2801210005G7	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F05	170	4.0	25.25	7.85	22.63	527	M2501208505G7	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.25	7.81	22.63	514	M2601208505G7	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
PWT15 / PWT18	CLASS III WALKIE HIGHLIFT STRADDLE		24 VOLTS , 25.70 X 11.50 X 27.36			Weight Minimum 536		Connector SB175		GRAY , Position A , Lead Length 032 Inches					
	24	100T09	400	9.3	25.27	10.88	22.63	728	M2801210009D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L09	340	7.9	25.27	10.88	22.63	704	M2901208509D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085C09	340	7.9	25.27	10.88	22.63	686	M2601208509D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
EOP11N2	CLASS II ORDER PICKER		24 VOLTS , 33.20 X 17.70 X 32.10			Weight Minimum 2200		Connector SB350		RED , Position C , Lead Length 012 Inches					
	24	140T13	700	16.3	32.75	17.13	30.50	2150	M2801214013A7D	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	32.75	17.13	30.50	2093	M2901212513A7D	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F13	750	17.5	32.75	17.13	30.50	2105	M2501212513A7D	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	32.75	17.13	30.50	2061	M2601212513A7D	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
EOP15HN2	CLASS II ORDER PICKER		24 VOLTS , 37.20 X 21.20 X 32.10			Weight Minimum 3000		Connector SB350		RED , Position C , Lead Length 012 Inches					
	24	140T17	1120	26.1	36.25	20.63	30.50	2451	M2801214017C7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	36.25	20.63	30.50	2157	M2901212517C7	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	36.25	20.63	30.50	2172	M2501212517C7	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	36.25	20.63	30.50	2115	M2601212517C7	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
ESR15/18/20N/EDR13N/ESS15	CLASS II NARROW AISLE REACH			36 VOLTS , 38.60 X 14.25 X 31.65											Weight Minimum 1600	Connector N/A	N/A	, Position B , Lead Length 025 Inches
	36	125L11	625	21.8	38.25	13.50	30.50	1825	M2901812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F11	625	21.8	38.06	13.50	30.50	1899	M2501812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C11	625	21.8	38.00	13.25	30.50	1836	M2601812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
ESR15/18/20N/EDR13N/ESS15/20N	CLASS II NARROW AISLE REACH			24 VOLTS , 38.60 X 14.25 X 31.65											Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 025 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)			
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)			
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)			
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)			
ESR15/18/20N/EDR13N/ESS15/20N	CLASS II NARROW AISLE REACH			24 VOLTS , 38.60 X 16.25 X 31.65											Weight Minimum 2000	Connector SB350	RED	, Position B , Lead Length 025 Inches
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)			
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)			
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)			
	24	125C19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)			
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)			
ESR15/18/20N/EDR13N/ESS15/20N	CLASS II NARROW AISLE REACH			36 VOLTS , 38.60 X 16.25 X 31.65											Weight Minimum 2000	Connector N/A	N/A	, Position B , Lead Length 025 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
FB16PNT	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.60 X 20.80 X 24.80											Weight Minimum 1910	Connector SB350	GRAY	, Position B , Lead Length 020 Inches
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)			
FB16PNT	CLASS I 3 WHEEL COUNTERBALANCED			48 VOLTS , 39.60 X 20.80 X 24.80											Weight Minimum 1910	Connector SB350	GRAY	, Position B , Lead Length 020 Inches
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F13	510	23.7	38.62	20.50	23.00	2419	M2502408513B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C13	510	23.7	38.62	20.50	22.62	1940	M2602408513B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
FB18PNT / FB20PNT	CLASS I 3 WHEEL COUNTERBALANCED			36 VOLTS , 39.60 X 25.10 X 24.80											Weight Minimum 2200	Connector SB350	GRAY	, Position B , Lead Length 020 Inches
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
FB18PNT / FB20PNT	CLASS I 3 WHEEL COUNTERBALANCED			48 VOLTS , 39.60 X 25.10 X 24.80											Weight Minimum 2200	Connector SB350	GRAY	, Position B , Lead Length 020 Inches
	48	100T15	700	32.6	38.56	23.88	22.88	2501	M2802410015B7	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	085L15	595	27.7	38.56	23.88	22.88	2400	M2902408515B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085F15	595	27.7	38.56	23.88	22.88	2419	M2502408515B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C15	595	27.7	38.31	23.63	22.63	2308	M2602408515B7	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
FBC15N / FBC18N	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 35.70 X 27.90 X 23.30											
			Weight Minimum 1650 Connector SB350 GRAY , Position B , Lead Length 024 Inches												
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100G15	700	24.7	35.30	26.00	19.68	2055	M8901810015AA059	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
FBC15N / FBC18N	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 35.70 X 27.90 X 23.30											
			Weight Minimum 1650 Connector SB350 GRAY , Position B , Lead Length 024 Inches												
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
FBC22N2	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.50 X 30.50 X 23.30											
			Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 024 Inches												
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
FBC22N2	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 39.50 X 30.50 X 23.30											
			Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 024 Inches												
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
FBC25N2	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.50 X 30.50 X 23.30											
			Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 024 Inches												
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
FBC25N2	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 39.50 X 30.50 X 23.30											
			Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 024 Inches												
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
FBC25EN2/25LN2/30N2/30LN2	CLASS I 4 WHEEL COUNTERBALANCED			36 VOLTS , 39.50 X 34.20 X 22.70											
			Weight Minimum 3100 Connector SB350 GRAY , Position B , Lead Length 024 Inches												
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
FBC25EN2/25LN2/30N2/30LN2	CLASS I 4 WHEEL COUNTERBALANCED			48 VOLTS , 39.50 X 34.20 X 22.70								Weight Minimum 3100	Connector SB350	GRAY , Position B , Lead Length 024 Inches			
	48	100T21	1000	46.6	38.75	33.00	22.63	3441	M2802410021B1	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	085F21	850	39.6	38.75	33.00	22.63	3332	M2502408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085C21	850	39.6	38.75	33.00	22.63	3222	M2602408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)		
FBC15NS / FBC18NS	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 14.25 X 31.70								Weight Minimum 1700	Connector SB350	GRAY , Position C , Lead Length 020 Inches			
	36	140T11	700	24.4	38.06	13.50	30.50	1972	M2801814011B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125L11	625	21.8	38.25	13.50	30.50	1825	M2901812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F11	625	21.8	38.06	13.50	30.50	1899	M2501812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125C11	625	21.8	38.00	13.25	30.50	1836	M2601812511B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
FBC15NS / FBC18NS	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 16.25 X 31.70								Weight Minimum 2000	Connector SB350	GRAY , Position C , Lead Length 020 Inches			
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
FBC15NS / FBC18NS / FBC20NS	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 18.25 X 31.70								Weight Minimum 2300	Connector SB350	GRAY , Position C , Lead Length 020 Inches			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
FBC20NS	CLASS I STAND-UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.60 X 21.25 X 31.70								Weight Minimum 2600	Connector SB350	GRAY , Position C , Lead Length 020 Inches			
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)