



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>SPB60</b>	<b>LOW LIFT WALKIE/RIDER</b>		<b>24 VOLTS , 32.00 X 13.50 X 31.00 Weight Minimum 854 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>SPB80</b>	<b>LOW LIFT WALKIE/RIDER</b>		<b>24 VOLTS , 32.00 X 13.50 X 31.00 Weight Minimum 854 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>SPN60</b>	<b>LOW LIFT WALKIE/RIDER</b>		<b>24 VOLTS , 32.00 X 13.50 X 31.00 Weight Minimum 854 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
SPN80	LOW LIFT WALKIE/RIDER		24 VOLTS , 32.00 X 13.50 X 31.00 Weight Minimum 854 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
WC-30	WALKIE COUNTERBALANCE		12 VOLTS , 32.00 X 8.25 X 31.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
WC-30	WALKIE COUNTERBALANCE		24 VOLTS , 32.00 X 13.50 X 31.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
WC-40	WALKIE COUNTERBALANCE		12 VOLTS , 32.00 X 8.25 X 31.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
WC-40	WALKIE COUNTERBALANCE		24 VOLTS , 32.00 X 13.50 X 31.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
WCN-30	WALKIE COUNTERBALANCE		12 VOLTS , 32.00 X 8.25 X 31.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
WCN-30	WALKIE COUNTERBALANCE		24 VOLTS , 32.00 X 13.50 X 31.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
WCN-40	WALKIE COUNTERBALANCE		12 VOLTS , 32.00 X 8.25 X 999.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
WCN-40	WALKIE COUNTERBALANCE		24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
WCN20	WALKIE COUNTERBALANCE		12 VOLTS , 32.00 X 8.25 X 999.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
EWP2-45	WALKIE PALLET		24 VOLTS , 28.50 X 9.00 X 40.00 Weight Minimum 200 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	090G07	270	6.4	27.50	8.58	25.82	625	M8901209007EPP059	Y	(CALL)			(CALL)	(CALL)
EWP45	WALKIE PALLET		24 VOLTS , 28.30 X 9.00 X 24.00 Weight Minimum 350 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	090G07	270	6.4	27.50	8.58	25.82	625	M8901209007EPP059	Y	(CALL)			(CALL)	(CALL)
EWP45	WALKIE PALLET		24 VOLTS , 31.30 X 9.00 X 24.00 Weight Minimum 350 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	(CALL)			(CALL)	(CALL)
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
WPN40	WALKIE PALLET		12 VOLTS , 32.00 X 8.25 X 999.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>WPN40</b>	<b>WALKIE PALLET</b>		<b>24 VOLTS , 32.00 X 13.50 X 999.00</b>										<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>WPN60</b>	<b>WALKIE PALLET</b>		<b>12 VOLTS , 32.00 X 8.25 X 999.00</b>										<b>Weight Minimum 410</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
<b>WPN60</b>	<b>WALKIE PALLET</b>		<b>24 VOLTS , 32.00 X 13.50 X 999.00</b>										<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
WPN80	WALKIE PALLET		12 VOLTS , 32.00 X 8.25 X 999.00 Weight Minimum 410 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
WPN80	WALKIE PALLET		24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
EWSN20	WALKIE STRADDLE		24 VOLTS , 27.40 X 9.00 X 999.00 Weight Minimum 350 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
EWSN25	WALKIE STRADDLE		24 VOLTS , 27.40 X 9.00 X 999.00 Weight Minimum 350 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
WS-30	WALKIE STRADDLE		12 VOLTS , 34.50 X 8.25 X 31.00													Weight Minimum 410	Connector SB175	GRAY	, Position B	, Lead Length 020 Inches
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)			(CALL)	(CALL)					
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
WS-30	WALKIE STRADDLE		24 VOLTS , 34.50 X 13.50 X 31.00													Weight Minimum 960	Connector SB175	GRAY	, Position B	, Lead Length 020 Inches
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)					
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
WS-40	WALKIE STRADDLE		12 VOLTS , 34.50 X 8.25 X 31.00													Weight Minimum 410	Connector SB175	GRAY	, Position B	, Lead Length 020 Inches
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)			(CALL)	(CALL)					
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
WS-40	WALKIE STRADDLE		24 VOLTS , 34.50 X 13.50 X 31.00						Weight Minimum 960	Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
WSN-30	WALKIE STRADDLE		12 VOLTS , 34.50 X 8.25 X 31.00						Weight Minimum 410	Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)			(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
WSN-30	WALKIE STRADDLE		24 VOLTS , 34.50 X 13.50 X 31.00						Weight Minimum 960	Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
WSN-40	WALKIE STRADDLE		12 VOLTS , 34.50 X 8.25 X 31.00													Weight Minimum 410	Connector SB175	GRAY	, Position B	, Lead Length 020 Inches
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)			(CALL)	(CALL)					
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
WSN-40	WALKIE STRADDLE		24 VOLTS , 34.50 X 13.50 X 31.00													Weight Minimum 960	Connector SB175	GRAY	, Position B	, Lead Length 020 Inches
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)					
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
WSN30	WALKIE STRADDLE		12 VOLTS , 30.87 X 8.25 X 31.00													Weight Minimum 410	Connector SB175	GRAY	, Position B	, Lead Length 020 Inches
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)			(CALL)	(CALL)					
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
WSN30	WALKIE STRADDLE		24 VOLTS , 30.87 X 13.50 X 31.00						Weight Minimum 960	Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
WSN40	WALKIE STRADDLE		12 VOLTS , 30.87 X 8.25 X 31.00						Weight Minimum 410	Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
WSN40	WALKIE STRADDLE		24 VOLTS , 30.87 X 13.50 X 31.00						Weight Minimum 960	Connector SB175	GRAY	, Position B , Lead Length 020 Inches				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
<b>RPB-60</b>	<b>WALKIE-RIDER</b>		<b>24 VOLTS , 31.00 X 13.25 X 31.62</b>										<b>Weight Minimum 900</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B</b>	<b>, Lead Length 020 Inches</b>
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
<b>RPB-80</b>	<b>WALKIE-RIDER</b>		<b>24 VOLTS , 31.00 X 13.25 X 31.62</b>										<b>Weight Minimum 900</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B</b>	<b>, Lead Length 020 Inches</b>
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
<b>RPN-60</b>	<b>WALKIE-RIDER</b>		<b>24 VOLTS , 31.00 X 13.25 X 31.62</b>										<b>Weight Minimum 900</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B</b>	<b>, Lead Length 020 Inches</b>
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>RPN-80</b>	<b>WALKIE-RIDER</b>		<b>24 VOLTS , 31.00 X 13.25 X 31.62 Weight Minimum 900 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>WPB-60</b>	<b>WALKIE-RIDER</b>		<b>24 VOLTS , 31.00 X 13.25 X 31.62 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>WPB-80</b>	<b>WALKIE-RIDER</b>		<b>24 VOLTS , 31.00 X 13.25 X 31.62 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
WPN-60	WALKIE-RIDER		24 VOLTS , 31.00 X 13.25 X 31.62 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
WPN-80	WALKIE-RIDER		24 VOLTS , 31.00 X 13.25 X 31.62 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
WRPN40	WALKIE-RIDER		24 VOLTS , 30.87 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
<b>WRPN60</b>	<b>WALKIE-RIDER</b>		<b>24 VOLTS , 30.87 X 13.50 X 999.00</b>										<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>		
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
<b>WRPN80</b>	<b>WALKIE-RIDER</b>		<b>24 VOLTS , 30.87 X 13.50 X 999.00</b>										<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>		
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
<b>DGN24</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 31.75 X 13.50 X 24.00</b>										<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>		
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>DGN24D</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 31.75 X 13.50 X 24.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>SGN200</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 32.00 X 13.50 X 31.00 Weight Minimum 854 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>SGN24</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>SGN24D</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>SGN24DF</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>SGN24F</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>SGXN60</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>SGXN80</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>SHGN24</b>	<b>WALKIE/RIDER PALLET TRUCK</b>		<b>24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
SHGN24F	WALKIE/RIDER PALLET TRUCK		24 VOLTS , 32.00 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
WSRN30	WALKIE/RIDER PALLET TRUCK		24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
SGB	WALKIE/RIDER TOW TRACTOR		24 VOLTS , 32.00 X 13.50 X 31.00 Weight Minimum 854 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
SCX30N	CLASS II NARROW AISLE REACH		36 VOLTS , 38.50 X 18.40 X 32.00 Weight Minimum 2175 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
SCX30SN	CLASS II NARROW AISLE REACH		36 VOLTS , 38.50 X 16.30 X 32.00			Weight Minimum 1885		Connector SB350	GRAY	, Position B , Lead Length 014 Inches					
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
SCX35N	CLASS II NARROW AISLE REACH		36 VOLTS , 38.50 X 18.40 X 32.00			Weight Minimum 2175		Connector SB350	GRAY	, Position B , Lead Length 014 Inches					
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965S1H	SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965S1H	SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965S1H	SCR20018965T1H	(CALL)	(CALL)
SCX40N	CLASS II NARROW AISLE REACH		36 VOLTS , 38.50 X 20.50 X 32.00			Weight Minimum 2460		Connector SB350	GRAY	, Position B , Lead Length 014 Inches					
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
RCOSN	RIDER COUNTERBALANCE ORDER SELECTOR		24 VOLTS , 38.80 X 14.50 X 32.00			Weight Minimum 1100		Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.25	14.00	30.50	1642	M2601212515B06B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	140T15	980	22.8	38.25	14.00	30.50	1667	M2801214015B06B	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
RCOSN	RIDER COUNTERBALANCE ORDER SELECTOR		36 VOLTS , 38.80 X 14.50 X 32.00			Weight Minimum 1600		Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ORDR30	RIDER DEEP REACH		36 VOLTS , 38.80 X 16.20 X 32.00			Weight Minimum 1900		Connector SB350	GRAY	, Position B , Lead Length 014 Inches					
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ORDR30	RIDER DEEP REACH		36 VOLTS , 38.80 X 18.50 X 32.00			Weight Minimum 2175		Connector SB350	GRAY	, Position B , Lead Length 014 Inches					
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965S1H	SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965S1H	SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965S1H	SCR20018965T1H	(CALL)	(CALL)
ORDR30	RIDER DEEP REACH		36 VOLTS , 38.80 X 21.00 X 32.00			Weight Minimum 2460		Connector SB350	GRAY	, Position B , Lead Length 014 Inches					
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)	SCR20018965S1H	SCR20018965T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>RRN30D</b>	<b>RIDER DEEP REACH</b>		<b>36 VOLTS , 38.80 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 014 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>RRN30D</b>	<b>RIDER DEEP REACH</b>		<b>36 VOLTS , 38.80 X 20.90 X 32.00 Weight Minimum 2400 Connector SB350 GRAY , Position B , Lead Length 014 Inches</b>												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
<b>OR35</b>	<b>RIDER REACH</b>		<b>24 VOLTS , 38.80 X 13.40 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 014 Inches</b>												
	24	055B29	770	18.1	37.08	13.50	29.87	1630	M2101205529FB7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
<b>OR35</b>	<b>RIDER REACH</b>		<b>36 VOLTS , 38.80 X 13.40 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 014 Inches</b>												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>OR35</b>	<b>RIDER REACH</b>		<b>36 VOLTS , 38.80 X 16.20 X 32.00 Weight Minimum 1900 Connector SB350 GRAY , Position B , Lead Length 014 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>OR40</b>	<b>RIDER REACH</b>		<b>24 VOLTS , 38.80 X 13.40 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 014 Inches</b>												
	24	055B29	770	18.1	37.08	13.50	29.87	1630	M2101205529FB7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
<b>OR40</b>	<b>RIDER REACH</b>		<b>36 VOLTS , 38.80 X 13.40 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 014 Inches</b>												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>OR40</b>	<b>RIDER REACH</b>		<b>36 VOLTS , 38.80 X 16.20 X 32.00 Weight Minimum 1900 Connector SB350 GRAY , Position B , Lead Length 014 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>OR45</b>	<b>RIDER REACH</b>		<b>36 VOLTS , 38.80 X 16.20 X 32.00 Weight Minimum 1900 Connector SB350 GRAY , Position B , Lead Length 014 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
OR45	RIDER REACH		36 VOLTS , 38.80 X 18.50 X 32.00													Weight Minimum 2175	Connector SB350	GRAY	, Position B , Lead Length 014 Inches
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
OR45	RIDER REACH		36 VOLTS , 38.80 X 21.00 X 32.00													Weight Minimum 2460	Connector SB350	GRAY	, Position B , Lead Length 014 Inches
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
RRN35	RIDER REACH		24 VOLTS , 38.80 X 14.40 X 32.00													Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 020 Inches
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C15	875	20.4	38.25	14.00	30.50	1642	M2601212515B06B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	140T15	980	22.8	38.25	14.00	30.50	1667	M2801214015B06B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
RRN35	RIDER REACH		24 VOLTS , 38.80 X 16.40 X 32.00													Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 020 Inches
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)				
RRN35	RIDER REACH		36 VOLTS , 38.80 X 14.40 X 32.00													Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 020 Inches
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
RRN35	RIDER REACH		36 VOLTS , 38.80 X 16.40 X 32.00													Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 020 Inches
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
RRN45	RIDER REACH		36 VOLTS , 38.80 X 16.40 X 32.00													Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 014 Inches
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
RRN45	RIDER REACH		36 VOLTS , 38.80 X 20.90 X 32.00													Weight Minimum 2400	Connector SB350	GRAY	, Position B , Lead Length 014 Inches
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
RSN40	RIDER STRADDLE		24 VOLTS , 38.80 X 14.40 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.25	14.00	30.50	1642	M2601212515B06B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	140T15	980	22.8	38.25	14.00	30.50	1667	M2801214015B06B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
RSN40	RIDER STRADDLE		24 VOLTS , 38.80 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
RSN40	RIDER STRADDLE		36 VOLTS , 38.80 X 14.40 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
RSN40	RIDER STRADDLE		36 VOLTS , 38.80 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
RSN50	RIDER STRADDLE		36 VOLTS , 38.80 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
RSN50	RIDER STRADDLE		36 VOLTS , 38.80 X 20.90 X 32.00 Weight Minimum 2400 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
OSN30	STAND-UP COUNTERBALANCE		24 VOLTS , 36.25 X 13.90 X 31.50 Weight Minimum 1650 Connector SB350 RED , Position C , Lead Length 015 Inches												
	24	125F15	875	20.4	35.25	13.06	30.50	1662	M2501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	13.06	30.50	1606	M2601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
OS25S	STAND-UP COUNTERBALANCE		36 VOLTS , 38.80 X 13.90 X 32.00 Weight Minimum 1280 Connector SB350 GRAY , Position D , Lead Length 012 Inches												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>OS30</b>	<b>STAND-UP COUNTERBALANCE</b>		<b>36 VOLTS , 38.80 X 16.10 X 32.00</b>													
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>OS30S</b>	<b>STAND-UP COUNTERBALANCE</b>		<b>36 VOLTS , 38.80 X 13.90 X 32.00</b>													
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>OS35</b>	<b>STAND-UP COUNTERBALANCE</b>		<b>36 VOLTS , 38.80 X 18.40 X 32.00</b>													
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
<b>OS45</b>	<b>STAND-UP COUNTERBALANCE</b>		<b>36 VOLTS , 38.80 X 20.80 X 32.00</b>													
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)	
<b>OS50</b>	<b>STAND-UP COUNTERBALANCE</b>		<b>36 VOLTS , 38.80 X 20.80 X 32.00</b>													
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)	
<b>BXP30</b>	<b>SIT DOWN RIDER</b>		<b>48 VOLTS , 38.81 X 26.56 X 18.78</b>													
	48	060C15	420	19.6	38.58	26.38	18.77	1748	M2602406015B33A	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
<b>BXP30L</b>	<b>SIT DOWN RIDER</b>		<b>48 VOLTS , 38.81 X 33.85 X 18.78</b>													
	48	060C19	540	25.1	38.58	33.66	18.78	2240	M2602406019B33	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
<b>BXP30S</b>	<b>SIT DOWN RIDER</b>		<b>48 VOLTS , 38.81 X 23.81 X 18.78</b>													
	48	060C15	420	19.6	38.58	23.63	18.77	1709	M2602406015B33	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
<b>BXP35</b>	<b>SIT DOWN RIDER</b>		<b>48 VOLTS , 38.81 X 26.56 X 18.78</b>													
	48	060C15	420	19.6	38.58	26.38	18.77	1748	M2602406015B33A	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
<b>BXP35L</b>	<b>SIT DOWN RIDER</b>		<b>48 VOLTS , 38.81 X 33.85 X 18.78</b>													
	48	060C19	540	25.1	38.58	33.66	18.78	2240	M2602406019B33	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
<b>BXP35S</b>	<b>SIT DOWN RIDER</b>		<b>48 VOLTS , 38.81 X 23.81 X 18.78</b>													
	48	060C15	420	19.6	38.58	23.63	18.77	1709	M2602406015B33	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)





# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>BXP40</b>	<b>SIT DOWN RIDER</b>														
	48 VOLTS , 38.81 X 33.85 X 18.78											Weight Minimum 1770 Connector SB350 GRAY , Position B , Lead Length 025 Inches			
	48	060C19	540	25.1	38.58	33.66	18.78	2240	M2602406019B33	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
<b>BXP40L</b>	<b>SIT DOWN RIDER</b>														
	48 VOLTS , 38.81 X 39.96 X 22.83											Weight Minimum 2535 Connector SB350 GRAY , Position B , Lead Length 025 Inches			
	48	085C25	1020	47.5	38.58	39.76	23.10	3700	M2602408525B33	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
<b>BXP50</b>	<b>SIT DOWN RIDER</b>														
	48 VOLTS , 38.81 X 33.85 X 18.78											Weight Minimum 1973 Connector SB350 GRAY , Position B , Lead Length 025 Inches			
	48	060C21	600	27.9	38.58	33.66	18.77	2394	M2602406021B33	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
<b>BXP50L</b>	<b>SIT DOWN RIDER</b>														
	48 VOLTS , 38.81 X 39.96 X 22.83											Weight Minimum 2535 Connector SB350 GRAY , Position B , Lead Length 025 Inches			
	48	085C25	1020	47.5	38.58	39.76	23.10	3700	M2602408525B33	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
<b>BX50EE</b>	<b>SIT DOWN RIDER</b>														
	36 VOLTS , 39.10 X 28.30 X 23.40											Weight Minimum 2490 Connector SB350 GRAY , Position B , Lead Length 018 Inches			
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
<b>BX50EE</b>	<b>SIT DOWN RIDER</b>														
	48 VOLTS , 39.10 X 28.30 X 23.40											Weight Minimum 2490 Connector SB350 GRAY , Position B , Lead Length 018 Inches			
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	060B21	600	28.2	38.50	27.25	23.11	2666	M2102406021DB75982	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
<b>LASERPE30Y</b>	<b>SIT DOWN RIDER</b>														
	36 VOLTS , 35.20 X 26.70 X 23.00											Weight Minimum 1840 Connector SB350 GRAY , Position B , Lead Length 014 Inches			
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	105B13	630	22.2	35.00	25.62	22.38	1954	M2101810513K	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	( CALL )		SCR20018965T1H	( CALL )	( CALL )
<b>LASERPE30Y</b>	<b>SIT DOWN RIDER</b>														
	48 VOLTS , 35.20 X 26.70 X 23.00											Weight Minimum 1840 Connector SB350 GRAY , Position B , Lead Length 014 Inches			
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
<b>LASERPE35Y</b>	<b>SIT DOWN RIDER</b>														
	36 VOLTS , 35.20 X 26.70 X 23.00											Weight Minimum 1840 Connector SB350 GRAY , Position B , Lead Length 014 Inches			
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	105B13	630	22.2	35.00	25.62	22.38	1954	M2101810513K	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	( CALL )		SCR20018965T1H	( CALL )	( CALL )
<b>LASERPE35Y</b>	<b>SIT DOWN RIDER</b>														
	48 VOLTS , 35.20 X 26.70 X 23.00											Weight Minimum 1840 Connector SB350 GRAY , Position B , Lead Length 014 Inches			
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>LASERPE40Y</b>	<b>SIT DOWN RIDER</b>		<b>36 VOLTS , 39.10 X 28.30 X 23.40 Weight Minimum 2490 Connector SB350 GRAY , Position B , Lead Length 018 Inches</b>												
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
<b>LASERPE40Y</b>	<b>SIT DOWN RIDER</b>		<b>48 VOLTS , 39.10 X 28.30 X 23.40 Weight Minimum 2490 Connector SB350 GRAY , Position B , Lead Length 018 Inches</b>												
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>LASERPE50LY</b>	<b>SIT DOWN RIDER</b>		<b>36 VOLTS , 39.10 X 34.20 X 23.40 Weight Minimum 3075 Connector SB350 GRAY , Position B , Lead Length 018 Inches</b>												
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
<b>LASERPE50Y</b>	<b>SIT DOWN RIDER</b>		<b>36 VOLTS , 39.10 X 28.30 X 23.40 Weight Minimum 2490 Connector SB350 GRAY , Position B , Lead Length 018 Inches</b>												
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
<b>LASERPE50Y</b>	<b>SIT DOWN RIDER</b>		<b>48 VOLTS , 39.10 X 28.30 X 23.40 Weight Minimum 2490 Connector SB350 GRAY , Position B , Lead Length 018 Inches</b>												
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	060B21	600	28.2	38.50	27.25	23.11	2666	M2102406021DB75982	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>LASERPE60Y</b>	<b>SIT DOWN RIDER</b>		<b>36 VOLTS , 39.10 X 34.20 X 23.40 Weight Minimum 3075 Connector SB350 GRAY , Position B , Lead Length 018 Inches</b>												
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	33.50	23.13	3350	M2101810523B059	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
<b>LASERPE60Y</b>	<b>SIT DOWN RIDER</b>		<b>48 VOLTS , 39.10 X 34.20 X 23.40 Weight Minimum 3075 Connector SB350 GRAY , Position B , Lead Length 018 Inches</b>												
	48	085C21	850	39.6	38.31	32.57	22.88	3143	M2602408521B7	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
<b>BXC30N</b>	<b>SIT DOWN RIDER (AC)</b>		<b>36 VOLTS , 35.15 X 26.68 X 22.81 Weight Minimum 1840 Connector SB350 GRAY , Position B , Lead Length 018 Inches</b>												
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.00	25.62	22.38	1954	M2101810513K	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085L19	765	26.7	35.18	25.81	22.62	2285	M2901808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>BXC30N</b>	<b>SIT DOWN RIDER (AC)</b>		<b>48 VOLTS , 35.15 X 26.68 X 22.81</b>												
											<b>Weight Minimum 1840</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>	
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
<b>BXC35N</b>	<b>SIT DOWN RIDER (AC)</b>		<b>36 VOLTS , 35.15 X 26.68 X 22.81</b>												
	36	105B13	630	22.2	35.00	25.62	22.38	1954	M2101810513K	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>BXC35N</b>	<b>SIT DOWN RIDER (AC)</b>		<b>48 VOLTS , 35.15 X 26.68 X 22.81</b>												
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
<b>BXC40N</b>	<b>SIT DOWN RIDER (AC)</b>		<b>36 VOLTS , 39.06 X 28.25 X 22.81</b>												
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
<b>BXC40N</b>	<b>SIT DOWN RIDER (AC)</b>		<b>48 VOLTS , 39.06 X 28.25 X 22.81</b>												
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>BXC50LN</b>	<b>SIT DOWN RIDER (AC)</b>		<b>36 VOLTS , 39.06 X 34.12 X 22.81</b>												
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
<b>BXC50LN</b>	<b>SIT DOWN RIDER (AC)</b>		<b>48 VOLTS , 39.06 X 34.12 X 22.81</b>												
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
<b>BXC50N</b>	<b>SIT DOWN RIDER (AC)</b>		<b>36 VOLTS , 39.06 X 28.25 X 22.81</b>												
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>BXC50N</b>	<b>SIT DOWN RIDER (AC)</b>			<b>48 VOLTS , 39.06 X 28.25 X 22.81</b>											<b>Weight Minimum 2491</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>	
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>BXC60N</b>	<b>SIT DOWN RIDER (AC)</b>			<b>36 VOLTS , 39.06 X 34.12 X 22.81</b>											<b>Weight Minimum 3075</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>	
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)				
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>BXC80N</b>	<b>SIT DOWN RIDER (AC)</b>			<b>36 VOLTS , 39.06 X 34.12 X 22.81</b>											<b>Weight Minimum 3351</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>	
	36	105B21	1050	37.0	38.61	32.62	22.55	3450	M2101810521B759	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
<b>BXC80N</b>	<b>SIT DOWN RIDER (AC)</b>			<b>48 VOLTS , 39.06 X 34.12 X 22.81</b>											<b>Weight Minimum 3075</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
<b>BX40</b>	<b>SIT DOWN RIDER (AC)</b>			<b>36 VOLTS , 39.09 X 28.26 X 23.42</b>											<b>Weight Minimum 2491</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>	
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>BXC60N</b>	<b>SIT DOWN RIDER (AC)</b>			<b>48 VOLTS , 39.06 X 34.12 X 22.81</b>											<b>Weight Minimum 3075</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 018 Inches</b>	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
<b>N30</b>	<b>THREE WHEEL SIT DOWN RIDER</b>			<b>48 VOLTS , 39.20 X 20.90 X 25.80</b>											<b>Weight Minimum 1545</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 014 Inches</b>	
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
<b>N35</b>	<b>THREE WHEEL SIT DOWN RIDER</b>			<b>48 VOLTS , 39.20 X 20.90 X 25.80</b>											<b>Weight Minimum 1545</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 014 Inches</b>	
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
<b>OT25S</b>	<b>THREE WHEEL SIT DOWN RIDER</b>			<b>36 VOLTS , 38.80 X 13.80 X 31.00</b>											<b>Weight Minimum 1650</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>OT30</b>	<b>THREE WHEEL SIT DOWN RIDER</b>			<b>36 VOLTS , 38.80 X 20.50 X 31.00</b>											<b>Weight Minimum 2590</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>OT30S</b>	<b>THREE WHEEL SIT DOWN RIDER</b>			<b>36 VOLTS , 38.80 X 13.80 X 31.00</b>											<b>Weight Minimum 1650</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>OT35</b>	<b>THREE WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 38.80 X 20.50 X 31.00</b>				<b>Weight Minimum 2590</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )				
<b>OT40</b>	<b>THREE WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 38.80 X 20.50 X 31.00</b>				<b>Weight Minimum 2590</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )				
<b>OT45</b>	<b>THREE WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 38.80 X 20.50 X 31.00</b>				<b>Weight Minimum 2590</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )				
<b>OT50</b>	<b>THREE WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 38.80 X 20.50 X 31.00</b>				<b>Weight Minimum 2590</b>	<b>Connector SB350</b>	<b>GRAY , Position A , Lead Length 018 Inches</b>	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )				
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )				
<b>TN30</b>	<b>THREE WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 39.20 X 20.90 X 25.80</b>				<b>Weight Minimum 1545</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 014 Inches</b>	
	36	060B25	720	25.4	38.50	20.34	25.69	2130	M2101806025B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )				
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				
<b>TN35</b>	<b>THREE WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 39.20 X 20.90 X 25.80</b>				<b>Weight Minimum 1545</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 014 Inches</b>	
	36	060B25	720	25.4	38.50	20.34	25.69	2130	M2101806025B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )				
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				
<b>TX30(AC)</b>	<b>THREE WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 39.17 X 20.86 X 25.78</b>				<b>Weight Minimum 1545</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 014 Inches</b>	
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				
<b>TX30(AC)</b>	<b>THREE WHEEL SIT DOWN RIDER</b>											<b>48 VOLTS , 39.17 X 20.86 X 25.78</b>				<b>Weight Minimum 1545</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 014 Inches</b>	
	48	100C13	600	27.9	38.50	20.63	25.63	2201	M2602410013B	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )				
<b>TX35(AC)</b>	<b>THREE WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 39.17 X 20.86 X 25.78</b>				<b>Weight Minimum 1545</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 014 Inches</b>	
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	( CALL )	SCR20012750S1H	SCR20012750T1H	( CALL )	( CALL )				
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Nissan-Barrett Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
			48 VOLTS , 39.17 X 20.86 X 25.78      Weight Minimum 1545      Connector SB350      GRAY , Position B , Lead Length 014 Inches														
TX35(AC)			THREE WHEEL SIT DOWN RIDER														
	48	100C13	600	27.9	38.50	20.63	25.63	2201	M2602410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)		
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)		
TX40(AC)			THREE WHEEL SIT DOWN RIDER														
			36 VOLTS , 39.17 X 25.19 X 25.78      Weight Minimum 2315      Connector SB350      GRAY , Position B , Lead Length 014 Inches														
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
TX40(AC)			THREE WHEEL SIT DOWN RIDER														
			48 VOLTS , 39.17 X 25.19 X 25.78      Weight Minimum 2315      Connector SB350      GRAY , Position B , Lead Length 014 Inches														
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)		
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)