



# Nissan Lift Trucks 2012 Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
OP22N216 / OP22HN278	CLASS II ORDER PICKER		24 VOLTS , 36.60 X 15.30 X 26.00 Weight Minimum 995 Connector SBE160 RED , Position , Lead Length 000 Inches												
	24	100C15	700	16.3	35.31	13.13	25.63	1270	M2601210015A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
SRX30 / SRX35 / SRX45	CLASS I REACH TRUCK		36 VOLTS , 16.40 X 38.50 X 32.00 Weight Minimum 1885 Connector SB350 GRAY , Position C , Lead Length 024 Inches												
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
SRX30 / SRX35 / SRX45	CLASS I REACH TRUCK		48 VOLTS , 16.40 X 38.50 X 32.00 Weight Minimum 1885 Connector SB350 GRAY , Position C , Lead Length 024 Inches												
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
SRX30L / SRX45L	CLASS I REACH TRUCK		48 VOLTS , 20.90 X 38.50 X 32.00 Weight Minimum 2460 Connector SB350 GRAY , Position C , Lead Length 024 Inches												
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
SRX30L / SRX48L	CLASS I REACH TRUCK		36 VOLTS , 20.90 X 38.50 X 32.00 Weight Minimum 2460 Connector SB350 GRAY , Position C , Lead Length 024 Inches												
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
TX30	CLASS I 3 WHEEL SIT DOWN		36 VOLTS , 38.75 X 20.56 X 25.63 Weight Minimum 1545 Connector SB350 GRAY , Position A , Lead Length 004 Inches												
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
TX30	CLASS I 3 WHEEL SIT DOWN		48 VOLTS , 38.75 X 20.56 X 25.63 Weight Minimum 1545 Connector SB350 GRAY , Position A , Lead Length 004 Inches												
	48	085C11	425	19.8	35.00	19.25	22.63	1610	M2602408511M	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
TX35 CUSHION	CLASS I 3 WHEEL SIT DOWN		36 VOLTS , 38.75 X 20.56 X 25.63 Weight Minimum 1545 Connector SB350 GRAY , Position A , Lead Length 004 Inches												
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
TX35 CUSHION	CLASS I 3 WHEEL SIT DOWN		48 VOLTS , 38.75 X 20.56 X 25.63 Weight Minimum 1545 Connector SB350 GRAY , Position A , Lead Length 004 Inches												
	48	085C11	425	19.8	35.00	19.25	22.63	1610	M2602408511M	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
TX35 SOLID PNEUMATIC	CLASS I 3 WHEEL SIT DOWN		36 VOLTS , 38.75 X 20.56 X 25.63 Weight Minimum 1545 Connector SB350 GRAY , Position A , Lead Length 004 Inches												
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
TX35 SOLID PNEUMATIC	CLASS I 3 WHEEL SIT DOWN		48 VOLTS , 38.75 X 20.56 X 25.63 Weight Minimum 1545 Connector SB350 GRAY , Position A , Lead Length 004 Inches												
	48	085C11	425	19.8	35.00	19.25	22.63	1610	M2602408511M	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)
TX40	CLASS I 3 WHEEL SIT DOWN		36 VOLTS , 38.75 X 24.81 X 25.63 Weight Minimum 2315 Connector SB350 GRAY , Position A , Lead Length 004 Inches												
	36	100A19	900	31.4	38.19	22.25	25.62	2438	M2601810019B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
TX40	CLASS I 3 WHEEL SIT DOWN		48 VOLTS , 38.75 X 24.81 X 25.63 Weight Minimum 2315 Connector SB350 GRAY , Position A , Lead Length 004 Inches												
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
SCX30 / SCX35	CLASS I 3 WHEEL STANDUP																	
			36 VOLTS , 18.40 X 38.50 X 32.00												Weight Minimum 2175	Connector SB350	GRAY , Position C , Lead Length 020 Inches	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
SCX30 / SCX35	CLASS I 3 WHEEL STANDUP																	
			48 VOLTS , 18.40 X 38.50 X 32.00												Weight Minimum 2175	Connector SB350	GRAY , Position C , Lead Length 020 Inches	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
SCX30S	CLASS I 3 WHEEL STANDUP																	
			36 VOLTS , 16.40 X 38.50 X 32.00												Weight Minimum 1885	Connector SB350	GRAY , Position C , Lead Length 020 Inches	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
SCX30S	CLASS I 3 WHEEL STANDUP																	
			48 VOLTS , 16.40 X 38.50 X 32.00												Weight Minimum 1885	Connector SB350	GRAY , Position C , Lead Length 020 Inches	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
SCX40	CLASS I 3 WHEEL STANDUP																	
			36 VOLTS , 20.90 X 38.50 X 32.00												Weight Minimum 2460	Connector SB350	GRAY , Position C , Lead Length 020 Inches	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
SCX40	CLASS I 3 WHEEL STANDUP																	
			48 VOLTS , 20.90 X 38.50 X 32.00												Weight Minimum 2460	Connector SB350	GRAY , Position C , Lead Length 020 Inches	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
BXC30 / BXC35	CLASS I 4 WHEEL SIT DOWN																	
			36 VOLTS , 35.19 X 26.69 X 22.81												Weight Minimum 1840	Connector SB350	GRAY , Position B , Lead Length 018 Inches	
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
BXC30 / BXC35	CLASS I 4 WHEEL SIT DOWN																	
			48 VOLTS , 35.31 X 26.29 X 22.81												Weight Minimum 1840	Connector SB350	GRAY , Position B , Lead Length 018 Inches	
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
BXC30 / BXC35	CLASS I 4 WHEEL SIT DOWN																	
			48 VOLTS , 35.31 X 26.69 X 22.81												Weight Minimum 1840	Connector SB350	GRAY , Position B , Lead Length 018 Inches	
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
BXC40 / BXC50	CLASS I 4 WHEEL SIT DOWN																	
			36 VOLTS , 39.06 X 28.25 X 22.81												Weight Minimum 2490	Connector SB350	GRAY , Position B , Lead Length 018 Inches	
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
BXC40 / BXC50	CLASS I 4 WHEEL SIT DOWN																	
			48 VOLTS , 39.06 X 28.25 X 22.81												Weight Minimum 2490	Connector SB350	GRAY , Position B , Lead Length 018 Inches	
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
BXC50L / BXC60 / BXC80	CLASS I 4 WHEEL SIT DOWN																	
			36 VOLTS , 39.06 X 34.12 X 22.81												Weight Minimum 3075	Connector SB350	GRAY , Position B , Lead Length 018 Inches	
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
<b>BXC50L / BXC60 / BXC80</b>	<b>CLASS I 4 WHEEL SIT DOWN</b>											<b>48 VOLTS , 39.06 X 34.12 X 22.81</b>				<b>Weight Minimum 3075</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
<b>BXP30 / BXP35</b>	<b>CLASS I 4 WHEEL SIT DOWN</b>											<b>48 VOLTS , 38.60 X 26.40 X 18.80</b>				<b>Weight Minimum 1585</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 025 Inches</b>
	48	060C15	420	19.6	38.58	26.38	18.77	1748	M2602406015B33A	N	( CALL )	SCR20024475S1H	SCR20024475T1H	( CALL )	( CALL )			
<b>BXP30L / BXP35L</b>	<b>CLASS I 4 WHEEL SIT DOWN</b>											<b>48 VOLTS , 38.60 X 33.70 X 18.80</b>				<b>Weight Minimum 1940</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 025 Inches</b>
	48	060C19	540	25.1	38.58	33.66	18.78	2240	M2602406019B33	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )			
<b>BXP40</b>	<b>CLASS I 4 WHEEL SIT DOWN</b>											<b>48 VOLTS , 38.60 X 33.70 X 18.80</b>				<b>Weight Minimum 1775</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 025 Inches</b>
	48	060C19	540	25.1	38.58	33.66	18.78	2240	M2602406019B33	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )			
<b>BXP40L / BXP50L</b>	<b>CLASS I 4 WHEEL SIT DOWN</b>											<b>48 VOLTS , 38.60 X 39.80 X 23.10</b>				<b>Weight Minimum 2535</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 025 Inches</b>
	48	100T25	1200	55.9	38.58	39.76	23.10	3950	M2802410025B33	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085C25	1020	47.5	38.58	39.76	23.10	3700	M2602408525B33	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )			
<b>BXP50</b>	<b>CLASS I 4 WHEEL SIT DOWN</b>											<b>48 VOLTS , 38.60 X 33.70 X 18.80</b>				<b>Weight Minimum 1975</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 025 Inches</b>
	48	060C19	540	25.1	38.58	33.66	18.78	2240	M2602406019B33	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )			
<b>QX40 / QX50</b>	<b>CLASS I 4 WHEEL SIT DOWN</b>											<b>80 VOLTS , 28.18 X 40.66 X 31.65</b>				<b>Weight Minimum 3240</b>	<b>Connector SBE320</b>	<b>BLACK , Position A , Lead Length 016 Inches</b>
	80	140T09	560	43.5	40.38	27.88	30.88	3613	M2804014009C6A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
	80	125C09	500	38.8	40.38	27.88	30.88	3405	M2604012509C6A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
<b>QX50L / QX60</b>	<b>CLASS I 4 WHEEL SIT DOWN</b>											<b>80 VOLTS , 33.85 X 40.66 X 31.65</b>				<b>Weight Minimum 3900</b>	<b>Connector SBE320</b>	<b>BLACK , Position A , Lead Length 016 Inches</b>
	80	140T11	700	54.3	40.38	33.50	30.88	4370	M2804014011C6A	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			

M20/21/89/90 - Element VRLA Absorbed Glass Mat

M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)

M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)

M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)

M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)