

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
102XM	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 26.75 X 7.75 X 32.00			Weight Minimum 200		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T05	200	4.7	26.50	7.50	23.25	499	M1801210005G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	26.50	7.50	27.25	466	M1901208505G6BFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L05	170	4.0	26.50	7.50	23.25	477	M1901208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F05	170	4.0	26.50	7.50	23.25	480	M1501208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	26.50	7.50	23.25	465	M1601208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
102XM	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 26.75 X 9.00 X 32.00			Weight Minimum 200		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)			(CALL)	(CALL)
8310	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 31.00 X 9.13 X 31.00			Weight Minimum 490		Connector SB175	GRAY	, Position B , Lead Length 018 Inches				
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
8310	CLASS III LOW LIFT WALKIE RIDER			24 VOLTS , 31.00 X 13.44 X 31.00			Weight Minimum 490		Connector SB175	GRAY	, Position B , Lead Length 018 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
8410	CLASS III LOW LIFT WALKIE RIDER			24 VOLTS , 31.00 X 13.38 X 31.00			Weight Minimum 490		Connector SB175	GRAY	, Position B , Lead Length 018 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
8510	CLASS III LOW LIFT WALKIE RIDER CENTER CONTROL			24 VOLTS , 31.00 X 13.38 X 31.00			Weight Minimum 980		Connector SB175	GRAY	, Position B , Lead Length 018 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
8910	CLASS III WALKIE RIDER END CONTROL		24 VOLTS , 31.00 X 13.00 X 31.00													Weight Minimum 980	Connector SB175	GRAY	, Position B	, Lead Length 018 Inches
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)					
8610	CLASS III TOW TRACTOR		24 VOLTS , 31.00 X 13.44 X 31.00													Weight Minimum 965	Connector SB175	GRAY	, Position B	, Lead Length 016 Inches
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
RCS20/30/40	CLASS III WALKIE HIGH LIFT COUNTERBALANCED STACKER		24 VOLTS , 32.30 X 13.30 X 999.00													Weight Minimum 950	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)					
RAS20/25	CLASS III ADJUSTABLE BASE LEG STACKER		24 VOLTS , 27.30 X 6.80 X 999.00													Weight Minimum 290	Connector SB175	RED	, Position B	, Lead Length 018 Inches
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085L05	170	4.0	25.25	6.63	27.25	415	M1901208505GFPCZ	Y	(CALL)			(CALL)	(CALL)					
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
RAS20/25	CLASS III ADJUSTABLE BASE LEG STACKER		24 VOLTS , 27.30 X 7.80 X 999.00													Weight Minimum 290	Connector SB175	RED	, Position B	, Lead Length 018 Inches
	24	100T05	200	4.7	26.50	7.50	23.25	499	M1801210005G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085L05	170	4.0	26.50	7.50	27.25	466	M1901208505G6BFPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085L05	170	4.0	26.50	7.50	23.25	477	M1901208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085F05	170	4.0	26.50	7.50	23.25	480	M1501208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085C05	170	4.0	26.50	7.50	23.25	465	M1601208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
RAS20/25	CLASS III ADJUSTABLE BASE LEG STACKER		24 VOLTS , 27.30 X 9.00 X 999.00													Weight Minimum 290	Connector SB175	RED	, Position B	, Lead Length 018 Inches
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)					

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
RSS22	CLASS III WALKIE STRADDLE STACKER											24 VOLTS , 32.30 X 9.00 X 999.00				Weight Minimum 300	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)					
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
RSS30/40	CLASS III WALKIE STRADDLE STACKER											24 VOLTS , 32.30 X 13.30 X 999.00				Weight Minimum 950	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
RRS30	CLASS III WALKIE REACH STACKER											24 VOLTS , 32.30 X 13.30 X 999.00				Weight Minimum 950	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
5200,5400	CLASS II 5000 SERIES ORDERPICKERS											24 VOLTS , 31.00 X 13.00 X 30.88				Weight Minimum 920	Connector SB350	RED	, Position C	, Lead Length 020 Inches
	24	100T13	600	14.0	30.63	12.69	22.63	1014	M2801210013A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)					
	24	085L13	510	11.9	30.63	12.69	22.63	968	M2901208513A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	085C13	510	11.9	30.63	12.69	22.63	946	M2601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	100C13	600	14.0	30.75	13.00	25.63	1100	M2601210013A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
5200,5400,5500	CLASS II 5000 SERIES ORDERPICKERS											24 VOLTS , 36.38 X 14.12 X 30.88				Weight Minimum 1600	Connector SB350	RED	, Position C	, Lead Length 020 Inches
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	140T13	840	19.6	36.00	13.88	30.38	1732	M2801214013A7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)					
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)					
	24	125L15	875	20.4	35.25	14.06	30.50	1734	M2901212515A6	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	125L13	750	17.5	36.00	13.88	30.38	1750	M2901212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	125L15	875	20.4	36.00	13.75	30.50	1783	M2901212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	125F13	750	17.5	36.00	13.88	30.38	1702	M2501212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	125F15	750	17.5	36.00	13.75	30.50	1737	M2501212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	125C13	750	17.5	36.00	13.88	30.38	1663	M2601212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	125C13	750	17.5	36.00	13.88	30.50	1419	M2601212513A11A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	125C15	875	20.4	36.00	13.75	30.50	1765	M2601212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)					
	24	055B29	770	18.1	37.08	13.50	29.87	1630	M2101205529FB7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)					

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
5600	CLASS II 5000 SERIES ORDERPICKERS							36 VOLTS , 38.38 X 13.69 X 30.88		Weight Minimum 1600	Connector SB350	GRAY	, Position C , Lead Length 012 Inches			
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	560	19.6	37.88	13.25	30.50	1819	M2801814011B11B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L11	625	21.8	37.88	13.25	30.50	1710	M2901812511B11B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	500	17.5	37.88	13.25	30.50	1762	M2501812511B11B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	500	17.5	37.88	13.25	30.50	1706	M2601812511B11B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
5600	CLASS II 5000 SERIES ORDERPICKERS							36 VOLTS , 38.38 X 16.12 X 30.88		Weight Minimum 2000	Connector SB350	GRAY	, Position C , Lead Length 012 Inches			
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-R30TT,TN	CLASS II EASI NARROW AISLE REACH							24 VOLTS , 38.62 X 14.12 X 30.33		Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches			
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)	SCR200121200T1H	(CALL)	(CALL)		
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)		
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)	SCR200121050T1H	(CALL)	(CALL)		
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)	SCR200121050T1H	(CALL)	(CALL)		
	24	125C17	1000	23.3	38.38	13.50	30.50	1797	M2601212517B11	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)		
	24	060B29	840	19.8	39.84	13.00	29.87	1637	M2101206029FB	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
EASI-R30TT,TN	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.62 X 14.12 X 30.33		Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L11	625	21.8	38.00	14.00	30.50	1901	M2901812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.00	14.00	30.50	1839	M2501812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.00	14.00	30.50	1777	M2601812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-R30TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.62 X 16.12 X 30.33		Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
EASI-R30TT	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.62 X 18.12 X 30.33				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
EASI-R35TT	CLASS II EASI NARROW AISLE REACH											24 VOLTS , 38.62 X 14.12 X 30.33				Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.38	13.50	30.50	1797	M2601212517B11	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B29	840	19.8	39.84	13.00	29.87	1637	M2101206029FB	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)				
EASI-R35TT	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.62 X 14.12 X 30.33				Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 011 Inches
	36	125L11	625	21.8	38.00	14.00	30.50	1901	M2901812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.00	14.00	30.50	1839	M2501812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.00	14.00	30.50	1777	M2601812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
EASI-R35TT	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.62 X 16.12 X 30.33				Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
EASI-R35TT	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.62 X 18.12 X 30.33				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
EASI-R40TT,TN	CLASS II EASI NARROW AISLE REACH											24 VOLTS , 38.62 X 14.12 X 30.33				Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.38	13.50	30.50	1797	M2601212517B11	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
EASI-R40TT,TN	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.62 X 14.12 X 30.33		Weight Minimum 1600	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L11	625	21.8	38.00	14.00	30.50	1901	M2901812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.00	14.00	30.50	1839	M2501812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.00	14.00	30.50	1777	M2601812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-R40TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.62 X 16.12 X 30.33		Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-R40TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.62 X 18.12 X 30.33		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)		
EASI-R40TT-M	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.63 X 16.12 X 30.33		Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-R40TT-M	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.63 X 18.12 X 30.33		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)		
EASI-R40TT-M	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 21.12 X 30.33		Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	(CALL)	(CALL)		
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)		
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)		
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)		
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)		

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
EASI-R45TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 16.12 X 30.33		Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-R45TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 18.12 X 30.33		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
EASI-R45TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 21.12 X 30.33		Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	(CALL)	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
EASI-R45TT-M	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 16.12 X 30.33		Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-R45TT-M	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 18.12 X 30.33		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
EASI-R45TT-M	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 21.12 X 30.33		Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	(CALL)	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
EASI-R45TT-MA	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 18.12 X 30.33		Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
EASI-R45TT-MA	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 21.12 X 30.33		Weight Minimum 2600	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
EASI-R45TT-MB	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 18.12 X 30.33		Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
EASI-R45TT-MB	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 21.12 X 30.33		Weight Minimum 2600	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2696	M2601812517B11	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
EASI-DR25TT	CLASS II EASI DEEP REACH							24 VOLTS , 38.62 X 14.12 X 30.33		Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches			
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.38	13.50	30.50	1797	M2601212517B11	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	060B29	840	19.8	39.84	13.00	29.87	1637	M2101206029FB	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
EASI-DR25TT	CLASS II EASI DEEP REACH							36 VOLTS , 38.62 X 14.12 X 30.33		Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T11	700	24.4	38.00	14.00	30.50	1899	M2801814011B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	700	24.4	38.00	13.88	30.50	1800	M2801814011B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.00	14.00	30.50	1839	M2501812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.00	14.00	30.50	1777	M2601812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.00	13.88	30.50	1726	M2601812511B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-DR25TT	CLASS II EASI DEEP REACH							36 VOLTS , 38.62 X 16.12 X 30.33		Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
EASI-DR25TT	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 18.12 X 30.33 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EASI-DR30TT	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 16.12 X 30.33 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
EASI-DR30TT	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 18.12 X 30.33 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EASI-DR30TT-A	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 18.12 X 30.33 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EASI-DR30TT-A	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 21.12 X 30.33 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
7500,7520 DR32TT,R35TT,R45TT	CLASS II 7000 SERIES REACH,DEEP REACH		36 VOLTS , 38.62 X 16.12 X 31.62 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 015 Inches												
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
7500,7520 DR32TT,R35TT,R45TT	CLASS II 7000 SERIES REACH,DEEP REACH			36 VOLTS , 38.62 X 18.12 X 31.62			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 015 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
7500,7520 DR32TT,R35TT,R45TT	CLASS II 7000 SERIES REACH,DEEP REACH			36 VOLTS , 38.62 X 21.12 X 30.33			Weight Minimum 2600		Connector SB350	GRAY	, Position B , Lead Length 015 Inches				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.38	13.50	30.50	1797	M2601212517B11	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)	
7700,7720-DR32TT,DR45TT	CLASS II REACH,DEEP REACH			36 VOLTS , 38.62 X 18.12 X 30.33			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 015 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	
7700,7720-DR32TT,DR45TT	CLASS II REACH,DEEP REACH			36 VOLTS , 38.62 X 21.12 X 30.33			Weight Minimum 2600		Connector SB350	GRAY	, Position B , Lead Length 015 Inches				
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	
4D-R45TT	CLASS II REACH FORK TRUCK EASI 4-D			36 VOLTS , 38.62 X 16.12 X 31.62			Weight Minimum 2000		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)	SCR20018600T1H	(CALL)	(CALL)	
40-R40TN/TT	REACH FORK TRUCK MODEL 40			24 VOLTS , 36.00 X 16.38 X 34.00			Weight Minimum 2000		Connector EC	ORANGE	, Position MTC, Lead Length 011 Inches				
	24	170C13	1020	23.7	35.50	15.75	31.25	2032	M1601217013D21	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)	
40-R45TN/TT	REACH FORK TRUCK MODEL 40			36 VOLTS , 36.00 X 16.38 X 34.00			Weight Minimum 2000		Connector EC	ORANGE	, Position MTC, Lead Length 011 Inches				
	24	170C13	1020	23.7	35.50	15.75	31.25	2032	M1601217013D21	N	(CALL)	SCR200121050T1H	(CALL)	(CALL)	
40-R60TN/TT	REACH FORK TRUCK MODEL 40			24 VOLTS , 37.00 X 19.00 X 34.00			Weight Minimum 2200		Connector EC	ORANGE	, Position MTC, Lead Length 011 Inches				
	24	170C15	1190	27.7	35.55	17.92	31.00	2192	M1601217015A21	N	(CALL)	SCR200121200T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
9600 CSR30T	CLASS II VERY NARROW AISLE / SWING REACH							48 VOLTS , 44.25 X 21.25 X 32.00			Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	140T13	840	39.1	44.13	20.63	30.50	3312	M2802414013B7	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	125L13	750	34.9	44.13	20.63	30.50	3167	M2902412513B7	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	125F13	750	34.9	44.13	20.63	30.50	3295	M2502412513B7	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	125C13	750	34.9	44.13	20.63	30.50	3159	M2602412513B7	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
9700 CSR30T	CLASS II VERY NARROW AISLE / SWING REACH							48 VOLTS , 44.25 X 24.00 X 32.00			Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	140T15	980	45.6	43.88	23.63	30.50	3291	M2802414015A6	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	125L15	875	40.7	43.88	23.63	30.50	3247	M2902412515A6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	125F15	875	40.7	43.88	23.63	30.50	3272	M2502412515A6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	125C15	875	40.7	43.88	23.63	30.50	3162	M2602412515A6	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
71-SLR20TT/SL40TT/SL60TF/TN	CLASS II SIDELOADER MODEL 71 (OLD STYLE / TWO BATTERIES REQ)							36 VOLTS , 41.88 X 9.25 X 30.88			Weight Minimum 2300	Connector SB350	GRAY , Position CTR, Lead Length 036 Inches		
	18	170C11	850	14.8	39.36	9.13	30.50	1285	M2600917011D	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
76-SL60TT-SL100TF/TN/TT	CLASS II SIDELOADER CLASS 76 (OLD STYLE / TWO BATTERIES REQ)							36 VOLTS , 42.38 X 12.75 X 30.88			Weight Minimum 0	Connector SB350	GRAY , Position CTR, Lead Length 036 Inches		
	18	170C15	1190	20.8	41.19	12.12	30.50	1653	M2600917015F	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	18	170C15	1190	20.8	41.25	12.63	30.50	1713	M2600917015F7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
9300,SLR20TT,SLR40TT,SL60TF,TN	CLASS II SIDELOADER (REQUIRES TWO BATTERIES)							24 VOLTS , 38.50 X 9.25 X 31.25			Weight Minimum 2300	Connector SB350	GRAY , Position K , Lead Length 036 Inches		
	24	140T11	700	16.3	38.00	9.00	30.50	1271	M2801214011B	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L11	625	14.6	38.00	9.00	30.50	1214	M2901212511B	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F11	625	14.6	38.00	9.00	30.50	1224	M2501212511B	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C11	625	14.6	38.00	9.00	30.50	1195	M2601212511B	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
9400,SL60TT,SL120TF/TN/TT	CLASS II SIDELOADER (REQUIRES TWO BATTERIES)							24 VOLTS , 38.50 X 12.75 X 31.25			Weight Minimum 3100	Connector SB350	BLUE , Position K , Lead Length 036 Inches		
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
96 TRANSTACKER (MODEL 89)	CLASS II TRANSTACKER (MODEL 89)							36 VOLTS , 999.00 X 999.00 X 999.00			Weight Minimum 0	Connector SB350	RED , Position B , Lead Length 011 Inches		
	36	100C07	300	10.5	25.75	12.81	25.63	927	M2601810007E	N	(CALL)	SCR20018475S1H	SCR20018475T1H	(CALL)	(CALL)
4450-C30 & C35S	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED							36 VOLTS , 38.80 X 20.61 X 23.00			Weight Minimum 1450	Connector SB350	GRAY , Position A , Lead Length 030 Inches		
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
4450-C30 & C35S	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED							48 VOLTS , 38.80 X 20.61 X 23.00			Weight Minimum 1450	Connector SB350	BLUE , Position A , Lead Length 030 Inches		
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
4450-C35 & C40	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 38.80 X 24.94 X 23.00 Weight Minimum 2050 Connector SB350 GRAY , Position A , Lead Length 030 Inches											
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
4450-C35 & C40	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 38.80 X 24.94 X 23.00 Weight Minimum 2050 Connector SB350 BLUE , Position A , Lead Length 030 Inches											
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
4700-C30	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 35.55 X 27.90 X 22.81 Weight Minimum 1800 Connector SB350 GRAY , Position B , Lead Length 024 Inches											
	36	100T17	800	27.9	34.02	26.63	22.63	2164	M2801810017J6	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	34.03	26.63	22.63	2067	M2901808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	34.03	26.63	22.63	2181	M2501808517J6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	34.03	26.63	22.63	2034	M2601808517J6	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
4700-C30	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 35.55 X 27.90 X 22.81 Weight Minimum 1800 Connector SB350 GRAY , Position B , Lead Length 024 Inches											
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	34.00	27.00	22.63	2025	M2902408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
4700-C40,C50	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 38.69 X 27.90 X 22.81 Weight Minimum 2450 Connector SB350 GRAY , Position B , Lead Length 024 Inches											
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
4700-C40,C50	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 38.69 X 27.90 X 22.81 Weight Minimum 2450 Connector SB350 GRAY , Position B , Lead Length 024 Inches											
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
4700-C50L/C60	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 39.40 X 33.75 X 22.80 Weight Minimum 3100 Connector SB350 BLUE , Position B , Lead Length 024 Inches											
	36	100T29	1400	48.9	38.63	33.75	22.63	3494	M2801810029B7	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L29	1190	41.6	38.63	33.75	22.63	3351	M2901808529B7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F29	1190	41.6	38.63	33.75	22.63	3385	M2501808529B7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.63	33.75	22.63	3279	M2601808529B7	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
4700-C50L/C60	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 39.40 X 33.75 X 22.81 Weight Minimum 3100 Connector SB350 BLUE , Position B , Lead Length 024 Inches											
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.75	33.00	22.63	3441	M2802410021B1	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.75	33.00	22.63	3298	M2902408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F21	850	39.6	38.75	33.00	22.63	3332	M2502408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.75	33.00	22.63	3222	M2602408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
4700-C50HM	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 38.69 X 27.90 X 22.81			Weight Minimum 2600		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	36	100T23	1100	38.4	38.50	27.25	22.63	2853	M2801810023B7B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.50	27.25	22.63	2740	M2901808523B7B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085F23	935	32.7	38.50	27.25	22.63	2767	M2501808523B7B	N	(CALL)			(CALL)	(CALL)
	36	085C23	935	32.7	38.50	27.25	22.63	2684	M2601808523B7B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
4700-C50HM	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 38.69 X 27.90 X 22.81			Weight Minimum 2600		Connector SB350	GRAY	, Position B , Lead Length 024 Inches				
	48	100T17	800	37.2	38.50	27.00	22.63	2854	M2802410017B7A	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.50	27.00	22.63	2741	M2902408517B7A	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	48	085F17	680	31.7	38.50	27.00	22.63	2768	M2502408517B7A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.50	27.00	22.63	2685	M2602408517B7A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
4150-C30/C35TF/TT	CLASS I STAND UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 13.75 X 32.30			Weight Minimum 1700		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
4150-C30/C35TF/TT	CLASS I STAND UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 16.25 X 32.30			Weight Minimum 1980		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
4150-C30/C35TF/TT	CLASS I STAND UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 18.25 X 32.30			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
4250-C30/C35TF/TT	CLASS I STAND UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 13.75 X 32.30			Weight Minimum 1700		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
4250-C30/C35TF/TT	CLASS I STAND UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 16.25 X 32.30			Weight Minimum 1980		Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
4250-C30-35/TF/TT/QM	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 18.25 X 32.30				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
4250-C40TF/TT/QM	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 21.00 X 32.30				Weight Minimum 2593	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125C17	1000	34.9	38.31	20.13	30.50	2696	M2601812517B11	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
4250-C50QM	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 23.50 X 32.30				Weight Minimum 2700	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	125L19	1125	39.3	38.31	22.38	30.50	3067	M2901812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
4250-C50TF/TT	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 23.50 X 32.30				Weight Minimum 2700	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	125L19	1125	39.3	38.31	22.38	30.50	3067	M2901812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)