

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
102XM	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 26.75 X 7.75 X 32.00			Weight Minimum 200		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	125F05	250	5.8	25.46	6.50	31.00	603	M1501212505D	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F05	170	4.0	26.50	7.50	23.25	480	M1501208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100C05	200	4.7	25.25	6.50	25.63	455	M1601210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	125C05	250	5.8	25.46	6.50	31.00	590	M1601212505D	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	26.50	7.50	23.25	465	M1601208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
102XM	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 26.75 X 8.87 X 32.00			Weight Minimum 200		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)			(CALL)	(CALL)
8300 111XD	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 31.00 X 9.13 X 31.00			Weight Minimum 490		Connector SB175	GRAY	, Position B , Lead Length 018 Inches				
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
8300 111XD	CLASS III LOW LIFT WALKIE RIDER			24 VOLTS , 31.00 X 13.44 X 31.00			Weight Minimum 490		Connector SB175	GRAY	, Position B , Lead Length 018 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
8400 112XD	CLASS III LOW LIFT WALKIE RIDER			24 VOLTS , 31.00 X 13.38 X 31.00			Weight Minimum 490		Connector SB175	GRAY	, Position B , Lead Length 018 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
8500 113XD	CLASS III LOW LIFT WALKIE RIDER CENTER CONTROL			24 VOLTS , 31.00 X 13.38 X 31.00			Weight Minimum 490		Connector SB175	GRAY	, Position B , Lead Length 018 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
8900 & 019ELF	CLASS III WALKIE RIDER END CONTROL		24 VOLTS , 31.00 X 13.00 X 31.00			Weight Minimum 490		Connector SB175	GRAY	, Position B , Lead Length 018 Inches					
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
8600 114XD	CLASS III TOW TRACTOR		24 VOLTS , 31.00 X 13.38 X 23.25			Weight Minimum 965		Connector SB175	GRAY	, Position B , Lead Length 016 Inches					
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
8600 114XD	CLASS III TOW TRACTOR		24 VOLTS , 31.00 X 13.38 X 31.00			Weight Minimum 965		Connector SB175	GRAY	, Position B , Lead Length 016 Inches					
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
40	CLASS II LOW LIFT PLATFORM TRUCK		24 VOLTS , 36.00 X 14.38 X 34.00			Weight Minimum 1600		Connector MTD	ORANGE	, Position N/A, Lead Length 000 Inches					
	24	140T15	980	22.8	35.31	13.13	31.00	1655	M1801214015A21	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	100T15	700	16.3	35.13	12.81	23.25	1157	M1801210015A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.13	12.94	31.00	1636	M1901212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.31	13.13	31.00	1704	M1501212515A21	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.13	12.94	31.00	1638	M1501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.31	13.13	31.00	1643	M1601212515A21	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.13	12.94	31.00	1582	M1601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	105B15	735	17.3	35.50	12.88	30.51	1475	M2101210515N06059	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
RCS20/30/40	CLASS III WALKIE HIGH LIFT COUNTERBALANCED STACKER		24 VOLTS , 32.30 X 13.30 X 999.00			Weight Minimum 950		Connector SB175	RED	, Position B , Lead Length 020 Inches					
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
RAS20/25	CLASS III ADJUSTABLE BASE LEG STACKER		24 VOLTS , 27.30 X 6.80 X 999.00			Weight Minimum 290		Connector SB175	RED	, Position B , Lead Length 015 Inches					
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE					
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)													
RAS20/25	CLASS III ADJUSTABLE BASE LEG STACKER											24 VOLTS , 27.30 X 7.80 X 999.00				Weight Minimum 290	Connector SB175	RED	, Position B	, Lead Length 015 Inches
	24	100T05	200	4.7	26.50	7.50	23.25	499	M1801210005G6B	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	085L05	170	4.0	26.50	7.50	23.25	477	M1901208505G6B	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	085F05	170	4.0	26.50	7.50	23.25	480	M1501208505G6B	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	085C05	170	4.0	26.50	7.50	23.25	465	M1601208505G6B	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
RAS20/25	CLASS III ADJUSTABLE BASE LEG STACKER											24 VOLTS , 27.30 X 9.00 X 999.00				Weight Minimum 290	Connector SB175	RED	, Position B	, Lead Length 015 Inches
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
RSS22	CLASS III WALKIE STRADDLE STACKER											24 VOLTS , 32.30 X 9.00 X 999.00				Weight Minimum 300	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H		(CALL)	(CALL)				
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	085L07	255	5.9	31.50	8.69	23.25	660	M1901208507DFPC	N	(CALL)				(CALL)	(CALL)				
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)				(CALL)	(CALL)				
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)				
RSS30/40	CLASS III WALKIE STRADDLE STACKER											24 VOLTS , 32.30 X 13.30 X 999.00				Weight Minimum 950	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
RRS30	CLASS III WALKIE REACH STACKER											24 VOLTS , 32.30 X 13.30 X 999.00				Weight Minimum 950	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H		(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
5200	CLASS II 5000 SERIES ORDERPICKERS			24 VOLTS , 31.00 X 13.00 X 30.88					Weight Minimum 920	Connector SB350	RED	, Position C , Lead Length 012 Inches				
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	22.63	1014	M2801210013A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	22.63	968	M2901208513A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	22.63	946	M2601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100C13	600	14.0	30.75	13.00	25.63	1100	M2601210013A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
5400	CLASS II 5000 SERIES ORDERPICKERS			24 VOLTS , 31.00 X 13.00 X 30.88					Weight Minimum 920	Connector SB350	RED	, Position C , Lead Length 012 Inches				
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	22.63	1014	M2801210013A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	22.63	968	M2901208513A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	22.63	946	M2601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100C13	600	14.0	30.75	13.00	25.63	1100	M2601210013A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
5400	CLASS II 5000 SERIES ORDERPICKERS			24 VOLTS , 36.38 X 14.12 X 30.88					Weight Minimum 1600	Connector SB350	RED	, Position C , Lead Length 012 Inches				
	24	140T15	980	22.8	35.25	13.06	30.50	1702	M2801214015A	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	36.00	13.88	30.38	1732	M2801214013A7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	36.00	13.88	30.38	1750	M2901212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125L15	875	20.4	36.00	13.75	30.50	1783	M2901212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125F15	875	20.4	35.25	13.06	30.50	1662	M2501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	36.00	13.88	30.38	1702	M2501212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F15	750	17.5	36.00	13.75	30.50	1737	M2501212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125C15	875	20.4	35.25	13.06	30.50	1606	M2601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	36.00	13.88	30.38	1663	M2601212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C15	875	20.4	36.00	13.75	30.50	1765	M2601212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	055B29	770	18.1	37.08	13.50	29.87	1630	M2101205529FB7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
5500	CLASS II 5000 SERIES ORDERPICKERS			24 VOLTS , 36.38 X 14.12 X 30.88					Weight Minimum 1600	Connector SB350	RED	, Position C , Lead Length 012 Inches				
	24	140T15	980	22.8	35.25	13.06	30.50	1702	M2801214015A	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	36.00	13.88	30.38	1732	M2801214013A7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	36.00	13.88	30.38	1750	M2901212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125L15	875	20.4	36.00	13.75	30.50	1783	M2901212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125F15	875	20.4	35.25	13.06	30.50	1662	M2501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	36.00	13.88	30.38	1702	M2501212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125F15	750	17.5	36.00	13.75	30.50	1737	M2501212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125C15	875	20.4	35.25	13.06	30.50	1606	M2601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	36.00	13.88	30.38	1663	M2601212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C15	875	20.4	36.00	13.75	30.50	1765	M2601212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	055B29	770	18.1	37.08	13.50	29.87	1630	M2101205529FB7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
5600	CLASS II 5000 SERIES ORDERPICKERS							36 VOLTS , 38.38 X 13.69 X 30.88			Weight Minimum 1600	Connector SB350	GRAY	, Position C , Lead Length 012 Inches		
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	24	055B29	770	18.1	37.08	13.50	29.87	1630	M2101205529FB7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
5600	CLASS II 5000 SERIES ORDERPICKERS							36 VOLTS , 38.38 X 16.12 X 30.88			Weight Minimum 2000	Connector SB350	GRAY	, Position C , Lead Length 012 Inches		
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-R30TT	CLASS II EASI NARROW AISLE REACH							24 VOLTS , 38.63 X 14.12 X 30.33			Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches		
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
EASI-R30TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.62 X 16.12 X 30.33			Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches		
	36	140T11	700	24.4	38.00	14.00	30.50	1899	M2801814011B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	700	24.4	38.00	13.88	30.50	1800	M2801814011B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.00	13.88	30.50	1726	M2601812511B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)	
EASI-R30TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.62 X 18.12 X 30.33			Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
EASI-R30TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 18.12 X 30.33			Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
EASI-R35TT	CLASS II EASI NARROW AISLE REACH							24 VOLTS , 38.63 X 14.12 X 30.33			Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches		
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.00	14.00	30.50	1839	M2501812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.00	14.00	30.50	1777	M2601812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
EASI-R35TT	CLASS II EASI NARROW AISLE REACH				36 VOLTS , 38.62 X 16.12 X 30.33				Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T11	700	24.4	38.00	14.00	30.50	1899	M2801814011B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.00	13.88	30.50	1800	M2801814011B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.00	14.00	30.50	1839	M2501812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.00	14.00	30.50	1777	M2601812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.00	13.88	30.50	1726	M2601812511B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)
EASI-R35TT	CLASS II EASI NARROW AISLE REACH				36 VOLTS , 38.82 X 18.12 X 30.33				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EASI-R35TT	CLASS II EASI NARROW AISLE REACH				36 VOLTS , 38.88 X 18.12 X 30.33				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EASI-R40TT	CLASS II EASI NARROW AISLE REACH				24 VOLTS , 38.63 X 14.12 X 30.33				Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches			
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
EASI-R40TT	CLASS II EASI NARROW AISLE REACH				36 VOLTS , 38.62 X 16.12 X 30.33				Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches			
	36	140T11	700	24.4	38.00	14.00	30.50	1899	M2801814011B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.00	13.88	30.50	1800	M2801814011B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.00	14.00	30.50	1839	M2501812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.00	14.00	30.50	1777	M2601812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.00	13.88	30.50	1726	M2601812511B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
EASI-R40TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 18.12 X 30.33		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
EASI-R40TT-M	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.62 X 16.12 X 30.33		Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)	
EASI-R40TT-M	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 18.12 X 30.33		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
EASI-R45TT	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 16.12 X 30.33		Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
EASI-R45TT	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.88 X 18.12 X 30.33				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
EASI-R45TT-M	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.88 X 16.12 X 30.33				Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)			
EASI-R45TT-M	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.88 X 18.12 X 30.33				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
EASI-R45TT-MA	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.88 X 18.12 X 30.33				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
EASI-R45TT-MA	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.88 X 21.12 X 30.33				Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	060B31	900	31.8	39.62	20.47	30.81	3015	M2101806031B15	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
EASI-R45TT-MB	CLASS II EASI NARROW AISLE REACH											36 VOLTS , 38.88 X 18.12 X 30.33				Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
EASI-R45TT-MB	CLASS II EASI NARROW AISLE REACH							36 VOLTS , 38.88 X 21.12 X 30.33		Weight Minimum 2600	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	060B31	900	31.8	39.62	20.47	30.81	3015	M2101806031B15	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
EASI-DR25TT	CLASS II EASI DEEP REACH							24 VOLTS , 38.63 X 14.12 X 30.33		Weight Minimum 1600	Connector SB350	RED , Position B , Lead Length 011 Inches				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.38	13.50	30.50	1797	M2601212517B11	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	060B29	840	19.8	39.84	13.00	29.87	1637	M2101206029FB	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
EASI-DR25TT	CLASS II EASI DEEP REACH							36 VOLTS , 38.62 X 14.12 X 30.33		Weight Minimum 1600	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T11	700	24.4	38.00	14.00	30.50	1899	M2801814011B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	700	24.4	38.00	13.88	30.50	1800	M2801814011B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.00	14.00	30.50	1839	M2501812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.00	14.00	30.50	1777	M2601812511B11	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C11	625	21.8	38.00	13.88	30.50	1726	M2601812511B6	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
EASI-DR25TT	CLASS II EASI DEEP REACH							36 VOLTS , 38.62 X 16.12 X 30.33		Weight Minimum 2000	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)	
EASI-DR25TT	CLASS II EASI DEEP REACH							36 VOLTS , 38.62 X 18.12 X 30.33		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
EASI-DR30TT	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 16.12 X 30.33 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)
EASI-DR30TT	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 18.12 X 30.33 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EASI-DR30TT-A	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 18.12 X 30.33 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EASI-DR30TT-A	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 21.12 X 30.33 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EASI-DR30TT-B	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 18.12 X 30.33 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
EASI-DR30TT-B	CLASS II EASI DEEP REACH		36 VOLTS , 38.62 X 21.12 X 30.33 Weight Minimum 2600 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2850	M2801814017B11	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
7000-R45TT	CLASS II 7000 SERIES REACH		36 VOLTS , 38.62 X 16.12 X 31.62						Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)	
7000-R45TT	CLASS II 7000 SERIES REACH		36 VOLTS , 38.62 X 18.12 X 31.62						Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
4D-R45TT	CLASS II REACH FORK TRUCK EASI 4-D		36 VOLTS , 38.62 X 16.12 X 31.62						Weight Minimum 2000	Connector SB350	GRAY	, Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	38.13	15.88	30.56	2225	M2801814013B28	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	38.13	15.88	30.50	2120	M2901812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	38.13	15.88	30.56	2132	M2501812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125C13	750	26.2	38.13	15.88	30.56	2060	M2601812513B28	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	050G25	600	21.2	38.62	15.57	30.43	2125	M8901805025B759	N	(CALL)		SCR20018600T1H	(CALL)	(CALL)	
40-R40TN	REACH FORK TRUCK MODEL 40		24 VOLTS , 38.63 X 14.12 X 31.62						Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
40-R40TT	REACH FORK TRUCK MODEL 40		24 VOLTS , 38.63 X 14.12 X 31.62						Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 011 Inches				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
40	CLASS II LOW LIFT PLATFORM TRUCK			24 VOLTS , 36.00 X 14.38 X 34.00			Weight Minimum 1600		Connector MTD	ORANGE , Position N/A, Lead Length 000 Inches					
	24	140T15	980	22.8	35.31	13.13	31.00	1655	M1801214015A21	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	100T15	700	16.3	35.13	12.81	23.25	1157	M1801210015A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.13	12.94	31.00	1636	M1901212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.31	13.13	31.00	1704	M1501212515A21	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.13	12.94	31.00	1638	M1501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.31	13.13	31.00	1643	M1601212515A21	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.13	12.94	31.00	1582	M1601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	105B15	735	17.3	35.50	12.88	30.51	1475	M2101210515N06059	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
76-SL60TT	CLASS II SIDELOADER MODEL 76			36 VOLTS , 42.38 X 12.75 X 30.88			Weight Minimum 3100		Connector SB350	GRAY , Position CTR, Lead Length 036 Inches					
	18	170C15	1190	20.8	41.19	12.12	30.50	1653	M2600917015F	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	18	170C15	1190	20.8	41.25	12.63	30.50	1713	M2600917015F7	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
76-SL100TN	CLASS II SIDELOADER CLASS 76			36 VOLTS , 42.38 X 12.75 X 30.88			Weight Minimum 0		Connector SB350	GRAY , Position CTR, Lead Length 036 Inches					
	18	170C15	1190	20.8	41.19	12.12	30.50	1653	M2600917015F	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	18	170C15	1190	20.8	41.25	12.63	30.50	1713	M2600917015F7	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
76-SL100TF	CLASS II SIDELOADER CLASS 76			36 VOLTS , 42.38 X 12.75 X 30.88			Weight Minimum 0		Connector SB350	GRAY , Position CTR, Lead Length 036 Inches					
	18	170C15	1190	20.8	41.19	12.12	30.50	1653	M2600917015F	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	18	170C15	1190	20.8	41.25	12.63	30.50	1713	M2600917015F7	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
76-SL100TT	CLASS II SIDELOADER MODEL 76			36 VOLTS , 42.38 X 12.75 X 30.88			Weight Minimum 3100		Connector SB350	GRAY , Position CTR, Lead Length 036 Inches					
	18	170C15	1190	20.8	41.19	12.12	30.50	1653	M2600917015F	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
	18	170C15	1190	20.8	41.25	12.63	30.50	1713	M2600917015F7	N	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
4450-C30	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 38.80 X 20.61 X 23.00			Weight Minimum 1450		Connector SB350	GRAY , Position A , Lead Length 030 Inches					
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
4450-C30	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 38.80 X 20.61 X 23.00			Weight Minimum 1450		Connector SB350	BLUE , Position A , Lead Length 030 Inches					
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
4450-C35S	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 38.80 X 20.61 X 23.00			Weight Minimum 1450		Connector SB350	GRAY , Position A , Lead Length 030 Inches					
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
4450-C35S	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 38.80 X 20.61 X 23.00			Weight Minimum 1450		Connector SB350	BLUE , Position A , Lead Length 030 Inches					
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
4450-C35	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 38.80 X 24.94 X 23.00			Weight Minimum 2050			Connector SB350	GRAY , Position A , Lead Length 030 Inches				
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
4450-C35	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 38.80 X 24.94 X 23.00			Weight Minimum 2050			Connector SB350	BLUE , Position A , Lead Length 030 Inches				
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
4450-C40	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 38.80 X 24.94 X 23.00			Weight Minimum 2050			Connector SB350	GRAY , Position A , Lead Length 030 Inches				
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
4450-C40	CLASS I 3 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 38.80 X 24.94 X 23.00			Weight Minimum 2050			Connector SB350	BLUE , Position A , Lead Length 030 Inches				
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
4700-C30	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			36 VOLTS , 38.50 X 18.50 X 32.30			Weight Minimum 2300			Connector SB350	GRAY , Position C , Lead Length 016 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
4700-C50L	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 39.40 X 33.75 X 22.81			Weight Minimum 3100			Connector SB350	BLUE , Position B , Lead Length 024 Inches				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.75	33.00	22.63	3441	M2802410021B1	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085F21	850	39.6	38.75	33.00	22.63	3332	M2502408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.75	33.00	22.63	3222	M2602408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
4700-C60	CLASS I 4 WHEEL SIT DOWN COUNTERBALANCED			48 VOLTS , 39.40 X 33.75 X 22.81			Weight Minimum 3100			Connector SB350	BLUE , Position B , Lead Length 024 Inches				
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.75	33.00	22.63	3441	M2802410021B1	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085F21	850	39.6	38.75	33.00	22.63	3332	M2502408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.75	33.00	22.63	3222	M2602408521B1	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
4150-C30/C35	CLASS I STAND UP END CONTROL COUNTERBALANCED			36 VOLTS , 38.50 X 16.25 X 32.30			Weight Minimum 1980			Connector SB350	GRAY , Position B , Lead Length 011 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
4150-C30/C35	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 18.25 X 32.30		Weight Minimum 1980	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
4250-C30TF/TT/QM	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 18.25 X 32.30		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
4250-C35TF/TT/QM	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 18.25 X 32.30		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
4250-C40TF/TT/QM	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 21.00 X 32.30		Weight Minimum 2593	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
4250-C40TF/TT/QM	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 23.50 X 32.30		Weight Minimum 2700	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	125L19	1125	39.3	38.31	22.38	30.50	3067	M2901812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
4250-C40QM	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 23.50 X 32.30		Weight Minimum 2700	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	125L19	1125	39.3	38.31	22.38	30.50	3067	M2901812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
4250-C50TF/TT	CLASS I STAND UP END CONTROL COUNTERBALANCED											36 VOLTS , 38.50 X 23.50 X 32.30		Weight Minimum 2700	Connector SB350	GRAY , Position B , Lead Length 011 Inches
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	125L19	1125	39.3	38.31	22.38	30.50	3067	M2901812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)