



# Toyota 2012 Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
7HBW23	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 26.75 X 7.80 X 999.00												
											Weight Minimum 200	Connector SB175	RED	, Position B , Lead Length 018 Inches		
	24	100T05	200	4.7	26.50	7.50	23.25	499	M1801210005G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L05	170	4.0	26.50	7.50	27.25	466	M1901208505G6BFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085L05	170	4.0	26.50	7.50	23.25	477	M1901208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085F05	170	4.0	26.50	7.50	23.25	480	M1501208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C05	170	4.0	26.50	7.50	23.25	465	M1601208505G6B	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
7HBW23	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 26.75 X 9.00 X 999.00												
											Weight Minimum 200	Connector SB175	RED	, Position B , Lead Length 018 Inches		
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100C07	300	7.0	25.52	8.75	26.00	652	M1601210007D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)			(CALL)	(CALL)	
8HBW30	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 31.50 X 9.20 X 999.00												
											Weight Minimum 490	Connector SB175	GRAY	, Position B , Lead Length 018 Inches		
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	090G07	270	6.4	31.00	8.64	25.36	575	M8901209007E27	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	090G07	270	6.4	27.50	8.58	25.82	625	M8901209007EPP059	Y	(CALL)			(CALL)	(CALL)	
8HBW30	CLASS III LOW LIFT WALKIE PALLET			24 VOLTS , 31.50 X 13.44 X 999.00												
											Weight Minimum 490	Connector SB175	GRAY	, Position B , Lead Length 018 Inches		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.75	24.20	860	M8901210009NPP	N	(CALL)			(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.88	21.92	825	M8901210009N059	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
8HBE30	CLASS III LOW LIFT WALKIE RIDER			24 VOLTS , 31.50 X 13.44 X 999.00												
											Weight Minimum 490	Connector SB175	GRAY	, Position B , Lead Length 018 Inches		
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.75	24.20	860	M8901210009NPP	N	(CALL)			(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.88	21.92	825	M8901210009N059	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>8HBE40</b>	<b>CLASS III LOW LIFT WALKIE RIDER</b>							<b>24 VOLTS , 31.50 X 13.44 X 999.00</b>		<b>Weight Minimum 490</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.75	24.20	860	M8901210009NPP	N	(CALL)			(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.88	21.92	825	M8901210009N059	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
<b>8HBC30</b>	<b>CLASS III LOW LIFT WALKIE CENTER CONTROL</b>							<b>24 VOLTS , 31.50 X 13.44 X 999.00</b>		<b>Weight Minimum 490</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.75	24.20	860	M8901210009NPP	N	(CALL)			(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.88	21.92	825	M8901210009N059	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
<b>8HBC40</b>	<b>CLASS III LOW LIFT WALKIE CENTER CONTROL</b>							<b>24 VOLTS , 31.50 X 13.44 X 999.00</b>		<b>Weight Minimum 490</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.75	24.20	860	M8901210009NPP	N	(CALL)			(CALL)	(CALL)	
	24	100G09	400	9.4	31.00	12.88	21.92	825	M8901210009N059	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
<b>8TB50</b>	<b>CLASS III TUGGER</b>							<b>24 VOLTS , 31.75 X 13.44 X 999.00</b>		<b>Weight Minimum 965</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 018 Inches</b>				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>2TE15/18</b>	<b>CLASS III TUGGER TRACTOR</b>							<b>80 VOLTS , 46.10 X 26.80 X 26.80</b>		<b>Weight Minimum 2500</b>	<b>Connector SBX350</b>	<b>GRAY , Position B , Lead Length 012 Inches</b>				
	80	100T11	500	38.8	45.50	26.13	22.63	2965	M2804010011C33	N	(CALL)			(CALL)	(CALL)	
	80	085L11	425	33.0	45.50	26.13	22.63	2838	M2904008511C33	N	(CALL)	SCR20040600T1H	SCR20040600T1H	(CALL)	(CALL)	
	80	100F11	500	38.8	45.50	26.31	25.63	3352	M2504010011C33	N	(CALL)	SCR20040600T1H	SCR20040600T1H	(CALL)	(CALL)	
	80	085F11	425	33.0	45.50	26.13	22.63	2867	M2504008511C33	N	(CALL)	SCR20040475T1H	SCR20040475T1H	(CALL)	(CALL)	
	80	100C11	500	38.8	45.50	26.31	25.63	3180	M2604010011C33	N	(CALL)	SCR20040600T1H	SCR20040600T1H	(CALL)	(CALL)	
	80	085C11	425	33.0	45.50	26.13	22.63	2778	M2604008511C33	N	(CALL)	SCR20040475T1H	SCR20040475T1H	(CALL)	(CALL)	
<b>CBT4</b>	<b>CLASS III FLOOR RUNNER-WITHOUT ROLLERS</b>							<b>48 VOLTS , 29.33 X 19.57 X 23.40</b>		<b>Weight Minimum 860</b>	<b>Connector SB175</b>	<b>RED , Position C , Lead Length 013 Inches</b>				
	48	100T09	400	18.6	28.75	19.19	22.62	1426	M2802410009E	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
	48	085L09	340	15.8	28.75	19.19	22.63	1375	M2902408509E	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
	48	085F09	340	15.8	28.75	19.19	22.63	1386	M2502408509E	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	
	48	085C09	340	15.8	28.75	19.19	22.62	1378	M2602408509E	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
<b>CBTY4(WITHROLLERS)</b>	<b>CLASS III FLOOR RUNNER</b>			<b>48 VOLTS , 29.20 X 19.60 X 18.70</b>											<b>Weight Minimum 617</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position A , Lead Length 014 Inches</b>
	48	060C09	240	11.2	29.00	19.25	18.13	1036	M2602406009M	N	( CALL )	SCR20024260S1H		( CALL )	( CALL )			
<b>CBT6</b>	<b>CLASS III FLOOR RUNNER-WITH ROLLERS</b>			<b>48 VOLTS , 29.33 X 19.57 X 20.60</b>											<b>Weight Minimum 794</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 008 Inches</b>
	48	060C09	240	11.2	29.00	19.25	18.13	1036	M2602406009M	N	( CALL )	SCR20024260S1H		( CALL )	( CALL )			
<b>CBT6</b>	<b>CLASS III FLOOR RUNNER-WITHOUT ROLLERS</b>			<b>48 VOLTS , 29.33 X 19.57 X 23.40</b>											<b>Weight Minimum 970</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position C , Lead Length 013 Inches</b>
	48	100T09	400	18.6	28.75	19.19	22.62	1426	M2802410009E	N	( CALL )	SCR20024475S1H	SCR20024475T1H	( CALL )	( CALL )			
	48	085L09	340	15.8	28.75	19.19	22.63	1375	M2902408509E	N	( CALL )	SCR20024475S1H	SCR20024475T1H	( CALL )	( CALL )			
	48	085F09	340	15.8	28.75	19.19	22.63	1386	M2502408509E	N	( CALL )	SCR20024475S1H	SCR20024475T1H	( CALL )	( CALL )			
	48	085C09	340	15.8	28.75	19.19	22.62	1378	M2602408509E	N	( CALL )	SCR20024475S1H	SCR20024475T1H	( CALL )	( CALL )			
<b>6BWC10</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED STACKER</b>			<b>24 VOLTS , 32.30 X 13.30 X 999.00</b>											<b>Weight Minimum 950</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	( CALL )	( CALL )	( CALL )	( CALL )	( CALL )			
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	( CALL )	SCR20012475S1H	SCR20012475T1H	( CALL )	( CALL )			
<b>6BWC15</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED STACKER</b>			<b>24 VOLTS , 32.30 X 13.30 X 999.00</b>											<b>Weight Minimum 950</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	( CALL )	( CALL )	( CALL )	( CALL )	( CALL )			
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	( CALL )	SCR20012475S1H	SCR20012475T1H	( CALL )	( CALL )			
<b>6BWC20</b>	<b>CLASS III WALKIE HIGH LIFT COUNTERBALANCED STACKER</b>			<b>24 VOLTS , 32.30 X 13.30 X 999.00</b>											<b>Weight Minimum 950</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	( CALL )	( CALL )	( CALL )	( CALL )	( CALL )			
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )			
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	( CALL )	SCR20012475S1H	SCR20012475T1H	( CALL )	( CALL )			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
7BWS10	CLASS III ADJUSTABLE BASE LEG STACKER			24 VOLTS , 27.30 X 6.80 X 999.00			Weight Minimum 290		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	27.25	415	M1901208505GFPCZ	Y	(CALL)			(CALL)	(CALL)
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
7BWS10	CLASS III ADJUSTABLE BASE LEG STACKER			24 VOLTS , 27.30 X 7.80 X 999.00			Weight Minimum 290		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	26.50	7.50	27.25	466	M1901208505G6BFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
7BWS10	CLASS III ADJUSTABLE BASE LEG STACKER			24 VOLTS , 27.30 X 9.00 X 999.00			Weight Minimum 290		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
7BWS13	CLASS III ADJUSTABLE BASE LEG STACKER			24 VOLTS , 27.30 X 6.80 X 999.00			Weight Minimum 290		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	27.25	415	M1901208505GFPCZ	Y	(CALL)			(CALL)	(CALL)
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
7BWS13	CLASS III ADJUSTABLE BASE LEG STACKER			24 VOLTS , 27.30 X 7.80 X 999.00			Weight Minimum 290		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	26.50	7.50	27.25	466	M1901208505G6BFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
7BWS13	CLASS III ADJUSTABLE BASE LEG STACKER			24 VOLTS , 27.30 X 9.00 X 999.00			Weight Minimum 290		Connector SB175	RED	, Position B , Lead Length 018 Inches				
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	090G07	270	6.4	27.00	8.70	27.88	615	M8901209007E0	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
6BWS11	CLASS III STRADDLE STACKER			24 VOLTS , 32.30 X 9.00 X 999.00			Weight Minimum 300		Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	090G07	270	6.4	31.00	8.64	25.36	575	M8901209007E27	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>6BWS15</b>	<b>CLASS III STRADDLE STACKER</b>			<b>24 VOLTS , 32.30 X 13.30 X 999.00</b>			<b>Weight Minimum 950</b>		<b>Connector SB175</b>		<b>RED , Position B , Lead Length 020 Inches</b>				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
<b>6BWS20</b>	<b>CLASS III STRADDLE STACKER</b>			<b>24 VOLTS , 32.30 X 13.30 X 999.00</b>			<b>Weight Minimum 950</b>		<b>Connector SB175</b>		<b>RED , Position B , Lead Length 020 Inches</b>				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
<b>6BWR15</b>	<b>CLASS III REACH STACKER</b>			<b>24 VOLTS , 32.30 X 13.30 X 999.00</b>			<b>Weight Minimum 950</b>		<b>Connector SB175</b>		<b>RED , Position B , Lead Length 020 Inches</b>				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	27.25	1023	M1901208513A25CFPCZ	N	(CALL)			(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
<b>6BPU15</b>	<b>CLASS II ORDER PICKER</b>			<b>24 VOLTS , 31.50 X 13.25 X 32.25</b>			<b>Weight Minimum 920</b>		<b>Connector SB350</b>		<b>RED , Position C , Lead Length 020 Inches</b>				
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>6BPU15</b>	<b>CLASS II ORDER PICKER</b>			<b>24 VOLTS , 36.75 X 14.50 X 32.25</b>			<b>Weight Minimum 1600</b>		<b>Connector SB350</b>		<b>RED , Position C , Lead Length 020 Inches</b>				
	24	140T13	840	19.6	36.00	13.88	30.38	1732	M2801214013A7	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	36.00	13.75	30.50	1783	M2901212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.25	14.06	30.50	1734	M2901212515A6	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125L13	750	17.5	36.00	13.88	30.38	1750	M2901212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F13	750	17.5	36.00	13.88	30.38	1702	M2501212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	750	17.5	36.00	13.75	30.50	1737	M2501212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C13	750	17.5	36.00	13.88	30.38	1663	M2601212513A7	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C13	750	17.5	36.00	13.88	30.50	1419	M2601212513A11A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C15	875	20.4	36.00	13.75	30.50	1765	M2601212515A11A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>7BPUE15</b>	<b>CLASS II REACH</b>		<b>24 VOLTS , 31.50 X 13.25 X 32.25 Weight Minimum 920 Connector SB350 RED , Position C , Lead Length 020 Inches</b>												
	24	140T13	840	19.6	30.81	12.94	30.50	1471	M2801214013A	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.81	12.94	30.50	1399	M2901212513A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.81	12.94	30.50	1422	M2501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.81	12.94	30.50	1370	M2601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B15	735	17.3	30.73	13.00	30.53	1415	M2101210515N	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>7BPUE15</b>	<b>CLASS II REACH</b>		<b>24 VOLTS , 36.75 X 14.50 X 32.25 Weight Minimum 1600 Connector SB350 RED , Position C , Lead Length 020 Inches</b>												
	24	140T15	980	22.8	35.25	14.00	30.50	1810	M2801214015A6	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.25	14.06	30.50	1734	M2901212515A6	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	35.25	14.00	30.50	1747	M2501212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	14.00	30.50	1700	M2601212515A6	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	170C11	850	19.8	35.25	13.31	30.50	1645	M2601217011D	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
<b>8BRU18</b>	<b>CLASS II REACH</b>		<b>24 VOLTS , 38.75 X 14.40 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b>												
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
<b>8BRU18</b>	<b>CLASS II REACH</b>		<b>24 VOLTS , 38.75 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b>												
	24	140T19	1260	29.3	38.31	15.25	30.50	2235	M2801214019B7	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.13	15.25	30.50	2230	M2901212519B7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.31	15.25	30.50	2177	M2501212519B7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125C19	1125	26.2	38.31	15.25	30.50	2105	M2601212519B7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
<b>8BRU18</b>	<b>CLASS II REACH</b>		<b>36 VOLTS , 38.75 X 14.40 X 32.00 Weight Minimum 1600 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b>												
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>8BRU18</b>	<b>CLASS II REACH</b>		<b>36 VOLTS , 38.75 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b>												
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	38.50	15.90	31.38	2070	M2101804531B0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>8BRU23</b>	<b>CLASS II REACH</b>		<b>36 VOLTS , 38.75 X 16.40 X 32.00 Weight Minimum 2000 Connector SB350 GRAY , Position C , Lead Length 015 Inches</b>												
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	38.50	15.90	31.38	2070	M2101804531B0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
<b>8BRU23</b>	<b>CLASS II REACH</b>		<b>36 VOLTS , 38.75 X 18.40 X 32.00</b>														
			<b>Weight Minimum 2300</b>										<b>Connector SB350</b>		<b>GRAY , Position C , Lead Length 015 Inches</b>		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	( CALL )		SCR20018965T1H	( CALL )	( CALL )		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )		
<b>8BRU23</b>	<b>CLASS II REACH</b>		<b>36 VOLTS , 38.75 X 20.90 X 32.00</b>														
			<b>Weight Minimum 2400</b>										<b>Connector SB350</b>		<b>GRAY , Position C , Lead Length 015 Inches</b>		
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )		
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )		
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )		
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )		
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )		
<b>8BDRU15</b>	<b>CLASS II DOUBLE REACH</b>		<b>36 VOLTS , 38.75 X 16.40 X 32.00</b>														
			<b>Weight Minimum 2000</b>										<b>Connector SB350</b>		<b>GRAY , Position C , Lead Length 015 Inches</b>		
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )		
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )		
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )		
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )		
	36	045B31	675	23.8	38.50	15.90	31.38	2070	M2101804531B0	N	( CALL )	SCR20012750S1H	SCR20012750T1H	( CALL )	( CALL )		
<b>8BDRU15</b>	<b>CLASS II DOUBLE REACH</b>		<b>36 VOLTS , 38.75 X 18.40 X 32.00</b>														
			<b>Weight Minimum 2300</b>										<b>Connector SB350</b>		<b>GRAY , Position C , Lead Length 015 Inches</b>		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	( CALL )		SCR20018965T1H	( CALL )	( CALL )		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )		
<b>8BDRU15</b>	<b>CLASS II DOUBLE REACH</b>		<b>36 VOLTS , 38.75 X 20.90 X 32.00</b>														
			<b>Weight Minimum 2400</b>										<b>Connector SB350</b>		<b>GRAY , Position C , Lead Length 015 Inches</b>		
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )		
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )		
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )		
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )		
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )		
<b>7FBUE15</b>	<b>CLASS I 3-WHEEL COUNTERBALANCED CUSHION</b>		<b>36 VOLTS , 39.20 X 21.70 X 24.10</b>														
			<b>Weight Minimum 1543</b>										<b>Connector SB350</b>		<b>GRAY , Position B , Lead Length 010 Inches</b>		
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )		
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )		
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )		
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )		
	36	060B23	660	23.3	38.50	19.62	23.69	1975	M2101806023B0	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )		
<b>7FBUE15</b>	<b>CLASS I 3-WHEEL COUNTERBALANCED CUSHION</b>		<b>48 VOLTS , 39.20 X 21.70 X 24.10</b>														
			<b>Weight Minimum 1543</b>										<b>Connector SB350</b>		<b>GRAY , Position B , Lead Length 010 Inches</b>		
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )		
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )		
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )		
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )		

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>7FBEU18</b>	<b>CLASS I 3-WHEEL COUNTERBALANCED CUSHION</b>			<b>36 VOLTS , 39.20 X 21.70 X 24.10</b>			<b>Weight Minimum 1543</b>		<b>Connector #N/A</b>	<b>GRAY , Position B , Lead Length 010 Inches</b>					
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	060B23	660	23.3	38.50	19.62	23.69	1975	M2101806023B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>7FBEU18</b>	<b>CLASS I 3-WHEEL COUNTERBALANCED CUSHION</b>			<b>48 VOLTS , 39.20 X 21.70 X 24.10</b>			<b>Weight Minimum 1543</b>		<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 010 Inches</b>					
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
<b>7FBEU18</b>	<b>CLASS I 3-WHEEL COUNTERBALANCED CUSHION</b>			<b>48 VOLTS , 39.20 X 25.10 X 24.10</b>			<b>Weight Minimum 2105</b>		<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 010 Inches</b>					
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
<b>7FBEU18</b>	<b>CLASS I 3-WHEEL COUNTERBALANCED CUSHION &amp; PNEUMATIC</b>			<b>36 VOLTS , 39.20 X 25.10 X 24.10</b>			<b>Weight Minimum 2105</b>		<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 010 Inches</b>					
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	075B23	825	29.1	38.50	24.00	23.82	2360	M2101807523B0	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
<b>7FBEU20</b>	<b>CLASS I 3-WHEEL COUNTERBALANCED CUSHION</b>			<b>36 VOLTS , 39.20 X 25.10 X 24.10</b>			<b>Weight Minimum 2105</b>		<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 010 Inches</b>					
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	075B23	825	29.1	38.50	24.00	23.82	2360	M2101807523B0	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
<b>7FBEU20</b>	<b>CLASS I 3-WHEEL COUNTERBALANCED CUSHION</b>			<b>48 VOLTS , 39.20 X 25.10 X 24.10</b>			<b>Weight Minimum 2105</b>		<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 010 Inches</b>					
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
<b>7FBCU15</b>	<b>CLASS I 4-WHEEL COUNTERBALANCED CUSHION</b>			<b>36 VOLTS , 34.60 X 26.80 X 23.80</b>			<b>Weight Minimum 1840</b>		<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 016 Inches</b>					
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
7FBCU15	CLASS I 4-WHEEL COUNTERBALANCED CUSHION				48 VOLTS , 34.60 X 26.80 X 23.80				Weight Minimum 1840	Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	48	100T13	600	27.9	34.50	26.13	22.63	2145	M2802410013A633	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085L13	510	23.7	34.50	26.13	22.63	2049	M2902408513A633	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	34.50	26.13	22.63	2091	M2502408513A633	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	34.50	26.13	22.63	1996	M2602408513A633	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	105B11	525	24.7	33.69	26.50	22.95	2070	M2102410511D81	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
7FBCU18	CLASS I 4-WHEEL COUNTERBALANCED CUSHION				36 VOLTS , 34.60 X 26.80 X 23.80				Weight Minimum 1840	Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
7FBCU18	CLASS I 4-WHEEL COUNTERBALANCED CUSHION				48 VOLTS , 34.60 X 26.80 X 23.80				Weight Minimum 1840	Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	48	100T13	600	27.9	34.50	26.13	22.63	2145	M2802410013A633	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085L13	510	23.7	34.50	26.13	22.63	2049	M2902408513A633	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	34.50	26.13	22.63	2091	M2502408513A633	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	34.50	26.13	22.63	1996	M2602408513A633	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	105B11	525	24.7	33.69	26.50	22.95	2070	M2102410511D81	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
8FBCU20	CLASS I 4-WHEEL COUNTERBALANCED CUSHION				36 VOLTS , 39.10 X 27.40 X 23.80				Weight Minimum 2400	Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	(CALL)	
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
8FBCU20	CLASS I 4-WHEEL COUNTERBALANCED CUSHION				36 VOLTS , 39.10 X 30.50 X 23.80				Weight Minimum 2400	Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)	SCR200181200T1H	(CALL)	(CALL)	(CALL)	
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)	SCR200181050T1H	(CALL)	(CALL)	(CALL)	
8FBCU20	CLASS I 4-WHEEL COUNTERBALANCED CUSHION				48 VOLTS , 39.10 X 27.40 X 23.80				Weight Minimum 2400	Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)	SCR20024865T1H	(CALL)	(CALL)	(CALL)	
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)	SCR20024750T1H	(CALL)	(CALL)	(CALL)	
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)	SCR20024750T1H	(CALL)	(CALL)	(CALL)	
8FBCU20	CLASS I 4-WHEEL COUNTERBALANCED CUSHION				48 VOLTS , 39.10 X 30.50 X 23.80				Weight Minimum 2400	Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)	SCR20024965T1H	(CALL)	(CALL)	(CALL)	
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)	SCR20024865T1H	(CALL)	(CALL)	(CALL)	
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)	SCR20024865T1H	(CALL)	(CALL)	(CALL)	
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)	SCR20024865T1H	(CALL)	(CALL)	(CALL)	
8FBCU25	CLASS I 4-WHEEL COUNTERBALANCED CUSHION				36 VOLTS , 39.10 X 27.40 X 23.80				Weight Minimum 2400	Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)	SCR200181200T1H	(CALL)	(CALL)	(CALL)	
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)	SCR20018965T1H	(CALL)	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
8FBCU25	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											36 VOLTS , 39.10 X 30.50 X 23.80				Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )			
8FBCU25	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											48 VOLTS , 39.10 X 27.40 X 23.80				Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )			
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )			
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )			
8FBCU25	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											48 VOLTS , 39.10 X 30.50 X 23.80				Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
8FBCU25	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											36 VOLTS , 39.10 X 34.30 X 23.80				Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
8FBCU25	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											48 VOLTS , 39.10 X 34.30 X 23.80				Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
8FBCU28	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											36 VOLTS , 39.10 X 30.50 X 23.80				Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )			
8FBCU28	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											48 VOLTS , 39.10 X 30.50 X 23.80				Weight Minimum 2400	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
8FBCU30	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											36 VOLTS , 39.10 X 34.30 X 23.80				Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
8FBCU30	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											48 VOLTS , 39.10 X 34.30 X 23.80				Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
8FBCU32	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											36 VOLTS , 39.10 X 34.30 X 23.80				Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )			
8FBCU32	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											48 VOLTS , 39.10 X 34.30 X 23.80				Weight Minimum 3000	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )			
7FBCU35	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											36 VOLTS , 45.20 X 39.20 X 23.80				Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	36	100T33	1600	55.9	43.38	38.62	22.62	3938	M2801810033C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085L33	1360	47.5	43.38	38.63	22.63	4085	M2901808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
7FBCU35	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											48 VOLTS , 45.20 X 39.20 X 23.80				Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	48	100T27	1300	60.5	41.88	38.44	22.63	4298	M2802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )			
	48	085L27	1105	51.4	41.89	38.44	22.63	4260	M2902408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )			
7FBCU45	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											36 VOLTS , 45.20 X 39.20 X 23.80				Weight Minimum 3600	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	36	100T33	1600	55.9	43.38	38.62	22.62	3938	M2801810033C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085L33	1360	47.5	43.38	38.63	22.63	4085	M2901808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )			
7FBCU45	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											48 VOLTS , 45.20 X 39.20 X 23.80				Weight Minimum 3600	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	48	100T27	1300	60.5	41.88	38.44	22.63	4298	M2802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )			
	48	085L27	1105	51.4	41.89	38.44	22.63	4260	M2902408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )			
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )			
7FBCU55 (2-36V BATS IN 1 TRAY)	CLASS I 4-WHEEL COUNTERBALANCED CUSHION											36 VOLTS , 45.20 X 45.70 X 23.80				Weight Minimum 4230	Connector SB350	GRAY , Position B , Lead Length 016 Inches
	36	100T19	1800	125.7	43.50	44.50	22.62	4500	M2803610019Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )			
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )			
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )			
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
7FBCU55	CLASS I 4-WHEEL COUNTERBALANCED CUSHION					48 VOLTS , 45.20 X 45.70 X 23.80			Weight Minimum 4230	Connector SB350	GRAY	, Position B , Lead Length 016 Inches			
	48	100T33	1600	74.5	44.88	44.63	22.88	5170	M2802410033W	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	085L33	1360	63.3	44.88	44.63	22.88	4981	M2902408533W	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	085F33	1360	63.3	44.88	44.63	22.88	5020	M2502408533W	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	085C33	1360	63.3	44.88	44.63	22.88	4851	M2602408533W	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
7FBH15,7FBH18	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC					48 VOLTS , 32.30 X 29.40 X 21.50			Weight Minimum 1775	Connector SB350	GRAY	, Position A , Lead Length 014 Inches			
	48	085T13	510	23.7	32.00	29.00	21.60	1920	M2802408513PZ33	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
7FBH20,7FBH25	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC					48 VOLTS , 35.90 X 32.30 X 21.50			Weight Minimum 2305	Connector SB350	GRAY	, Position A , Lead Length 014 Inches			
	48	085T17	680	31.7	35.50	32.00	21.60	2550	M2802408517PX33	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	105B13	630	29.6	35.55	31.39	20.78	2455	M2102410513E81	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
7FB30,7FBJ35	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC					80 VOLTS , 37.60 X 32.40 X 22.40			Weight Minimum 2030	Connector SBX350	BLACK	, Position A , Lead Length 014 Inches			
	80	085T11	425	33.0	35.50	32.00	22.60	2590	M2804008511B33	N	(CALL)		SCR20040475T1H	(CALL)	(CALL)
7BNCU15	CLASS I STAND-UP END CONTROL COUNTERBALANCED					36 VOLTS , 38.50 X 18.50 X 32.30			Weight Minimum 2300	Connector SB350	GRAY	, Position D , Lead Length 016 Inches			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
7BNCU18	CLASS I STAND-UP END CONTROL COUNTERBALANCED					36 VOLTS , 38.50 X 18.50 X 32.30			Weight Minimum 2300	Connector SB350	GRAY	, Position D , Lead Length 016 Inches			
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
7BNCU20	CLASS I STAND-UP END CONTROL COUNTERBALANCED					36 VOLTS , 38.50 X 21.25 X 32.30			Weight Minimum 2600	Connector SB350	GRAY	, Position D , Lead Length 016 Inches			
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	20.25	30.69	2625	M2101806031B0	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
7BNCU25	CLASS I STAND-UP END CONTROL COUNTERBALANCED					36 VOLTS , 38.50 X 23.75 X 32.30			Weight Minimum 2700	Connector SB350	GRAY	, Position D , Lead Length 016 Inches			
	36	140T19	1260	44.0	38.31	22.38	30.50	3181	M2801814019B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	125L19	1125	39.3	38.31	22.38	30.50	3067	M2901812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125F19	1125	39.3	38.31	22.38	30.50	3018	M2501812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125C19	1125	39.3	38.31	22.38	30.50	2975	M2601812519B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)