

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
500WPE-1A	Lowlift Walkie							12 VOLTS , 31.75 X 8.13 X 999.00	Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 015 Inches			
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100G11	500	5.9	30.56	7.69	26.40	570	M8900610011APP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
500WPE-1A	Lowlift Walkie							12 VOLTS , 31.75 X 13.31 X 999.00	Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 015 Inches			
	12	085C25	1020	11.9	29.13	13.00	23.25	957	M1600608525C	N	(CALL)		SCR200061050T1H	(CALL)	(CALL)
650RPE-1A	Lowlift Walkie							24 VOLTS , 31.75 X 13.31 X 999.00	Weight Minimum 980	Connector SB175	RED	, Position B , Lead Length 015 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
650WPE-1A	Lowlift Walkie							24 VOLTS , 31.75 X 13.31 X 999.00	Weight Minimum 980	Connector SB175	RED	, Position B , Lead Length 015 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
800PRE-1A	Lowlift Walkie							24 VOLTS , 31.75 X 13.31 X 999.00	Weight Minimum 980	Connector SB175	RED	, Position B , Lead Length 015 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>800WPE-1A</b>	<b>Lowlift Walkie</b>		<b>24 VOLTS , 31.75 X 13.31 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 015 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>MWH20-1A</b>	<b>Walkie Stacker</b>		<b>24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>200WCE-1A</b>	<b>Walkie Stacker</b>		<b>24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>300WCE-1A</b>	<b>Walkie Stacker</b>		<b>24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>300WRE-1A</b>	<b>Walkie Stacker</b>		<b>24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>300WSE-1A</b>	<b>Walkie Stacker</b>		<b>24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>400WCE-1A</b>	<b>Walkie Stacker</b>		<b>24 VOLTS , 32.30 X 13.30 X 999.00 Weight Minimum 980 Connector SB175 RED , Position B , Lead Length 020 Inches</b>												
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.85	12.88	22.83	1040	M2101210511N	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)
	24	100G13	600	14.1	30.69	12.75	30.91	1180	M8901210013N059	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
<b>300RDE-2A</b>	<b>Double Reach Truck</b>		<b>36 VOLTS , 38.75 X 16.40 X 32.00 Weight Minimum 2000 Connector N/A N/A , Position N/A, Lead Length 000 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	38.50	15.90	31.38	2070	M2101804531B0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>300RDE-2A</b>	<b>Double Reach Truck</b>		<b>36 VOLTS , 38.75 X 20.90 X 32.00 Weight Minimum 2400 Connector N/A N/A , Position N/A, Lead Length 000 Inches</b>												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	(CALL)	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	(CALL)	SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)	(CALL)	SCR20018965T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	(CALL)	SCR200181200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
350RRE-2A	Reach Truck		24 VOLTS , 38.75 X 14.40 X 32.00		Weight Minimum 1600			Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.19	13.50	31.69	1826	M3401212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
350RRE-2A	Reach Truck		24 VOLTS , 38.75 X 16.40 X 32.00		Weight Minimum 2000			Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	24	125C19	1125	26.2	38.31	15.25	30.50	2105	M2601212519B7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.31	15.25	30.50	2177	M2501212519B7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.31	15.25	30.50	2235	M2801214019B7	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.13	15.25	30.50	2230	M2901212519B7	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
350RRE-2A	Reach Truck		36 VOLTS , 38.75 X 14.40 X 32.00		Weight Minimum 1600			Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.00	13.25	31.63	1746	M3401812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
350RRE-2A	Reach Truck		36 VOLTS , 38.75 X 16.40 X 32.00		Weight Minimum 2000			Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	38.13	15.62	31.70	2114	M3401812513B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
500RSE-2A	Reach Truck		36 VOLTS , 38.75 X 16.40 X 32.00		Weight Minimum 2000			Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
500RSE-2A	Reach Truck		36 VOLTS , 38.75 X 20.90 X 32.00		Weight Minimum 2400			Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
300CBSH-7	COUNTERBALANCED SIT-DOWN		36 VOLTS , 36.20 X 27.00 X 24.20		Weight Minimum 1940			Connector SB350	GRAY	, Position B , Lead Length 014 Inches					
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100G15	700	24.7	35.30	26.00	19.68	2055	M8901810015AA059	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.00	25.62	22.38	1954	M2101810513K	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G15	700	24.7	33.89	26.50	23.75	2065	M8901810015HA63	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>300CBSH-7</b>	<b>COUNTERBALANCED SIT-DOWN</b>		<b>48 VOLTS , 36.20 X 27.00 X 24.20</b>													
											<b>Weight Minimum 1940</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 014 Inches</b>		
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
<b>350CBSH-7</b>	<b>COUNTERBALANCED SIT-DOWN</b>		<b>36 VOLTS , 36.20 X 27.00 X 24.20</b>													
											<b>Weight Minimum 1940</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 014 Inches</b>		
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100G15	700	24.7	35.30	26.00	19.68	2055	M8901810015AA059	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)	
	36	105B13	630	22.2	35.00	25.62	22.38	1954	M2101810513K	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	100G15	700	24.7	33.89	26.50	23.75	2065	M8901810015HA63	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
<b>350CBSH-7</b>	<b>COUNTERBALANCED SIT-DOWN</b>		<b>48 VOLTS , 36.20 X 27.00 X 24.20</b>													
											<b>Weight Minimum 1940</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 014 Inches</b>		
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
<b>1000CBH-1</b>	<b>FOUR WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 44.90 X 39.60 X 24.00</b>													
											<b>Weight Minimum 3450</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>		
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)	
<b>1000CBH-1</b>	<b>FOUR WHEEL SIT DOWN RIDER</b>		<b>48 VOLTS , 44.90 X 39.60 X 24.00</b>													
											<b>Weight Minimum 3450</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>		
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)	
<b>1000CBP-1</b>	<b>FOUR WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 44.90 X 39.60 X 24.00</b>													
											<b>Weight Minimum 3450</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>		
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)	
<b>1000CBP-1</b>	<b>FOUR WHEEL SIT DOWN RIDER</b>		<b>48 VOLTS , 44.90 X 39.60 X 24.00</b>													
											<b>Weight Minimum 3450</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>		
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)	
<b>1200CBH-1</b>	<b>FOUR WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 44.90 X 39.60 X 24.00</b>													
											<b>Weight Minimum 4250</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position A , Lead Length 018 Inches</b>		
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
1200CBH-1		FOUR WHEEL SIT DOWN RIDER						48 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 4250	Connector SB350	GRAY , Position A , Lead Length 018 Inches				
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )	
1200CBP-1		FOUR WHEEL SIT DOWN RIDER						36 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 4250	Connector SB350	GRAY , Position A , Lead Length 018 Inches				
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	( CALL )		SCR20036865T1H	( CALL )	( CALL )	
1200CBP-1		FOUR WHEEL SIT DOWN RIDER						48 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 4250	Connector SB350	GRAY , Position A , Lead Length 018 Inches				
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )	
700CBH-1		FOUR WHEEL SIT DOWN RIDER						36 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3490	Connector SB350	GRAY , Position A , Lead Length 018 Inches				
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	( CALL )		SCR20036865T1H	( CALL )	( CALL )	
700CBH-1		FOUR WHEEL SIT DOWN RIDER						48 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3490	Connector SB350	GRAY , Position A , Lead Length 018 Inches				
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )	
700CBP-1		FOUR WHEEL SIT DOWN RIDER						36 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3490	Connector SB350	GRAY , Position A , Lead Length 018 Inches				
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	( CALL )		SCR20036865T1H	( CALL )	( CALL )	
700CBP-1		FOUR WHEEL SIT DOWN RIDER						48 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3490	Connector SB350	GRAY , Position A , Lead Length 018 Inches				
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )	
800CBH-1		FOUR WHEEL SIT DOWN RIDER						36 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3585	Connector SB350	GRAY , Position A , Lead Length 018 Inches				
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )	
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	( CALL )		SCR20036865T1H	( CALL )	( CALL )	
800CBH-1		FOUR WHEEL SIT DOWN RIDER						48 VOLTS , 44.90 X 39.60 X 24.00		Weight Minimum 3585	Connector SB350	GRAY , Position A , Lead Length 018 Inches				
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
800CBP-1	FOUR WHEEL SIT DOWN RIDER		36 VOLTS , 44.90 X 39.60 X 24.00 Weight Minimum 3585 Connector SB350 GRAY , Position A , Lead Length 018 Inches												
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085C19	1530	106.9	44.44	38.56	22.63	4407	M2603608519Z	N	(CALL)		SCR20036865T1H	(CALL)	(CALL)
800CBP-1	FOUR WHEEL SIT DOWN RIDER		48 VOLTS , 44.90 X 39.60 X 24.00 Weight Minimum 3585 Connector SB350 GRAY , Position A , Lead Length 018 Inches												
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)
400CBSGH-6	SIT DOWN		36 VOLTS , 38.80 X 36.20 X 23.80 Weight Minimum 3000 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
400CBSGH-6	SIT DOWN		48 VOLTS , 38.80 X 36.20 X 23.80 Weight Minimum 3000 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
400CBSH-6	SIT DOWN		36 VOLTS , 38.80 X 29.10 X 23.80 Weight Minimum 2430 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
400CBSH-6	SIT DOWN		48 VOLTS , 38.80 X 29.10 X 23.80 Weight Minimum 2430 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)	SCR20024865T1H	(CALL)	(CALL)	
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
500CBEH-6	SIT DOWN		36 VOLTS , 38.80 X 36.20 X 23.80 Weight Minimum 3000 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
500CBEH-6	SIT DOWN		48 VOLTS , 38.80 X 36.20 X 23.80 Weight Minimum 3000 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
500CBSGH-6	SIT DOWN				36 VOLTS , 38.80 X 36.20 X 23.80						Weight Minimum 3000	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
500CBSGH-6	SIT DOWN				48 VOLTS , 38.80 X 36.20 X 23.80						Weight Minimum 3000	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
500CBSH-6	SIT DOWN				36 VOLTS , 38.80 X 29.10 X 23.80						Weight Minimum 2430	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	085C23	935	32.7	38.25	27.00	23.81	2674	M3401808523B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)	
500CBSH-6	SIT DOWN				48 VOLTS , 38.80 X 29.10 X 23.80						Weight Minimum 2430	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
600CBSH-6	SIT DOWN				36 VOLTS , 38.80 X 36.20 X 23.80						Weight Minimum 3000	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
600CBSH-6	SIT DOWN				48 VOLTS , 38.80 X 36.20 X 23.80						Weight Minimum 3000	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
650CBSH-6	SIT DOWN				36 VOLTS , 38.80 X 36.20 X 23.80						Weight Minimum 3000	Connector SB350	GRAY	, Position B , Lead Length 030 Inches		
	36	085F29	1190	41.6	38.44	33.81	22.63	3207	M2501808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085C29	1190	41.6	38.44	33.81	22.63	3202	M2601808529B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	100T29	1400	48.9	38.44	33.81	22.63	3378	M2801810029B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L29	1190	41.6	38.44	33.81	22.63	3308	M2901808529B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
250SBT-1	STAND UP				36 VOLTS , 38.70 X 20.70 X 31.50						Weight Minimum 2800	Connector SB350	GRAY	, Position D , Lead Length 009 Inches		
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
300SB-1	STAND UP							36 VOLTS , 38.70 X 16.10 X 31.50		Weight Minimum 1925	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
300SBH-1	STAND UP							36 VOLTS , 38.70 X 16.10 X 31.50		Weight Minimum 1925	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
330SBH-1	STAND UP							36 VOLTS , 38.70 X 18.10 X 31.50		Weight Minimum 2175	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
350SB-1	STAND UP							36 VOLTS , 38.70 X 16.10 X 31.50		Weight Minimum 1925	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
350SBH-1	STAND UP							36 VOLTS , 38.70 X 16.10 X 31.50		Weight Minimum 1925	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
380SBH-1	STAND UP							36 VOLTS , 38.70 X 18.10 X 31.50		Weight Minimum 2175	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
400SB-1	STAND UP							36 VOLTS , 38.70 X 20.70 X 31.50		Weight Minimum 2700	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
400SBH-1	STAND UP							36 VOLTS , 38.70 X 20.70 X 31.50		Weight Minimum 2700	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
450SBH-1	STAND UP							36 VOLTS , 38.70 X 20.70 X 31.50		Weight Minimum 2700	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
500SBH-1	STAND UP							36 VOLTS , 38.70 X 20.70 X 31.50		Weight Minimum 2700	Connector SB350	GRAY , Position D , Lead Length 009 Inches			
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
550SBH-1	STAND UP		36 VOLTS , 38.70 X 20.70 X 31.50 Weight Minimum 2700 Connector SB350 GRAY , Position D , Lead Length 009 Inches												
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
600SBH-1	STAND UP		36 VOLTS , 38.70 X 20.70 X 31.50 Weight Minimum 2800 Connector SB350 GRAY , Position D , Lead Length 009 Inches												
	36	125C17	1000	34.9	38.31	20.12	31.00	2804	M2601812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	31.00	2901	M2501812517B1	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
300MBS-3	3 Wheel Sit-Down		36 VOLTS , 38.80 X 21.30 X 24.00 Weight Minimum 1570 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
300MBS-3	3 Wheel Sit-Down		48 VOLTS , 38.80 X 21.30 X 24.00 Weight Minimum 1570 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
350MBS-3	3 Wheel Sit-Down		36 VOLTS , 38.80 X 21.30 X 24.00 Weight Minimum 1570 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	060B23	660	23.3	39.50	19.41	23.13	1960	M2101806023B	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
350MBS-3	3 Wheel Sit-Down		48 VOLTS , 38.80 X 21.30 X 24.00 Weight Minimum 1570 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
350MBSG-3	3 Wheel Sit-Down		36 VOLTS , 39.00 X 25.00 X 24.00 Weight Minimum 2160 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
36	075B23	825	29.1	38.50	24.00	23.82	2360	M2101807523B0	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
350MBSG-3	3 Wheel Sit-Down		48 VOLTS , 39.00 X 25.00 X 24.00 Weight Minimum 2160 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
48	075B17	600	28.2	38.50	24.56	25.46	2500	M2102407517B75981	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
400MBS-3	3 Wheel Sit-Down		36 VOLTS , 39.00 X 25.00 X 24.00 Weight Minimum 2160 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
36	075B23	825	29.1	38.50	24.00	23.82	2360	M2101807523B0	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
400MBS-3	3 Wheel Sit-Down		48 VOLTS , 39.00 X 25.00 X 24.00 Weight Minimum 2160 Connector SB350 GRAY , Position B , Lead Length 014 Inches												
48	075B17	600	28.2	38.50	24.56	25.46	2500	M2102407517B75981	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)