

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
MPB040-E	CLASS III LOW LIFT WALKIE PALLET											24 VOLTS , 28.00 X 9.10 X 999.00		Weight Minimum 310	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)			
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)			(CALL)	(CALL)			
MPB040-E	CLASS III LOW LIFT WALKIE PALLET											24 VOLTS , 28.50 X 8.10 X 999.00		Weight Minimum 310	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T05	200	4.7	27.75	7.57	23.25	496	M1801210005D6	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085L05	170	4.0	25.25	6.63	27.25	415	M1901208505GFPCZ	Y	(CALL)			(CALL)	(CALL)			
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	CHP	195	.0	27.30	7.50	26.45	400	M90004S24CHPX	Y	(CALL)			(CALL)	(CALL)			
MPW050-E	CLASS III LOW LIFT WALKIE-PALLET											24 VOLTS , 28.00 X 9.10 X 999.00		Weight Minimum 300	Connector SB175	RED	, Position B	, Lead Length 020 Inches
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)			
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	100C07	300	7.0	25.52	8.75	26.00	652	M1601210007D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)			(CALL)	(CALL)			
MPW060-E	CLASS III LOW LIFT WALKIE-PALLET											24 VOLTS , 32.00 X 9.00 X 999.00		Weight Minimum 500	Connector SB175	GRAY	, Position B	, Lead Length 016 Inches
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)			
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)			
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085L07	255	5.9	31.50	8.69	23.25	660	M1901208507DFPC	N	(CALL)			(CALL)	(CALL)			
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)			
MPW060-E	CLASS III LOW LIFT WALKIE-PALLET											24 VOLTS , 32.00 X 13.40 X 999.00		Weight Minimum 500	Connector SB175	GRAY	, Position B	, Lead Length 016 Inches
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)			
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)			
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)			
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)			
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)			
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)			
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)			
	24	100G09	400	9.4	31.00	12.75	24.20	860	M8901210009NPP	N	(CALL)			(CALL)	(CALL)			
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
MPW080-E	CLASS III LOW LIFT WALKIE-PALLET		24 VOLTS , 32.00 X 9.00 X 999.00		Weight Minimum 500			Connector SB175	GRAY	, Position B , Lead Length 016 Inches					
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	31.50	8.69	23.25	660	M1901208507DFPC	N	(CALL)			(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
MPW080-E	CLASS III LOW LIFT WALKIE-PALLET		24 VOLTS , 32.00 X 13.40 X 999.00		Weight Minimum 500			Connector SB175	GRAY	, Position B , Lead Length 016 Inches					
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
MPE060-VG	CLASS III LOW LIFT WALKIE/RIDER PALLET		24 VOLTS , 31.25 X 9.00 X 999.00		Weight Minimum 500			Connector SB175	RED	, Position B , Lead Length 020 Inches					
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
MPE060-VG	CLASS III LOW LIFT WALKIE/RIDER PALLET		24 VOLTS , 31.25 X 13.40 X 999.00		Weight Minimum 500			Connector SB175	RED	, Position B , Lead Length 020 Inches					
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
MPE080-VG	CLASS III LOW LIFT WALKIE/RIDER PALLET		24 VOLTS , 31.25 X 9.00 X 999.00		Weight Minimum 500			Connector SB175	RED	, Position B , Lead Length 020 Inches					
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
MPE080-VG	CLASS III LOW LIFT WALKIE/RIDER PALLET				24 VOLTS , 31.25 X 13.40 X 999.00				Weight Minimum 500	Connector SB175	RED	, Position B , Lead Length 020 Inches			
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
MPC060-F	CLASS III LOW LIFT WALKIE/RIDER CENTER CONTROL				24 VOLTS , 31.20 X 13.40 X 999.00				Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches			
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
MPC080-F	CLASS III LOW LIFT WALKIE/RIDER CENTER CONTROL				24 VOLTS , 31.20 X 13.40 X 999.00				Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches			
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
MTR005-F	CLASS III TRACTOR TUGGER				24 VOLTS , 31.20 X 13.40 X 999.00				Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches			
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
MTR007-F	CLASS III TRACTOR TUGGER			24 VOLTS , 31.20 X 13.40 X 999.00					Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
MCW025-E	CLASS III WALKIE HIGH LIFT COUNTERBALANCED			24 VOLTS , 33.00 X 13.50 X 999.00					Weight Minimum 900	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
MCW030-E	CLASS III WALKIE HIGH LIFT COUNTERBALANCED			24 VOLTS , 33.00 X 13.50 X 999.00					Weight Minimum 900	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
MCW040-E	CLASS III WALKIE HIGH LIFT COUNTERBALANCED			24 VOLTS , 33.00 X 13.50 X 999.00					Weight Minimum 900	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
MRW020-E	CLASS III WALKIE HIGH LIFT COUNTERBALANCED			24 VOLTS , 33.00 X 13.50 X 999.00					Weight Minimum 600	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
MRW030-E	CLASS III WALKIE HIGH LIFT COUNTERBALANCED			24 VOLTS , 33.00 X 13.50 X 999.00					Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
MSW025-F	CLASS III WALKIE HIGH LIFT STRADDLE			24 VOLTS , 28.30 X 8.00 X 999.00					Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L05	170	4.0	26.50	7.50	27.25	466	M1901208505G6BFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100C05	200	4.7	25.25	6.50	25.63	455	M1601210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
MSW025-F	CLASS III WALKIE HIGH LIFT STRADDLE			24 VOLTS , 28.30 X 9.00 X 999.00					Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100C07	300	7.0	25.52	8.75	26.00	652	M1601210007D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
MSW025-F	CLASS III WALKIE HIGH LIFT STRADDLE			24 VOLTS , 32.90 X 9.00 X 999.00					Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
MSW030-F	CLASS III WALKIE HIGH LIFT STRADDLE			24 VOLTS , 28.30 X 8.00 X 999.00					Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L05	170	4.0	26.50	7.50	27.25	466	M1901208505G6BFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100C05	200	4.7	25.25	6.50	25.63	455	M1601210005G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
MSW030-F	CLASS III WALKIE HIGH LIFT STRADDLE			24 VOLTS , 28.30 X 9.00 X 999.00					Weight Minimum 800	Connector SB175	RED	, Position B , Lead Length 020 Inches				
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	25.38	8.69	27.25	593	M1901208507DFPCZ	N	(CALL)			(CALL)	(CALL)	
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	100C07	300	7.0	25.52	8.75	26.00	652	M1601210007D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
MSW030-F	CLASS III WALKIE HIGH LIFT STRADDLE		24 VOLTS , 32.90 X 9.00 X 999.00 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
MSW040-E	CLASS III WALKIE HIGH LIFT STRADDLE		24 VOLTS , 33.00 X 9.00 X 999.00 Weight Minimum 400 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	27.25	609	M1901208507D2FPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	090G05	180	4.2	32.50	8.61	23.56	678	M8901209005CPP25	Y	(CALL)			(CALL)	(CALL)
MSW040-E	CLASS III WALKIE HIGH LIFT STRADDLE		24 VOLTS , 33.00 X 13.50 X 999.00 Weight Minimum 600 Connector SB175 RED , Position B , Lead Length 020 Inches												
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T11	500	11.6	30.81	12.88	23.25	910	M1801210011A25A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	27.25	991	M1901208513AFPCZ	N	(CALL)			(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C11	425	9.9	30.81	12.88	23.25	860	M1601208511A25A	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
OS030BF	CLASS II ORDER PICKER		24 VOLTS , 39.00 X 14.60 X 31.50 Weight Minimum 1600 Connector SB350 RED , Position B , Lead Length 016 Inches												
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B29	840	19.8	38.50	14.19	30.80	1635	M2101206029FB0	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
OS030BF	CLASS II ORDER PICKER		36 VOLTS , 39.00 X 14.60 X 31.50 Weight Minimum 1500 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
OS030EF	CLASS II ORDER PICKER		24 VOLTS , 36.00 X 13.50 X 25.00 Weight Minimum 945 Connector SB175 RED , Position B , Lead Length 016 Inches												
	24	100T15	700	16.3	35.06	12.88	22.50	1145	M2801210015A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085L15	595	13.9	35.06	12.88	22.50	1109	M2901208515A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F15	595	13.9	35.06	12.88	22.50	1127	M2501208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C15	595	13.9	35.06	12.88	22.50	1076	M2601208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
SS030BF	CLASS II ORDER PICKER		24 VOLTS , 39.00 X 14.60 X 30.80 Weight Minimum 1500 Connector SB350 RED , Position B , Lead Length 016 Inches												
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
FS030BF	CLASS II ORDER PICKER		24 VOLTS , 39.00 X 14.60 X 31.50 Weight Minimum 1500 Connector SB350 RED , Position B , Lead Length 025 Inches												
	24	060B29	840	19.8	38.50	14.19	30.80	1635	M2101206029FB0	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
SS030BF	CLASS II ORDER PICKER		36 VOLTS , 39.00 X 14.60 X 30.80 Weight Minimum 1500 Connector SB350 RED , Position B , Lead Length 016 Inches												
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
FS030BF	CLASS II FURNITURE ORDER PICKER		24 VOLTS , 39.00 X 14.60 X 30.80 Weight Minimum 1500 Connector SB350 RED , Position B , Lead Length 016 Inches												
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
FS030BF	CLASS II FURNITURE ORDER PICKER		36 VOLTS , 39.00 X 14.60 X 30.80 Weight Minimum 1500 Connector SB350 RED , Position B , Lead Length 016 Inches												
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NR035DA	CLASS II NARROW AISLE REACH		24 VOLTS , 39.00 X 12.50 X 31.50 Weight Minimum 1400 Connector SB350 RED , Position B , Lead Length 016 Inches												
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
NR035DA	CLASS II NARROW AISLE REACH		24 VOLTS , 39.00 X 14.50 X 31.50 Weight Minimum 1600 Connector SB350 RED , Position B , Lead Length 016 Inches												
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
NR035DA	CLASS II NARROW AISLE REACH		36 VOLTS , 39.00 X 14.50 X 31.50 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
NR035DA	CLASS II NARROW AISLE REACH											36 VOLTS , 39.00 X 16.50 X 31.50				Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NR040DA	CLASS II NARROW AISLE REACH											24 VOLTS , 39.00 X 12.50 X 31.50				Weight Minimum 1400	Connector SB350	RED	, Position B , Lead Length 016 Inches
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
NR040DA	CLASS II NARROW AISLE REACH											24 VOLTS , 39.00 X 14.50 X 31.50				Weight Minimum 1600	Connector SB350	RED	, Position B , Lead Length 016 Inches
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
NR040DA	CLASS II NARROW AISLE REACH											36 VOLTS , 39.00 X 14.50 X 31.50				Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NR040DA	CLASS II NARROW AISLE REACH											36 VOLTS , 39.00 X 16.50 X 31.50				Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NR035EA	CLASS II NARROW AISLE REACH											36 VOLTS , 39.00 X 14.50 X 31.50				Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NR035EA	CLASS II NARROW AISLE REACH											36 VOLTS , 39.00 X 16.50 X 31.50				Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NR040EA	CLASS II NARROW AISLE REACH											36 VOLTS , 39.00 X 14.50 X 31.50				Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NR040EA	CLASS II NARROW AISLE REACH			36 VOLTS , 39.00 X 16.50 X 31.50			Weight Minimum 1850		Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NR045EA	CLASS II NARROW AISLE REACH			36 VOLTS , 39.00 X 16.50 X 31.50			Weight Minimum 1850		Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NR045EA	CLASS II NARROW AISLE REACH			36 VOLTS , 39.00 X 18.50 X 31.50			Weight Minimum 2200		Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
NR045EA	CLASS II NARROW AISLE REACH			36 VOLTS , 39.00 X 21.50 X 31.50			Weight Minimum 2500		Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
NDR030DA	CLASS II NARROW AISLE DOUBLE REACH			24 VOLTS , 39.00 X 12.50 X 31.50			Weight Minimum 1400		Connector SB350	RED	, Position B , Lead Length 016 Inches				
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
NDR030DA	CLASS II NARROW AISLE DOUBLE REACH			24 VOLTS , 39.00 X 14.50 X 31.50			Weight Minimum 1600		Connector SB350	RED	, Position B , Lead Length 016 Inches				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
NDR030DA	CLASS II NARROW AISLE DOUBLE REACH			36 VOLTS , 39.00 X 14.50 X 31.50			Weight Minimum 1600		Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NDR030DA	CLASS II NARROW AISLE DOUBLE REACH			36 VOLTS , 39.00 X 16.50 X 31.50			Weight Minimum 1850		Connector SB350	GRAY	, Position B , Lead Length 016 Inches				
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
NDR030EA	CLASS II NARROW AISLE DOUBLE REACH											36 VOLTS , 39.00 X 14.50 X 31.50				Weight Minimum 1600	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NDR030EA	CLASS II NARROW AISLE DOUBLE REACH											36 VOLTS , 39.00 X 16.50 X 31.50				Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NDR035EA	CLASS II NARROW AISLE DOUBLE REACH											36 VOLTS , 39.00 X 16.50 X 31.50				Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
NDR035EA	CLASS II NARROW AISLE DOUBLE REACH											36 VOLTS , 39.00 X 18.50 X 31.50				Weight Minimum 2200	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
NDR035EA	CLASS II NARROW AISLE DOUBLE REACH											36 VOLTS , 39.00 X 21.50 X 31.50				Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
NTA030SB	CLASS II VERY NARROW AISLE TURRET											48 VOLTS , 41.00 X 25.50 X 36.00				Weight Minimum 3068	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	140T15	980	45.6	38.31	24.63	31.00	3756	M2802414015B7	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	125L15	875	40.7	38.31	24.63	31.00	3588	M2902412515B7	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	125F15	875	40.7	38.31	24.63	31.00	3613	M2502412515B7	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	125C15	875	40.7	38.31	24.63	31.00	3494	M2602412515B7	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
NTA030SB	CLASS II VERY NARROW AISLE TURRET											48 VOLTS , 41.00 X 28.30 X 36.00				Weight Minimum 3068	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	140T17	1120	52.1	38.44	26.88	30.50	3862	M2802414017B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
	48	125L17	1000	46.6	38.44	26.88	30.50	3741	M2902412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	125F17	1000	46.6	38.44	26.88	30.50	3763	M2502412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	125C17	1000	46.6	38.44	26.88	30.50	3636	M2602412517B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
NTA030SB	CLASS II VERY NARROW AISLE TURRET											48 VOLTS , 41.80 X 24.20 X 36.00				Weight Minimum 2976	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	140T15	980	45.6	38.31	23.62	30.50	3283	M2802414015B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)				
	48	125L15	825	38.4	38.31	23.62	30.50	3167	M2902412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	125F15	875	40.7	38.31	23.62	30.50	3170	M2502412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
	48	125C15	875	40.7	38.31	23.62	30.50	3084	M2602412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
NTA030SB	CLASS II VERY NARROW AISLE TURRET											48 VOLTS , 44.90 X 21.50 X 36.00				Weight Minimum 2976	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	140T13	840	39.1	44.19	20.88	30.50	3291	M2802414013B40	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	125L13	750	34.9	44.19	20.88	30.50	3144	M2902412513B40	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	125F13	750	34.9	44.19	20.88	30.50	3169	M2502412513B40	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	125C13	750	34.9	44.19	20.88	30.50	3063	M2602412513B40	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
NTA035SB	CLASS II VERY NARROW AISLE TURRET											72 VOLTS , 41.00 X 28.30 X 36.00				Weight Minimum 3307	Connector SB350	GREEN , Position B , Lead Length 030 Inches
	72	140T11	700	48.9	37.81	26.81	30.50	3528	M2803614011B	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)			
	72	125L11	625	43.7	37.81	26.82	30.50	3473	M2903612511B	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)			
	72	125F11	625	43.7	37.81	26.81	30.50	3413	M2503612511B	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)			
	72	125C11	625	43.7	37.81	26.81	30.50	3312	M2603612511B	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)			
NTA035SB	CLASS II VERY NARROW AISLE TURRET											72 VOLTS , 41.00 X 32.10 X 36.00				Weight Minimum 4079	Connector SB350	GREEN , Position B , Lead Length 030 Inches
	72	125F13	750	52.4	38.81	31.31	30.75	4446	M2903612513B41A	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)			
	72	125F13	750	52.4	38.81	31.31	30.75	4498	M2503612513B41A	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)			
	72	125C13	750	52.4	38.81	31.31	30.75	4337	M2603612513B41A	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)			
NTA035SB-TWO BATTERIES NEEDED (2*36=72 VOLT)	CLASS II VERY NARROW AISLE TURRET											72 VOLTS , 41.00 X 28.30 X 36.00				Weight Minimum 3307	Connector SB350	GREEN , Position B , Lead Length 030 Inches
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125L11	625	21.8	38.00	13.25	30.50	1725	M2901812511B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
NTA035SB-TWO BATTERIES NEEDED (2*36=72 VOLT)	CLASS II VERY NARROW AISLE TURRET											72 VOLTS , 41.00 X 32.10 X 36.00				Weight Minimum 4079	Connector SB350	GREEN , Position B , Lead Length 030 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
NTA035SB-TWO BATTERIES NEEDED (2*36=72 VOLT)	CLASS II VERY NARROW AISLE TURRET											72 VOLTS , 41.00 X 38.30 X 36.00				Weight Minimum 4189	Connector SB350	GREEN , Position B , Lead Length 030 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	48	100L11	500	23.3	31.94	21.94	25.63	1930	M2902410011Z	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)			
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
NTA035SB-TWO BATTERIES NEEDED (2*36=72 VOLT)	CLASS II VERY NARROW AISLE TURRET											72 VOLTS , 41.00 X 41.10 X 36.00				Weight Minimum 4189	Connector SB350	GREEN , Position B , Lead Length 030 Inches
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
ERP030VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.00 X 21.50 X 23.90				Weight Minimum 1700	Connector SB350	GRAY , Position A , Lead Length 020 Inches
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)			
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
ERP030VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE										36 VOLTS , 39.00 X 21.50 X 25.40	Weight Minimum 1700	Connector SB350	GRAY , Position A , Lead Length 020 Inches		
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
ERP030VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE										36 VOLTS , 39.00 X 21.50 X 26.70	Weight Minimum 2000	Connector SB350	GRAY , Position A , Lead Length 020 Inches		
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
ERP030VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE										48 VOLTS , 39.00 X 21.50 X 23.90	Weight Minimum 1700	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
ERP030VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE										48 VOLTS , 39.00 X 21.50 X 25.40	Weight Minimum 1700	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
ERP030VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE										48 VOLTS , 39.00 X 21.50 X 26.70	Weight Minimum 2000	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	100F13	600	27.9	38.50	20.63	25.63	2300	M2502410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100C13	600	27.9	38.50	20.63	25.63	2201	M2602410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
ERP035VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE										36 VOLTS , 39.00 X 25.30 X 23.90	Weight Minimum 2100	Connector SB350	GRAY , Position B , Lead Length 020 Inches		
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
ERP035VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE										36 VOLTS , 39.00 X 25.30 X 25.40	Weight Minimum 2100	Connector SB350	GRAY , Position B , Lead Length 020 Inches		
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
ERP035VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE										36 VOLTS , 39.00 X 25.30 X 26.70	Weight Minimum 2500	Connector SB350	GRAY , Position B , Lead Length 020 Inches		
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
ERP035VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE										48 VOLTS , 39.00 X 25.30 X 23.90	Weight Minimum 2100	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
ERP035VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.00 X 25.30 X 25.40				Weight Minimum 2100	Connector SB350	BLUE	, Position B , Lead Length 020 Inches
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)			(CALL)	(CALL)				
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
ERP035VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.00 X 25.30 X 26.70				Weight Minimum 2100	Connector SB350	BLUE	, Position B , Lead Length 020 Inches
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
ERP040VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.00 X 25.30 X 23.90				Weight Minimum 2100	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
ERP040VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.00 X 25.30 X 25.40				Weight Minimum 2100	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
ERP040VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.00 X 25.30 X 26.70				Weight Minimum 2500	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
ERP040VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.00 X 25.30 X 23.90				Weight Minimum 2100	Connector SB350	BLUE	, Position B , Lead Length 020 Inches
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
ERP040VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.00 X 25.30 X 25.40				Weight Minimum 2100	Connector SB350	BLUE	, Position B , Lead Length 020 Inches
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
ERP040VT	CLASS I 3-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.00 X 25.30 X 26.70				Weight Minimum 2500	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



Yale 2012 Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC030VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE				36 VOLTS , 35.80 X 27.60 X 23.50			Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 020 Inches				
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L19	765	26.7	35.18	25.81	22.62	2285	M2901808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC030VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE				36 VOLTS , 35.80 X 27.60 X 24.00			Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 020 Inches				
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085L19	765	26.7	35.18	25.81	22.62	2285	M2901808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ERC030VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE				48 VOLTS , 35.80 X 27.60 X 23.50			Weight Minimum 1850	Connector SB350	BLUE	, Position B , Lead Length 020 Inches				
	48	100T13	600	27.9	30.92	25.62	22.62	1924	M2802410013A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)
	48	085L13	510	23.7	30.81	25.63	22.63	2040	M2902408513A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	30.92	25.62	22.62	2006	M2502408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	30.92	25.62	22.62	1930	M2602408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERC030VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE				48 VOLTS , 35.80 X 27.60 X 24.00			Weight Minimum 1850	Connector SB350	BLUE	, Position B , Lead Length 020 Inches				
	48	100T13	600	27.9	30.92	25.62	22.62	1924	M2802410013A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)
	48	085L13	510	23.7	30.81	25.63	22.63	2040	M2902408513A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	30.92	25.62	22.62	2006	M2502408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	30.92	25.62	22.62	1930	M2602408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC035VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE				36 VOLTS , 35.80 X 27.60 X 23.50				Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 020 Inches			
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085L19	765	26.7	35.18	25.81	22.62	2285	M2901808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ERC035VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE				36 VOLTS , 35.80 X 27.60 X 24.00				Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 020 Inches			
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L19	765	26.7	35.18	25.81	22.62	2285	M2901808519V	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC035VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE				48 VOLTS , 35.80 X 27.60 X 23.50				Weight Minimum 1850	Connector SB350	BLUE	, Position B , Lead Length 020 Inches			
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T13	600	27.9	30.92	25.62	22.62	1924	M2802410013A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	30.81	25.63	22.63	2040	M2902408513A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	30.92	25.62	22.62	2006	M2502408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	30.92	25.62	22.62	1930	M2602408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERC035VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE				48 VOLTS , 35.80 X 27.60 X 24.00				Weight Minimum 1850	Connector SB350	BLUE	, Position B , Lead Length 020 Inches			
	48	100T13	600	27.9	30.92	25.62	22.62	1924	M2802410013A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L13	510	23.7	30.81	25.63	22.63	2040	M2902408513A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	30.92	25.62	22.62	2006	M2502408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	30.92	25.62	22.62	1930	M2602408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC040VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 35.80 X 27.60 X 23.50			Weight Minimum 1850		Connector SB350	GRAY , Position B , Lead Length 020 Inches					
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H		(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L19	765	26.7	35.18	25.81	22.62	2285	M2901808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC040VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 35.80 X 27.60 X 24.00			Weight Minimum 1850		Connector SB350	GRAY , Position B , Lead Length 020 Inches					
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H		(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085L19	765	26.7	35.18	25.81	22.62	2285	M2901808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ERC040VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			48 VOLTS , 35.80 X 27.60 X 23.50			Weight Minimum 1850		Connector SB350	BLUE , Position B , Lead Length 020 Inches					
	48	100T13	600	27.9	30.92	25.62	22.62	1924	M2802410013A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085L13	510	23.7	30.81	25.63	22.63	2040	M2902408513A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	30.92	25.62	22.62	2006	M2502408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	30.92	25.62	22.62	1930	M2602408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERC040VA	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			48 VOLTS , 35.80 X 27.60 X 24.00			Weight Minimum 1850		Connector SB350	BLUE , Position B , Lead Length 020 Inches					
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T13	600	27.9	30.92	25.62	22.62	1924	M2802410013A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L15	595	27.7	35.31	25.38	22.63	2280	M2902408515A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L13	510	23.7	30.81	25.63	22.63	2040	M2902408513A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	30.92	25.62	22.62	2006	M2502408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	30.92	25.62	22.62	1930	M2602408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERC045VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 39.10 X 27.60 X 23.90			Weight Minimum 2300		Connector SB350	GRAY , Position B , Lead Length 020 Inches					
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)	SCR20018965T1H		(CALL)	(CALL)
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)	SCR20018965T1H		(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)	SCR20018965T1H		(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)	SCR20018865T1H		(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
ERC045VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.10 X 30.90 X 23.90		Weight Minimum 2500	Connector SB350	GRAY , Position B , Lead Length 020 Inches	
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
ERC045VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.10 X 33.30 X 23.90		Weight Minimum 2900	Connector SB350	GRAY , Position B , Lead Length 020 Inches	
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
ERC045VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.10 X 27.60 X 23.90		Weight Minimum 2300	Connector SB350	BLUE , Position B , Lead Length 020 Inches	
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)		
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)		
ERC045VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.10 X 30.90 X 23.90		Weight Minimum 2500	Connector SB350	BLUE , Position B , Lead Length 020 Inches	
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)		
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)		
ERC045VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.10 X 33.30 X 23.90		Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 020 Inches	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)		
ERC045VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											80 VOLTS , 39.10 X 27.60 X 23.90		Weight Minimum 2300	Connector SB350	BLACK , Position B , Lead Length 020 Inches	
	80	085C09	340	26.4	38.00	27.00	22.63	2417	M2604008509X	N	(CALL)		SCR20040475T1H	(CALL)	(CALL)		
ERC045VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											80 VOLTS , 39.10 X 30.90 X 23.90		Weight Minimum 2500	Connector SB350	BLACK , Position B , Lead Length 020 Inches	
	80	085C09	340	26.4	38.00	30.00	22.63	2671	M2604008509XA	N	(CALL)		SCR20040475T1H	(CALL)	(CALL)		
ERC045VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											80 VOLTS , 39.10 X 33.30 X 23.90		Weight Minimum 2900	Connector SB350	BLACK , Position B , Lead Length 020 Inches	
	80	085C11	425	33.0	38.00	32.50	22.63	3112	M2604008511X	N	(CALL)		SCR20040475T1H	(CALL)	(CALL)		
ERC050VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.10 X 27.60 X 23.90		Weight Minimum 2300	Connector SB350	GRAY , Position B , Lead Length 020 Inches	
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)		

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC050VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 39.10 X 30.90 X 23.90			Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC050VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 39.10 X 33.30 X 23.90			Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC050VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			48 VOLTS , 39.10 X 27.60 X 23.90			Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 020 Inches					
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
ERC050VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			48 VOLTS , 39.10 X 30.90 X 23.90			Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 020 Inches					
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
ERC050VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			48 VOLTS , 39.10 X 33.30 X 23.90			Weight Minimum 2900	Connector SB350	BLUE	, Position B , Lead Length 020 Inches					
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
ERC050VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			80 VOLTS , 39.10 X 27.60 X 23.90			Weight Minimum 2300	Connector SB350	BLACK	, Position B , Lead Length 020 Inches					
	80	085C09	340	26.4	38.00	27.00	22.63	2417	M2604008509X	N	(CALL)		SCR20040475T1H	(CALL)	(CALL)
ERC050VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			80 VOLTS , 39.10 X 30.90 X 23.90			Weight Minimum 2500	Connector SB350	BLACK	, Position B , Lead Length 020 Inches					
	80	085C09	340	26.4	38.00	30.00	22.63	2671	M2604008509XA	N	(CALL)		SCR20040475T1H	(CALL)	(CALL)
ERC050VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			80 VOLTS , 39.10 X 33.30 X 23.90			Weight Minimum 2900	Connector SB350	BLACK	, Position B , Lead Length 020 Inches					
	80	085C11	425	33.0	38.00	32.50	22.63	3112	M2604008511X	N	(CALL)		SCR20040475T1H	(CALL)	(CALL)
ERC055VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 39.10 X 33.30 X 23.90			Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 020 Inches					
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
ERC055VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.10 X 33.30 X 23.90	Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)		
ERC055VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											80 VOLTS , 39.10 X 33.30 X 23.90	Weight Minimum 2900	Connector SB350	BLACK , Position B , Lead Length 020 Inches		
	80	085C11	425	33.0	38.00	32.50	22.63	3112	M2604008511X	N	(CALL)		SCR20040475T1H	(CALL)	(CALL)		
ERC060VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.10 X 33.30 X 23.90	Weight Minimum 2900	Connector SB350	GRAY , Position B , Lead Length 020 Inches		
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
ERC060VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.10 X 33.30 X 23.90	Weight Minimum 2900	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)		
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)		
ERC060VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											80 VOLTS , 39.10 X 33.30 X 23.90	Weight Minimum 2900	Connector SB350	BLACK , Position B , Lead Length 020 Inches		
	80	085C11	425	33.0	38.00	32.50	22.63	3112	M2604008511X	N	(CALL)		SCR20040475T1H	(CALL)	(CALL)		
ERC065VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.10 X 36.70 X 23.90	Weight Minimum 3100	Connector SB350	GRAY , Position B , Lead Length 020 Inches		
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)		
	36	085L31	1275	44.5	38.44	36.13	22.63	3555	M2901808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	105B23	1155	40.7	39.61	36.00	23.25	3400	M2101810523B01459	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
ERC065VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.10 X 40.00 X 23.90	Weight Minimum 3100	Connector SB350	GRAY , Position B , Lead Length 020 Inches		
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)		
	36	085L33	1360	47.5	38.37	38.43	22.62	3787	M2901808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
ERC065VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.10 X 36.70 X 23.90	Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	085L23	935	43.5	38.44	35.88	22.63	3560	M2902408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)		
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)		
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
ERC065VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.10 X 40.00 X 23.90	Weight Minimum 3100	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	085F25	1020	47.5	38.88	38.44	23.12	4150	M2502408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	085C25	1020	47.5	38.88	38.44	23.12	3911	M2602408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
ERC065VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											80 VOLTS , 39.10 X 36.70 X 23.90	Weight Minimum 3100	Connector SB350	BLACK , Position B , Lead Length 020 Inches		
	80	085C13	510	39.6	38.00	35.75	22.63	3301	M2604008513X	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)		
ERC065VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											80 VOLTS , 39.10 X 40.00 X 23.90	Weight Minimum 3400	Connector SB350	BLACK , Position B , Lead Length 020 Inches		
	80	085C13	510	39.6	38.00	38.75	22.63	3586	M2604008513XA	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)		
ERC070VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 39.10 X 40.00 X 23.90	Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 020 Inches		
	36	100T33	1600	55.9	38.37	38.43	22.62	3977	M2801810033C	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)		
	36	085L33	1360	47.5	38.37	38.43	22.62	3787	M2901808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085F33	1360	47.5	38.37	38.43	22.62	3854	M2501808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085C33	1360	47.5	38.37	38.43	22.62	3722	M2601808533C	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	105B23	1155	40.7	39.61	38.75	23.50	3525	M2101810523B714	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
ERC070VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 39.10 X 40.00 X 23.90	Weight Minimum 3100	Connector SB350	BLUE , Position B , Lead Length 020 Inches		
	48	085F25	1020	47.5	38.88	38.44	23.12	4150	M2502408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
	48	085C25	1020	47.5	38.88	38.44	23.12	3911	M2602408525C	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
ERC070VG	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											80 VOLTS , 39.10 X 40.00 X 23.90	Weight Minimum 3400	Connector SB350	BLACK , Position B , Lead Length 020 Inches		
	80	085C13	510	39.6	38.00	38.75	22.63	3586	M2604008513XA	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)		
ERC070HH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 44.10 X 39.20 X 23.15	Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	100T33	1600	55.9	43.38	38.62	22.62	3938	M2801810033C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085L33	1360	47.5	43.38	38.63	22.63	4085	M2901808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
ERC070HH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											36 VOLTS , 45.20 X 39.20 X 24.60	Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches		
	36	085F33	1360	47.5	43.38	38.43	23.25	4148	M1501808533C6	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)		
ERC070HH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 44.10 X 39.20 X 23.15	Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches		
	48	100T27	1300	60.5	41.88	38.44	22.63	4298	M2802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)		
	48	085L27	1105	51.4	41.89	38.44	22.63	4260	M2902408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
ERC070HH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE											48 VOLTS , 45.20 X 39.20 X 24.60	Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches		
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	(CALL)		SCR200241450T1H	(CALL)	(CALL)		
	48	085L27	1105	51.4	41.89	38.44	23.25	4330	M1902408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)		
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC080VH / ERC100VHS	CLASS I 4-WHEEL COUNTERBALANCED			36 VOLTS , 45.40 X 39.20 X 24.50			Weight Minimum 3400		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	36	100T33	1600	55.9	43.38	38.62	22.62	3938	M2801810033C6	N	(CALL)	SCR200181450T1H	(CALL)	(CALL)	
	36	085L33	1360	47.5	43.38	38.63	22.63	4085	M2901808533C6	N	(CALL)	SCR200181450T1H	(CALL)	(CALL)	
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	(CALL)	SCR200181450T1H	(CALL)	(CALL)	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	(CALL)	SCR200181450T1H	(CALL)	(CALL)	
ERC080VH / ERC100VHS	CLASS I 4-WHEEL COUNTERBALANCED			48 VOLTS , 45.40 X 39.20 X 24.50			Weight Minimum 3400		Connector SB350	BLUE	, Position B , Lead Length 025 Inches				
	48	100T29	1400	65.2	45.06	38.62	22.63	4500	M2802410029C	N	(CALL)	SCR200241450T1H	(CALL)	(CALL)	
	48	085L29	1190	55.4	44.88	38.44	22.63	4338	M2902408529C	N	(CALL)	SCR200241200T1H	(CALL)	(CALL)	
	48	085F29	1190	55.4	45.06	38.63	22.63	4434	M2502408529C	N	(CALL)	SCR200241200T1H	(CALL)	(CALL)	
	48	085C29	1190	55.4	45.06	38.62	22.63	4274	M2602408529C	N	(CALL)	SCR200241200T1H	(CALL)	(CALL)	
ERC080VH / ERC100VHS	CLASS I 4-WHEEL COUNTERBALANCED			80 VOLTS , 45.40 X 39.20 X 24.50			Weight Minimum 3400		Connector SBE320	BLACK	, Position B , Lead Length 025 Inches				
	80	100T15	700	54.3	41.09	38.31	22.63	3990	M2804010015K	N	(CALL)	SCR20040750T1H	(CALL)	(CALL)	
	80	085L15	595	46.2	41.09	38.31	22.63	3812	M2904008515K	N	(CALL)	SCR20040600T1H	(CALL)	(CALL)	
	80	085F15	595	46.2	41.09	38.31	22.63	3841	M2504008515K	N	(CALL)	SCR20040600T1H	(CALL)	(CALL)	
	80	085C15	595	46.2	41.09	38.31	22.63	3712	M2604008515K	N	(CALL)	SCR20040600T1H	(CALL)	(CALL)	
ERC100VH / ERC120VH	CLASS I 4-WHEEL COUNTERBALANCED			36 VOLTS , 45.40 X 45.70 X 24.50			Weight Minimum 4000		Connector SB350	GRAY	, Position B , Lead Length 025 Inches				
	36	100T19	1800	125.7	43.50	44.50	22.62	4500	M2803610019Z6	N	(CALL)	SCR200181700T1H	(CALL)	(CALL)	
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	(CALL)	SCR200181700T1H	(CALL)	(CALL)	
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	(CALL)	SCR200181700T1H	(CALL)	(CALL)	
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	(CALL)	SCR200181700T1H	(CALL)	(CALL)	
ERC100VH / ERC120VH	CLASS I 4-WHEEL COUNTERBALANCED			48 VOLTS , 45.40 X 45.70 X 24.50			Weight Minimum 4000		Connector SB350	BLUE	, Position B , Lead Length 025 Inches				
	48	100T33	1600	74.5	44.88	44.63	22.88	5170	M2802410033W	N	(CALL)	SCR200241450T1H	(CALL)	(CALL)	
	48	085L33	1360	63.3	44.88	44.63	22.88	4981	M2902408533W	N	(CALL)	SCR200241450T1H	(CALL)	(CALL)	
	48	085F33	1360	63.3	44.88	44.63	22.88	5020	M2502408533W	N	(CALL)	SCR200241450T1H	(CALL)	(CALL)	
	48	085C33	1360	63.3	44.88	44.63	22.88	4851	M2602408533W	N	(CALL)	SCR200241450T1H	(CALL)	(CALL)	
ERC100VH / ERC120VH	CLASS I 4-WHEEL COUNTERBALANCED			80 VOLTS , 45.40 X 45.70 X 24.50			Weight Minimum 4000		Connector SBE320	BLACK	, Position B , Lead Length 025 Inches				
	80	100T17	800	62.1	39.81	44.59	22.65	4632	M2804010017H	N	(CALL)	SCR20040865T1H	(CALL)	(CALL)	
	80	085L17	680	52.8	39.81	44.59	22.63	4425	M2904008517H	N	(CALL)	SCR20040750T1H	(CALL)	(CALL)	
	80	085F17	680	52.8	39.81	44.59	22.63	4459	M2504008517H	N	(CALL)	SCR20040750T1H	(CALL)	(CALL)	
	80	085C17	680	52.8	39.81	44.59	22.63	4309	M2604008517H	N	(CALL)	SCR20040750T1H	(CALL)	(CALL)	
ERP030VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE			36 VOLTS , 39.00 X 21.50 X 23.90			Weight Minimum 1700		Connector SB350	GRAY	, Position A , Lead Length 020 Inches				
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	060B21	600	21.2	38.50	20.75	24.50	2077	M2101806021B7	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
ERP030VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE			36 VOLTS , 39.00 X 21.50 X 25.40			Weight Minimum 1700		Connector SB350	GRAY	, Position A , Lead Length 020 Inches				
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	060B21	600	21.2	38.50	20.75	24.50	2077	M2101806021B7	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
ERP030VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											36 VOLTS , 39.00 X 21.50 X 26.70				Weight Minimum 2000	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	060B25	720	25.4	38.50	20.34	25.69	2130	M2101806025B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ERP030VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											48 VOLTS , 39.00 X 21.50 X 23.90				Weight Minimum 1700	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
ERP030VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											48 VOLTS , 39.00 X 21.50 X 25.40				Weight Minimum 1700	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085L13	510	23.7	38.00	20.50	22.63	1878	M2902408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
ERP030VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											48 VOLTS , 39.00 X 21.50 X 26.70				Weight Minimum 2000	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100F13	600	27.9	38.50	20.63	25.63	2300	M2502410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100C13	600	27.9	38.50	20.63	25.63	2201	M2602410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
ERP035VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											36 VOLTS , 39.00 X 25.30 X 23.90				Weight Minimum 2100	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ERP035VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											36 VOLTS , 39.00 X 25.30 X 25.40				Weight Minimum 2100	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ERP035VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											36 VOLTS , 39.00 X 25.30 X 26.70				Weight Minimum 2500	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
ERP035VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											48 VOLTS , 39.00 X 25.30 X 23.90				Weight Minimum 2100	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
ERP035VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											48 VOLTS , 39.00 X 25.30 X 25.40				Weight Minimum 2100	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
ERP035VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											48 VOLTS , 39.00 X 25.30 X 26.70				Weight Minimum 2500	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
ERP040VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											36 VOLTS , 39.00 X 25.30 X 23.90				Weight Minimum 2100	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ERP040VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											36 VOLTS , 39.00 X 25.30 X 25.40				Weight Minimum 2100	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ERP040VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											36 VOLTS , 39.00 X 25.30 X 26.70				Weight Minimum 2500	Connector SB350	GRAY	, Position A , Lead Length 020 Inches
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
ERP040VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											48 VOLTS , 39.00 X 25.30 X 23.90				Weight Minimum 2100	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
ERP040VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											48 VOLTS , 39.00 X 25.30 X 25.40				Weight Minimum 2100	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100T15	700	32.6	38.19	23.50	22.62	2307	M2802410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085L15	595	27.7	38.19	23.50	22.63	2177	M2902408515B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
ERP040VF	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											48 VOLTS , 39.00 X 25.30 X 26.70				Weight Minimum 2500	Connector SB350	BLUE	, Position A , Lead Length 020 Inches
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
ERP045VL	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											80 VOLTS , 40.70 X 28.20 X 31.20				Weight Minimum 3700	Connector SBE320	BLACK	, Position A , Lead Length 020 Inches
	80	140T09	560	43.5	40.00	27.50	30.50	3986	M2804014009X76A	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125L09	500	38.8	40.00	27.50	30.50	3902	M2904012509X76A	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125F09	500	38.8	40.00	27.50	30.50	3995	M2504012509X76A	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125C09	500	38.8	40.00	27.50	30.50	3835	M2604012509X76A	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
ERP050VL	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											80 VOLTS , 40.70 X 28.20 X 31.20				Weight Minimum 3700	Connector SBE320	BLACK	, Position A , Lead Length 020 Inches
	80	140T09	560	43.5	40.00	27.50	30.50	3986	M2804014009X76A	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125L09	500	38.8	40.00	27.50	30.50	3902	M2904012509X76A	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125F09	500	38.8	40.00	27.50	30.50	3995	M2504012509X76A	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
	80	125C09	500	38.8	40.00	27.50	30.50	3835	M2604012509X76A	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)				
ERP050VL	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											80 VOLTS , 40.70 X 33.90 X 31.20				Weight Minimum 4500	Connector SBE320	BLACK	, Position A , Lead Length 020 Inches
	80	140T11	700	54.3	40.05	32.71	30.50		M2804014011X76A	N	(CALL)			(CALL)	(CALL)				
	80	125L11	625	48.5	40.05	32.71	30.50	4662	M2904012511X76A	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125F11	625	48.5	40.05	32.71	30.50	4862	M2504012511X76A	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125C11	625	48.5	40.05	32.71	30.50	4581	M2604012511X76A	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
ERP060VL	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											80 VOLTS , 40.70 X 33.90 X 31.20				Weight Minimum 4500	Connector SBE320	BLACK	, Position A , Lead Length 020 Inches
	80	140T11	700	54.3	40.05	32.71	30.50		M2804014011X76A	N	(CALL)			(CALL)	(CALL)				
	80	125L11	625	48.5	40.05	32.71	30.50	4662	M2904012511X76A	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125F11	625	48.5	40.05	32.71	30.50	4862	M2504012511X76A	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125C11	625	48.5	40.05	32.71	30.50	4581	M2604012511X76A	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
ERP070VL	CLASS I 4-WHEEL COUNTERBALANCED PNEUMATIC TIRE											80 VOLTS , 40.70 X 33.90 X 31.20				Weight Minimum 4500	Connector SBE320	BLACK	, Position A , Lead Length 020 Inches
	80	140T11	700	54.3	40.05	32.71	30.50		M2804014011X76A	N	(CALL)			(CALL)	(CALL)				
	80	125L11	625	48.5	40.05	32.71	30.50	4662	M2904012511X76A	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125F11	625	48.5	40.05	32.71	30.50	4862	M2504012511X76A	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
	80	125C11	625	48.5	40.05	32.71	30.50	4581	M2604012511X76A	N	(CALL)		SCR20040750T1H	(CALL)	(CALL)				
ESC030AC	CLASS I 3-WHEEL STAND UP COUNTERBALANCED											36 VOLTS , 38.60 X 16.30 X 31.10				Weight Minimum 1885	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
ESC030AC	CLASS I 3-WHEEL STAND UP COUNTERBALANCED											36 VOLTS , 38.60 X 18.30 X 32.38				Weight Minimum 2315	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
ESC035AC	CLASS I 3-WHEEL STAND UP COUNTERBALANCED											36 VOLTS , 38.60 X 18.30 X 31.10				Weight Minimum 2315	Connector SB350	GRAY	, Position B , Lead Length 016 Inches
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ESC035AC	CLASS I 3-WHEEL STAND UP COUNTERBALANCED			36 VOLTS , 38.60 X 20.80 X 31.10			Weight Minimum 2540	Connector SB350	GRAY	, Position B , Lead Length 016 Inches					
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ESC040AC	CLASS I 3-WHEEL STAND UP COUNTERBALANCED			36 VOLTS , 38.60 X 18.30 X 31.10			Weight Minimum 2200	Connector SB350	GRAY	, Position B , Lead Length 025 Inches					
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.75	31.00	2333	M1601812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ESC040AC	CLASS I 3-WHEEL STAND UP COUNTERBALANCED			36 VOLTS , 38.60 X 20.80 X 31.10			Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 025 Inches					
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)