

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
MPW065-E	CLASS III LOW LIFT WALKIE-PALLET										12 VOLTS , 32.00 X 9.00 X 999.00		Weight Minimum 500	Connector SB175	YELLOW , Position B , Lead Length 016 Inches	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
MPW065-E	CLASS III LOW LIFT WALKIE-PALLET										12 VOLTS , 32.00 X 13.40 X 999.00		Weight Minimum 500	Connector SB175	YELLOW , Position B , Lead Length 016 Inches	
	12	BATC19	765	8.9	31.44	12.94	23.25	800	M1600608519C6	N	(CALL)	SCR20006865S1H	SCR20006865T1H	(CALL)	(CALL)	
MPE060-F	CLASS III LOW LIFT WALKIE/RIDER PALLET										24 VOLTS , 32.00 X 9.00 X 999.00		Weight Minimum 500	Connector SB175	RED , Position B , Lead Length 020 Inches	
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	31.50	8.69	23.25	660	M1901208507DFPC	N	(CALL)			(CALL)	(CALL)	
MPE060-F	CLASS III LOW LIFT WALKIE/RIDER PALLET										24 VOLTS , 32.00 X 13.40 X 999.00		Weight Minimum 500	Connector SB175	RED , Position B , Lead Length 020 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
MPE080-F	CLASS III LOW LIFT WALKIE/RIDER PALLET										24 VOLTS , 32.00 X 9.00 X 999.00		Weight Minimum 500	Connector SB175	RED , Position B , Lead Length 020 Inches	
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)	
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	31.50	8.69	23.25	660	M1901208507DFPC	N	(CALL)			(CALL)	(CALL)	
MPE080-F	CLASS III LOW LIFT WALKIE/RIDER PALLET										24 VOLTS , 32.00 X 13.40 X 999.00		Weight Minimum 500	Connector SB175	RED , Position B , Lead Length 020 Inches	
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
MPW045-E	LOW LIFT PALLET TRUCK										24 VOLTS , 28.50 X 9.10 X 999.00		Weight Minimum 300	Connector SB175	RED , Position B , Lead Length 020 Inches	
	24	085C05	170	4.0	27.76	8.75	23.25	467	M1601208505G6	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085C07	255	5.9	27.75	8.63	23.25	587	M1601208507D625	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	
	24	085L07	255	5.9	27.75	8.63	23.25	620	M1901208507D625	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>MPB030A</b>	<b>PALLET TRUCKS</b>														
24 VOLTS , 29.50 X 7.60 X 25.40											Weight Minimum 300	Connector SB175	GRAY	, Position B , Lead Length 016 Inches	
24	090G05	180	4.2	28.00	6.52	25.42	525	M8901209005GPP0	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	(CALL)				(CALL)	(CALL)
<b>MPB040</b>	<b>PALLET TRUCKS</b>														
24 VOLTS , 28.00 X 9.10 X 999.00											Weight Minimum 300	Connector SB175	RED	, Position B , Lead Length 020 Inches	
24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
<b>MPB040</b>	<b>PALLET TRUCKS</b>														
24 VOLTS , 28.50 X 8.10 X 999.00											Weight Minimum 310	Connector SB175	RED	, Position B , Lead Length 020 Inches	
24	CHP	195	.0	27.30	7.50	26.45	400	M90004S24CHPX	Y	(CALL)				(CALL)	(CALL)
24	100T05	200	4.7	27.75	7.57	23.25	496	M1801210005D6	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)
<b>MPB040A</b>	<b>PALLET TRUCKS</b>														
24 VOLTS , 29.50 X 7.60 X 25.40											Weight Minimum 300	Connector SB175	GRAY	, Position B , Lead Length 016 Inches	
24	090G05	180	4.2	28.00	6.52	25.42	525	M8901209005GPP0	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	(CALL)				(CALL)	(CALL)
<b>MPB040AC</b>	<b>PALLET TRUCKS</b>														
24 VOLTS , 28.97 X 7.69 X 24.30											Weight Minimum 300	Connector SB175	GRAY	, Position B , Lead Length 016 Inches	
24	090G05	180	4.2	28.00	6.52	25.42	525	M8901209005GPP0	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	CHP	195	.0	27.30	7.50	26.45	400	M90004S24CHPX	Y	(CALL)				(CALL)	(CALL)
<b>MPB040AC</b>	<b>PALLET TRUCKS</b>														
24 VOLTS , 29.50 X 7.25 X 999.00											Weight Minimum 300	Connector SB175	GRAY	, Position B , Lead Length 016 Inches	
24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	090G05	180	4.2	28.00	6.52	25.42	525	M8901209005GPP0	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
<b>MP030A</b>	<b>PALLET TRUCKS</b>														
24 VOLTS , 29.50 X 7.60 X 25.40											Weight Minimum 300	Connector SB175	GRAY	, Position B , Lead Length 016 Inches	
24	090G05	180	4.2	28.00	6.52	25.42	525	M8901209005GPP0	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	(CALL)				(CALL)	(CALL)
<b>MP040A</b>	<b>PALLET TRUCKS</b>														
24 VOLTS , 29.50 X 7.60 X 25.40											Weight Minimum 300	Connector SB175	GRAY	, Position B , Lead Length 016 Inches	
24	090G05	180	4.2	28.00	6.52	25.42	525	M8901209005GPP0	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	(CALL)				(CALL)	(CALL)
<b>MSW020-E</b>	<b>STRADDLE STACKER</b>														
24 VOLTS , 27.80 X 8.10 X 999.00											Weight Minimum 310	Connector SBX175	RED	, Position N/A, Lead Length 020 Inches	
24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	100C05	200	4.7	25.25	6.50	25.63	455	M1601210005G	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	100T05	200	4.7	25.25	6.63	23.25	429	M1801210005G	N	(CALL)	SCR20012260S1H			(CALL)	(CALL)
24	CHP	195	.0	27.30	7.50	26.45	400	M90004S24CHPX	Y	(CALL)				(CALL)	(CALL)
24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H			(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
MSW025-E	STRADDLE STACKER		24 VOLTS , 27.80 X 9.10 X 999.00						Weight Minimum 350	Connector SB175	RED	, Position B , Lead Length 020 Inches			
	24	085C07	255	5.9	25.38	8.69	23.25	565	M1601208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085F05	170	4.0	25.25	6.63	23.25	421	M1501208505G	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C05	170	4.0	25.25	6.63	23.25	406	M1601208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100C07	300	7.0	25.52	8.75	26.00	652	M1601210007D	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085C05	170	4.0	25.38	8.63	23.25	486	M1601208505FFPC	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T07	300	7.0	25.38	8.69	23.25	601	M1801210007D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	CHP	195	.0	27.30	7.50	26.45	400	M90004S24CHPX	Y	(CALL)			(CALL)	(CALL)
	24	085L07	255	5.9	25.38	8.69	23.25	585	M1901208507D	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L05	170	4.0	25.25	6.63	23.25	423	M1901208505G	Y	(CALL)	SCR20012260S1H		(CALL)	(CALL)
MSW030-E	STRADDLE STACKER		24 VOLTS , 33.00 X 9.00 X 999.00						Weight Minimum 400	Connector SB175	RED	, Position B , Lead Length 020 Inches			
	24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	090G05	180	4.2	32.50	8.61	23.56	678	M8901209005CPPWAL	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)
	24	090G05	180	4.2	32.50	8.61	23.56	678	M8901209005CPP25	Y	(CALL)			(CALL)	(CALL)
MSW030-E	STRADDLE STACKER		24 VOLTS , 33.00 X 13.50 X 999.00						Weight Minimum 600	Connector SB175	RED	, Position B , Lead Length 020 Inches			
	24	105B11	525	12.3	30.88	12.88	22.95	1090	M2101210511N059	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.69	12.88	26.40	1075	M8901210011N059	Y	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	085C11	425	9.9	30.81	12.88	23.25	860	M1601208511A25A	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T11	500	11.6	30.81	12.88	23.25	910	M1801210011A25A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.82	12.88	23.25	1013	M1901208513A25C	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.82	12.88	23.25	993	M1601208513A25C	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
MCW020	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS		12 VOLTS , 31.87 X 13.40 X 999.00						Weight Minimum 800	Connector SB175	GRAY	, Position B , Lead Length 020 Inches			
	12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)		SCR200061200T1H	(CALL)	(CALL)
MCW020	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS		24 VOLTS , 31.87 X 13.40 X 999.00						Weight Minimum 800	Connector SB175	GRAY	, Position B , Lead Length 020 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>MCW025 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 31.87 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)		SCR200061200T1H	(CALL)	(CALL)
<b>MCW025 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 24 VOLTS , 31.87 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>MCW030 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 31.87 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)		SCR200061200T1H	(CALL)	(CALL)
<b>MCW030 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 24 VOLTS , 31.87 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>MCW040 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 24 VOLTS , 31.87 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>MLW040</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>							<b>12 VOLTS , 32.00 X 8.10 X 999.00</b>		<b>Weight Minimum 300</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>				
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
<b>MLW040</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>							<b>12 VOLTS , 32.00 X 13.40 X 999.00</b>		<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>				
	12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)	SCR200061200T1H	(CALL)	(CALL)	(CALL)	
<b>MLW040</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>							<b>24 VOLTS , 32.00 X 13.40 X 999.00</b>		<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>MLW060</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>							<b>12 VOLTS , 32.00 X 8.10 X 999.00</b>		<b>Weight Minimum 300</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>				
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
<b>MLW060</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>							<b>12 VOLTS , 32.00 X 13.40 X 999.00</b>		<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>				
	12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)	SCR200061200T1H	(CALL)	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>MLW060</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>							<b>24 VOLTS , 32.00 X 13.40 X 999.00</b>		<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>MPC040</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>							<b>12 VOLTS , 32.00 X 9.00 X 999.00</b>		<b>Weight Minimum 500</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>				
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	125F13	750	8.7	30.56	7.69	31.00	709	M1500612513A	N	(CALL)	SCR20006750T1H	(CALL)	(CALL)	(CALL)	
	12	125C13	750	8.7	30.56	7.69	31.00	708	M1600612513A	N	(CALL)	(CALL)	SCR20006750T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	140T13	840	9.8	30.56	7.69	31.00	755	M1800614013A	N	(CALL)	SCR20006865S1H	SCR20006865T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	125L13	750	8.7	30.56	7.69	31.00	740	M1900612513A	N	(CALL)	(CALL)	SCR20006750T1H	(CALL)	(CALL)	
<b>MPC040</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>							<b>12 VOLTS , 32.00 X 13.40 X 999.00</b>		<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>				
	12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)	(CALL)	SCR200061200T1H	(CALL)	(CALL)	
<b>MPC040</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>							<b>24 VOLTS , 32.00 X 13.40 X 999.00</b>		<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>GRAY , Position B , Lead Length 020 Inches</b>				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
MPC060	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS							12 VOLTS , 32.00 X 9.00 X 999.00		Weight Minimum 500	Connector SB175	GRAY , Position B , Lead Length 020 Inches				
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	125F13	750	8.7	30.56	7.69	31.00	709	M1500612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)	
	12	125C13	750	8.7	30.56	7.69	31.00	708	M1600612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	140T13	840	9.8	30.56	7.69	31.00	755	M1800614013A	N	(CALL)	SCR20006865S1H	SCR20006865T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
	12	125L13	750	8.7	30.56	7.69	31.00	740	M1900612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)	
MPC060	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS							12 VOLTS , 32.00 X 13.40 X 999.00		Weight Minimum 800	Connector SB175	GRAY , Position B , Lead Length 020 Inches				
	12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)		SCR200061200T1H	(CALL)	(CALL)	
MPC060	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS							24 VOLTS , 32.00 X 13.40 X 999.00		Weight Minimum 800	Connector SB175	GRAY , Position B , Lead Length 020 Inches				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>MPC080 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 32.00 X 9.00 X 999.00 Weight Minimum 500 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
12	085F13		510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	085F13		510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	085C13		510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	085C13		510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	100C13		600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	100C13		600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	125F13		750	8.7	30.56	7.69	31.00	709	M1500612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
12	125C13		750	8.7	30.56	7.69	31.00	708	M1600612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
12	100G13		600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	100G13		600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	100T13		600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	100T13		600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	140T13		840	9.8	30.56	7.69	31.00	755	M1800614013A	N	(CALL)	SCR20006865S1H	SCR20006865T1H	(CALL)	(CALL)
12	085L13		510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	085L13		510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	125L13		750	8.7	30.56	7.69	31.00	740	M1900612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
<b>MPC080 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 32.00 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
12	085C27		1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)		SCR200061200T1H	(CALL)	(CALL)
<b>MPC080 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 24 VOLTS , 32.00 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
24	100C13		600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
24	100F13		600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
24	125F13		750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
24	125C13		750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
24	100G11		500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
24	085F13		510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
24	105B15		735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
24	140T13		840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
24	100T13		600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
24	085L13		510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
24	125L13		750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
24	085C13		510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>MPE040 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 32.00 X 8.10 X 999.00 Weight Minimum 300 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
12	085F13		510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	085F13		510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	085C13		510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	085C13		510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	100C13		600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	100C13		600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	100G13		600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	100G13		600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	100T13		600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	100T13		600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
12	085L13		510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
12	085L13		510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>MPE040 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 32.00 X 9.00 X 999.00 Weight Minimum 500 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	125F13	750	8.7	30.56	7.69	31.00	709	M1500612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)	
12	125C13	750	8.7	30.56	7.69	31.00	708	M1600612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)	
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	140T13	840	9.8	30.56	7.69	31.00	755	M1800614013A	N	(CALL)	SCR20006865S1H	SCR20006865T1H	(CALL)	(CALL)	
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	125L13	750	8.7	30.56	7.69	31.00	740	M1900612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)	
<b>MPE040 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 32.00 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)		SCR200061200T1H	(CALL)	(CALL)	
<b>MPE040 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 24 VOLTS , 32.00 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 RED , Position B , Lead Length 020 Inches</b>															
24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)	
24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)	
24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)	
24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)	
<b>MPE060 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 32.00 X 9.00 X 999.00 Weight Minimum 300 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)	
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>MPE060 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 32.00 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	( CALL )		SCR200061200T1H	( CALL )	( CALL )
<b>MPE060 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 24 VOLTS , 32.00 X 9.00 X 999.00 Weight Minimum 300 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	( CALL )			( CALL )	( CALL )
<b>MPE060 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 24 VOLTS , 32.00 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	( CALL )	SCR20012750S1H	SCR20012750T1H	( CALL )	( CALL )
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	( CALL )	SCR20012750S1H	SCR20012750T1H	( CALL )	( CALL )
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	( CALL )			( CALL )	( CALL )
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	( CALL )	SCR20012750S1H	SCR20012750T1H	( CALL )	( CALL )
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	( CALL )	SCR20012965S1H	SCR20012865T1H	( CALL )	( CALL )
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	( CALL )	SCR20012750S1H	SCR20012750T1H	( CALL )	( CALL )
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	( CALL )	SCR20012600S1H	SCR20012600T1H	( CALL )	( CALL )
<b>MPE080 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 12 VOLTS , 32.00 X 9.00 X 999.00 Weight Minimum 300 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	( CALL )	SCR20006600S1H	SCR20006600T1H	( CALL )	( CALL )
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	( CALL )	SCR20006600S1L	SCR20006600T1H	( CALL )	( CALL )
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	( CALL )	SCR20006600S1H	SCR20006600T1H	( CALL )	( CALL )
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	( CALL )	SCR20006600S1L	SCR20006600T1H	( CALL )	( CALL )
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	( CALL )	SCR20006600S1H	SCR20006600T1H	( CALL )	( CALL )
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	( CALL )	SCR20006600S1L	SCR20006600T1H	( CALL )	( CALL )
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	( CALL )	SCR20006600S1H	SCR20006600T1H	( CALL )	( CALL )
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	( CALL )	SCR20006600S1L	SCR20006600T1H	( CALL )	( CALL )
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	( CALL )	SCR20006600S1H	SCR20006600T1H	( CALL )	( CALL )
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	( CALL )	SCR20006600S1L	SCR20006600T1H	( CALL )	( CALL )
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	( CALL )	SCR20006600S1H	SCR20006600T1H	( CALL )	( CALL )
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	( CALL )	SCR20006600S1L	SCR20006600T1H	( CALL )	( CALL )
<b>MPE080 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS 24 VOLTS , 32.00 X 9.00 X 999.00 Weight Minimum 300 Connector SB175 GRAY , Position B , Lead Length 020 Inches</b>															
	24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	( CALL )			( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
<b>MPE080 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>			<b>24 VOLTS , 32.00 X 13.40 X 999.00</b>						<b>Weight Minimum 800</b>		<b>Connector SB175</b>		<b>GRAY , Position B , Lead Length 020 Inches</b>			
24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)		
24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)		
24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)		
24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)		
<b>MPW040 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>			<b>12 VOLTS , 32.00 X 8.10 X 999.00</b>						<b>Weight Minimum 300</b>		<b>Connector SB350</b>		<b>GRAY , Position B , Lead Length 020 Inches</b>			
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
<b>MPW040 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>			<b>12 VOLTS , 32.00 X 9.00 X 999.00</b>						<b>Weight Minimum 500</b>		<b>Connector SB350</b>		<b>GRAY , Position B , Lead Length 020 Inches</b>			
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	125F13	750	8.7	30.56	7.69	31.00	709	M1500612513A	N	(CALL)	(CALL)	SCR20006750T1H	(CALL)	(CALL)		
12	125C13	750	8.7	30.56	7.69	31.00	708	M1600612513A	N	(CALL)	(CALL)	SCR20006750T1H	(CALL)	(CALL)		
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	140T13	840	9.8	30.56	7.69	31.00	755	M1800614013A	N	(CALL)	SCR20006865S1H	SCR20006865T1H	(CALL)	(CALL)		
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)		
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)		
12	125L13	750	8.7	30.56	7.69	31.00	740	M1900612513A	N	(CALL)	(CALL)	SCR20006750T1H	(CALL)	(CALL)		
<b>MPW040 WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>			<b>12 VOLTS , 32.00 X 13.40 X 999.00</b>						<b>Weight Minimum 800</b>		<b>Connector SB350</b>		<b>GRAY , Position B , Lead Length 020 Inches</b>			
12	085C27	1105	12.9	31.25	13.00	23.25	1038	M1600608527C	N	(CALL)	(CALL)	SCR200061200T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>MPW040</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>24 VOLTS , 32.00 X 13.40 X 999.00</b>				<b>Weight Minimum 800</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 020 Inches</b>
24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)	(CALL)	(CALL)	(CALL)	(CALL)					
24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)					
24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)					
24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)					
<b>MPW045DA</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>12 VOLTS , 31.75 X 8.09 X 999.00</b>				<b>Weight Minimum 300</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
<b>MPW045DA</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>12 VOLTS , 32.00 X 9.00 X 999.00</b>				<b>Weight Minimum 300</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)					
12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)					
<b>MPW045DA</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>24 VOLTS , 32.00 X 9.00 X 999.00</b>				<b>Weight Minimum 300</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
24	085F07	255	5.9	30.00	8.63	23.25	567	M1501208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
24	085C07	255	5.9	30.00	8.63	23.25	567	M1601208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					
24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	(CALL)			(CALL)	(CALL)					
24	100T07	300	7.0	30.00	8.63	23.25	604	M1801210007D2	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)					
24	085L07	255	5.9	30.00	8.63	23.25	581	M1901208507D2	N	(CALL)	SCR20012260S1H		(CALL)	(CALL)					

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
MPW060	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS			12 VOLTS , 32.00 X 9.00 X 999.00			Weight Minimum 300			Connector SB175 GRAY , Position B , Lead Length 020 Inches					
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	125F13	750	8.7	30.56	7.69	31.00	709	M1500612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
	12	125C13	750	8.7	30.56	7.69	31.00	708	M1600612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	140T13	840	9.8	30.56	7.69	31.00	755	M1800614013A	N	(CALL)	SCR20006865S1H	SCR20006865T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	125L13	750	8.7	30.56	7.69	31.00	740	M1900612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
MPW060	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS			24 VOLTS , 32.00 X 9.00 X 999.00			Weight Minimum 300			Connector SB175 GRAY , Position B , Lead Length 020 Inches					
	24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	(CALL)			(CALL)	(CALL)
MPW060	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS			24 VOLTS , 32.00 X 13.40 X 999.00			Weight Minimum 800			Connector SB175 GRAY , Position B , Lead Length 020 Inches					
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
MPW080	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS											12 VOLTS , 32.00 X 9.00 X 999.00 Weight Minimum 300 Connector SB175 GRAY , Position B , Lead Length 020 Inches			
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085F13	510	5.9	30.44	7.63	23.25	534	M1500608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085C13	510	5.9	30.44	7.63	23.25	513	M1600608513A	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100C13	600	7.0	30.56	7.75	26.13	632	M1600610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	125F13	750	8.7	30.56	7.69	31.00	709	M1500612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
	12	125C13	750	8.7	30.56	7.69	31.00	708	M1600612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100G13	600	7.1	30.56	7.69	30.92	630	M8900610013A059	Y	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	100T13	600	7.0	30.44	7.63	23.25	543	M1800610013A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	140T13	840	9.8	30.56	7.69	31.00	755	M1800614013A	N	(CALL)	SCR20006865S1H	SCR20006865T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1H	SCR20006600T1H	(CALL)	(CALL)
	12	085L13	510	5.9	30.44	7.63	23.25	523	M1900608513A	N	(CALL)	SCR20006600S1L	SCR20006600T1H	(CALL)	(CALL)
	12	125L13	750	8.7	30.56	7.69	31.00	740	M1900612513A	N	(CALL)		SCR20006750T1H	(CALL)	(CALL)
MPW080	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS											24 VOLTS , 32.00 X 9.00 X 999.00 Weight Minimum 300 Connector SB175 GRAY , Position B , Lead Length 020 Inches			
	24	MSB	195	.0	29.00	7.50	26.45	400	M90004S24CHPB	N	(CALL)			(CALL)	(CALL)
MPW080	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS											24 VOLTS , 32.00 X 13.40 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
MRW020	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS											24 VOLTS , 35.20 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
MRW030	WALKIE PLATFORM TRUCKS/STRADDLE STACKERS											24 VOLTS , 35.20 X 13.50 X 999.00 Weight Minimum 800 Connector SB175 GRAY , Position B , Lead Length 020 Inches			
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>MSW020</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>24 VOLTS , 35.20 X 13.50 X 999.00</b>				<b>Weight Minimum 600</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)				
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
<b>MSW020</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>24 VOLTS , 35.40 X 8.12 X 999.00</b>				<b>Weight Minimum 600</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
<b>MSW030</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>24 VOLTS , 35.20 X 13.50 X 999.00</b>				<b>Weight Minimum 600</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)				
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
<b>MSW030</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>24 VOLTS , 35.40 X 8.12 X 999.00</b>				<b>Weight Minimum 600</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100C07	300	7.0	33.81	6.63	26.13	624	M1601210007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	125C07	375	8.7	33.88	6.63	31.00	802	M1601212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	140T07	420	9.8	33.88	6.63	31.00	856	M1801214007G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
	24	125L07	375	8.7	33.88	6.63	31.00	840	M1901212507G	N	(CALL)	SCR20012475S1H	SCR20012475T1H	(CALL)	(CALL)				
<b>MSW040</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>24 VOLTS , 35.20 X 13.50 X 999.00</b>				<b>Weight Minimum 600</b>	<b>Connector SB175</b>	<b>GRAY</b>	<b>, Position B , Lead Length 020 Inches</b>
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100G11	500	11.8	30.70	12.75	28.42	1035	M8901210011NPP059	Y	(CALL)			(CALL)	(CALL)				
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
<b>MTR005-E</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>											<b>24 VOLTS , 31.30 X 13.40 X 999.00</b>				<b>Weight Minimum 800</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>MTR007-E</b>	<b>WALKIE PLATFORM TRUCKS/STRADDLE STACKERS</b>			<b>24 VOLTS , 31.30 X 13.40 X 999.00</b>			<b>Weight Minimum 800</b>		<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>				
	24	100C13	600	14.0	30.63	12.69	26.13	1107	M1601210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100F13	600	14.0	30.63	12.69	26.13	1149	M1501210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125F13	750	17.5	30.63	12.81	31.00	1383	M1501212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125C13	750	17.5	30.63	12.81	31.00	1341	M1601212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085F13	510	11.9	30.63	12.69	23.25	1001	M1501208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	105B15	735	17.3	31.00	12.88	30.51	1415	M2101210515N0	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T13	840	19.6	30.63	12.81	31.00	1435	M1801214013A	Y	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	100T13	600	14.0	30.63	12.69	23.25	1020	M1801210013A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085L13	510	11.9	30.63	12.69	23.25	983	M1901208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	125L13	750	17.5	30.63	12.81	31.00	1358	M1901212513A	Y	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085C13	510	11.9	30.63	12.69	23.25	966	M1601208513A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>OS030BE</b>	<b>CLASS II ORDER PICKER</b>			<b>24 VOLTS , 39.00 X 14.60 X 31.50</b>			<b>Weight Minimum 1600</b>		<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>				
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B29	840	19.8	38.50	14.19	30.80	1635	M2101206029FB0	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
<b>OS030BE</b>	<b>CLASS II ORDER PICKER</b>			<b>36 VOLTS , 39.00 X 14.60 X 31.50</b>			<b>Weight Minimum 1500</b>		<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 016 Inches</b>				
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>OS030EC</b>	<b>CLASS II ORDER PICKER</b>			<b>24 VOLTS , 36.00 X 13.50 X 25.00</b>			<b>Weight Minimum 945</b>		<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>				
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085F15	595	13.9	35.06	12.88	22.50	1127	M2501208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	085C15	595	13.9	35.06	12.88	22.50	1076	M2601208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
	24	100T15	700	16.3	35.06	12.88	22.50	1145	M2801210015A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	085L15	595	13.9	35.06	12.88	22.50	1109	M2901208515A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)
<b>SS030BC</b>	<b>CLASS II ORDER PICKER</b>			<b>24 VOLTS , 38.88 X 14.60 X 31.50</b>			<b>Weight Minimum 1500</b>		<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 025 Inches</b>				
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
<b>SS030BE</b>	<b>CLASS II ORDER PICKER</b>			<b>24 VOLTS , 38.88 X 14.60 X 31.50</b>			<b>Weight Minimum 1500</b>		<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 025 Inches</b>				
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B29	840	19.8	38.50	14.19	30.80	1635	M2101206029FB0	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
<b>SS030BE</b>	<b>CLASS II ORDER PICKER</b>			<b>36 VOLTS , 38.88 X 14.60 X 31.50</b>			<b>Weight Minimum 1500</b>		<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 025 Inches</b>				
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
<b>NTA030SBMWB</b>	<b>CLASS II VERY NARROW AISLE TURRET</b>											<b>48 VOLTS , 40.30 X 24.60 X 36.00</b>					
			<b>Weight Minimum 2700</b>											<b>Connector SB350</b>			
			<b>BLUE , Position B , Lead Length 030 Inches</b>														
	48	125F15	875	40.7	38.31	23.62	30.50	3170	M2502412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)		
	48	125C15	875	40.7	38.31	23.62	30.50	3084	M2602412515B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)		
	48	140T15	980	45.6	38.31	23.62	30.50	3283	M2802414015B	N	(CALL)		SCR200241050T1H	(CALL)	(CALL)		
<b>NDR030A</b>	<b>NARROW AISLE DOUBLE REACH</b>											<b>36 VOLTS , 39.00 X 14.00 X 31.50</b>					
			<b>Weight Minimum 1550</b>											<b>Connector SB350</b>			
			<b>GRAY , Position B , Lead Length 025 Inches</b>														
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
<b>NDR030A</b>	<b>NARROW AISLE DOUBLE REACH</b>											<b>36 VOLTS , 39.00 X 16.20 X 31.50</b>					
			<b>Weight Minimum 1800</b>											<b>Connector SB350</b>			
			<b>GRAY , Position B , Lead Length 025 Inches</b>														
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)		
<b>NDR030BC</b>	<b>NARROW AISLE DOUBLE REACH</b>											<b>36 VOLTS , 38.88 X 18.80 X 31.50</b>					
			<b>Weight Minimum 2200</b>											<b>Connector SB350</b>			
			<b>GRAY , Position B , Lead Length 030 Inches</b>														
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
<b>NDR030BC</b>	<b>NARROW AISLE DOUBLE REACH</b>											<b>36 VOLTS , 38.88 X 21.10 X 31.50</b>					
			<b>Weight Minimum 2500</b>											<b>Connector SB350</b>			
			<b>GRAY , Position B , Lead Length 030 Inches</b>														
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
<b>NDR030CA</b>	<b>NARROW AISLE DOUBLE REACH</b>											<b>36 VOLTS , 38.88 X 18.80 X 31.50</b>					
			<b>Weight Minimum 2200</b>											<b>Connector SB350</b>			
			<b>GRAY , Position B , Lead Length 030 Inches</b>														
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
<b>NDR030CA</b>	<b>NARROW AISLE DOUBLE REACH</b>											<b>36 VOLTS , 38.88 X 21.10 X 31.50</b>					
			<b>Weight Minimum 2500</b>											<b>Connector SB350</b>			
			<b>GRAY , Position B , Lead Length 030 Inches</b>														
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)		
<b>NDR030GA</b>	<b>NARROW AISLE DOUBLE REACH</b>											<b>36 VOLTS , 38.88 X 18.80 X 31.50</b>					
			<b>Weight Minimum 2200</b>											<b>Connector SB350</b>			
			<b>GRAY , Position B , Lead Length 030 Inches</b>														
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)		
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)		
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)		
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)		

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>NDR030GA</b>	<b>NARROW AISLE DOUBLE REACH</b>											<b>36 VOLTS , 38.88 X 21.10 X 31.50</b>				<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)				
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
<b>OS030BC</b>	<b>NARROW AISLE ORDER SELECTOR</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.50</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 025 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B29	840	19.8	38.50	14.19	30.80	1635	M2101206029FB0	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>OS030BC</b>	<b>NARROW AISLE ORDER SELECTOR</b>											<b>36 VOLTS , 38.88 X 14.60 X 31.50</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 025 Inches</b>
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>OS030EB</b>	<b>NARROW AISLE ORDER SELECTOR</b>											<b>24 VOLTS , 36.00 X 13.50 X 25.00</b>				<b>Weight Minimum 945</b>	<b>Connector SB175</b>	<b>RED</b>	<b>, Position B , Lead Length 016 Inches</b>
	24	105B11	525	12.3	35.00	12.88	22.95	1080	M2101210511N0	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085F15	595	13.9	35.06	12.88	22.50	1127	M2501208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	085C15	595	13.9	35.06	12.88	22.50	1076	M2601208515A	Y	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
	24	100T15	700	16.3	35.06	12.88	22.50	1145	M2801210015A	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)				
	24	085L15	595	13.9	35.06	12.88	22.50	1109	M2901208515A	N	(CALL)	SCR20012600S1H	SCR20012600T1H	(CALL)	(CALL)				
<b>SS030BC</b>	<b>NARROW AISLE ORDER SELECTOR</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.50</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>RED</b>	<b>, Position B , Lead Length 025 Inches</b>
	24	060B29	840	19.8	38.50	14.19	30.80	1635	M2101206029FB0	N	(CALL)	SCR20012965S1H	SCR20012865T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>SS030BC</b>	<b>NARROW AISLE ORDER SELECTOR</b>											<b>36 VOLTS , 38.88 X 14.60 X 31.50</b>				<b>Weight Minimum 1500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 025 Inches</b>
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>NDR030AC</b>	<b>NARROW AISLE REACH</b>											<b>24 VOLTS , 38.88 X 14.60 X 31.50</b>				<b>Weight Minimum 1550</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 025 Inches</b>
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)				
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)				
<b>NDR030AC</b>	<b>NARROW AISLE REACH</b>											<b>24 VOLTS , 38.88 X 16.60 X 31.50</b>				<b>Weight Minimum 1700</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 025 Inches</b>
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)				
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>NDR030AC</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 14.60 X 31.50 Weight Minimum 1550 Connector SB350 GRAY , Position B , Lead Length 025 Inches</b>												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>NDR030AC</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 16.60 X 31.50 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 025 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>NDR030AD</b>	<b>NARROW AISLE REACH</b>		<b>24 VOLTS , 38.88 X 16.60 X 31.50 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 025 Inches</b>												
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)	SCR200121450T1H	SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
<b>NDR030AD</b>	<b>NARROW AISLE REACH</b>		<b>24 VOLTS , 39.00 X 14.60 X 31.50 Weight Minimum 1550 Connector SB350 GRAY , Position B , Lead Length 025 Inches</b>												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
<b>NDR030AD</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 16.60 X 31.50 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 025 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>NDR030AD</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 39.00 X 14.60 X 31.50 Weight Minimum 1550 Connector SB350 GRAY , Position B , Lead Length 025 Inches</b>												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>NR035A</b>	<b>NARROW AISLE REACH</b>		<b>24 VOLTS , 39.00 X 12.50 X 31.50 Weight Minimum 1400 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
NR035A		NARROW AISLE REACH						24 VOLTS , 39.00 X 14.60 X 31.50		Weight Minimum 1550	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
NR035A		NARROW AISLE REACH						24 VOLTS , 39.00 X 16.20 X 31.50		Weight Minimum 1800	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)	
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
NR035A		NARROW AISLE REACH						36 VOLTS , 39.00 X 12.50 X 31.50		Weight Minimum 1400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	125C09	500	17.5	38.00	11.00	30.50	1421	M2601812509B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
	36	140T09	560	19.6	38.00	11.00	30.50	1426	M2801814009B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
NR035A		NARROW AISLE REACH						36 VOLTS , 39.00 X 14.60 X 31.50		Weight Minimum 1550	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
NR035A		NARROW AISLE REACH						36 VOLTS , 39.00 X 16.20 X 31.50		Weight Minimum 1800	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
NR035AC		NARROW AISLE REACH						24 VOLTS , 38.88 X 12.50 X 31.50		Weight Minimum 1400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
NR035AC		NARROW AISLE REACH						24 VOLTS , 38.88 X 14.60 X 31.50		Weight Minimum 1550	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
NR035AC		NARROW AISLE REACH						24 VOLTS , 38.88 X 16.60 X 31.50		Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)	
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NR035AC	NARROW AISLE REACH		36 VOLTS , 38.88 X 14.60 X 31.50			Weight Minimum 1550		Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NR035AC	NARROW AISLE REACH		36 VOLTS , 38.88 X 16.60 X 31.50			Weight Minimum 1700		Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NR035BC	NARROW AISLE REACH		36 VOLTS , 38.88 X 18.80 X 31.50			Weight Minimum 2200		Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
NR035BC	NARROW AISLE REACH		36 VOLTS , 38.88 X 21.10 X 31.50			Weight Minimum 2500		Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
NR040A	NARROW AISLE REACH		24 VOLTS , 39.00 X 12.50 X 31.50			Weight Minimum 1400		Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
NR040A	NARROW AISLE REACH		24 VOLTS , 39.00 X 14.60 X 31.50			Weight Minimum 1550		Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NR040A	NARROW AISLE REACH		24 VOLTS , 39.00 X 16.20 X 31.50			Weight Minimum 1800		Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
NR040A	NARROW AISLE REACH		36 VOLTS , 39.00 X 12.50 X 31.50			Weight Minimum 1400		Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	125C09	500	17.5	38.00	11.00	30.50	1421	M2601812509B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
	36	140T09	560	19.6	38.00	11.00	30.50	1426	M2801814009B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE								
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)																
NR040A	NARROW AISLE REACH															36 VOLTS , 39.00 X 14.60 X 31.50			Weight Minimum 1550	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
NR040A	NARROW AISLE REACH															36 VOLTS , 39.00 X 16.20 X 31.50			Weight Minimum 1800	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)								
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
NR040AC	NARROW AISLE REACH															24 VOLTS , 38.88 X 12.50 X 31.50			Weight Minimum 1400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)								
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)								
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)								
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)								
NR040AC	NARROW AISLE REACH															24 VOLTS , 38.88 X 14.60 X 31.50			Weight Minimum 1550	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)								
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)								
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)								
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)								
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)								
NR040AC	NARROW AISLE REACH															24 VOLTS , 38.88 X 16.60 X 31.50			Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)								
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)								
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)								
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)	SCR200121450T1H	SCR200121450T1H	(CALL)	(CALL)								
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)	SCR200121200T1H	SCR200121200T1H	(CALL)	(CALL)								
NR040AC	NARROW AISLE REACH															36 VOLTS , 38.88 X 14.60 X 31.50			Weight Minimum 1550	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
NR040AC	NARROW AISLE REACH															36 VOLTS , 38.88 X 16.60 X 31.50			Weight Minimum 1700	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)								
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
NR045A	NARROW AISLE REACH															36 VOLTS , 39.00 X 14.60 X 31.50			Weight Minimum 1550	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)								

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>NR045A</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 39.00 X 16.20 X 31.50 Weight Minimum 1800 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>NR045AC</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 14.60 X 31.50 Weight Minimum 1550 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>NR045AC</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 16.60 X 31.50 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>NR045AE</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 14.60 X 31.50 Weight Minimum 1550 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>NR045AE</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 16.60 X 31.50 Weight Minimum 1800 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>NR045BC</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 18.80 X 31.50 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
<b>NR045BC</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 21.10 X 31.50 Weight Minimum 2500 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)	SCR200181200T1H	SCR200181200T1H	(CALL)	(CALL)
<b>NR045CA</b>	<b>NARROW AISLE REACH</b>		<b>36 VOLTS , 38.88 X 18.80 X 31.50 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NR045CA	NARROW AISLE REACH		36 VOLTS , 38.88 X 21.10 X 31.50												
											Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
NR045GA	NARROW AISLE REACH		36 VOLTS , 38.88 X 18.80 X 31.50												
											Weight Minimum 2200	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
NR045GA	NARROW AISLE REACH		36 VOLTS , 38.88 X 21.10 X 31.50												
											Weight Minimum 2600	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
NS035A	NARROW AISLE STRADDLE		24 VOLTS , 38.88 X 12.50 X 31.50												
											Weight Minimum 1400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
NS035A	NARROW AISLE STRADDLE		24 VOLTS , 39.00 X 14.60 X 31.50												
											Weight Minimum 1550	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NS035A	NARROW AISLE STRADDLE		24 VOLTS , 39.00 X 16.20 X 31.50												
											Weight Minimum 1800	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
NS035A	NARROW AISLE STRADDLE		36 VOLTS , 38.88 X 12.50 X 31.50												
											Weight Minimum 1400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	125C09	500	17.5	38.00	11.00	30.50	1421	M2601812509B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
	36	140T09	560	19.6	38.00	11.00	30.50	1426	M2801814009B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
NS035A	NARROW AISLE STRADDLE		36 VOLTS , 39.00 X 14.60 X 31.50												
											Weight Minimum 1550	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NS035A	NARROW AISLE STRADDLE							36 VOLTS , 39.00 X 16.20 X 31.50		Weight Minimum 1800	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NS040A	NARROW AISLE STRADDLE							24 VOLTS , 38.88 X 12.50 X 31.50		Weight Minimum 1400	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
NS040A	NARROW AISLE STRADDLE							24 VOLTS , 39.00 X 14.60 X 31.50		Weight Minimum 1550	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NS040A	NARROW AISLE STRADDLE							24 VOLTS , 39.00 X 16.20 X 31.50		Weight Minimum 1800	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
NS040A	NARROW AISLE STRADDLE							36 VOLTS , 38.88 X 12.50 X 31.50		Weight Minimum 1400	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	36	125C09	500	17.5	38.00	11.00	30.50	1421	M2601812509B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
	36	140T09	560	19.6	38.00	11.00	30.50	1426	M2801814009B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
NS040A	NARROW AISLE STRADDLE							36 VOLTS , 39.00 X 14.60 X 31.50		Weight Minimum 1550	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NS040A	NARROW AISLE STRADDLE							36 VOLTS , 39.00 X 16.20 X 31.50		Weight Minimum 1800	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NS040AD	NARROW AISLE STRADDLE							24 VOLTS , 38.88 X 12.50 X 31.50		Weight Minimum 1400	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)	SCR200121050T1H	SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NS040AD	NARROW AISLE STRADDLE		24 VOLTS , 38.88 X 14.60 X 31.50												
			Weight Minimum 1550 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NS040AD	NARROW AISLE STRADDLE		24 VOLTS , 38.88 X 16.60 X 31.50												
			Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
NS040AD	NARROW AISLE STRADDLE		36 VOLTS , 38.88 X 12.50 X 31.50												
			Weight Minimum 1400 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	125C09	500	17.5	38.00	11.00	30.50	1421	M2601812509B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
	36	140T09	560	19.6	38.00	11.00	30.50	1426	M2801814009B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
NS040AD	NARROW AISLE STRADDLE		36 VOLTS , 38.88 X 14.60 X 31.50												
			Weight Minimum 1550 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NS040AD	NARROW AISLE STRADDLE		36 VOLTS , 38.88 X 16.60 X 31.50												
			Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NS040AE	NARROW AISLE STRADDLE		24 VOLTS , 38.88 X 12.50 X 31.50												
			Weight Minimum 1400 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
NS040AE	NARROW AISLE STRADDLE		24 VOLTS , 38.88 X 14.60 X 31.50												
			Weight Minimum 1550 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
NS040AE	NARROW AISLE STRADDLE		24 VOLTS , 38.88 X 16.60 X 31.50												
			Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
NS040AE	NARROW AISLE STRADDLE															
36 VOLTS , 38.88 X 12.50 X 31.50											Weight Minimum 1400		Connector SB350		GRAY , Position B , Lead Length 030 Inches	
	36	125C09	500	17.5	38.00	11.00	30.50	1421	M2601812509B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
	36	140T09	560	19.6	38.00	11.00	30.50	1426	M2801814009B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)	
NS040AE	NARROW AISLE STRADDLE															
36 VOLTS , 38.88 X 14.60 X 31.50											Weight Minimum 1550		Connector SB350		GRAY , Position B , Lead Length 030 Inches	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
NS040AE	NARROW AISLE STRADDLE															
36 VOLTS , 38.88 X 16.60 X 31.50											Weight Minimum 1700		Connector SB350		GRAY , Position B , Lead Length 030 Inches	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
NS050AD	NARROW AISLE STRADDLE															
36 VOLTS , 38.88 X 14.60 X 31.50											Weight Minimum 1550		Connector SB350		GRAY , Position B , Lead Length 030 Inches	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
NS050AD	NARROW AISLE STRADDLE															
36 VOLTS , 38.88 X 16.60 X 31.50											Weight Minimum 1700		Connector SB350		GRAY , Position B , Lead Length 030 Inches	
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
NS050AE	NARROW AISLE STRADDLE															
24 VOLTS , 38.88 X 14.60 X 31.50											Weight Minimum 1550		Connector SB350		GRAY , Position B , Lead Length 030 Inches	
	24	125F17	1000	23.3	38.13	13.44	30.50	1839	M2501212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	125C17	1000	23.3	38.13	13.44	30.50	1775	M2601212517B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
	24	060B31	900	21.2	39.71	14.19	30.69	1850	M2101206031FB	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)	
	24	140T17	1120	26.1	38.13	13.44	30.50	1885	M2801214017B	Y	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125L17	1000	23.3	38.13	13.44	30.50	1809	M2901212517B	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)	
NS050AE	NARROW AISLE STRADDLE															
24 VOLTS , 38.88 X 16.60 X 31.50											Weight Minimum 1700		Connector SB350		GRAY , Position B , Lead Length 030 Inches	
	24	125C19	1125	26.2	38.19	15.00	30.50	1967	M2601212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	125F19	1125	26.2	38.19	15.00	30.50	2053	M2501212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
	24	140T19	1260	29.3	38.19	15.00	30.50	2080	M2801214019B	N	(CALL)		SCR200121450T1H	(CALL)	(CALL)	
	24	125L19	1125	26.2	38.19	15.00	30.50	2029	M2901212519B	N	(CALL)		SCR200121200T1H	(CALL)	(CALL)	
NS050AE	NARROW AISLE STRADDLE															
36 VOLTS , 38.88 X 14.60 X 31.50											Weight Minimum 1550		Connector SB350		GRAY , Position B , Lead Length 030 Inches	
	36	125C11	625	21.8	38.01	13.25	30.50	1705	M2601812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	125F11	625	21.8	38.01	13.25	30.50	1792	M2501812511B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	140T11	700	24.4	38.11	13.25	30.50	1811	M2801814011B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
NS050AE	NARROW AISLE STRADDLE		36 VOLTS , 38.88 X 16.60 X 31.50      Weight Minimum 1700      Connector SB350      GRAY , Position B , Lead Length 030 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
NTA030SA	NARROW AISLE TURRET		48 VOLTS , 44.76 X 21.65 X 33.46      Weight Minimum 2640      Connector SB350      BLUE , Position CTR, Lead Length 012 Inches												
	48	125F13	750	34.9	44.13	20.63	30.50	3295	M2502412513B7	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	125C13	750	34.9	44.13	20.63	30.50	3159	M2602412513B7	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	060B23	660	31.0	44.12	21.09	32.00	2725	M2102406023B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	140T13	840	39.1	44.13	20.63	30.50	3312	M2802414013B7	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
NTA040SA	NARROW AISLE TURRET		72 VOLTS , 40.43 X 27.87 X 34.40      Weight Minimum 3300      Connector SB350      GRAY , Position CTR, Lead Length 012 Inches												
	72	125C11	625	43.7	40.35	27.86	34.41	3598	M2603612511B41	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)
	72	140T11	700	48.9	40.35	27.86	34.41	3598	M2803614011B41	N	(CALL)		SCR20036750T1H	(CALL)	(CALL)
ESC020A	STAND-UP RIDER		24 VOLTS , 36.50 X 13.60 X 31.30      Weight Minimum 1225      Connector SB350      GRAY , Position B , Lead Length 020 Inches												
	24	125F15	875	20.4	35.13	12.94	31.00	1638	M1501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.13	12.94	31.00	1582	M1601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C13	750	17.5	35.44	12.94	31.00	1514	M1601212513A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.13	12.94	31.00	1676	M1801214015A	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	105B15	735	17.3	35.50	12.88	30.51	1475	M2101210515N06059	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.13	12.94	31.00	1636	M1901212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
ESC020AB	STAND-UP RIDER		24 VOLTS , 36.50 X 13.60 X 31.30      Weight Minimum 1225      Connector SB350      GRAY , Position B , Lead Length 020 Inches												
	24	125F15	875	20.4	35.13	12.94	31.00	1638	M1501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.13	12.94	31.00	1582	M1601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C13	750	17.5	35.44	12.94	31.00	1514	M1601212513A6	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.13	12.94	31.00	1676	M1801214015A	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	105B15	735	17.3	35.50	12.88	30.51	1475	M2101210515N06059	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.13	12.94	31.00	1636	M1901212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
ESC025A	STAND-UP RIDER		24 VOLTS , 36.50 X 13.60 X 31.30      Weight Minimum 1225      Connector SB350      GRAY , Position B , Lead Length 020 Inches												
	24	125F15	875	20.4	35.13	12.94	31.00	1638	M1501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.13	12.94	31.00	1582	M1601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.13	12.94	31.00	1676	M1801214015A	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	105B15	735	17.3	35.50	12.88	30.51	1475	M2101210515N06059	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.13	12.94	31.00	1636	M1901212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
ESC025AB	STAND-UP RIDER		24 VOLTS , 36.50 X 13.60 X 31.30      Weight Minimum 1225      Connector SB350      GRAY , Position B , Lead Length 020 Inches												
	24	125F15	875	20.4	35.13	12.94	31.00	1638	M1501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.13	12.94	31.00	1582	M1601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.13	12.94	31.00	1676	M1801214015A	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	105B15	735	17.3	35.50	12.88	30.51	1475	M2101210515N06059	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.13	12.94	31.00	1636	M1901212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ESC025G		STAND-UP RIDER	24 VOLTS , 38.31 X 12.13 X 30.81 Weight Minimum 1225 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	24	125F15	875	20.4	38.18	11.98	30.50	1619	M2501212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	38.18	11.98	30.50	1562	M2601212515B	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	38.18	11.98	30.50	1638	M2801214015B	Y	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	125L15	875	20.4	38.18	11.98	30.50	1588	M2901212515B	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
ESC030A		STAND-UP RIDER	24 VOLTS , 36.50 X 13.60 X 31.30 Weight Minimum 1225 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	24	125F15	875	20.4	35.13	12.94	31.00	1638	M1501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.13	12.94	31.00	1582	M1601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	13.00	31.56	1592	M3401212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.13	12.94	31.00	1676	M1801214015A	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	105B15	735	17.3	35.50	12.88	30.51	1475	M2101210515N06059	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.13	12.94	31.00	1636	M1901212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
ESC030AB		STAND-UP RIDER	24 VOLTS , 36.50 X 13.60 X 31.30 Weight Minimum 1225 Connector SB350 GRAY , Position B , Lead Length 020 Inches												
	24	125F15	875	20.4	35.13	12.94	31.00	1638	M1501212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.13	12.94	31.00	1582	M1601212515A	Y	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	125C15	875	20.4	35.25	13.00	31.56	1592	M3401212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
	24	140T15	980	22.8	35.13	12.94	31.00	1676	M1801214015A	N	(CALL)		SCR200121050T1H	(CALL)	(CALL)
	24	105B15	735	17.3	35.50	12.88	30.51	1475	M2101210515N06059	N	(CALL)	SCR20012750S1H	SCR20012750T1H	(CALL)	(CALL)
	24	125L15	875	20.4	35.13	12.94	31.00	1636	M1901212515A	N	(CALL)	SCR20012965S1H	SCR20012965T1H	(CALL)	(CALL)
ESC030HC		STAND-UP RIDER	36 VOLTS , 39.00 X 16.00 X 31.00 Weight Minimum 1400 Connector SB350 GRAY , Position B , Lead Length 024 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100C13	600	21.0	38.13	15.50	25.63	1698	M2601810013B	Y	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ESC030ZA		STAND-UP RIDER	36 VOLTS , 38.75 X 16.12 X 31.50 Weight Minimum 1925 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C13	750	26.2	38.00	15.50	31.00	2025	M1601812513B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.00	15.50	31.00	2021	M1801814013B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ESC030ZA		STAND-UP RIDER	36 VOLTS , 38.81 X 18.12 X 31.50 Weight Minimum 2175 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.75	31.00	2333	M1601812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.31	17.75	31.00	2469	M1801814015B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ESC035ZA		STAND-UP RIDER	36 VOLTS , 38.75 X 16.12 X 31.50 Weight Minimum 1925 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C13	750	26.2	38.00	15.50	31.00	2025	M1601812513B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	38.00	15.50	31.00	2021	M1801814013B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ESC035ZA		STAND-UP RIDER	36 VOLTS , 38.81 X 18.12 X 31.50 Weight Minimum 2175 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	055B31	825	29.1	39.50	18.04	30.69	2380	M2101805531B	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ESC040HC	STAND-UP RIDER		36 VOLTS , 39.00 X 20.80 X 31.00 Weight Minimum 1600 Connector SB350 GRAY , Position B , Lead Length 024 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.50	19.41	30.69	2600	M2101806031B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ESC040ZA	STAND-UP RIDER		36 VOLTS , 38.88 X 20.75 X 31.50 Weight Minimum 2700 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C17	1000	34.9	38.50	20.19	31.00	2750	M1601812517B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.63	19.47	31.31	2790	M2101806031B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ESC050ZA	STAND-UP RIDER		36 VOLTS , 38.88 X 20.75 X 31.50 Weight Minimum 2700 Connector SB350 GRAY , Position B , Lead Length 011 Inches												
	36	125C17	1000	34.9	38.50	20.19	31.00	2750	M1601812517B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	060B31	900	31.8	39.63	19.47	31.31	2790	M2101806031B7	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ESC030FA	THREE WHEEL STAND-UP RIDER		36 VOLTS , 38.60 X 16.30 X 31.10 Weight Minimum 1885 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	125C13	750	26.2	37.94	15.63	30.50	2046	M2601812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	125F13	750	26.2	37.94	15.63	30.50	2113	M2501812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	045B31	675	23.8	39.25	15.99	30.69	2070	M2101804531B37	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	140T13	840	29.3	37.94	15.63	30.50	2166	M2801814013B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	125L13	750	26.2	37.94	15.63	30.50	2090	M2901812513B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ESC030FA	THREE WHEEL STAND-UP RIDER		36 VOLTS , 38.60 X 18.30 X 32.38 Weight Minimum 2315 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ESC035FA	THREE WHEEL STAND-UP RIDER		36 VOLTS , 38.60 X 18.30 X 31.10 Weight Minimum 2315 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ESC035FA	THREE WHEEL STAND-UP RIDER		36 VOLTS , 38.60 X 20.80 X 31.10 Weight Minimum 2540 Connector SB350 GRAY , Position B , Lead Length 016 Inches												
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ESC040FA	THREE WHEEL STAND-UP RIDER		36 VOLTS , 38.60 X 18.30 X 31.10 Weight Minimum 2200 Connector SB350 GRAY , Position B , Lead Length 025 Inches												
	36	125C15	875	30.6	38.31	17.75	31.00	2333	M1601812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125C15	875	30.6	38.31	17.88	30.50	2340	M2601812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125F15	875	30.6	38.31	17.88	30.50	2417	M2501812515B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	125L15	875	30.6	38.25	17.81	30.50	2383	M2901812515B	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	140T15	980	34.2	38.25	17.81	30.50	2492	M2801814015B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
ESC040FA	THREE WHEEL STAND-UP RIDER			36 VOLTS , 38.60 X 20.80 X 31.10								Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 025 Inches	
	36	125C17	1000	34.9	38.31	20.13	30.50	2673	M2601812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	125F17	1000	34.9	38.31	20.13	30.50	2762	M2501812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	140T17	1120	39.1	38.31	20.13	30.50	2843	M2801814017B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	125L17	1000	34.9	38.31	20.13	30.50	2711	M2901812517B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
ERC030AH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 34.57 X 27.36 X 24.29								Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
ERC030AH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 35.79 X 27.36 X 24.29								Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
ERC030AH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			48 VOLTS , 34.57 X 27.36 X 24.29								Weight Minimum 1850	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
ERC030AH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			48 VOLTS , 35.79 X 27.36 X 24.29								Weight Minimum 1850	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)	
ERC040AH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 34.57 X 27.36 X 24.29								Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
ERC040AH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			36 VOLTS , 35.79 X 27.36 X 24.29								Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)	
	36	085C19	765	26.7	35.18	25.81	23.88	2280	M3401808519V	N	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)	
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)	
ERC040AH	CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE			48 VOLTS , 34.57 X 27.36 X 24.29								Weight Minimum 1850	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	
	48	085C13	510	23.7	34.00	27.00	23.81	2026	M3402408513A6	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>ERC040AH</b>	<b>CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE</b>											<b>48 VOLTS , 35.79 X 27.36 X 24.29</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>	
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
<b>ERC100HH</b>	<b>CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE</b>											<b>48 VOLTS , 44.10 X 39.20 X 23.15</b>				<b>Weight Minimum 3600</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)				
<b>ERC120HH</b>	<b>CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE</b>											<b>36 VOLTS , 44.10 X 45.70 X 23.15</b>				<b>Weight Minimum 4200</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>	
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)				
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)				
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)				
<b>ERC120HH</b>	<b>CLASS I 4-WHEEL COUNTERBALANCED CUSHION TIRE</b>											<b>48 VOLTS , 44.10 X 45.70 X 23.15</b>				<b>Weight Minimum 4200</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>	
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)				
<b>ERCP025AC</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 35.00 X 26.50 X 23.00</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>	
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>ERCP030AC</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 35.00 X 26.50 X 23.00</b>				<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>	
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>ERCP030BC</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>											<b>36 VOLTS , 39.25 X 27.70 X 23.00</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>	
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)				
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)				
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)				
<b>ERCP030BC</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>											<b>48 VOLTS , 39.25 X 27.70 X 23.00</b>				<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>	
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)				
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERCP040AC	FOUR-WHEEL SIT DOWN RIDER			36 VOLTS , 35.00 X 26.50 X 23.00			Weight Minimum 1850		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERCP040BC	FOUR-WHEEL SIT DOWN RIDER			36 VOLTS , 39.25 X 27.70 X 23.00			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERCP040BC	FOUR-WHEEL SIT DOWN RIDER			48 VOLTS , 39.25 X 27.70 X 23.00			Weight Minimum 2300		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC025A	FOUR-WHEEL SIT DOWN RIDER			36 VOLTS , 35.00 X 26.50 X 23.00			Weight Minimum 1850		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC030A	FOUR-WHEEL SIT DOWN RIDER			36 VOLTS , 35.00 X 26.50 X 23.00			Weight Minimum 1850		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	48	085L13	510	23.7	30.81	25.63	22.63	2040	M2902408513A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC030A	FOUR-WHEEL SIT DOWN RIDER			48 VOLTS , 35.00 X 26.50 X 23.00			Weight Minimum 1850		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F13	510	23.7	30.92	25.62	22.62	2006	M2502408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	30.92	25.62	22.62	1930	M2602408513A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T13	600	27.9	30.92	25.62	22.62	1924	M2802410013A	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERC030AF	FOUR-WHEEL SIT DOWN RIDER			36 VOLTS , 34.57 X 27.36 X 24.29			Weight Minimum 1850		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>ERC030AF</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 35.79 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
<b>ERC030AF</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>48 VOLTS , 34.57 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 BLUE , Position B , Lead Length 030 Inches</b>												
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
<b>ERC030AF</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>48 VOLTS , 35.79 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 BLUE , Position B , Lead Length 030 Inches</b>												
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
<b>ERC030AG</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 34.57 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>ERC030AG</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 35.79 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
<b>ERC030AG</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>48 VOLTS , 34.57 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 BLUE , Position B , Lead Length 030 Inches</b>												
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
<b>ERC030AG</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>48 VOLTS , 35.79 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 BLUE , Position B , Lead Length 030 Inches</b>												
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
<b>ERC030B</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 39.25 X 27.70 X 23.00 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 030 Inches</b>												
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>ERC030B</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>48 VOLTS , 39.25 X 27.70 X 23.00</b>												
											Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
<b>ERC030BG</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 34.57 X 27.36 X 24.29</b>												
											Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
<b>ERC030BG</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 35.79 X 27.36 X 24.29</b>												
											Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	( CALL )		SCR20018965T1H	( CALL )	( CALL )
<b>ERC030BG</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>48 VOLTS , 34.57 X 27.36 X 24.29</b>												
											Weight Minimum 1850	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
<b>ERC030BG</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>48 VOLTS , 35.79 X 27.36 X 24.29</b>												
											Weight Minimum 1850	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
<b>ERC035A</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 35.00 X 26.50 X 23.00</b>												
											Weight Minimum 1850	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
<b>ERC035B</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>		<b>36 VOLTS , 39.25 X 27.70 X 23.00</b>												
											Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>ERC035B</b>		<b>FOUR-WHEEL SIT DOWN RIDER</b>				<b>48 VOLTS , 39.25 X 27.70 X 23.00</b>			<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>			
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>ERC040A</b>		<b>FOUR-WHEEL SIT DOWN RIDER</b>				<b>36 VOLTS , 35.00 X 26.50 X 23.00</b>			<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>			
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>ERC040AF</b>		<b>FOUR-WHEEL SIT DOWN RIDER</b>				<b>36 VOLTS , 34.57 X 27.36 X 24.29</b>			<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>			
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>ERC040AF</b>		<b>FOUR-WHEEL SIT DOWN RIDER</b>				<b>36 VOLTS , 35.79 X 27.36 X 24.29</b>			<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>			
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)	SCR20018965T1H	SCR20018965T1H	(CALL)	(CALL)
<b>ERC040AF</b>		<b>FOUR-WHEEL SIT DOWN RIDER</b>				<b>48 VOLTS , 34.57 X 27.36 X 24.29</b>			<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>			
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
<b>ERC040AF</b>		<b>FOUR-WHEEL SIT DOWN RIDER</b>				<b>48 VOLTS , 35.79 X 27.36 X 24.29</b>			<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>			
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
<b>ERC040AG</b>		<b>FOUR-WHEEL SIT DOWN RIDER</b>				<b>36 VOLTS , 34.57 X 27.36 X 24.29</b>			<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>			
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
<b>ERC040AG</b>		<b>FOUR-WHEEL SIT DOWN RIDER</b>				<b>36 VOLTS , 35.79 X 27.36 X 24.29</b>			<b>Weight Minimum 1850</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>			
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC040AG	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 34.57 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERC040AG	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 35.79 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
ERC040B	FOUR-WHEEL SIT DOWN RIDER		36 VOLTS , 39.25 X 27.70 X 23.00 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERC040B	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 39.25 X 27.70 X 23.00 Weight Minimum 2300 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC040BG	FOUR-WHEEL SIT DOWN RIDER		36 VOLTS , 34.57 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085F17	680	23.7	33.25	25.63	22.63	2038	M2501808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085C17	680	23.7	33.25	25.63	22.63	1960	M2601808517G	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T17	800	27.9	33.25	25.63	22.63	2083	M2801810017G	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	33.25	25.63	22.63	1988	M2901808517G	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC040BG	FOUR-WHEEL SIT DOWN RIDER		36 VOLTS , 35.79 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085F19	765	26.7	35.18	25.81	22.62	2279	M2501808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085C19	765	26.7	35.18	25.81	22.62	2198	M2601808519V	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	105B13	630	22.2	35.25	26.63	22.38	2075	M2101810513K7	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T19	900	31.4	35.19	25.81	22.62	2325	M2801810019V	N	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERC040BG	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 34.57 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085C13	510	23.7	34.00	27.00	22.63	2044	M2602408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085F13	510	23.7	34.00	27.00	22.63	2109	M2502408513A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T13	600	27.9	34.00	27.00	22.63	2156	M2802410013A625	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERC040BG	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 35.79 X 27.36 X 24.29 Weight Minimum 1850 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085F15	595	27.7	35.31	25.38	22.63	2330	M2502408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	35.31	25.62	22.62	2231	M2602408515A	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T15	700	32.6	35.31	25.38	22.63	2369	M2802410015A	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
<b>ERC040GH</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>			<b>36 VOLTS , 38.86 X 27.36 X 24.41</b>											<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)			
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
<b>ERC040GH</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>			<b>36 VOLTS , 38.86 X 30.75 X 24.41</b>											<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
<b>ERC040GH</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>			<b>36 VOLTS , 38.86 X 33.15 X 24.41</b>											<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
<b>ERC040GH</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>			<b>48 VOLTS , 38.86 X 27.36 X 24.41</b>											<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)			
<b>ERC040GH</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>			<b>48 VOLTS , 38.86 X 30.75 X 24.41</b>											<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
<b>ERC040GH</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>			<b>48 VOLTS , 38.86 X 33.15 X 24.41</b>											<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE</b>	<b>, Position B , Lead Length 030 Inches</b>
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
<b>ERC050GH</b>	<b>FOUR-WHEEL SIT DOWN RIDER</b>			<b>36 VOLTS , 38.86 X 27.36 X 24.41</b>											<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY</b>	<b>, Position B , Lead Length 030 Inches</b>
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)			
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
ERC050GH	FOUR-WHEEL SIT DOWN RIDER			36 VOLTS , 38.86 X 30.75 X 24.41											Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
ERC050GH	FOUR-WHEEL SIT DOWN RIDER			36 VOLTS , 38.86 X 33.15 X 24.41											Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
ERC050GH	FOUR-WHEEL SIT DOWN RIDER			48 VOLTS , 38.86 X 27.36 X 24.41											Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)			
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
ERC050GH	FOUR-WHEEL SIT DOWN RIDER			48 VOLTS , 38.86 X 30.75 X 24.41											Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)			
ERC050GH	FOUR-WHEEL SIT DOWN RIDER			48 VOLTS , 38.86 X 33.15 X 24.41											Weight Minimum 2900	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
ERC060GH	FOUR-WHEEL SIT DOWN RIDER			36 VOLTS , 38.86 X 33.15 X 24.41											Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)			
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)			
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)			
ERC060GH	FOUR-WHEEL SIT DOWN RIDER			48 VOLTS , 38.86 X 33.15 X 24.41											Weight Minimum 2900	Connector SB350	BLUE	, Position B , Lead Length 030 Inches
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)			
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC060HC	FOUR-WHEEL SIT DOWN RIDER							36 VOLTS , 39.10 X 33.60 X 26.00		Weight Minimum 3300	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100C27	1300	45.4	38.50	31.63	25.63	3458	M2601810027B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	100F27	1300	45.4	38.50	31.63	25.63	3573	M2501810027B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
ERC060HC	FOUR-WHEEL SIT DOWN RIDER							48 VOLTS , 39.10 X 33.60 X 26.00		Weight Minimum 3300	Connector SB350	BLUE , Position B , Lead Length 030 Inches			
	48	100C21	1000	46.6	38.43	32.93	25.62	3664	M2602410021B	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
ERC070HC	FOUR-WHEEL SIT DOWN RIDER							36 VOLTS , 39.10 X 33.60 X 26.00		Weight Minimum 3300	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	36	105B23	1155	40.7	39.61	32.00	23.25	3400	M2101810523B0	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100C27	1300	45.4	38.50	31.63	25.63	3458	M2601810027B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	100F27	1300	45.4	38.50	31.63	25.63	3573	M2501810027B	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
ERC070HC	FOUR-WHEEL SIT DOWN RIDER							48 VOLTS , 39.10 X 33.60 X 26.00		Weight Minimum 3300	Connector SB350	BLUE , Position B , Lead Length 030 Inches			
	48	100C21	1000	46.6	38.43	32.93	25.62	3664	M2602410021B	N	( CALL )		SCR200241050T1H	( CALL )	( CALL )
ERC070HD	FOUR-WHEEL SIT DOWN RIDER							48 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches			
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
ERC070HD	FOUR-WHEEL SIT DOWN RIDER							48 VOLTS , 44.10 X 39.20 X 24.25		Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches			
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )
ERC070HG	FOUR-WHEEL SIT DOWN RIDER							36 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L33	1360	47.5	43.38	38.63	22.63	4085	M2901808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	100T33	1600	55.9	43.38	38.62	22.62	3938	M2801810033C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
ERC070HG	FOUR-WHEEL SIT DOWN RIDER							48 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches			
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
	48	100T27	1300	60.5	41.89	38.44	22.63	4308	M2802410027B	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )
ERC080HC	FOUR-WHEEL SIT DOWN RIDER							36 VOLTS , 39.10 X 39.10 X 26.00		Weight Minimum 3300	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	36	100C33	1600	55.9	38.44	38.38	25.63	4320	M2601810033B	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )
ERC080HC	FOUR-WHEEL SIT DOWN RIDER							48 VOLTS , 39.10 X 39.10 X 26.00		Weight Minimum 3300	Connector SB350	BLUE , Position B , Lead Length 030 Inches			
	48	100C25	1200	55.9	38.87	38.43	25.62	4257	M2602410025C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )
ERC080HD	FOUR-WHEEL SIT DOWN RIDER							36 VOLTS , 44.10 X 39.20 X 24.25		Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches			
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )
ERC080HD	FOUR-WHEEL SIT DOWN RIDER							48 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches			
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE		
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)										
ERC080HD	FOUR-WHEEL SIT DOWN RIDER												48 VOLTS , 44.10 X 39.20 X 24.25		Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )		
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )		
ERC080HG	FOUR-WHEEL SIT DOWN RIDER												36 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3400	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )		
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )		
	36	085L33	1360	47.5	43.38	38.63	22.63	4085	M2901808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )		
	36	100T33	1600	55.9	43.38	38.62	22.62	3938	M2801810033C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )		
ERC080HG	FOUR-WHEEL SIT DOWN RIDER												48 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3400	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )		
	48	085C27	1105	51.4	41.89	38.44	22.63	4022	M2602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		
	48	085F27	1105	51.4	41.89	38.44	22.63	4184	M2502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		
	48	100T27	1300	60.5	38.44	41.89	22.63	4308	M2802410027B	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )		
ERC100HC	FOUR-WHEEL SIT DOWN RIDER												36 VOLTS , 39.10 X 39.10 X 26.00		Weight Minimum 3300	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	100C33	1600	55.9	38.44	38.38	25.63	4320	M2601810033B	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )		
ERC100HC	FOUR-WHEEL SIT DOWN RIDER												48 VOLTS , 39.10 X 39.10 X 26.00		Weight Minimum 3300	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	100C25	1200	55.9	38.87	38.43	25.62	4257	M2602410025C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		
ERC100HD	FOUR-WHEEL SIT DOWN RIDER												48 VOLTS , 44.10 X 39.20 X 23.15		Weight Minimum 3600	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )		
ERC100HD	FOUR-WHEEL SIT DOWN RIDER												48 VOLTS , 44.10 X 39.20 X 24.25		Weight Minimum 3600	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )		
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )		
ERC100HD	FOUR-WHEEL SIT DOWN RIDER												48 VOLTS , 44.10 X 45.70 X 23.15		Weight Minimum 3600	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		
ERC100HD	FOUR-WHEEL SIT DOWN RIDER												48 VOLTS , 45.00 X 45.70 X 24.25		Weight Minimum 3600	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		
ERC120HC	FOUR-WHEEL SIT DOWN RIDER												36 VOLTS , 39.10 X 39.10 X 26.00		Weight Minimum 4000	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	100C33	1600	55.9	38.44	38.38	25.63	4320	M2601810033B	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )		
ERC120HC	FOUR-WHEEL SIT DOWN RIDER												36 VOLTS , 39.10 X 43.10 X 26.75		Weight Minimum 4000	Connector SB350	GRAY , Position B , Lead Length 030 Inches
	36	100C33	1600	55.9	38.50	38.44	26.13	4374	M1601810033B	N	( CALL )		SCR200181700T1H	( CALL )	( CALL )		
ERC120HC	FOUR-WHEEL SIT DOWN RIDER												48 VOLTS , 39.10 X 39.10 X 26.00		Weight Minimum 4000	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	100C25	1200	55.9	38.87	38.43	25.62	4257	M2602410025C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )		

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
ERC120HC	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 39.10 X 43.10 X 26.75													
	48	100C25	1200	55.9	38.87	39.06	26.12	4440	M1602410025B	N	( CALL )	Connector SB350	BLUE , Position B , Lead Length 030 Inches	SCR200241200T1H	( CALL )	( CALL )
ERC120HD	FOUR-WHEEL SIT DOWN RIDER		36 VOLTS , 44.10 X 45.70 X 23.15													
	36	085C19	1530	106.9	43.50	44.50	22.62	4367	M2603608519Z6	N	( CALL )	Connector SB350	GRAY , Position B , Lead Length 030 Inches	SCR200181700T1H	( CALL )	( CALL )
	36	085F19	1530	106.9	43.50	44.50	22.62	4502	M2503608519Z6	N	( CALL )			SCR200181700T1H	( CALL )	( CALL )
	36	085L19	1530	106.9	43.50	44.50	22.62	4396	M2903608519Z6	N	( CALL )			SCR200181700T1H	( CALL )	( CALL )
ERC120HD	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 44.10 X 45.70 X 23.15													
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	( CALL )	Connector SB350	BLUE , Position B , Lead Length 030 Inches	SCR200241200T1H	( CALL )	( CALL )
	48	085C29	1190	55.4	44.90	43.00	22.62	4585	M2602408529C25	N	( CALL )			SCR200241200T1H	( CALL )	( CALL )
ERC120HD	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 45.00 X 45.70 X 24.25													
	48	075B31	1125	52.9	43.50	45.00	22.19	4425	M2102407531BB81	N	( CALL )	Connector SB350	BLUE , Position B , Lead Length 030 Inches	SCR200241200T1H	( CALL )	( CALL )
ERP030B	FOUR-WHEEL SIT DOWN RIDER		36 VOLTS , 39.25 X 27.70 X 23.00													
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )	Connector SB350	GRAY , Position B , Lead Length 030 Inches	SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )			SCR20018965T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	( CALL )			SCR20018865T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )			SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )			SCR20018965T1H	( CALL )	( CALL )
ERP030B	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 39.25 X 27.70 X 23.00													
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )	Connector SB350	BLUE , Position B , Lead Length 030 Inches	SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )			SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )			SCR20024865T1H	( CALL )	( CALL )
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )	
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )	
ERP035B	FOUR-WHEEL SIT DOWN RIDER		36 VOLTS , 39.25 X 27.70 X 23.00													
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )	Connector SB350	GRAY , Position B , Lead Length 030 Inches	SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )			SCR20018965T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	( CALL )			SCR20018865T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )			SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )			SCR20018965T1H	( CALL )	( CALL )
ERP035B	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 39.25 X 27.70 X 23.00													
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )	Connector SB350	BLUE , Position B , Lead Length 030 Inches	SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )			SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )			SCR20024865T1H	( CALL )	( CALL )
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )	
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )	
ERP040B	FOUR-WHEEL SIT DOWN RIDER		36 VOLTS , 39.25 X 27.70 X 23.00													
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )	Connector SB350	GRAY , Position B , Lead Length 030 Inches	SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )			SCR20018965T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	( CALL )			SCR20018865T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )			SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )			SCR20018965T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERP040B	FOUR-WHEEL SIT DOWN RIDER		48 VOLTS , 39.25 X 27.70 X 23.00 Weight Minimum 2300 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC040RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)		36 VOLTS , 38.86 X 27.30 X 23.15 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERC040RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)		36 VOLTS , 38.86 X 27.30 X 24.57 Weight Minimum 2300 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085C23	935	32.7	38.44	27.00	23.25	2608	M1601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.44	27.00	23.25	2775	M1801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC040RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)		36 VOLTS , 38.86 X 30.70 X 23.15 Weight Minimum 2500 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ERC040RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)		36 VOLTS , 38.86 X 30.70 X 24.57 Weight Minimum 2500 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC040RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)		48 VOLTS , 38.86 X 27.30 X 23.15 Weight Minimum 2300 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC040RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)		48 VOLTS , 38.86 X 27.30 X 24.57 Weight Minimum 2300 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085C17	680	31.7	38.31	26.75	23.25	2605	M1602408517B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.31	26.75	23.25	2619	M1802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
ERC040RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)							48 VOLTS , 38.86 X 30.70 X 23.15		Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )	
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )	
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )	
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )	
ERC040RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)							48 VOLTS , 38.86 X 30.70 X 24.57		Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )	
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )	
ERC050RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)							36 VOLTS , 38.86 X 27.30 X 23.15		Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )	
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )	
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )	
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )	
ERC050RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)							36 VOLTS , 38.86 X 27.30 X 24.57		Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )	
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )	
	36	085C23	935	32.7	38.44	27.00	23.25	2608	M1601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )	
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )	
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	100T23	1100	38.4	38.44	27.00	23.25	2775	M1801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )	
ERC050RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)							36 VOLTS , 38.86 X 30.70 X 23.15		Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )	
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )	
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )	
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )	
ERC050RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)							36 VOLTS , 38.86 X 30.70 X 24.57		Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	105B23	1155	40.7	39.50	29.73	23.13	3235	M2101810523B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )	
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )	
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )	
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )	
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )	
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC050RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)			48 VOLTS , 38.86 X 27.30 X 23.15			Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
ERC050RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)			48 VOLTS , 38.86 X 27.30 X 24.57			Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.31	26.75	23.25	2605	M1602408517B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.31	26.75	23.25	2619	M1802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
ERC050RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)			48 VOLTS , 38.86 X 30.70 X 23.15			Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
ERC050RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)			48 VOLTS , 38.86 X 30.70 X 24.57			Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
ERC060RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)			36 VOLTS , 38.86 X 27.30 X 23.15			Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
ERC060RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)			36 VOLTS , 38.86 X 27.30 X 24.57			Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.44	27.00	23.25	2608	M1601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	27.00	22.55	2530	M8901810019B059	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.44	27.00	23.25	2775	M1801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC060RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)			48 VOLTS , 38.86 X 27.30 X 23.15			Weight Minimum 2300		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
ERC060RA	FOUR-WHEEL SIT DOWN RIDER (RA-SERIES)			48 VOLTS , 38.86 X 27.30 X 24.57			Weight Minimum 2300		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085C17	680	31.7	38.31	26.75	23.25	2605	M1602408517B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.31	26.75	23.25	2619	M1802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
ERC040RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			36 VOLTS , 38.86 X 27.36 X 24.41			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	( CALL )		SCR20018750T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
ERC040RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			36 VOLTS , 38.86 X 30.75 X 24.41			Weight Minimum 2500		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
ERC040RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			36 VOLTS , 38.86 X 33.15 X 24.41			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
ERC040RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			48 VOLTS , 38.86 X 27.36 X 24.41			Weight Minimum 2300		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
ERC040RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			48 VOLTS , 38.86 X 30.75 X 24.41			Weight Minimum 2500		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>ERC040RF</b> <b>FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)</b> <b>48 VOLTS , 38.86 X 33.15 X 24.41</b> <b>Weight Minimum 2900</b> <b>Connector SB350</b> <b>BLUE</b> , Position B , Lead Length 030 Inches															
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
<b>ERC050RF</b> <b>FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)</b> <b>36 VOLTS , 38.86 X 27.36 X 24.41</b> <b>Weight Minimum 2300</b> <b>Connector SB350</b> <b>GRAY</b> , Position B , Lead Length 030 Inches															
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	( CALL )		SCR20018750T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
<b>ERC050RF</b> <b>FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)</b> <b>36 VOLTS , 38.86 X 30.75 X 24.41</b> <b>Weight Minimum 2500</b> <b>Connector SB350</b> <b>GRAY</b> , Position B , Lead Length 030 Inches															
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
<b>ERC050RF</b> <b>FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)</b> <b>36 VOLTS , 38.86 X 33.15 X 24.41</b> <b>Weight Minimum 2900</b> <b>Connector SB350</b> <b>GRAY</b> , Position B , Lead Length 030 Inches															
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
<b>ERC050RF</b> <b>FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)</b> <b>48 VOLTS , 38.86 X 27.36 X 24.41</b> <b>Weight Minimum 2300</b> <b>Connector SB350</b> <b>BLUE</b> , Position B , Lead Length 030 Inches															
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
<b>ERC050RF</b> <b>FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)</b> <b>48 VOLTS , 38.86 X 30.75 X 24.41</b> <b>Weight Minimum 2500</b> <b>Connector SB350</b> <b>BLUE</b> , Position B , Lead Length 030 Inches															
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC050RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			48 VOLTS , 38.86 X 33.15 X 24.41			Weight Minimum 2900		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
ERC060RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			36 VOLTS , 38.86 X 33.15 X 24.41			Weight Minimum 2900		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC060RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			48 VOLTS , 38.86 X 33.15 X 24.41			Weight Minimum 2900		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
ERC065RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			36 VOLTS , 38.86 X 36.54 X 24.41			Weight Minimum 3100		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
ERC065RF	FOUR-WHEEL SIT DOWN RIDER (RF-SERIES)			48 VOLTS , 38.86 X 36.54 X 24.41			Weight Minimum 3100		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
ERC040RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)			36 VOLTS , 38.86 X 27.36 X 24.41			Weight Minimum 2300		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERC040RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)			36 VOLTS , 38.86 X 30.75 X 24.41			Weight Minimum 2500		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>ERC040RG</b>	<b>FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)</b>				<b>36 VOLTS , 38.86 X 33.15 X 24.41</b>			<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>					
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
<b>ERC040RG</b>	<b>FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)</b>				<b>48 VOLTS , 38.86 X 27.36 X 24.41</b>			<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>					
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
<b>ERC040RG</b>	<b>FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)</b>				<b>48 VOLTS , 38.86 X 30.75 X 24.41</b>			<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>					
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
<b>ERC040RG</b>	<b>FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)</b>				<b>48 VOLTS , 38.86 X 33.15 X 24.41</b>			<b>Weight Minimum 2900</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>					
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
<b>ERC040RH</b>	<b>FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)</b>				<b>36 VOLTS , 38.86 X 27.36 X 24.41</b>			<b>Weight Minimum 2300</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>					
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	( CALL )		SCR20018750T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
<b>ERC040RH</b>	<b>FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)</b>				<b>36 VOLTS , 38.86 X 30.75 X 24.41</b>			<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>					
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC040RH	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)				36 VOLTS , 38.86 X 33.15 X 24.41				Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
ERC040RH	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)				48 VOLTS , 38.86 X 27.36 X 24.41				Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
ERC040RH	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)				48 VOLTS , 38.86 X 30.75 X 24.41				Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
ERC040RH	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)				48 VOLTS , 38.86 X 33.15 X 24.41				Weight Minimum 2900	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
ERC050RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)				36 VOLTS , 38.86 X 27.36 X 24.41				Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	( CALL )		SCR20018750T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
ERC050RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)				36 VOLTS , 38.86 X 30.75 X 24.41				Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC050RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)											36 VOLTS , 38.86 X 33.15 X 24.41 Weight Minimum 2900 Connector SB350 GRAY , Position B , Lead Length 030 Inches			
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085C27	1105	38.6	38.31	31.50	23.81	3060	M3401808527B2	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC050RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)											48 VOLTS , 38.86 X 27.36 X 24.41 Weight Minimum 2300 Connector SB350 BLUE , Position B , Lead Length 030 Inches			
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC050RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)											48 VOLTS , 38.86 X 30.75 X 24.41 Weight Minimum 2500 Connector SB350 BLUE , Position B , Lead Length 030 Inches			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
ERC050RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)											48 VOLTS , 38.86 X 33.15 X 24.41 Weight Minimum 2900 Connector SB350 BLUE , Position B , Lead Length 030 Inches			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
ERC065GH	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)											36 VOLTS , 38.86 X 36.54 X 24.41 Weight Minimum 3100 Connector SB350 GRAY , Position B , Lead Length 030 Inches			
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
ERC065GH	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)											48 VOLTS , 38.86 X 36.54 X 24.41 Weight Minimum 3100 Connector SB350 BLUE , Position B , Lead Length 030 Inches			
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
ERC065RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)											36 VOLTS , 38.86 X 36.54 X 24.41 Weight Minimum 3100 Connector SB350 GRAY , Position B , Lead Length 030 Inches			
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
ERC065RG	FOUR-WHEEL SIT DOWN RIDER (RG-SERIES)											48 VOLTS , 38.86 X 36.54 X 24.41 Weight Minimum 3100 Connector SB350 BLUE , Position B , Lead Length 030 Inches			
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC040ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			36 VOLTS , 38.86 X 27.30 X 23.15			Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERC040ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			36 VOLTS , 38.86 X 27.30 X 24.57			Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERC040ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			36 VOLTS , 38.86 X 30.70 X 23.15			Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ERC040ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			36 VOLTS , 38.86 X 30.70 X 24.57			Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ERC040ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			48 VOLTS , 38.86 X 27.30 X 23.15			Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC040ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			48 VOLTS , 38.86 X 27.30 X 24.57			Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC040ZA		FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)				48 VOLTS , 38.86 X 30.70 X 23.15			Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
ERC040ZA		FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)				48 VOLTS , 38.86 X 30.70 X 24.57			Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
ERC050ZA		FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)				36 VOLTS , 38.86 X 27.30 X 23.15			Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERC050ZA		FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)				36 VOLTS , 38.86 X 27.30 X 24.57			Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERC050ZA		FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)				36 VOLTS , 38.86 X 30.70 X 23.15			Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC050ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			36 VOLTS , 38.86 X 30.70 X 24.57			Weight Minimum 2500		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ERC050ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			36 VOLTS , 38.86 X 33.11 X 23.15			Weight Minimum 2700		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC050ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			36 VOLTS , 38.86 X 33.11 X 24.57			Weight Minimum 2700		Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC050ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			48 VOLTS , 38.86 X 27.30 X 23.15			Weight Minimum 2300		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	060B21	600	28.2	38.50	27.06	22.11	2567	M2102406021DB782	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC050ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			48 VOLTS , 38.86 X 27.30 X 24.57			Weight Minimum 2300		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC050ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)			48 VOLTS , 38.86 X 30.70 X 23.15			Weight Minimum 2500		Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE	
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)									
ERC050ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)					48 VOLTS , 38.86 X 30.70 X 24.57			Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)	
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
ERC050ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)					48 VOLTS , 38.86 X 33.11 X 23.15			Weight Minimum 2700	Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	105B15	735	34.6	39.25	30.19	22.54	3090	M2102410515B75981	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
ERC050ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)					48 VOLTS , 38.86 X 33.11 X 24.57			Weight Minimum 2700	Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
ERC060ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)					36 VOLTS , 38.86 X 33.11 X 23.15			Weight Minimum 2700	Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
ERC060ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)					36 VOLTS , 38.86 X 33.11 X 24.57			Weight Minimum 2700	Connector SB350	GRAY	, Position B , Lead Length 030 Inches				
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)	
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)	
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)	
ERC060ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)					48 VOLTS , 38.86 X 33.11 X 23.15			Weight Minimum 2700	Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	105B15	735	34.6	39.25	32.44	23.04	3445	M2102410515B781	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
ERC060ZA	FOUR-WHEEL SIT DOWN RIDER (ZA-SERIES)					48 VOLTS , 38.86 X 33.11 X 24.57			Weight Minimum 2700	Connector SB350	BLUE	, Position B , Lead Length 030 Inches				
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)	
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)	

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC040ZF	FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)			36 VOLTS , 38.86 X 27.36 X 24.41			Weight Minimum 2300	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	(CALL)		SCR20018965T1H	(CALL)	(CALL)
ERC040ZF	FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)			36 VOLTS , 38.86 X 30.75 X 24.41			Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ERC040ZF	FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)			36 VOLTS , 38.86 X 33.15 X 24.41			Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches					
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC040ZF	FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)			48 VOLTS , 38.86 X 27.36 X 24.41			Weight Minimum 2300	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERC040ZF	FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)			48 VOLTS , 38.86 X 30.75 X 24.41			Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
ERC040ZF	FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)			48 VOLTS , 38.86 X 33.15 X 24.41			Weight Minimum 2900	Connector SB350	BLUE	, Position B , Lead Length 030 Inches					
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
<b>ERC050ZF      FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)      36 VOLTS , 38.86 X 27.36 X 24.41      Weight Minimum 2300      Connector SB350      GRAY      , Position B , Lead Length 030 Inches</b>															
	36	085F23	935	32.7	38.25	26.88	22.63	2651	M2501808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	085C23	935	32.7	38.25	26.88	22.63	2544	M2601808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
	36	100G17	800	28.2	38.50	27.00	20.75	2326	M8901810017B060	N	( CALL )		SCR20018750T1H	( CALL )	( CALL )
	36	100T23	1100	38.4	38.25	26.88	22.63	2685	M2801810023B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L23	935	32.7	38.25	26.88	22.63	2587	M2901808523B	Y	( CALL )		SCR20018965T1H	( CALL )	( CALL )
<b>ERC050ZF      FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)      36 VOLTS , 38.86 X 30.75 X 24.41      Weight Minimum 2500      Connector SB350      GRAY      , Position B , Lead Length 030 Inches</b>															
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	( CALL )		SCR20018865T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
<b>ERC050ZF      FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)      36 VOLTS , 38.86 X 33.15 X 24.41      Weight Minimum 2900      Connector SB350      GRAY      , Position B , Lead Length 030 Inches</b>															
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	( CALL )		SCR200181050T1H	( CALL )	( CALL )
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	( CALL )		SCR200181450T1H	( CALL )	( CALL )
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	( CALL )		SCR200181200T1H	( CALL )	( CALL )
<b>ERC050ZF      FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)      48 VOLTS , 38.86 X 27.36 X 24.41      Weight Minimum 2300      Connector SB350      BLUE      , Position B , Lead Length 030 Inches</b>															
	48	085F17	680	31.7	38.38	26.69	22.63	2642	M2502408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	085C17	680	31.7	38.38	26.69	22.63	2535	M2602408517B	Y	( CALL )		SCR20024750T1H	( CALL )	( CALL )
	48	100T17	800	37.2	38.38	26.69	22.63	2700	M2802410017B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085L17	680	31.7	38.25	26.63	22.63	2558	M2902408517B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )
<b>ERC050ZF      FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)      48 VOLTS , 38.86 X 30.75 X 24.41      Weight Minimum 2500      Connector SB350      BLUE      , Position B , Lead Length 030 Inches</b>															
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
<b>ERC050ZF      FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)      48 VOLTS , 38.86 X 33.15 X 24.41      Weight Minimum 2900      Connector SB350      BLUE      , Position B , Lead Length 030 Inches</b>															
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	( CALL )		SCR200241050T1H	( CALL )	( CALL )
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	( CALL )		SCR20024865T1H	( CALL )	( CALL )

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERC060ZF		FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)				36 VOLTS , 38.86 X 30.75 X 24.41			Weight Minimum 2500	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085C25	1020	35.6	38.25	29.25	22.63	2756	M2601808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.25	29.25	22.63	2863	M2501808525B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085F25	1020	35.6	38.44	29.25	23.50	2925	M1501808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100G19	900	31.8	39.50	29.25	22.55	3035	M8901810019B759	N	(CALL)		SCR20018865T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	39.50	29.73	21.24	2970	M2101810521B0	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.25	29.25	22.63	2938	M2801810025B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	100T25	1200	41.9	38.44	29.25	23.50	3006	M1801810025B	N	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085L25	1020	35.6	38.25	29.25	22.63	2794	M2901808525B	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
ERC060ZF		FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)				36 VOLTS , 38.86 X 33.15 X 24.41			Weight Minimum 2900	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085C27	1105	38.6	38.44	31.50	22.63	2960	M2601808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	085F27	1105	38.6	38.44	31.50	22.63	3086	M2501808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
	36	105B21	1050	37.0	38.61	32.50	22.05	3075	M2101810521B059	N	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100T27	1300	45.4	38.44	31.50	22.63	3127	M2801810027B	Y	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085L27	1105	38.6	38.25	31.50	22.63	3003	M2901808527B	Y	(CALL)		SCR200181200T1H	(CALL)	(CALL)
ERC060ZF		FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)				48 VOLTS , 38.86 X 30.75 X 24.41			Weight Minimum 2500	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085C19	765	35.6	38.44	29.88	22.62	2804	M2602408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085F19	765	35.6	38.44	29.88	22.62	2923	M2502408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C19	765	35.6	38.44	29.88	23.25	2925	M1602408519B	N	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	22.62	2965	M2802410019B	Y	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T19	900	41.9	38.44	29.88	23.25	2906	M1802410019B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085L19	765	35.6	38.44	29.88	22.63	2970	M2902408519B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
ERC060ZF		FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)				48 VOLTS , 38.86 X 33.15 X 24.41			Weight Minimum 2900	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085F21	850	39.6	38.25	32.63	22.63	3211	M2502408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	085C21	850	39.6	38.25	32.63	22.63	3087	M2602408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	105B17	840	39.5	39.61	32.69	23.90	3270	M2102410517B81	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
	48	100T21	1000	46.6	38.25	32.63	22.63	3293	M2802410021B	Y	(CALL)		SCR200241050T1H	(CALL)	(CALL)
	48	085L21	850	39.6	38.38	32.69	22.63	3157	M2902408521B	Y	(CALL)		SCR20024865T1H	(CALL)	(CALL)
ERC065ZF		FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)				36 VOLTS , 38.86 X 36.54 X 24.41			Weight Minimum 3100	Connector SB350	GRAY	, Position B , Lead Length 030 Inches			
	36	085C31	1275	44.5	38.44	36.13	22.63	3514	M2601808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	085F31	1275	44.5	38.44	36.13	22.63	3742	M2501808531B	N	(CALL)		SCR200181450T1H	(CALL)	(CALL)
	36	100T31	1500	52.4	38.44	36.13	22.63	3730	M2801810031B	N	(CALL)		SCR200181700T1H	(CALL)	(CALL)
ERC065ZF		FOUR-WHEEL SIT DOWN RIDER (ZF-SERIES)				48 VOLTS , 38.86 X 36.54 X 24.41			Weight Minimum 3100	Connector SB350	BLUE	, Position B , Lead Length 030 Inches			
	48	085C23	935	43.5	38.44	35.88	22.63	3458	M2602408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	085F23	935	43.5	38.44	35.88	22.63	3626	M2502408523B	N	(CALL)		SCR20024965T1H	(CALL)	(CALL)
	48	100T23	1100	51.2	38.44	35.88	22.63	3688	M2802410023B	N	(CALL)		SCR200241200T1H	(CALL)	(CALL)
ERP040DH		SIT DOWN				80 VOLTS , 40.60 X 28.30 X 30.90			Weight Minimum 3720	Connector SBE320	BLACK	, Position A , Lead Length 012 Inches			
	80	140T09	560	43.5	40.00	27.50	30.50	3985	M2804014009X7625	N	(CALL)		SCR20040600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE						
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)														
ERC080HH	SIT-DOWN FOUR WHEEL COUNTER BALANCED															48 VOLTS , 45.20 X 39.20 X 24.60	Weight Minimum 3400	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )						
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )						
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )						
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )						
	48	085L27	1105	51.4	41.89	38.44	23.25	4330	M1902408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )						
ERC70HH	SIT-DOWN FOUR WHEEL COUNTER BALANCED															36 VOLTS , 44.10 X 39.20 X 23.15	Weight Minimum 3400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )						
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )						
ERC70HH	SIT-DOWN FOUR WHEEL COUNTER BALANCED															36 VOLTS , 45.20 X 39.20 X 24.57	Weight Minimum 3400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )						
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )						
ERC70HH	SIT-DOWN FOUR WHEEL COUNTER BALANCED															48 VOLTS , 44.10 X 39.20 X 23.15	Weight Minimum 3400	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )						
ERC70HH	SIT-DOWN FOUR WHEEL COUNTER BALANCED															48 VOLTS , 45.20 X 39.20 X 24.57	Weight Minimum 3400	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )						
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )						
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )						
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )						
ERC80HH	SIT-DOWN FOUR WHEEL COUNTER BALANCED															36 VOLTS , 44.10 X 39.20 X 23.15	Weight Minimum 3400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085C33	1360	47.5	43.38	38.62	22.62	3807	M2601808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )						
	36	085F33	1360	47.5	43.38	38.62	22.62	3988	M2501808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )						
ERC80HH	SIT-DOWN FOUR WHEEL COUNTER BALANCED															36 VOLTS , 45.20 X 39.20 X 24.57	Weight Minimum 3400	Connector SB350	GRAY	, Position B , Lead Length 030 Inches	
	36	085C33	1360	47.5	38.44	38.38	23.81	3730	M3401808533C2	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )						
	36	085C33	1360	47.5	44.50	38.31	23.81	3790	M3401808533C6	N	( CALL )		SCR200181450T1H	( CALL )	( CALL )						
ERC80HH	SIT-DOWN FOUR WHEEL COUNTER BALANCED															48 VOLTS , 44.10 X 39.20 X 23.15	Weight Minimum 3400	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )						
ERC80HH	SIT-DOWN FOUR WHEEL COUNTER BALANCED															48 VOLTS , 45.20 X 39.20 X 24.57	Weight Minimum 3400	Connector SB350	BLUE	, Position B , Lead Length 030 Inches	
	48	085C27	1105	51.4	41.89	38.44	23.25	4132	M1602408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )						
	48	085F27	1105	51.4	41.89	38.44	23.25	4314	M1502408527C	N	( CALL )		SCR200241200T1H	( CALL )	( CALL )						
	48	060B31	900	42.3	44.00	38.61	22.75	3770	M2102406031BB81	N	( CALL )		SCR20024965T1H	( CALL )	( CALL )						
	48	100T27	1300	60.5	41.89	38.44	23.25	4366	M1802410027C	N	( CALL )		SCR200241450T1H	( CALL )	( CALL )						
ERP30TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															36 VOLTS , 39.00 X 21.50 X 23.10	Weight Minimum 1700	Connector SB350	GRAY	, Position A , Lead Length 025 Inches	
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )						
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )						
	36	060B21	600	21.2	38.50	20.75	24.50	2077	M2101806021B7	N	( CALL )	SCR20018600S1H	SCR20018600T1H	( CALL )	( CALL )						
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )						

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE						
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)														
ERP030TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															36 VOLTS , 39.00 X 21.50 X 26.10			Weight Minimum 2000	Connector SB350	GRAY , Position A , Lead Length 025 Inches
	36	060B25	720	25.4	38.50	20.34	25.69	2130	M2101806025B	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )						
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
ERP030TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															48 VOLTS , 39.00 X 21.50 X 23.10			Weight Minimum 1700	Connector SB350	BLUE , Position A , Lead Length 025 Inches
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )						
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )						
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )						
ERP030TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															48 VOLTS , 39.00 X 21.50 X 26.10			Weight Minimum 2000	Connector SB350	BLUE , Position A , Lead Length 025 Inches
	48	100C13	600	27.9	38.50	20.63	25.63	2201	M2602410013B	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )						
ERP035TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															36 VOLTS , 39.00 X 25.20 X 23.10			Weight Minimum 2100	Connector SB350	GRAY , Position A , Lead Length 025 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )						
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	( CALL )	SCR200181050T1H	SCR200181050T1H	( CALL )	( CALL )						
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
ERP035TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															36 VOLTS , 39.00 X 25.20 X 26.10			Weight Minimum 2500	Connector SB350	GRAY , Position A , Lead Length 025 Inches
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )						
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )						
	36	085C21	850	29.7	38.31	24.56	24.30	2560	M3401808521B72	N	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
ERP035TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															48 VOLTS , 39.00 X 25.20 X 23.10			Weight Minimum 2100	Connector SB350	BLUE , Position A , Lead Length 025 Inches
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )						
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )						
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	( CALL )	SCR20024600S1H	SCR20024600T1H	( CALL )	( CALL )						
ERP035TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															48 VOLTS , 39.00 X 25.20 X 26.10			Weight Minimum 2500	Connector SB350	BLUE , Position A , Lead Length 025 Inches
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )						
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )						
ERP040TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															36 VOLTS , 39.00 X 25.30 X 23.10			Weight Minimum 2100	Connector SB350	GRAY , Position A , Lead Length 025 Inches
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
	36	075B21	750	26.5	38.50	24.00	23.25	2170	M2101807521B0	N	( CALL )	SCR20018750S1H	SCR20018750T1H	( CALL )	( CALL )						
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	( CALL )	SCR200181050T1H	SCR200181050T1H	( CALL )	( CALL )						
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						
ERP040TH	SIT-DOWN THREE WHEEL COUNTER BALANCED															36 VOLTS , 39.00 X 25.30 X 26.10			Weight Minimum 2500	Connector SB350	GRAY , Position A , Lead Length 025 Inches
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )						
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	( CALL )		SCR200181050T1H	( CALL )	( CALL )						
	36	085C21	850	29.7	38.31	24.56	24.30	2560	M3401808521B72	N	( CALL )	SCR20018865S1H	SCR20018865T1H	( CALL )	( CALL )						

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)



# Yale Selector Guide

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE				
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)												
<b>ERP040TH</b>	<b>SIT-DOWN THREE WHEEL COUNTER BALANCED</b>												<b>48 VOLTS , 39.00 X 25.30 X 23.10</b>		<b>Weight Minimum 2100</b>	<b>Connector SB350</b>	<b>BLUE , Position A , Lead Length 025 Inches</b>		
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	075B15	525	24.7	39.25	24.85	22.29	2180	M2102407515B781	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
<b>ERP040TH</b>	<b>SIT-DOWN THREE WHEEL COUNTER BALANCED</b>												<b>48 VOLTS , 39.00 X 25.30 X 26.10</b>		<b>Weight Minimum 2500</b>	<b>Connector SB350</b>	<b>BLUE , Position A , Lead Length 025 Inches</b>		
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)				
<b>ERPS30TF</b>	<b>THREE-WHEEL SIT DOWN RIDER</b>												<b>36 VOLTS , 39.00 X 16.70 X 26.12</b>		<b>Weight Minimum 1250</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>		
	36	085C13	510	17.8	38.00	15.50	22.63	1425	M2601808513B	Y	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
	36	100C13	600	21.0	38.13	15.50	25.63	1698	M2601810013B	Y	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
	36	100T13	600	21.0	38.00	15.50	22.63	1516	M2801810013B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
	36	085L13	510	17.8	38.00	15.50	22.63	1452	M2901808513B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
<b>ERPS30TF</b>	<b>THREE-WHEEL SIT DOWN RIDER</b>												<b>48 VOLTS , 39.00 X 16.70 X 26.12</b>		<b>Weight Minimum 1150</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>		
	48	085C09	340	15.8	37.82	15.00	22.63	1299	M2602408509B	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	100T09	400	18.6	37.82	15.00	22.63	1437	M2802410009B	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
<b>ERPS30TG</b>	<b>THREE-WHEEL SIT DOWN RIDER</b>												<b>36 VOLTS , 39.00 X 16.70 X 26.12</b>		<b>Weight Minimum 1250</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>		
	36	085C13	510	17.8	38.00	15.50	22.63	1425	M2601808513B	Y	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
	36	100C13	600	21.0	38.13	15.50	25.63	1698	M2601810013B	Y	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
	36	100T13	600	21.0	38.00	15.50	22.63	1516	M2801810013B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
	36	085L13	510	17.8	38.00	15.50	22.63	1452	M2901808513B	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
<b>ERPS30TG</b>	<b>THREE-WHEEL SIT DOWN RIDER</b>												<b>48 VOLTS , 39.00 X 16.70 X 26.12</b>		<b>Weight Minimum 1150</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>		
	48	085C09	340	15.8	37.82	15.00	22.63	1299	M2602408509B	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
	48	100T09	400	18.6	37.82	15.00	22.63	1437	M2802410009B	N	(CALL)	SCR20024475S1H	SCR20024475T1H	(CALL)	(CALL)				
<b>ERP030TF</b>	<b>THREE-WHEEL SIT DOWN RIDER</b>												<b>36 VOLTS , 39.00 X 21.50 X 26.12</b>		<b>Weight Minimum 1700</b>	<b>Connector SB350</b>	<b>GRAY , Position B , Lead Length 030 Inches</b>		
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	060B21	600	21.2	38.50	20.75	24.50	2077	M2101806021B7	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)				
	36	060B25	720	25.4	38.50	20.34	25.69	2130	M2101806025B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)				
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)				
<b>ERP030TF</b>	<b>THREE-WHEEL SIT DOWN RIDER</b>												<b>48 VOLTS , 39.00 X 21.50 X 26.12</b>		<b>Weight Minimum 1700</b>	<b>Connector SB350</b>	<b>BLUE , Position B , Lead Length 030 Inches</b>		
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100C13	600	27.9	38.50	20.63	25.63	2201	M2602410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)				

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERP030TG	THREE-WHEEL SIT DOWN RIDER		36 VOLTS , 39.00 X 21.50 X 22.80 Weight Minimum 1700 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085C17	680	23.7	38.25	19.94	22.63	1933	M2601808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	085F17	680	23.7	38.25	19.94	22.63	2014	M2501808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	060B21	600	21.2	38.50	20.75	24.50	2077	M2101806021B7	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
	36	100T17	800	27.9	38.25	19.94	22.63	2049	M2801810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085L17	680	23.7	38.25	19.94	22.63	1963	M2901808517B	Y	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
ERP030TG	THREE-WHEEL SIT DOWN RIDER		36 VOLTS , 39.00 X 21.50 X 25.80 Weight Minimum 2000 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	060B21	600	21.2	38.50	20.75	24.50	2077	M2101806021B7	N	(CALL)	SCR20018600S1H	SCR20018600T1H	(CALL)	(CALL)
	36	060B25	720	25.4	38.50	20.34	25.69	2130	M2101806025B	N	(CALL)	SCR20018750S1H	SCR20018750T1H	(CALL)	(CALL)
	36	100C17	800	27.9	38.19	20.00	25.62	2156	M2601810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100F17	800	27.9	38.19	20.00	25.63	2272	M2501810017B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ERP030TG	THREE-WHEEL SIT DOWN RIDER		48 VOLTS , 39.00 X 21.50 X 22.80 Weight Minimum 1700 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085F13	510	23.7	38.00	20.50	22.63	1944	M2502408513B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C13	510	23.7	38.00	20.50	22.63	1869	M2602408513B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100T13	600	27.9	38.00	20.50	22.63	2016	M2802410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERP030TG	THREE-WHEEL SIT DOWN RIDER		48 VOLTS , 39.00 X 21.50 X 25.80 Weight Minimum 2000 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	100C13	600	27.9	38.50	20.63	25.63	2201	M2602410013B	N	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERP035TF	THREE-WHEEL SIT DOWN RIDER		36 VOLTS , 39.00 X 25.20 X 26.12 Weight Minimum 2100 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	090G19	810	28.6	38.62	24.00	22.50	2500	M8901809019B758	Y	(CALL)	SCR20018750T1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ERP035TF	THREE-WHEEL SIT DOWN RIDER		48 VOLTS , 39.00 X 25.20 X 26.12 Weight Minimum 2000 Connector SB350 BLUE , Position B , Lead Length 030 Inches												
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)	SCR20024750T1H	SCR20024750T1H	(CALL)	(CALL)
ERP035TG	THREE-WHEEL SIT DOWN RIDER		36 VOLTS , 39.00 X 25.20 X 22.80 Weight Minimum 2100 Connector SB350 GRAY , Position B , Lead Length 030 Inches												
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	090G19	810	28.6	38.62	24.00	22.50	2500	M8901809019B758	Y	(CALL)	SCR20018750T1H	SCR20018750T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)	SCR200181050T1H	SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat

M15/M25 -Titan Flooded Flat-Plate (Cover/No Cover)

M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)

M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)

M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)								
ERP035TG	THREE-WHEEL SIT DOWN RIDER			36 VOLTS , 39.00 X 25.20 X 25.80			Weight Minimum 2500		Connector SB350	GRAY , Position B , Lead Length 030 Inches					
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	090G19	810	28.6	38.62	24.00	22.50	2500	M8901809019B758	Y	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ERP035TG	THREE-WHEEL SIT DOWN RIDER			48 VOLTS , 39.00 X 25.20 X 22.80			Weight Minimum 2100		Connector SB350	BLUE , Position B , Lead Length 030 Inches					
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
ERP035TG	THREE-WHEEL SIT DOWN RIDER			48 VOLTS , 39.00 X 25.20 X 25.80			Weight Minimum 2500		Connector SB350	BLUE , Position B , Lead Length 030 Inches					
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
ERP040TF	THREE-WHEEL SIT DOWN RIDER			36 VOLTS , 39.00 X 25.30 X 26.12			Weight Minimum 2100		Connector SB350	GRAY , Position B , Lead Length 030 Inches					
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	090G19	810	28.6	38.62	24.00	22.50	2500	M8901809019B758	Y	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ERP040TF	THREE-WHEEL SIT DOWN RIDER			48 VOLTS , 39.00 X 25.30 X 26.12			Weight Minimum 2000		Connector SB350	BLUE , Position B , Lead Length 030 Inches					
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	(CALL)		SCR20024750T1H	(CALL)	(CALL)
ERP040TG	THREE-WHEEL SIT DOWN RIDER			36 VOLTS , 39.00 X 25.30 X 22.80			Weight Minimum 2100		Connector SB350	GRAY , Position B , Lead Length 030 Inches					
	36	085C21	850	29.7	38.25	24.56	22.63	2314	M2601808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	085F21	850	29.7	38.25	24.56	22.63	2411	M2501808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
	36	090G19	810	28.6	38.62	24.00	22.50	2500	M8901809019B758	Y	(CALL)		SCR20018750T1H	(CALL)	(CALL)
	36	100T21	1000	34.9	38.25	24.56	22.63	2455	M2801810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	085L21	850	29.7	38.25	24.56	22.63	2350	M2901808521B	Y	(CALL)	SCR20018865S1H	SCR20018865T1H	(CALL)	(CALL)
ERP040TG	THREE-WHEEL SIT DOWN RIDER			36 VOLTS , 39.00 X 25.30 X 25.80			Weight Minimum 2500		Connector SB350	GRAY , Position B , Lead Length 030 Inches					
	36	100C21	1000	34.9	38.31	24.75	25.62	2727	M2601810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	100F21	1000	34.9	38.31	24.75	25.63	2890	M2501810021B	Y	(CALL)		SCR200181050T1H	(CALL)	(CALL)
	36	090G19	810	28.6	38.62	24.00	22.50	2500	M8901809019B758	Y	(CALL)		SCR20018750T1H	(CALL)	(CALL)
ERP040TG	THREE-WHEEL SIT DOWN RIDER			48 VOLTS , 39.00 X 25.30 X 22.80			Weight Minimum 2100		Connector SB350	BLUE , Position B , Lead Length 030 Inches					
	48	085F15	595	27.7	38.19	23.50	22.62	2231	M2502408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)
	48	085C15	595	27.7	38.19	23.50	22.62	2148	M2602408515B	Y	(CALL)	SCR20024600S1H	SCR20024600T1H	(CALL)	(CALL)

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
 M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
 M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
 M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
 M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)

TRUCK MODEL	VOLT	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			BATT. WT. (LBS.)	BATTERY MODEL NUMBER	Q-SHP	BATTERY LIST PRICE	SINGLE PHASE CHARGER (S-1)	THREE PHASE CHARGER (T-1)	S-1 CHARGER LIST PRICE	T-1 CHARGER LIST PRICE			
			A.H.	KwH	X in. (Length)	Y in. (Width)	Z in. (Height)											
ERP040TG	THREE-WHEEL SIT DOWN RIDER												48 VOLTS , 39.00 X 25.30 X 25.80			Weight Minimum 2500	Connector SB350	BLUE , Position B , Lead Length 030 Inches
	48	100C15	700	32.6	38.31	23.63	25.63	2536	M2602410015B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )			
	48	100F15	700	32.6	38.31	23.63	25.63	2651	M2502410015B	N	( CALL )		SCR20024750T1H	( CALL )	( CALL )			
ERP050DH	4 WHEEL SIT DOWN												80 VOLTS , 40.60 X 28.30 X 30.90			Weight Minimum 3720	Connector SBE320	BLACK , Position A , Lead Length 012 Inches
	80	140T09	560	43.5	40.00	27.50	30.50	3985	M2804014009X7625	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
	80	125C09	500	38.8	40.00	27.50	30.50	3835	M2604012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
	80	125F09	500	38.8	40.00	27.50	30.50	3995	M2504012509X76A	N	( CALL )		SCR20040600T1H	( CALL )	( CALL )			
ERP050DH	4 WHEEL SIT DOWN												80 VOLTS , 40.60 X 33.90 X 30.90			Weight Minimum 4456	Connector SBE320	BLACK , Position A , Lead Length 012 Inches
	80	140T11	700	54.3	40.50	33.21	30.50	4674	M2804014011X7625	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
ERP060DH	4 WHEEL SIT DOWN												80 VOLTS , 40.60 X 33.90 X 30.90			Weight Minimum 4456	Connector SBE320	BLACK , Position A , Lead Length 012 Inches
	80	140T11	700	54.3	40.50	33.21	30.50	4674	M2804014011X7625	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			
ERP065DH	4 WHEEL SIT DOWN												80 VOLTS , 40.60 X 33.90 X 30.90			Weight Minimum 4456	Connector SBE320	BLACK , Position A , Lead Length 012 Inches
	80	140T11	700	54.3	40.50	33.21	30.50	4674	M2804014011X7625	N	( CALL )		SCR20040750T1H	( CALL )	( CALL )			

M20/21/89/90 - Element VRLA Absorbed Glass Mat  
M15/M25 - Titan Flooded Flat-Plate (Cover/No Cover)  
M16/M26 - GNB Flooded Classic Flat-Plate (Cover/No Cover)  
M18/M28 - Tubular-HP High Performance Flooded Tubular-Plate (Cover/No Cover)  
M19/M29 - Liberator Low Maintenance Flooded Tubular-Plate (Cover/No Cover)